

[Home](#)

CLASSES

rcb

- endScript
- getBoardId
- getBoardVersion
- getFirmwareVersion
- onKeyPress
- setDebugMode
- wait

console

- append
- clear
- error
- overwrite
- print
- remove
- setVerbose
- warning

files

- appendTextFile
- newLogEntry
- newLogFile
- newTextFile

output

- ramp
- set
- steps
- steps2

sensors

- averageResultsArray
- read
- readOhm
- setMotorPoles
- setSafetyLimit
- tareCurrent
- tareLoadCells

udp

- ab2str
- init
- onReceive
- send
- str2ab

GLOBAL

rcb

rcb

new rcb(args)

Api constructor. Called by the GUI to start the script (do not use in scripts).

Parameters:

| Name | Type | Description |
|------|--------|----------------|
| args | Object | GUI arguments. |

Source: [rcbApi.js, line 79](#)

Classes

- [console](#)
- [files](#)
- [output](#)
- [sensors](#)
- [udp](#)

Methods

(static) endScript()

Finishes the script execution. If this function is not called, the user will have to press the "Stop" button to stop the script.

Source: [rcbApi.js, line 407](#)

(static) getBoardId() → {string}

Returns the board's unique ID.

[Home](#)**CLASSES****rcb**

- endScript
- getBoardId
- getBoardVersion
- getFirmwareVersion
- onKeyPress
- setDebugMode
- wait

console

- append
- clear
- error
- overwrite
- print
- remove
- setVerbose
- warning

files

- appendTextFile
- newLogEntry
- newLogFile
- newTextFile

output

- ramp
- set
- steps
- steps2

sensors

- averageResultsArray
- read
- readOhm
- setMotorPoles
- setSafetyLimit
- tareCurrent
- tareLoadCells

udp

- ab2str
- init
- onReceive
- send
- str2ab

GLOBALSource: [rcbApi.js, line 384](#)**Returns:**

A string representing the board's unique serial number.

Type string

Example

```
var boardId = rcb.getBoardId();
rcb.console.print(boardId);
rcb.endScript();
```

(static) getBoardVersion() → {string}

Returns the board's hardware version.

Source: [rcbApi.js, line 392](#)**Returns:**

A string representing the board's hardware version.

Type string

(static) getFirmwareVersion() → {string}

Returns the board's firmware version.

Source: [rcbApi.js, line 400](#)**Returns:**

A string representing the board's firmware version.

Type string

(static) onKeyPress(callback)

[Home](#)

CLASSES

rcb

- endScript
- getBoardId
- getBoardVersion
- getFirmwareVersion
- onKeyPress
- setDebugMode
- wait

console

- append
- clear
- error
- overwrite
- print
- remove
- setVerbose
- warning

files

- appendTextFile
- newLogEntry
- newLogFile
- newTextFile

output

- ramp
- set
- steps
- steps2

sensors

- averageResultsArray
- read
- readOhm
- setMotorPoles
- setSafetyLimit
- tareCurrent
- tareLoadCells

udp

- ab2str
- init
- onReceive
- send
- str2ab

GLOBAL

Allows for interactive scripts by triggering a special callback when a key is pressed. To use the 'enter' key, make sure the focus is not on the 'stop script' button otherwise the script will stop. The callback you specify will be returned with the ASCII value of the key pressed. For example, spacebar is 32.

Parameters:

| Name | Type | Description |
|----------|------------|---|
| callback | keyPressed | Function to execute when a key is pressed |

Source: [rcbApi.js, line 448](#)

Example

```
// Example illustrating how to use the onKeyboar

rcb.console.print("Listening for keypress...");

// Setup keypress callback function
rcb.onKeyPress(function(key){
    // Print on screen which key was pressed
    var ascii = String.fromCharCode(key);
    rcb.console.print("You pressed " + ascii + "
});
```

(static) setDebugMode(enable)

Activates or deactivates the debug mode.

Parameters:

| Name | Type | Description |
|--------|---------|--|
| enable | boolean | Set to "true" to activate debug mode, "false" otherwise. |

Source: [rcbApi.js, line 418](#)

[Home](#)

CLASSES

rcb

- endScript
- getBoardId
- getBoardVersion
- getFirmwareVersion
- onKeyPress
- setDebugMode
- wait

console

- append
- clear
- error
- overwrite
- print
- remove
- setVerbose
- warning

files

- appendTextFile
- newLogEntry
- newLogFile
- newTextFile

output

- ramp
- set
- steps
- steps2

sensors

- averageResultsArray
- read
- readOhm
- setMotorPoles
- setSafetyLimit
- tareCurrent
- tareLoadCells

udp

- ab2str
- init
- onReceive
- send
- str2ab

GLOBAL

(static) wait(callback, delay)

Waits a certain number of seconds before executing the callback function. Note that calling this function again will cancel a previous wait. Use the javascript setTimeout function if you need multiple delays in parallel.

Parameters:

| Name | Type | Description |
|----------|--------------------------|---|
| callback | waitDone | The function to execute after the delay is over. |
| delay | number | Wait delay in seconds (can be floating numbers like 0.1 for 100ms). |

Source: [rcbApi.js, line 1191](#)

Example

```
//Illustrates the use of the wait and overwrite
rcb.console.print("LEGEND...");
rcb.console.setVerbose(false);
rcb.wait(callback1, 2);

function callback1(){
    rcb.console.overwrite("LEGEND... wait for it");
    rcb.wait(callback2, 2);
}

function callback2(){
    rcb.console.overwrite("LEGEND... wait for it");
    rcb.wait(callback3, 1.5);
}

function callback3(){
    rcb.console.overwrite("LEGENDARY!");
    rcb.endScript();
}
```

[Home](#)

Documentation generated by [JSDoc 3.6.3](#) on Wed Aug 21 2019
09:49:26 GMT-0400 (Eastern Daylight Time) using the *Minami*
theme.

CLASSES

rcb

- endScript
- getBoardId
- getBoardVersion
- getFirmwareVersion
- onKeyPress
- setDebugMode
- wait

console

- append
- clear
- error
- overwrite
- print
- remove
- setVerbose
- warning

files

- appendTextFile
- newLogEntry
- newLogFile
- newTextFile

output

- ramp
- set
- steps
- steps2

sensors

- averageResultsArray
- read
- readOhm
- setMotorPoles
- setSafetyLimit
- tareCurrent
- tareLoadCells

udp

- ab2str
- init
- onReceive
- send
- str2ab

GLOBAL