

Index objects and labeled data

MANIPULATING DATAFRAMES WITH PANDAS



Anaconda
Instructor

pandas data structures

- Key building blocks
- `Index` es: Sequence of labels
 - Immutable (Like dictionary keys)
 - Homogeneous in data type (Like NumPy arrays)
- `Series` : 1D array with Index
- `DataFrame` s: 2D array with Series as columns

Creating a Series

```
import pandas as pd
prices = [10.70, 10.86, 10.74, 10.71, 10.79]
shares = pd.Series(prices)
print(shares)
```

```
0    10.70
1    10.86
2    10.74
3    10.71
4    10.79
dtype: float64
```

Creating an index

```
days = ['Mon', 'Tue', 'Wed', 'Thur', 'Fri']  
shares = pd.Series(prices, index=days)  
print(shares)
```

```
Mon    10.70  
Tue    10.86  
Wed    10.74  
Thur    10.71  
Fri    10.79  
dtype: float64
```

Examining an index

```
print(shares.index)
```

```
Index(['Mon', 'Tue', 'Wed',  
      'Thur', 'Fri'],  
      dtype='object')
```

```
print(shares.index[2])
```

```
Wed
```

```
print(shares.index[:2])
```

```
Index(['Mon', 'Tue'],  
      dtype='object')
```

```
print(shares.index[-2:])
```

```
Index(['Thur', 'Fri'],  
      dtype='object')
```

```
print(shares.index.name)
```

```
None
```

Modifying index name

```
shares.index.name = 'weekday'  
print(shares)
```

```
weekday  
Monday      10.70  
Tuesday     10.86  
Wednesday   10.74  
Thursday    10.71  
Friday      10.79  
dtype: float64
```

Modifying index entries

```
shares.index[2] = 'Wednesday'
```

```
TypeError: Index does not support mutable operations
```

```
shares.index[:4] = ['Monday', 'Tuesday', 'Wednesday',  
                  'Thursday']
```

```
TypeError: Index does not support mutable operations
```

Modifying all index entries

```
shares.index = ['Monday', 'Tuesday', 'Wednesday',  
               'Thursday', 'Friday']
```

```
print(shares)
```

```
Monday      10.70  
Tuesday     10.86  
Wednesday   10.74  
Thursday    10.71  
Friday      10.79  
dtype: float64
```


Unemployment data

```
unemployment = pd.read_csv('Unemployment.csv')  
unemployment.head()
```

	Zip	unemployment	participants
0	1001	0.06	13801
1	1002	0.09	24551
2	1003	0.17	11477
3	1005	0.10	4086
4	1007	0.05	11362

Unemployment data

```
unemployment.info()
```

```
<class 'pandas.core.frame.DataFrame'>  
RangeIndex: 33120 entries, 0 to 33119  
Data columns (total 3 columns):  
Zip                33120 non-null int64  
unemployment       32556 non-null float64  
participants       33120 non-null int64  
dtypes: float64(1), int64(2)  
memory usage: 776.3 KB
```

Assigning the index

```
unemployment.index = unemployment['Zip']  
unemployment.head()
```

	Zip	unemployment	participants
Zip			
1001	1001	0.06	13801
1002	1002	0.09	24551
1003	1003	0.17	11477
1005	1005	0.10	4086
1007	1007	0.05	11362

Removing extra column

```
unemployment.head(3)
```

	Zip	unemployment	participants
Zip			
1001	1001	0.06	13801
1002	1002	0.09	24551
1003	1003	0.17	11477

```
del unemployment['Zip']  
unemployment.head(3)
```

	unemployment	participants
Zip		
1001	0.06	13801
1002	0.09	24551
1003	0.17	11477

Examining index and columns

```
print(unemployment.index)
```

```
Int64Index([1001, 1002, 1003, ...],  
           dtype='int64',  
           name='Zip',  
           length=33120)
```

```
print(unemployment.index.name)
```

```
Zip
```

```
print(type(unemployment.index))
```

```
<class  
'pandas.indexes.numeric.Int64Index'>
```

```
print(unemployment.columns)
```

```
Index(['unemployment',  
       'participants'],  
      dtype='object')
```

read_csv() with index_col

```
unemployment = pd.read_csv('Unemployment.csv',  
                           index_col='Zip')
```

```
unemployment.head()
```

	unemployment	participants
Zip		
1001	0.06	13801
1002	0.09	24551
1003	0.17	11477
1005	0.10	4086
1007	0.05	11362

Let's practice!

MANIPULATING DATAFRAMES WITH PANDAS

Hierarchical Indexing

MANIPULATING DATAFRAMES WITH PANDAS



Anaconda
Instructor

Stock data

```
import pandas as pd
stocks = pd.read_csv('datasets/stocks.csv')
print(stocks)
```

	Date	Close	Volume	Symbol
0	2016-10-03	31.50	14070500	CSCO
1	2016-10-03	112.52	21701800	AAPL
2	2016-10-03	57.42	19189500	MSFT
3	2016-10-04	113.00	29736800	AAPL
4	2016-10-04	57.24	20085900	MSFT
5	2016-10-04	31.35	18460400	CSCO
6	2016-10-05	57.64	16726400	MSFT
7	2016-10-05	31.59	11808600	CSCO
8	2016-10-05	113.05	21453100	AAPL

Setting index

```
stocks = stocks.set_index(['Symbol', 'Date'])  
print(stocks)
```

		Close	Volume
Symbol	Date		
CSCO	2016-10-03	31.50	14070500
AAPL	2016-10-03	112.52	21701800
MSFT	2016-10-03	57.42	19189500
AAPL	2016-10-04	113.00	29736800
MSFT	2016-10-04	57.24	20085900
CSCO	2016-10-04	31.35	18460400
MSFT	2016-10-05	57.64	16726400
CSCO	2016-10-05	31.59	11808600
AAPL	2016-10-05	113.05	21453100

```
print(stocks.index)
```

```
MultiIndex(levels=[['AAPL', 'CSCO', 'MSFT'],  
                  ['2016-10-03', '2016-10-04', '2016-10-05']],  
            labels=[[1, 0, 2, 0, 2, 1, 2, 1, 0],  
                   [0, 0, 0, 1, 1, 1, 2, 2, 2]],  
            names=['Symbol', 'Date'])
```

```
print(stocks.index.name)
```

```
None
```

```
print(stocks.index.names)
```

```
['Symbol', 'Date']
```

Sorting index

```
stocks = stocks.sort_index()  
print(stocks)
```

		Close	Volume
Symbol	Date		
AAPL	2016-10-03	112.52	21701800
	2016-10-04	113.00	29736800
	2016-10-05	113.05	21453100
CSCO	2016-10-03	31.50	14070500
	2016-10-04	31.35	18460400
	2016-10-05	31.59	11808600
MSFT	2016-10-03	57.42	19189500
	2016-10-04	57.24	20085900
	2016-10-05	57.64	16726400

Indexing (individual row)

```
stocks.loc[('CSCO', '2016-10-04')]
```

```
Close          31.35  
Volume    18460400.00  
Name: (CSCO, 2016-10-04), dtype: float64
```

```
stocks.loc[('CSCO', '2016-10-04'), 'Volume']
```

```
18460400.0
```

Slicing (outermost index)

```
stocks.loc['AAPL']
```

	Close	Volume
Date		
2016-10-03	112.52	21701800
2016-10-04	113.00	29736800
2016-10-05	113.05	21453100

Slicing (outermost index)

```
stocks.loc['CSCO':'MSFT']
```

		Close	Volume
Symbol	Date		
CSCO	2016-10-03	31.50	14070500
	2016-10-04	31.35	18460400
	2016-10-05	31.59	11808600
MSFT	2016-10-03	57.42	19189500
	2016-10-04	57.24	20085900
	2016-10-05	57.64	16726400

Fancy indexing (outermost index)

```
stocks.loc([( 'AAPL', 'MSFT' ], '2016-10-05'), :]
```

		Close	Volume
Symbol	Date		
AAPL	2016-10-05	113.05	21453100
MSFT	2016-10-05	57.64	16726400

```
stocks.loc([( 'AAPL', 'MSFT' ], '2016-10-05'), 'Close']
```

Symbol	Date	
AAPL	2016-10-05	113.05
MSFT	2016-10-05	57.64

Name: Close, dtype: float64

Fancy indexing (innermost index)

```
stocks.loc(['CSCO', ['2016-10-05', '2016-10-03']], :]
```

		Close	Volume
Symbol	Date		
CSCO	2016-10-03	31.50	14070500
	2016-10-05	31.59	11808600

Slicing (both indexes)

```
stocks.loc[(slice(None), slice('2016-10-03', '2016-10-04')),:]
```

		Close	Volume
Symbol	Date		
AAPL	2016-10-03	112.52	21701800
	2016-10-04	113.00	29736800
CSCO	2016-10-03	31.50	14070500
	2016-10-04	31.35	18460400
MSFT	2016-10-03	57.42	19189500
	2016-10-04	57.24	20085900

Let's practice!

MANIPULATING DATAFRAMES WITH PANDAS