CASH MOBILE

CHANGE REQUEST

Push Notifications & CMS Administration

Campaigns • Scheduled & targeted messaging

Automatic transaction notifications

Customer usage analytics • Roles & approvals

DRAFT FOR REVIEW

CR-CM-2026-001 | Version 1.0

20 October 2026

Audience: Business, Mobile, Backend, CMS, QA and Operations

Purpose: scope approval, technical estimation and acceptance testing

Status: requested target state; not a certificate of implementation

Contents

1. Document Control & Approval 3

2. Business Objective, Scope & Assumptions 4

3. Actors, Identity & Customer/Device Rules 5

4. CMS Interface & Navigation 6

5. Dashboard, Filters & Metric Definitions 8

6. Campaign Creation & Audience Targeting 9

7. Recipient File Import & Validation 11

8. Scheduling, Approvals, Sending & Resending 12

9. Automated Notifications & Event Catalogue 13

10. Incoming Transfer — End-to-End Flow 14

11. Reliability, Retry & Delivery-State Model 15

12. Customer Directory & Notification History 16

13. Usage Analytics: Sessions, Screens & Actions 17

14. CMS Users, Roles & Permission Matrix 18

15. Approval Controls, Security & Audit 19

16. Integration Contract & Data Model 20

17. Non-Functional Requirements & Retention 22

18. Acceptance Criteria & Traceability 23

19. Dependencies, Decisions & Delivery Plan 25

20. Rollout, Risks & Final Sign-off 26

1. Document Control & Approval

Field	Value
Change request ID	CR-CM-2026-001
Title	Cash Mobile — Push Notifications, CMS and Usage Analytics
Version / date	1.0 / 20 October 2026
Status	Draft for business and engineering review
Business owner	Cash Mobile — named owner to be assigned
Delivery owner / target release	To be assigned / to be estimated after scope review
Platforms	CMS web; Cash Mobile Android first. iOS requires separate scope confirmation.
Related baseline	Existing Cash Mobile notification prototype and developer handoff. Actual production integration remains to be validated.

This CR defines the requested target state. A requirement in this document does not mean that it exists in the current application. Engineering shall assess reuse of the prototype, identify gaps and estimate the delivery scope before approval.

Approval record

Reviewer	Responsibility	Decision / date
Business / Product Owner	Audience rules, event catalogue, templates and scope	Pending
Mobile Lead	Instrumentation, token lifecycle and safe navigation	Pending
Backend / CMS Lead	Identity, event ingestion, delivery and permissions	Pending
QA Lead	Acceptance coverage and release readiness	Pending
Operations / Security Owner	Secrets, access, retention, monitoring and rollout	Pending

Requirement terms

MUST identifies required release scope. **SHOULD** identifies a recommended capability. **Proposed / TBC** identifies a planning assumption that requires an explicit decision. Scope changes after approval must update this CR and its acceptance criteria.

2. Business Objective, Scope & Assumptions

Provide a controlled CMS for Cash Mobile communications: send and schedule campaigns, target customer phone numbers or uploaded lists, automatically notify customers of confirmed financial events, and measure notification and application usage outcomes.

In scope	Release expectation
Campaign messaging	All eligible accounts, selected phone numbers, CSV/XLSX audience upload, scheduling, approvals, cancellation and controlled resend.
Transactional notifications	Incoming transfers as the primary use case; configurable catalogue for payments, top-ups, failures, refunds and reminders.
CMS interface	Dashboard, campaigns, automated events, customers, analytics, users/roles, audit logs and settings; English/Arabic and RTL.
Reporting	Delivery outcomes, observed receipt/open tracking where instrumented, customer sessions, pages, dwell time and named actions.
Integration	Existing payment-system identity, registered devices, backend event interface, reliable event persistence and monitoring.

Out of scope unless separately approved	Reason / boundary
SMS, email, USSD and message inbox chat	This CR concerns mobile push notifications.
Financial execution or balance editing in CMS	The payment backend remains the financial system of record.
Replacing Cash Mobile login / customer registration	Existing company authentication remains authoritative.
Screen recording, keystroke capture or arbitrary input collection	Analytics covers approved screen and action events, excluding sensitive field contents.
Guaranteed push delivery or exact-once network transport	Delivery depends on devices, permissions, connectivity and provider behavior.
iOS, non-GMS Android and new paid infrastructure	Require explicit technical and commercial scope decisions.

Budget assumption: begin with existing infrastructure and free service tiers where practical. Free-tier capacity must be measured against expected load; this CR does not assume unlimited free events, storage or campaigns.

3. Actors, Identity & Customer/Device Rules

Actor	Responsibility
Cash Mobile customer	Uses the payment app; receives notifications and manages permitted preferences.
CMS operator	Creates audiences, composes campaigns and monitors results within assigned permissions.
CMS approver	Independently reviews and approves or rejects campaigns when policy requires approval.
Payment backend	Authenticates customers, confirms financial events and resolves the true event recipient.
Notification service	Persists events, selects eligible devices, sends through FCM and records outcomes.
Mobile application	Registers tokens; receives, displays and opens notifications; emits approved analytics events.

Required identity and device behavior

FR-ID-01 — Authoritative identity

Use an immutable customer ID from the payment backend. Phone number and name are display/search attributes; changes to phone number must not create a new customer or transfer another customer’s history.

FR-ID-02 — Automatic device binding

After successful app login, register the installation ID and FCM token against the authenticated customer. The backend derives customer identity from its verified session, not a client-selected customer ID.

FR-ID-03 — Token and permission lifecycle

Update rotated tokens; record last-seen, app version, platform, permission state and preferences. Denying notification permission must not block login or payment.

FR-ID-04 — Multiple devices and logout

Support multiple active devices per account. Confirmed logout deactivates that device binding, while other devices remain active. Clear customer-specific local data when switching accounts.

FR-ID-05 — Eligibility and preferences

Select active devices compatible with the audience and notification category. Keep marketing consent separate from transaction categories; respect OS permission restrictions.

FR-ID-06 — Ownership at send/open time


Recheck device ownership before dispatch. On open, authenticate and authorize access to transaction details. An in-flight OS notification may not be retractable; keep lock-screen content appropriately limited.

4. CMS Interface & Navigation

The visual direction follows the Cash Mobile reference: a dark navy sidebar, yellow primary actions, white cards and tables on a light background, and the original transparent Cash Mobile logo.

Area	Required interface
Sidebar	Dashboard; Campaigns; Automated Notifications; Customers; Usage Analytics; CMS Users & Roles; Audit Logs; Settings. Hide inaccessible functions according to role.
Top bar	Page title and breadcrumb; contextual search; operational alerts; language selector; administrator profile and logout.
Dashboard	Date/customer/type filters, key statistics, recent campaigns, delivery chart, status/type breakdown, recent activity and quick actions.
Tables	Search, sorting, status/date filters, pagination, visible total count, clear empty states and permitted CSV/XLSX export.
Forms	Required-field validation, previews, explicit save/submit states, loading indicators and actionable error messages.
Responsive layout	Desktop sidebar and grids; compact mobile navigation; readable forms; table scrolling contained within the table area.
Languages / accessibility	English LTR and Arabic RTL, consistent terminology, keyboard navigation, focus indicators, readable contrast and text labels alongside status colors.
Data integrity	Use actual records. Show N/A when a metric is not instrumented, and zero only when a supported metric has no results.

Illustrative dashboard layout



Wireframe only. Dashes are placeholders, not production statistics. Exact labels and component sizing may be refined during UI design without changing functionality.

5. Dashboard, Filters & Metric Definitions

Every metric MUST display its date range, unit and definition. Distinguish customers, logical notifications and per-device delivery attempts. Store timestamps in UTC and display the configured IANA timezone.

Metric	Definition / date basis
Total customers	Accounts synchronized from the payment system; current snapshot, shown separately from date-period activity.
Eligible audience	Distinct customers with at least one active device satisfying the category, audience and consent rules; current snapshot at validation or dispatch.
Campaign count by status	Campaigns created in the selected period, grouped by current draft/approval/scheduled/sending/completed/cancelled status.
Device delivery outcomes	Distinct delivery IDs created in the selected cohort; queued, sending, accepted, failed, unknown, expired or cancelled. Show the cohort basis in the UI.
Confirmed acceptance rate	Accepted / (accepted + failed + unknown), excluding queued/sending/cancelled/expired records. Unknown must be displayed separately and must not be labelled a confirmed failure.
Potential customer reach	Distinct customers with at least one FCM-accepted device delivery; not proof that the user saw the notification.
Observed receipts / opens	Distinct accepted device delivery IDs with authenticated received/opened events; attribute late events to the original delivery cohort.
Observed receipt / open rate	Observed distinct delivery receipts or opens / accepted device deliveries. Label measurement coverage and N/A if application tracking is unavailable.
Operational health	Queue depth, oldest pending age, dispatch latency, failures by reason, unknown outcomes and invalid-token count.
Usage engagement	Active authenticated customers, sessions, foreground time, screen visits and named actions in the selected activity period.

Required filters and chart behavior

• Date range and display timezone; campaign, notification category/type, status, audience and platform.

• Customer ID, phone/name search and app version where supported; mask identifiers for restricted roles.

• Charts for delivery trends, event types, campaign states and failure reasons; campaign and transaction datasets remain distinguishable.

• Use the same cohort for a rate numerator and denominator. Explain whether a date filter uses campaign creation, delivery creation or usage-event occurrence time.


• Comparison against the previous equivalent period is optional; display N/A when comparable data is unavailable.

• Export must preserve the applied filters, metric definitions and timezone, and be audited.

6. Campaign Creation & Audience Targeting

ID	Requirement
FR-CMP-01	Create/edit a draft with internal campaign name, category, language, notification title/body and an approved destination screen. Show a device-style preview and validate length/encoding before submission.
FR-CMP-02	Choose all eligible customers, manually entered phone numbers, a selected customer list, or a CSV/XLSX upload. These modes select existing accounts; importing a number must not create a customer account.
FR-CMP-03	Normalize and validate recipient numbers, resolve them to immutable customer IDs, remove duplicates and calculate distinct eligible customers and device deliveries.
FR-CMP-04	Show included/excluded counts and reasons, including invalid number, unmatched account, no active device, permission/consent exclusion and duplicate.
FR-CMP-05	Require a final review of title/body, destination, audience counts, category and delivery time before approval/send. Never substitute all users for an empty or invalid audience.
FR-CMP-06	Freeze the approved content and customer-ID audience snapshot. Re-evaluate device eligibility and account status at dispatch; expose changes between reviewed and actual eligible counts.
FR-CMP-07	For all-customer campaigns, snapshot eligible customer IDs at final approval. Newly created accounts after that point are excluded; an explicit audience refresh requires reapproval.
FR-CMP-08	Record the creator, reviewer, source list, template/content version and all lifecycle changes. Internal notes must not appear in the delivered notification.

Illustrative campaign composer



Audience validation and final confirmation are required workflow stages, regardless of whether the final UI uses tabs, panels or a stepper.

7. Recipient File Import & Validation

Supported formats and template

FR-IMP-01: support UTF-8 CSV and XLSX. Provide downloadable templates. A phone_number column is mandatory; optional customer_id and name columns may be supported. XLS, XLSM, macros and executable content are not supported.

```
phone_number,customer_id,name
<international phone>,<optional stable customer ID>,<optional display name>
```

Phone cells must be read as strings to preserve + and leading zeroes. Support Arabic digit normalization and common whitespace/separators. Use the configured country rule only when an unambiguous local number can be normalized; otherwise report it as invalid. Never silently guess the country.

Stage	Required result
Upload	Validate extension, content format and configured size/row limits. Use bounded parsing and avoid storing unnecessary source-file data.
Column mapping	Recognize or let the operator map the phone column; reject missing required columns with a clear message.
Normalization	Convert to canonical international format, preserving the original row reference for feedback.
Resolution	Match the normalized number to the authoritative customer directory. If customer_id is supplied, it must identify the same account as the phone; reject mismatches.
Deduplication	Deduplicate by resolved immutable customer ID, not only raw phone text; do not send twice when the same account appears multiple times.
Eligibility	Evaluate active devices, notification permissions, category preferences, platform and environment.
Preview	Show original row count, invalid rows, duplicate rows, unresolved unique accounts, excluded unique accounts, and eligible customers/device deliveries. Clearly label row-based vs customer-based counts.
Operator decision	Permit sending to the validated eligible subset only after explicit acknowledgement of exclusions, or allow correction/re-upload. Block an empty result.
Error report	Download rejected rows with row number and reason. Escape spreadsheet-formula prefixes in exports. Customer data must be visible only to authorized staff.

Proposed first-release limits: 10,000 rows and 5 MB per file, configurable and subject to load testing on the selected hosting plan. These are proposed product limits, not confirmed platform capacity.

Stored audience behavior

Retain the normalized customer-ID snapshot and import summary for audit. Remove the original file according to retention policy. If a customer changes phone number later, the approved campaign continues to refer to the same customer ID; devices are revalidated before sending.

8. Scheduling, Approvals, Sending & Resending

ID	Requirement
FR-SCH-01	Support Send Now and Schedule. Capture local date/time and an explicit IANA timezone, show the UTC equivalent, and reject a past schedule. Handle ambiguous/nonexistent daylight-saving times explicitly.
FR-SCH-02	Only valid, approved campaigns may enter the scheduled queue when approval is enabled. Pending approvals are not dispatchable.
FR-SCH-03	Allow permitted editing/cancellation before dispatch. A change to content, audience, destination or delivery time invalidates approval and requires review again.
FR-SCH-04	Show estimated recipient/device counts and processing status. Do not describe scheduled time as a guaranteed device-receipt time.
FR-SND-01	Claim each delivery atomically, process bounded batches, persist results and recover interrupted work without indiscriminate re-sending.
FR-SND-02	Cancellation during sending stops only unsent work. Already submitted/in-flight notifications cannot be guaranteed to be recalled; show submitted and cancelled counts separately.
FR-SND-03	Resend creates a new campaign/attempt linked to the original and preserves the selected customer IDs. Default to a new draft and approval; never overwrite historical outcomes.
FR-SND-04	Offer clearly defined resend audiences, such as original selected customers or confirmed failed deliveries. Unknown outcomes require explicit operator acknowledgement before a repeat.
FR-APR-01	Approval is configurable by campaign category, audience size or operator role. Proposed production default: campaign approval enabled with author self-approval blocked.
FR-APR-02	Approvers see the full preview, resolved audience summary, scheduling/timezone, exclusions and prior revisions before approving or rejecting with a reason.

Campaign lifecycle

```
Draft -> Pending Approval -> Approved -> Scheduled / Ready
      -> Sending -> Completed
Rejected -> Draft revision
Scheduled / Ready -> Cancelled
Sending -> Completed with cancelled unsent work
Interrupted processing -> Recoverable state / Operator review
```

Completed means no dispatchable work remains; it does not mean every device received or opened the message. Outcome counters must communicate partial acceptance, failures, unknown results and cancellations.

9. Automated Notifications & Event Catalogue

FR-AUTO-01: automatic notifications originate from trusted backend events after the underlying business state is confirmed. They are not triggered by a mobile screen claiming that a payment succeeded.

Event type	Recipient and trigger	Requirement
transfer_received	Recipient of a confirmed, posted incoming transfer	Mandatory primary use case. Resolve the actual recipient, not the initiating user.
invoice_paid	Payer after final bill-payment confirmation	Include safe transaction reference/destination; do not notify on a merely pending status.
balance_topup	Account owner after confirmed top-up	Backend-confirmed credit event.
operation_failed	Affected customer after a confirmed final rejection/failure	An unknown payment result is not a confirmed failure.
payment_refunded	Customer after an actual completed refund	New event linked to the original transaction, not reuse of the original success event.
invoice_reminder	Customer with a due invoice at a configured reminder time	Scheduled backend rule; prevent repeated reminders for the same rule occurrence.
security_alert	Affected account after an approved security event	Optional catalogue item; content and preferences require business policy.

Template and rule management

• **FR-AUTO-02:** Manage type key, display name, description, category, language variants, title/body templates, allowed variables, destination screen and enabled state.

• **FR-AUTO-03:** Validate variables against a type-specific schema, reject unknown placeholders, and provide a sample preview without using real customer secrets.

• **FR-AUTO-04:** Version templates. Save the resolved/versioned content for a queued event so later edits cannot silently change a previously approved or queued message.

• **FR-AUTO-05:** Apply role-controlled template changes and an auditable activation process. Critical financial/security template changes SHOULD require independent review.

• **FR-AUTO-06:** Automatic financial events do not wait for manual campaign approval. Apply the already approved event rule/template and dispatch eligibility rules.

• **FR-AUTO-07:** Provide a test-only mode restricted to explicit test accounts/devices and environment. A test event must not execute any real financial operation.

10. Incoming Transfer — End-to-End Flow

1. Transfer confirmed
Payment backend validates and commits transfer.

↓

2. Event persisted
Recipient + unique event ID saved in the same transaction.

↓

3. Event delivered to CMS
Authenticated backend request; durable acknowledgement.

↓

4. Recipient devices resolved
Active bindings, permissions, preferences and template.

↓

5. Push sent through FCM
Provider outcome recorded separately from receipt/open.

↓

6. User opens notification
Authenticate; authorize recipient; fetch transfer details.

Required processing rules

• **1.** Payment backend verifies the provider/ledger result and identifies the recipient’s immutable customer ID.

• **2.** Persist the final transfer state and a unique notification Outbox event in the same database transaction.

• **3.** An Outbox worker sends the event to the notification service through authenticated server-to-server integration, retrying delivery with the same event ID.

• **4.** CMS validates the source, schema and event identity, stores the event durably, and acknowledges the stored event. Duplicate matching events return their existing result.

• **5.** Resolve the recipient’s current active devices and the approved template. If none exist, record no_devices; do not broadcast to other accounts.

• **6.** Create per-device delivery records and send through FCM. Track accepted/failed/unknown separately from app-reported receipt/open events.

• **7.** On notification tap, require valid login and transaction ownership before opening details fetched from the payment API.

• **8.** If notification processing fails, retain recoverable work or a failure record; do not roll back or repeat the financial transfer.

Customer-facing example: Title: “Transfer received”. Message: “You have received a transfer. Open Cash Mobile for details.” Showing amount or sender identity on the lock screen is a separate, configurable privacy decision.

11. Reliability, Retry & Delivery-State Model

State	Meaning / handling
queued	Event/delivery durably stored and awaiting processing.
sending	Work is claimed/in progress; use a lease and atomic claim to prevent simultaneous dispatch by multiple workers.
accepted	FCM accepted the request. Not a device delivery receipt.
failed	Known unsuccessful outcome; distinguish permanent vs eligible temporary errors.
unknown	Provider outcome cannot be confirmed after timeout/interruption. Do not label it accepted or confirmed failed, and do not blindly replay it.
no_devices	No eligible customer device. Record the reason and apply an explicitly approved wait-until-TTL or terminal policy.
expired	The configured notification TTL expired before a valid attempt.
cancelled	Unsent work was cancelled. Already submitted work is reported separately.
received / opened	Independent authenticated client observations attached to delivery IDs, not replacement financial statuses.

• **FR-REL-01:** Use an immutable event ID for a business occurrence. Repeated identical requests return the existing event; the same ID with conflicting customer/type/entity/payload returns a conflict.

• **FR-REL-02:** Deduplicate delivery work per event/recipient/device and app inbox items using stable notification/delivery IDs. A retry is not a new financial transaction.

• **FR-REL-03:** Retry eligible temporary errors with bounded exponential backoff, jitter and Retry-After. Respect TTL and configured attempt limits.

• **FR-REL-04:** Disable unregistered/expired tokens. Diagnose payload errors before treating a token as invalid.

• **FR-REL-05:** A timeout after submitting to FCM may follow actual acceptance. Record unknown; provide a controlled review/retry policy and audit explicit repeats.

• **FR-REL-06:** Ensure campaign batches cannot indefinitely starve transaction notifications. Monitor queue depth, oldest pending work and retry backlog.

The product targets reliable event persistence and duplicate-resistant processing. It does not promise exactly-once transport or guaranteed push visibility on every device. Device connectivity, OS policy and permissions affect receipt.

12. Customer Directory & Notification History

ID	Requirement
FR-CUS-01	Search/filter customers by immutable customer ID, phone number, name, status, app version and active-device availability. Customer identity is synchronized from the payment system.
FR-CUS-02	Customer detail shows profile reference, linked devices, platform/app version, last-seen, permission/preference state and notification eligibility. Never display full device tokens to normal operators.
FR-CUS-03	Show campaign and automatic-event history with category/type, transaction reference, time, provider outcome, and observed receipt/open records where available.
FR-CUS-04	Support targeted campaign selection from customer lists. Selection counts must be distinct customers; show the associated eligible device count separately.
FR-CUS-05	Provide a permitted device-deactivation action with confirmation and reason. Device deactivation must not modify the customer’s financial account or balance.
FR-CUS-06	Honor field masking, export permission and record access restrictions. Support should not automatically receive unrestricted bulk customer exports.

Customer detail layout

Header: customer name, masked/full phone according to permission, immutable customer ID and account/notification status.
Tabs: Overview; Devices; Notification History; Sessions & Actions (restricted); Preferences.
History table: source campaign/event, type, time, device count, accepted/failed/unknown outcomes, observed opens and detail link.

Marketing and transaction preferences

Preferences are category-aware. Marketing opt-out removes marketing eligibility; transactional/security behavior follows the approved business policy and available OS permission. The interface must explain why a selected account is not eligible. A blocked or inactive account is handled according to an explicit synchronization rule.

13. Usage Analytics: Sessions, Screens & Actions

FR-ANA-01: instrument all agreed business-relevant screens and actions through a maintained event catalogue. CMS cannot infer mobile button presses without application instrumentation. Login-session validity and foreground usage sessions are separate concepts.

Event	Minimum data / definition
session_start	Unique usage session ID; authenticated customer resolved by backend; installation ID; UTC occurrence time; app/OS version. Start on authenticated foreground entry; a configurable background/inactivity threshold determines a new session.
screen_view	Stable screen ID, session ID, occurrence time and prior screen ID if available. Screen names must not embed customer names, phones or transaction amounts.
screen_time	Incremental foreground-visible duration for the active screen; measure elapsed time with a monotonic clock. Close/flush on navigation/background and checkpoint periodically. Do not double-count checkpoints and final intervals.
button_click / action	Stable action ID, screen ID, session ID, timestamp and optional allowlisted result/error code. Examples: transfer_submit, invoice_open, campaign_notification_open.
session_end	End reason, last-seen and accumulated foreground duration. If an app is killed, use checkpoints/inferred closure and label it accordingly.
notification_received / opened	Stable notification ID and per-device delivery ID; authenticated recipient binding; UTC time. Coverage varies by platform and background behavior.

Reports and individual user view

• **FR-ANA-02:** Dashboard: active customers, sessions, average/total foreground duration, screen views, time per screen, named action frequency, and app-version distribution.

• **FR-ANA-03:** User drill-down: session list and event timeline, page sequence, dwell intervals and action/result sequence. Show available evidence rather than assuming unobserved actions occurred.

• **FR-ANA-04:** Filters: date/timezone, customer, usage session, screen, action, platform and app version. Paginate event history and permit exports only to authorized roles.

• **FR-ANA-05:** Queue events locally during transient disconnection, batch uploads, cap local retention, retry with stable event IDs, and deduplicate server ingestion. Document limits and possible loss when the app is terminated or local capacity is exceeded.

• **FR-ANA-06:** Exclude passwords, OTPs, PINs, field values, card details, session credentials and full push tokens. Analytics payloads use allowlisted names/attributes; customer identity is derived from verified authentication.

• **FR-ANA-07:** Maintain an approved screen/action inventory and QA coverage map. Newly added app screens/actions require instrumentation and catalogue updates.

• **FR-ANA-08:** Authenticated customer analytics is in scope. Anonymous pre-login tracking is optional and requires a separate identity/retention decision. Usage analytics is observational telemetry, not a financial audit record.

14. CMS Users, Roles & Permission Matrix

CMS staff accounts are separate from Cash Mobile customer accounts. Each staff user has an individual identity, active/suspended state and assigned roles. No shared administrator login is acceptable for production auditability.

Role	Purpose
Super Admin	Manage CMS configuration, integrations, roles and staff accounts; all authorized CMS operations, but no financial ledger/balance editing.
Campaign Manager	Create/edit campaigns, import audiences, schedule/submit for approval and monitor permitted results. Sending requires explicit permission and applicable approval.
Approver	Review, approve or reject campaigns under policy. Cannot approve their own campaign when separation of duties is enabled.
Customer Support	Search permitted customers and inspect notification/device history; identifiers masked as configured. No default bulk send or export.
Analyst	Read approved aggregate dashboards and reports. Identifiable user/session drill-down and raw exports require separate grants.

Default permission matrix — configurable

Permission	Super Admin	Campaign Manager	Approver	Support	Analyst
View aggregate dashboards	Yes	Yes	Yes	Scoped	Yes
Create/edit own drafts	Yes	Yes	No	No	No
Import recipient files	Yes	Yes	No	No	No
Submit/schedule approved work	Yes	Yes	No	No	No
Approve/reject campaigns	Yes*	No	Yes*	No	No
Send/cancel/resend	Yes*	Granted*	No	No	No
View identifiable customers	Yes	Scoped	Scoped	Masked	No
Deactivate a device	Yes	No	No	Granted	No
Edit automated templates/rules	Yes*	Granted*	Review*	No	No
View identifiable usage timeline	Yes	Granted	No	Granted	Granted
Export customer/event data	Yes	Granted	No	No	Granted
Manage users/roles/integrations	Yes	No	No	No	No
View audit records	Yes	Own work	Review work	Own work	Granted

Scoped: constrained to permitted records/fields. **Granted:** an explicit additional permission, not a default. ***:** subject to approval and separation-of-duties policies; Super Admin must not silently bypass the configured author self-approval rule.

15. Approval Controls, Security & Audit

FR-IAM-01: permissions MUST be enforced by backend authorization as well as UI visibility. Role changes and suspension invalidate or re-evaluate active staff access. Permission tests must include direct API access, not only hidden buttons.

Staff account controls

• **FR-IAM-02:** Create/invite, activate, suspend and deactivate staff accounts; assign roles and scoped permissions; display last login and security-relevant account state.

• **FR-IAM-03:** Support MFA for staff and require it for privileged production roles. Reuse the company identity provider where available; final authentication architecture is an implementation decision.

• **FR-IAM-04:** Provide session expiry, logout, recovery and privileged-change confirmation appropriate to the company identity system. Removing access must block future API operations.

• **FR-AUD-01:** Append audit records for staff login/security events, role changes, audience imports/exports, template edits, approvals/rejections, schedules, sends, cancellation, resends and configuration changes.

• **FR-AUD-02:** Each audit record includes actor, effective role, action, affected record, UTC timestamp, result and correlation ID; record before/after changes where appropriate without secrets or full sensitive payloads.

• **FR-AUD-03:** Audit entries are append-only from normal CMS roles. Search/filter/export audit data only through explicitly granted permissions and retention policy.

Application and integration protection

• **FR-SEC-01:** Use HTTPS; keep Firebase service credentials and integration keys on servers in managed secrets. No private service key or shared backend secret in APKs, browser code, exports or logs.

• **FR-SEC-02:** Authenticate server-to-server event and device synchronization; protect signed requests against replay and support credential rotation. Integration identity must be scoped to the approved environment/service.

• **FR-SEC-03:** Validate recipient ownership, event schemas, payload length, file limits and permitted destination routes. Apply bounded rate/resource limits to imports, event ingestion, authentication and exports.

• **FR-SEC-04:** Limit lock-screen content and expose transaction details only after user authentication and ownership checks. Allow approved screen routes/App Links, not arbitrary executable URLs.

• **FR-SEC-05:** Apply category preferences, retention, masking and privacy controls approved by the business/data owner. Avoid collecting unnecessary personal data in analytics.

16. Integration Contract & Data Model

Production integration MUST preserve the current Cash Mobile login system. The payment backend derives customer identity from the existing session and synchronizes devices to the notification service. The app does not send its password to the CMS.

Interface — target requirement	Responsibility
App -> Payment backend: register/update device	Authenticated installation ID, FCM token, platform, app version, language and preferences; backend determines the customer ID.
App -> Payment backend: logout/device disconnect	Revoke the current device binding and clear customer-scoped local data; leave other devices active.
Payment backend -> Notification service: event submission	Authenticated immutable business event; durable acknowledgement and idempotent retry semantics.
App -> Authorized analytics ingestion	Approved event batch; server-derived identity, per-event IDs and ownership checks.
App -> Payment backend: entity details	Authenticated read after notification open, enforcing access to the referenced transaction.
CMS -> Notification service: campaign commands	Staff-session authorization, approved audience/content snapshots, audit and lifecycle controls.

Incoming transfer event — illustrative payload

```
{
  "eventId": "transfer:TRF-000184:received:CUST-1001:v1",
  "eventType": "transfer_received",
  "externalCustomerId": "CUST-1001",
  "occurredAt": "2026-10-20T09:00:00Z",
  "entity": {
    "type": "transfer",
    "id": "TRF-000184"
  },
  "payload": {
    "amountMinor": 2000000,
    "currency": "SYP"
  }
}
```

Use integer minor units with an agreed per-currency scale. The example is illustrative and does not define the company’s existing amount representation. A response acknowledging a queued event is not proof of device receipt.

Core entities

Entity	Required identity / data
Customer	Immutable external ID; display name/phone; synchronization status; language/preferences.
Device / installation	Installation ID; verified customer binding; private routing token; platform/app version; active/permission state; last-seen.
Campaign / audience snapshot	Versioned content, category, customer IDs, upload summary, approval, schedule/timezone, creator and history.
Business event / Outbox	Immutable event ID, source/entity reference, recipient ID, payload hash, occurrence/expiry time and state.
Logical notification / device delivery	Notification ID and delivery ID; template version; device; provider request/result; attempts and tracking observations.
Usage session / usage event	Session and event IDs, verified customer/device, screen/action, foreground interval, event/received times and app version.
Staff / role / audit	Individual identity, roles/grants, authentication state and immutable action log.

17. Non-Functional Requirements & Retention

ID / area	Requirement and proposed target
NFR-01 — Responsiveness	CMS lists use server-side pagination and scoped filters. Proposed target: common filtered views p95 <= 2 seconds at an agreed representative load; confirm by performance testing.
NFR-02 — Event acknowledgement	Acknowledge a new event only after durable persistence. Proposed p95 target <= 2 seconds at agreed load; financial processing must not block on FCM delivery.
NFR-03 — Dispatch latency	Proposed start-of-dispatch p95 <= 10 seconds for normal transactional workload, excluding upstream outages. Requires measured worker/queue design; no device-receipt SLA is implied.
NFR-04 — Scheduling	Dispatch becomes eligible at the stored UTC schedule. Report queue delay separately; missed starts are monitored and recovered according to TTL/policy.
NFR-05 — Scale	Agree customers, devices/customer, events/day, peak events/second, campaign audience size, upload limits and retention before sizing. Respect host/FCM quotas and isolate transaction priority.
NFR-06 — Reliability	Use durable events, atomic claims, idempotency, bounded retries, lease recovery and explicit unknown outcomes. Test restart/network interruption scenarios.
NFR-07 — Observability	Correlate event, campaign, notification, delivery and entity IDs. Alert on queue age, failure/unknown spikes, invalid tokens, ingestion rejection and resource limits.
NFR-08 — Localization/accessibility	English and Arabic/RTL, clear timezone display, keyboard-accessible controls and accessible contrast/status labels.
NFR-09 — Data retention	Proposed starting policy: 14 days raw usage events, 90 days aggregate analytics, 180 days operational/audit records. Business owner must approve final periods and verify storage/cost feasibility.
NFR-10 — Cleanup and portability	Automated expiry/deletion with documented handling of customer removal, backups and export access. Do not retain uploaded files longer than necessary.
NFR-11 — Service constraints	FCM/OS/network behavior can delay or suppress notifications. Free service tiers are a budget assumption, not a capacity guarantee.

Targets and retention above are planning proposals, not a contractual SLA or confirmation of existing performance. Record approved values and workload assumptions before implementation sign-off.

18. Acceptance Criteria & Traceability

ID	Testable acceptance condition	Requirements
AC-01	An authorized operator sends an approved campaign to all eligible customer IDs. Ineligible/opted-out marketing customers are excluded with reasons.	FR-ID-05; FR-CMP-02/06/07
AC-02	A manual phone list resolves to the correct accounts. Invalid/unmatched numbers never trigger a fallback broadcast.	FR-CMP-03/04/05
AC-03	CSV/XLSX import reports mapping errors, normalization, duplicates, ID/phone mismatches and eligibility; the final send uses the accepted customer-ID snapshot.	FR-IMP-01; FR-CMP-03/04
AC-04	A future schedule shows timezone and UTC; pending approval does not send; edits invalidate approval; permitted cancellation blocks unsent work.	FR-SCH-01/02/03; FR-SND-02
AC-05	An author cannot self-approve under the configured policy. A direct unauthorized API send is denied and audited.	FR-APR-01/02; FR-IAM-01
AC-06	Resend creates a new linked campaign, preserves selected customer IDs, follows approval and keeps original results intact.	FR-SND-03/04
AC-07	A confirmed incoming transfer notifies the recipient’s eligible devices. The payer is not substituted for the recipient. Payment succeeds even if push fails.	FR-AUTO-01; Section 10
AC-08	Repeated backend events/webhooks do not create duplicate business notifications; conflicting reuse of an event ID is rejected. Concurrent workers do not claim the same delivery.	FR-REL-01/02
AC-09	Known temporary errors back off; unregistered tokens deactivate; a submission timeout becomes unknown under the defined review policy.	FR-REL-03/04/05
AC-10	Foreground/background/open handling works on agreed Android devices without duplicate app-generated display. Receipt/open statistics remain clearly distinct from provider acceptance.	Sections 5/11; FR-ID-03

Acceptance criteria — continued

ID	Testable acceptance condition	Requirements
AC-11	Token rotation updates the current binding. Logout disables that installation; another device stays active. Account switch cannot expose the previous customer’s transaction details.	FR-ID-02/03/04/06
AC-12	Notification open after session expiry requests login, then checks ownership before fetching the referenced transfer. Invalid routes are rejected.	FR-ID-06; FR-SEC-04
AC-13	Usage sessions show agreed screens/actions. Foreground duration excludes background time; offline event retries deduplicate; inferred endings are labeled.	FR-ANA-01/02/03/05/07
AC-14	Raw payload and log review confirms no passwords, OTPs, PINs, field values, service secrets or full push tokens in analytics or staff reports.	FR-ANA-06; FR-SEC-01/05
AC-15	Role matrix is enforced on UI and APIs. Restricted roles see masked fields and cannot export or read identifiable session history without a separate grant.	FR-IAM-01; FR-CUS-06
AC-16	Dashboard metrics reproduce source records using the documented cohort/formulas; uninstrumented receipt/open metrics show N/A. Exports match active filters.	Section 5; FR-AUD-01
AC-17	Template version changes affect new events only under policy, with preview/allowed-variable validation and an auditable activation record.	FR-AUTO-02/03/04/05
AC-18	English/Arabic views, RTL navigation, responsive forms and table pagination remain usable on the approved desktop/mobile viewports.	Section 4; NFR-08
AC-19	Representative event peaks plus a large campaign meet approved queue/response targets and import limits without transaction starvation or uncontrolled resource use.	FR-REL-06; NFR-01/02/03/05
AC-20	Retention cleanup removes expired raw records/source files according to the approved policy, with operational monitoring and preserved permitted audit evidence.	NFR-09/10; FR-AUD-03

19. Dependencies, Decisions & Delivery Plan

Required inputs / decisions before scope approval

Input / decision	Owner
Actual app framework/version, Android applicationId and supported device list	Mobile Lead
Payment API authentication, stable customer ID, recipient resolution and transaction state model	Backend Lead
Event catalogue, template languages, lock-screen content and destination routes	Business + Mobile + Backend
Firebase environment/project choice, server permissions and deployment access	Operations
Audience consent/account-state rules, all-customer snapshot policy, no-device/unknown handling and resend policy	Business + Operations
Role matrix, approval thresholds, MFA/identity-provider choice and support masking	Business + Security
Expected load, hosting budget, import limits, retention and service targets	Product + Engineering + Operations
Approved screen/action inventory and analytics data-use/visibility policy	Product + Mobile + Data Owner
Named owners, estimates, target release and sign-off representatives	Project Owner

Delivery workstreams

Stage	Output / gate
1. Design and contract	Approve this CR, UX wireframes, data/event contracts, workload and role policies.
2. CMS foundation	Navigation, staff identity/RBAC, customer directory, settings and audit infrastructure.
3. Campaign workflow	Composer, number targeting/import, approval, scheduling, cancellation, resend and reports.
4. Transaction integration	Backend Outbox, authenticated ingestion, recipient binding, templates, delivery worker and recovery.
5. Mobile integration and analytics	FCM lifecycle, safe detail navigation, screen/action instrumentation and reporting.
6. Verification and rollout	Acceptance/security/load tests; staging and employee pilot; production approval; gradual rollout and monitoring.

Some workstreams may run concurrently after contracts are agreed. Engineering must provide estimates and dependency sequencing; this CR does not invent delivery dates or assume that all prototype features are production-ready.

20. Rollout, Risks & Final Sign-off

Release and rollback requirements

• Separate test and production audiences, credentials and device registrations. Test messages must not reach production customers.

• Deploy backward-compatible schema changes and server interfaces before mobile features that depend on them. Preserve existing campaign and account history.

• Provide feature controls to disable new campaigns, automated-event dispatch or usage ingestion independently; disabling push must not disable payments.

• Disable or isolate payment-simulation endpoints and test self-registration paths from production business integration.

• Pilot with explicit employee/test accounts, then a limited customer group before general availability.

• Rollback pauses new notification work safely and preserves event/audit records for reconciliation. Already submitted device notifications cannot be recalled reliably.

• Operational handover includes templates/catalogue, permission owners, runbooks, dashboards, incident escalation and retention settings.

Key risks and mitigations

Risk	Required mitigation
Wrong recipient after phone/device changes	Immutable customer IDs, verified ownership, audience snapshots and dispatch/open-time checks.
Duplicate or uncertain notification outcome	Event idempotency, delivery claims, stable IDs and an explicit unknown/retry policy.
Large campaign delays financial events	Separate priority/worker budgets; bounded batches and oldest-pending monitoring.
Analytics volume exceeds free-tier resources	Agree instrumentation scope, batch ingestion, aggregate reports and bounded retention; benchmark real workload.
Missing receipt/open evidence	Declare measurement coverage; show N/A or observed counts, not invented delivery success.
Unauthorized customer-data access or bulk send	Backend-enforced roles, masking, approval gates, individual staff accounts and audit.

Completion / release sign-off

The CR is complete only when all approved MUST requirements and acceptance criteria have evidence, outstanding defects are dispositioned, operational owners have accepted the runbook, and the release is approved by the named business and engineering owners.

Approval gate	Evidence / decision
Business acceptance	Campaign/audience rules, automatic transfer flow and templates approved.
Engineering acceptance	API contracts, identity/device lifecycle, migrations and failure recovery validated.
QA acceptance	AC-01 through AC-20 executed with results and approved exceptions.
Operations acceptance	Monitoring, access, retention, capacity and rollback verified.
Final authorization	Named approver, approved release/version and date recorded.

Named approval record

Role	Name / signature	Date / decision
Business Owner	To be assigned	Pending
Mobile Lead	To be assigned	Pending
Backend / CMS Lead	To be assigned	Pending
QA Lead	To be assigned	Pending
Operations / Security	To be assigned	Pending

Approval status: Draft. No signatures, implementation completion or production-readiness approval are implied by this document.