

```

"""
Django settings for project1 project.

Generated by 'django-admin startproject' using Django 4.1.5.

For more information on this file, see
https://docs.djangoproject.com/en/4.1/topics/settings/

For the full list of settings and their values, see
https://docs.djangoproject.com/en/4.1/ref/settings/
"""

from pathlib import Path

# Build paths inside the project like this: BASE_DIR / 'subdir'.
BASE_DIR = Path(__file__).resolve().parent.parent

# Quick-start development settings - unsuitable for production
# See https://docs.djangoproject.com/en/4.1/howto/deployment/checklist/

# SECURITY WARNING: keep the secret key used in production secret!
SECRET_KEY = 'django-insecure-q!waelj6h+s=zbq=wl-^bsjeggw-09qcnx$neav0a8a&g@2@5)'

# SECURITY WARNING: don't run with debug turned on in production!
DEBUG = True

ALLOWED_HOSTS = []

# Application definition

INSTALLED_APPS = [
    'django.contrib.admin',
    'django.contrib.auth',
    'django.contrib.contenttypes',
    'django.contrib.sessions',
    'django.contrib.messages',
    'django.contrib.staticfiles',
    'imdb',
    'rest_framework',
    "corsheaders",
]

MIDDLEWARE = [
    'django.middleware.security.SecurityMiddleware',
    'django.contrib.sessions.middleware.SessionMiddleware',
    'django.middleware.common.CommonMiddleware',
    'django.middleware.csrf.CsrfViewMiddleware',
    'django.contrib.auth.middleware.AuthenticationMiddleware',
    'django.contrib.messages.middleware.MessageMiddleware',
    'django.middleware.clickjacking.XFrameOptionsMiddleware',
    "corsheaders.middleware.CorsMiddleware",
    "corsheaders.middleware.CorsPostCsrfMiddleware",
]

ROOT_URLCONF = 'project1.urls'

TEMPLATES = [
    {
        'BACKEND': 'django.template.backends.django.DjangoTemplates',
        'DIRS': [],
    }
]

```

```

        'APP_DIRS': True,
        'OPTIONS': {
            'context_processors': [
                'django.template.context_processors.debug',
                'django.template.context_processors.request',
                'django.contrib.auth.context_processors.auth',
                'django.contrib.messages.context_processors.messages',
            ],
        },
    ],
]

```

```
WSGI_APPLICATION = 'project1.wsgi.application'
```

```

# Database
# https://docs.djangoproject.com/en/4.1/ref/settings/#databases

```

```

DATABASES = {
    'default': {
        'ENGINE': 'django.db.backends.sqlite3',
        'NAME': BASE_DIR / 'db.sqlite3',
    }
}

```

```

# Password validation
# https://docs.djangoproject.com/en/4.1/ref/settings/#auth-password-validators

```

```

AUTH_PASSWORD_VALIDATORS = [
    {
        'NAME':
        'django.contrib.auth.password_validation.UserAttributeSimilarityValidator',
    },
    {
        'NAME':
        'django.contrib.auth.password_validation.MinimumLengthValidator',
    },
    {
        'NAME':
        'django.contrib.auth.password_validation.CommonPasswordValidator',
    },
    {
        'NAME':
        'django.contrib.auth.password_validation.NumericPasswordValidator',
    },
]

```

```

# Internationalization
# https://docs.djangoproject.com/en/4.1/topics/i18n/

```

```
LANGUAGE_CODE = 'en-us'
```

```
TIME_ZONE = 'Europe/Kiev'
```

```
USE_I18N = True
```

```
USE_TZ = True
```

```
# Static files (CSS, JavaScript, Images)
# https://docs.djangoproject.com/en/4.1/howto/static-files/

STATIC_URL = 'static/'
MEDIA_URL = 'media/'
MEDIA_ROOT = 'mediafiles'

# Default primary key field type
# https://docs.djangoproject.com/en/4.1/ref/settings/#default-auto-field

DEFAULT_AUTO_FIELD = 'django.db.models.BigAutoField'

CORS_ALLOWED_ORIGINS = [
    "http://localhost:8001",
]

CSRF_TRUSTED_ORIGINS = [
    "http://localhost:8001",
]

CORS_ALLOW_METHODS = [
    "DELETE",
    "GET",
    "POST",
]

CORS_ALLOW_HEADERS = [
    "accept",
    "accept-encoding",
    "authorization",
    "content-type",
    "dnt",
    "origin",
    "user-agent",
    "x-csrftoken",
    "x-requested-with",
]
```