

Contents		6.16 FFT	15
		6.17 NTT	16
		6.18 WalshHadamard	16
1	All Macros	1	
2	DP	1	
2.1	1D-1D	1	
2.2	Convex Hull Trick	1	
2.3	Divide and Conquer dp	2	
2.4	Knuth optimization	2	
2.5	Li Chao Tree	2	
3	Data Structure	2	
3.1	BIT-2D	2	
3.2	Divide And Conquer Query Offline	2	
3.3	MO with Update	2	
3.4	Merge Sort Tree	3	
3.5	SparseTable (Rectangle Query)	3	
3.6	Segment Tree	3	
3.7	Persistent Segment Tree	3	
3.8	Implicit Segment Tree	4	
3.9	HashTable	4	
3.10	Treap	4	
3.11	DSU With Rollbacks	5	
3.12	Binary Trie	5	
4	Geometry	5	
4.1	Point	5	
4.2	Linear	5	
4.3	Circular	6	
4.4	Convex	7	
4.5	Polygon	8	
4.6	Intersecting Segments	8	
5	Graph	9	
5.1	Link Cut Tree	9	
5.2	Graph Template	9	
5.3	LCA, ETT, VT	9	
5.4	SCC	10	
5.5	Euler Tour on Edge	10	
5.6	LCA In O(1)	10	
5.7	HLD	10	
5.8	Centroid Decomposition	11	
5.9	Dinic Max Flow	11	
5.10	Min Cost Max Flow	11	
5.11	StoerWanger	12	
5.12	Hungarian	12	
5.13	Block Cut Tree	12	
5.14	Bridge Tree	12	
5.15	Tree Isomorphism	13	
6	Math	13	
6.1	Adaptive Simpsons	13	
6.2	Berlekamp Massey	13	
6.3	Fractional Binary Search	13	
6.4	Gaussian Elimination	13	
6.5	Green Hackenbush	14	
6.6	Lagrange	14	
6.7	Matrix Exponentiation	14	
6.8	Pollard Rho	14	
6.9	Shanks' Baby Step, Giant Step	15	
6.10	Stirling Numbers	15	
6.11	Xor Basis	15	
6.12	Combi	15	
6.13	Linear Sieve	15	
6.14	Chinese Remainder Theorem	15	
6.15	Mobius Function	15	
7	String	16	
7.1	Aho Corasick	16	
7.2	Double hash	17	
7.3	Manacher's	17	
7.4	Palindromic Tree	17	
7.5	String Match FFT	18	
7.6	Suffix Array	18	
7.7	Suffix Automata	18	
7.8	Z Algo	19	
8	Equations and Formulas	20	
8.1	Catalan Numbers	20	
8.2	Stirling Numbers First Kind .	20	
8.3	Stirling Numbers Second Kind	20	
8.4	Other Combinatorial Identities	20	
8.5	Different Math Formulas . . .	20	
8.6	GCD and LCM	20	

Sublime Build

```
{
    "cmd" : ["g++ -std=c++14 -DSONIC
        $file_name -o $file_base_name &&
        timeout 4s ./ $file_base_name

```

vimrc

```
set mouse=a
set termguicolors
filetype plugin indent on
syntax on
```

```
" Some useful settings
set smartindent expandtab ignorecase
    smartcase incsearch relativenumber
    nowrap autoread splitright splitbelow
set tabstop=4        "the width of a tab
set shiftwidth=4     "the width for indent
colorscheme torte
```

```
"auto pair curlybraces
inoremap {<ENTER> {}<LEFT><CR><ESC><S-o>
```

```
" mapping jj to esc
inoremap jj <ESC>
```

```
"compile and run using file input put
autocmd filetype cpp map <F5> :wa<CR>:!
    clear && g++ % -D LOCAL -std=c++17 -
    Wall -Wextra -Wconversion -Wshadow -
    Wfloat-equal -o ~/Codes/prog && (
    timeout 5 ~/Codes/prog < ~/Codes/in)
    > ~/Codes/out<CR>
```

```
"copy to input file
map <F4> :!xclip -o -sel clip > ~/Codes/in
    <CR><CR>
map <F6> :vsplit ~/Codes/in<CR>:split ~/
    Codes/out<CR><C-w>=20<C-w><<C-w><C-h>
```

```
" Leader key
let mapleader=',,'
```

```
" Copy template
noremap <Leader>t :!cp ~/Codes/temp.cpp %<
    CR><CR>
:autocmd BufNewFile *.cpp Or ~/Codes/temp.
    cpp
```

```
"note if vim-features +clipboard is not
    found, it will not work
"for fast check :echo has('clipboard') = 0
    if clipboard features not present,
"need vim-gtk / vim-gtk3 package for this
    set clipboard=unnamedplus
```

1 All Macros

```
//#pragma GCC optimize("Ofast")
//#pragma GCC optimization ("O3")
//#pragma comment(linker, "/stack
    :2000000000")
//#pragma GCC optimize("unroll-loops")
//#pragma GCC target("sse,sse2,sse3,ssse3,
    sse4,popcnt,abm,mmx,avx,tune=native")

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
    //find_by_order(k) --> returns iterator
    to the kth largest element counting
    from 0
    //order_of_key(val) --> returns the
    number of items in a set that are
    strictly smaller than our item
template <typename DT>
using ordered_set = tree <DT, null_type,
    less<DT>, rb_tree_tag,
```

```
tree_order_statistics_node_update>;
```

```
/*--- DEBUG TEMPLATE STARTS HERE ---*/
#ifdef LEL
void show(int x) {cerr << x;}
void show(long long x) {cerr << x;}
void show(double x) {cerr << x;}
void show(char x) {cerr << '\'' << x << '\''
    ;}
void show(const string &x) {cerr << '\\"' <<
    x << '\\"';}
void show(bool x) {cerr << (x ? "true" : "
    false");}
```

```
template<typename T, typename V>
void show(pair<T, V> x) { cerr << '\''; show(
    x.first); cerr << ", "; show(x.second); }
    cerr << '\''; }
```

```
template<typename T>
void show(T x) {int f = 0; cerr << "{"; for
    (auto &i: x) cerr << (f++ ? ", " : ""),
    show(i); cerr << "}";}
```

```
void debug_out(string s) {
    cerr << '\n';
}
```

```
template <typename T, typename... V>
void debug_out(string s, T t, V... v) {
    s.erase(remove(s.begin(), s.end(), ' '),
        s.end());
    cerr << " "; // 8 spaces
    cerr << s.substr(0, s.find(','));
    s = s.substr(s.find(',') + 1);
    cerr << " = ";
    show(t);
    cerr << endl;
    if(sizeof...(v)) debug_out(s, v...);
}
```

```
#define debug(x...) cerr << "LINE: " <<
    __LINE__ << endl; debug_out(#x, x);
    cerr << endl;
```

```
#else
#define debug(x...)
#endif
```

2 DP

2.1 1D-1D

```
/// Author: anachor
#include <bits/stdc++.h>
using namespace std;

/// Solves dp[i] = min(dp[j] + cost(j+1, i))
    given that cost() is QF
long long solve1D(int n, long long cost(int,
    int)) {
    vector<long long> dp(n + 1, opt(n + 1));
    deque<pair<int, int>> dq;
    dq.push_back({0, 1});
    dp[0] = 0;
```

```
for (int i = 1; i <= n; i++) {
    opt[i] = dq.front().first;
    dp[i] = dp[opt[i]] + cost(opt[i] + 1, i)
        ;
    if (i == n) break;
```

```
    dq[0].second++;
    if (dq.size() > 1 && dq[0].second == dq
        [1].second) dq.pop_front();
```

```
int en = n;
while (dq.size()) {
    int o = dq.back().first, st = dq.back()
        .second;
    if (dp[o] + cost(o + 1, st) >= dp[i] +
        cost(i + 1, st))
        dq.pop_back();
    else {
        int lo = st, hi = en;
        while (lo < hi) {
            int mid = (lo + hi + 1) / 2;
```

```
if (dp[o] + cost(o + 1, mid) < dp[i]
    ] + cost(i + 1, mid))
    lo = mid;
else
    hi = mid - 1;
}
if (lo < n) dq.push_back({i, lo +
    1});
break;
}
en = st - 1;
}
if (dq.empty()) dq.push_back({i, i + 1})
    ;
}
```

```
return dp[n];
```

```
/// Solves https://open.kattis.com/problems/coveredwalkway
```

```
const int N = 1e6 + 7;
long long x[N];
int c;
long long cost(int l, int r) { return (x[r]
    - x[l]) * (x[r] - x[l]) + c; }
```

```
int main() {
    ios::sync_with_stdio(false);
    cin.tie(0);
```

```
int n;
cin >> n >> c;
for (int i = 1; i <= n; i++) cin >> x[i];
cout << solve1D(n, cost) << endl;
}
```

2.2 Convex Hull Trick

```
struct line {
    ll m, c;
    line() {}
    line(ll m, ll c) : m(m), c(c) {}
};
struct convex_hull_trick {
    vector<line> lines;
    int ptr = 0;
    convex_hull_trick() {}
    bool bad(line a, line b, line c) {
        return 1.0 * (c.c - a.c) * (a.m - b.m) <
            1.0 * (b.c - a.c) * (a.m - c.m);
    }
    void add(line L) {
        int sz = lines.size();
        while (sz >= 2 && bad(lines[sz - 2],
            lines[sz - 1], L)) {
            lines.pop_back();
            sz--;
        }
        lines.pb(L);
    }
    ll get(int idx, int x) { return (ll *
        lines[idx].m * x + lines[idx].c); }
    ll query(int x) {
        if (lines.empty()) return 0;
        if (ptr >= lines.size()) ptr = lines.
            size() - 1;
        while (ptr < lines.size() - 1 && get(ptr
            , x) > get(ptr + 1, x)) ptr++;
        return get(ptr, x);
    }
};
ll sum[MAX];
ll dp[MAX];
int arr[MAX];
int main() {
    fastio;
    int t;
    cin >> t;
    while (t--) {
        int n, a, b, c;
        cin >> n >> a >> b >> c;
        for (int i = 1; i <= n; i++) cin >> sum[
            i];
        for (int i = 1; i <= n; i++) dp[i] = 0,
            sum[i] += sum[i - 1];
```

```

convex_hull_trick cht;
cht.add(line(0, 0));
for (int pos = 1; pos <= n; pos++) {
    dp[pos] = cht.query(sum[pos]) - 1ll *
        a * sqr(sum[pos]) - c;
    cht.add(line(2ll * a * sum[pos], dp[
        pos] - a * sqr(sum[pos])));
}
ll ans = (-1ll * dp[n]);
ans += (1ll * sum[n] * b);
cout << ans << "\n";
}
}

```

2.3 Divide and Conquer dp

```

const int K = 805, N = 4005;
LL dp[2][N], _cost[N][N];
// 1-indexed for convenience
LL cost(int l, int r) {
    return _cost[r][r] - _cost[l - 1][r] -
        _cost[r][l - 1] + _cost[l - 1][l - 1]
        >> 1;
}
void compute(int cnt, int l, int r, int optl
    , int optr) {
    if (l > r) return;
    int mid = l + r >> 1;
    LL best = INT_MAX;
    int opt = -1;
    for (int i = optl; i <= min(mid, optr); i
        ++){
        LL cur = dp[cnt ^ 1][i - 1] + cost(i,
            mid);
        if (cur < best) best = cur, opt = i;
    }
    dp[cnt][mid] = best;
    compute(cnt, l, mid - 1, optl, opt);
    compute(cnt, mid + 1, r, opt, optr);
}
LL dnc_dp(int k, int n) {
    fill(dp[0] + 1, dp[0] + n + 1, INT_MAX);
    for (int cnt = 1; cnt <= k; cnt++) {
        compute(cnt & 1, 1, n, 1, n);
    }
    return dp[k & 1][n];
}
}

```

2.4 Knuth optimization

```

const int N = 1005;
LL dp[N][N], a[N];
int opt[N][N];
LL cost(int i, int j) { return a[j + 1] - a[i]; }
LL knuth_optimization(int n) {
    for (int i = 0; i < n; i++) {
        dp[i][i] = 0;
        opt[i][i] = i;
    }
    for (int i = n - 2; i >= 0; i--) {
        for (int j = i + 1; j < n; j++) {
            LL mn = LLONG_MAX;
            LL c = cost(i, j);
            for (int k = opt[i][j - 1]; k <= min(j
                - 1, opt[i + 1][j]); k++) {
                if (mn > dp[i][k] + dp[k + 1][j] + c
                    ) {
                    mn = dp[i][k] + dp[k + 1][j] + c;
                    opt[i][j] = k;
                }
            }
            dp[i][j] = mn;
        }
    }
    return dp[0][n - 1];
}
}

```

2.5 Li Chao Tree

```

struct line {
    LL m, c;
    line(LL m = 0, LL c = 0) : m(m), c(c) {}
};
LL calc(line L, LL x){ return 1LL * L.m * x
    + L.c; }

```

```

struct node {
    LL m, c;
    line L;
    node *lft, *rt;
    node(LL m = 0, LL c = 0, node *lft = NULL,
        node *rt = NULL)
        : L(line(m, c)), lft(lft), rt(rt) {}
};
struct LiChao {
    node *root;
    LiChao() { root = new node(); }
    void update(node *now, int L, int R, line
        newline) {
        int mid = L + (R - L) / 2;
        line lo = now->L, hi = newline;
        if (calc(lo, L) > calc(hi, L)) swap(lo,
            hi);
        if (calc(lo, R) <= calc(hi, R)) {
            now->L = hi;
            return;
        }
        if (calc(lo, mid) < calc(hi, mid)) {
            now->L = hi;
            if (now->rt == NULL) now->rt = new
                node();
            update(now->rt, mid + 1, R, lo);
        } else {
            now->L = lo;
            if (now->lft == NULL) now->lft = new
                node();
            update(now->lft, L, mid, hi);
        }
    }
    LL query(node *now, int L, int R, LL x) {
        if (now == NULL) return -inf;
        int mid = L + (R - L) / 2;
        if (x <= mid)
            return max(calc(now->L, x), query(now
                ->lft, L, mid, x));
        else
            return max(calc(now->L, x), query(now
                ->rt, mid + 1, R, x));
    }
};

```

3 Data Structure

3.1 BIT-2D

```

const int N = 1008;
int bit[N][N], n, m;
int a[N][N], q;
void update(int x, int y, int val) {
    for (; x < N; x += -x & x)
        for (int j = y; j < N; j += -j & j) bit[
            x][j] += val;
}
int get(int x, int y) {
    int ans = 0;
    for (; x; x -= x & -x)
        for (int j = y; j; j -= j & -j) ans +=
            bit[x][j];
    return ans;
}
int get(int x1, int y1, int x2, int y2) {
    return get(x2, y2) - get(x1 - 1, y2) - get
        (x2, y1 - 1) + get(x1 - 1, y1 - 1);
}

```

3.2 Divide And Conquer Query Of- fine

```

namespace up {
    int l[N], r[N], u[N], v[N], tm;
    void push(int _l, int _r, int _u, int _v) {
        l[tm] = _l, r[tm] = _r, u[tm] = _u, v[tm]
            = _v;
        tm++;
    }
} // namespace up
namespace que {
    int node[N], tm;
    LL ans[N];
    void push(int _node) { node[++tm] = _node; }
} // namespace que

```

```

namespace edge_set {
    void push(int i) { dsu ::merge(up ::u[i], up
        ::v[i]); }
    void pop(int t) { dsu ::rollback(t); }
    int time() { return dsu ::op.size(); }
    LL query(int u) { return a[dsu ::root(u)]; }
} // namespace edge_set
namespace dncq {
    vector<int> tree[4 * N];
    void update(int idx, int l = 0, int r = que
        ::tm, int node = 1) {
        int ul = up ::l[idx], ur = up ::r[idx];
        if (r < ul || ur < l) return;
        if (ul <= l and r <= ur) {
            tree[node].push_back(idx);
            return;
        }
        int m = l + r >> 1;
        update(idx, l, m, node << 1);
        update(idx, m + 1, r, node << 1 | 1);
    }
    void dfs(int l = 0, int r = que ::tm, int
        node = 1) {
        int cur = edge_set ::time();
        for (int e : tree[node]) edge_set ::push(e
            );
        if (l == r) {
            que ::ans[l] = edge_set ::query(que ::
                node[l]);
        } else {
            int m = l + r >> 1;
            dfs(l, m, node << 1);
            dfs(m + 1, r, node << 1 | 1);
        }
        edge_set ::pop(cur);
    }
} // namespace dncq
void push_updates() {
    for (int i = 0; i < up ::tm; i++) dncq ::
        update(i);
}

```

3.3 MO with Update

```

const int N = 1e5 + 5, sz = 2700, bs = 25;
int arr[N], freq[2 * N], cnt[2 * N], id[N],
    ans[N];
struct query {
    int l, r, t, L, R;
    query(int l = 1, int r = 0, int t = 1, int
        id = -1)
        : l(l), r(r), t(t), L(L / sz), R(R /
            sz) {}
    bool operator<(const query &rhs) const {
        return (L < rhs.L) or (L == rhs.L and R
            < rhs.R) or
            (L == rhs.L and R == rhs.R and t <
                rhs.t);
    }
} Q[N];
struct update {
    int idx, val, last;
} Up[N];
int qi = 0, ui = 0;
int l = 1, r = 0, t = 0;
void add(int idx) {
    --cnt[freq[arr[idx]]];
    freq[arr[idx]]++;
    cnt[freq[arr[idx]]]++;
}
void remove(int idx) {
    --cnt[freq[arr[idx]]];
    freq[arr[idx]]--;
    cnt[freq[arr[idx]]]++;
}
void apply(int t) {
    const bool f = l <= Up[t].idx and Up[t].
        idx <= r;
    if (f) remove(Up[t].idx);
    arr[Up[t].idx] = Up[t].val;
    if (f) add(Up[t].idx);
}
void undo(int t) {

```

```

const bool f = 1 <= Up[t].idx and Up[t].
    idx <= r;
if (f) remove(Up[t].idx);
arr[Up[t].idx] = Up[t].last;
if (f) add(Up[t].idx);
}
int mex() {
    for (int i = 1; i <= N; i++)
        if (!cnt[i]) return i;
    assert(0);
}
int main() {
    int n, q;
    cin >> n >> q;
    int counter = 0;
    map<int, int> M;
    for (int i = 1; i <= n; i++) {
        cin >> arr[i];
        if (!M[arr[i]]) M[arr[i]] = ++counter;
        arr[i] = M[arr[i]];
    }
    iota(id, id + N, 0);
    while (q--) {
        int tp, x, y;
        cin >> tp >> x >> y;
        if (tp == 1)
            Q[++qi] = query(x, y, ui);
        else {
            if (!M[y]) M[y] = ++counter;
            y = M[y];
            Up[++ui] = {x, y, arr[x]};
            arr[x] = y;
        }
    }
    t = ui;
    cnt[0] = 3 * n;
    sort(id + 1, id + qi + 1, [&](int x, int y) { return Q[x] < Q[y]; });
    for (int i = 1; i <= qi; i++) {
        int x = id[i];
        while (Q[x].t > t) apply(++t);
        while (Q[x].t < t) undo(t--);
        while (Q[x].l < 1) add(--l);
        while (Q[x].r > r) add(++r);
        while (Q[x].l > 1) remove(l++);
        while (Q[x].r < r) remove(r--);
        ans[x] = mex();
    }
    for (int i = 1; i <= qi; i++) cout << ans[i] << '\n';
}

```

3.4 Merge Sort Tree

```

vector<LL> Tree[4 * MAXN];
LL arr[MAXN];

vector<LL> merge(vector<LL> v1, vector<LL> v2) {
    LL i = 0, j = 0;
    vector<LL> ret;

    while (i < v1.size() || j < v2.size()) {
        if (i == v1.size()) {
            ret.push_back(v2[j]);
            j++;
        } else if (j == v2.size()) {
            ret.push_back(v1[i]);
            i++;
        } else {
            if (v1[i] < v2[j]) {
                ret.push_back(v1[i]);
                i++;
            } else {
                ret.push_back(v2[j]);
                j++;
            }
        }
    }

    return ret;
}

void Build(LL node, LL bg, LL ed) {
    if (bg == ed) {

```

```

        Tree[node].push_back(arr[bg]);
        return;
    }

    LL leftNode = 2 * node, rightNode = 2 * node + 1;
    LL mid = (bg + ed) / 2;

    Build(leftNode, bg, mid);
    Build(rightNode, mid + 1, ed);

    Tree[node] = merge(Tree[leftNode], Tree[rightNode]);
}

LL query(LL node, LL bg, LL ed, LL l, LL r, LL k) {
    if (ed < l || bg > r) return 0;

    if (l <= bg && ed <= r)
        return upper_bound(Tree[node].begin(), Tree[node].end(), k) - Tree[node].begin();

    LL leftNode = 2 * node, rightNode = 2 * node + 1;
    LL mid = (bg + ed) / 2;

    return query(leftNode, bg, mid, l, r, k) + query(rightNode, mid + 1, ed, l, r, k);
}

```

3.5 SparseTable (Rectangle Query)

```

#include <bits/stdc++.h>
using namespace std;

const int MAXN = 505;
const int LOGN = 9;

// 0(n^2 (logn)^2
// Supports Rectangular Query
int A[MAXN][MAXN];
int M[MAXN][MAXN][LOGN][LOGN];

void Build2DSparse(int N) {
    for (int i = 1; i <= N; i++) {
        for (int j = 1; j <= N; j++) {
            M[i][j][0][0] = A[i][j];
        }
        for (int q = 1; (1 << q) <= N; q++) {
            int add = 1 << (q - 1);
            for (int j = 1; j + add <= N; j++) {
                M[i][j][q][q] = max(M[i][j][q-1][q-1], M[i][j+add][q-1][q-1]);
            }
        }
    }
}

// returns max of all A[i][j], where x1<=i<=x2 and y1<=j<=y2
int Query(int x1, int y1, int x2, int y2) {
    int kX = log2(x2 - x1 + 1);
    int kY = log2(y2 - y1 + 1);
    int addX = 1 << kX;
    int addY = 1 << kY;

    int ret1 = max(M[x1][y1][kX][kY], M[x1][y2 - addY + 1][kX][kY]);
    int ret2 = max(M[x2 - addX + 1][y1][kX][kY],

```

```

        M[x2 - addX + 1][y2 - addY + 1][kX][kY]);
    return max(ret1, ret2);
}

```

3.6 Segment Tree

```

const int N = 1000006;

using DT = LL;
using LT = LL;
constexpr DT I = 0;
constexpr LT None = 0;
DT val[4 * N];
LT lazy[4 * N];
int L, R;

void pull(int s, int e, int node) {
    val[node] = val[node << 1] + val[node << 1 | 1];
}

void apply(const LT &U, int s, int e, int node) {
    val[node] += (e - s + 1) * U;
    lazy[node] += U;
}

void reset(int node) { lazy[node] = None; }
DT merge(const DT &a, const DT &b) { return a + b; }
DT get(int s, int e, int node) { return val[node]; }

void push(int s, int e, int node) {
    if (s == e) return;
    apply(lazy[node], s, s + e >> 1, node << 1);
    apply(lazy[node], s + e >> 1, e, node << 1 | 1);
    reset(node);
}

void build(int s, int e, vector<DT> &v, int node = 1) {
    int m = s + e >> 1;
    if (s == e) {
        val[node] = v[s];
        return;
    }
    build(s, m, v, node * 2);
    build(m + 1, e, v, node * 2 + 1);
    pull(s, e, node);
}

void update(int S, int E, LT uval, int s = L, int e = R, int node = 1) {
    if (S > E) return;
    if (S == s and E == e) {
        apply(uval, s, e, node);
        return;
    }
    push(s, e, node);
    int m = s + e >> 1;
    update(S, min(m, E), uval, s, m, node * 2);
    update(max(S, m + 1), E, uval, m + 1, e, node * 2 + 1);
    pull(s, e, node);
}

DT query(int S, int E, int s = L, int e = R, int node = 1) {
    if (S > E) return I;
    if (s == S and e == E) return get(s, e, node);
    push(s, e, node);
    int m = s + e >> 1;
    DT L = query(S, min(m, E), s, m, node * 2);
    DT R = query(max(S, m + 1), E, m + 1, e, node * 2 + 1);
    return merge(L, R);
}

void init(int _L, int _R, vector<DT> &v) {
    L = _L, R = _R;
    build(L, R, v);
}

```

3.7 Persistent Segment Tree

```

struct Node {
    Node *l, *r;
    int sum;

    Node(int val) : l(nullptr), r(nullptr),
        sum(val) {}
    Node(Node* l, Node* r) : l(l), r(r), sum
        (0) {
        if (l) sum += l->sum;
        if (r) sum += r->sum;
    }
};

int a[MAXN];
Node* root[MAXN];

Node* Build(int bg, int ed) {
    if (bg == ed) return new Node(a[bg]);
    int mid = (bg + ed) / 2;
    return new Node(Build(bg, mid), Build(mid
        + 1, ed));
}

int Query(Node* v, int bg, int ed, int l,
    int r) {
    if (l > ed || r < bg) return 0;
    if (l <= bg && ed <= r) return v->sum;
    int mid = (bg + ed) / 2;
    return Query(v->l, bg, mid, l, r) + Query(
        v->r, mid + 1, ed, l, r);
}

Node* Update(Node* v, int bg, int ed, int
    pos, int new_val) {
    if (bg == ed) return new Node(v->sum +
        new_val);
    int mid = (bg + ed) / 2;
    if (pos <= mid)
        return new Node(Update(v->l, bg, mid,
            pos, new_val), v->r);
    else
        return new Node(v->l, Update(v->r, mid +
            1, ed, pos, new_val));
}

```

3.8 Implicit Segment Tree

```

struct node {
    int val;
    node *lft, *rt;
    node() {}
    node(int val = 0) : val(val), lft(NULL),
        rt(NULL) {}
};

struct implicit_segtree {
    node *root;
    implicit_segtree() {}
    implicit_segtree(int n) {
        root = new node(n);
    }
    void update(node *now, int L, int R, int
        idx, int val) {
        if (L == R) {
            now->val += val;
            return;
        }
        int mid = L + (R - L) / 2;
        if (now->lft == NULL) now->lft = new
            node(mid - L + 1);
        if (now->rt == NULL) now->rt = new node(
            R - mid);
        if (idx <= mid) update(now->lft, L, mid,
            idx, val);
        else update(now->rt, mid + 1, R, idx,
            val);
        now->val = (now->lft->val + (now->rt->
            val);
    }

    int query(node *now, int L, int R, int k)
    {
        if (L == R) return L;
        int mid = L + (R - L) / 2;

```

```

        if (now->lft == NULL) now->lft = new
            node(mid - L + 1);
        if (now->rt == NULL) now->rt = new node(
            R - mid);
        if (k <= (now->lft->val) return query(
            now->lft, L, mid, k);
        else return query(now->rt, mid + 1, R, k
            - (now->lft->val);
    }
};

```

3.9 HashTable

```

#include <bits/stdc++.h>
#include <ext/pb_ds/assoc_container.hpp>
using namespace std;
using namespace __gnu_pbds;

const int RANDOM =
    chrono::high_resolution_clock::now().
        time_since_epoch().count();
unsigned hash_f(unsigned x) {
    x = ((x >> 16) ^ x) * 0x45d9f3b;
    x = ((x >> 16) ^ x) * 0x45d9f3b;
    x = (x >> 16) ^ x;
    return x;
}

unsigned hash_combine(unsigned a, unsigned b)
    { return a * 31 + b; }
struct chash {
    int operator()(int x) const { return
        hash_f(x); }
};
typedef gp_hash_table<int, int, chash> gp;
gp table;

```

3.10 Treap

```

mt19937 rnd(chrono::steady_clock::now().
    time_since_epoch().count());
typedef struct node* pnode;
struct node {
    int prior, val, sz;
    ll sum;
    node *lft, *rt;
    node(int val = 0, node *lft = NULL, node *
        rt = NULL) :
        lft(lft), rt(rt), prior(rnd()), val(val)
        , sz(1), sum(0) {}
};
struct treap {
    pnode root;
    treap() {
        root = NULL;
    }
    int get_sz(pnode now) {
        return now ? now->sz : 0;
    }
    void update_sz(pnode now) {
        if (!now) return;
        now->sz = 1 + get_sz(now->lft) + get_sz(
            now->rt);
    }
    ll get(pnode now) {
        return now ? now->sum : 0;
    }
    void push(pnode now) {}
    void combine(pnode now) {
        if (!now) return;
        now->sum = now->val + get(now->lft) +
            get(now->rt);
    }
    pnode unite(pnode lft, pnode rt) {
        if (!lft || !rt) return lft ? lft : rt;
        // push(lft), push(rt); this not tested
        if (lft->prior < rt->prior) swap(lft, rt
            );
        pnode l, r;
        split(rt, l, r, lft->val);
        lft->lft = unite(lft->lft, l), update_sz
            (lft);
        lft->rt = unite(lft->rt, r), update_sz(
            lft);
        // combine(lft); this not tested

```

```

        return lft;
    }
    //value < val goes to left, value >= val
    goes to right
    void split(pnode now, pnode &lft, pnode &
        rt, int val, int add = 0) {
        push(now);
        if (!now) return void(lft = rt = NULL);
        if (now->val < val) split(now->rt, now->
            rt, rt, val), lft = now;
        else split(now->lft, lft, now->lft, val)
            , rt = now;
        update_sz(now), combine(now);
    }
    void merge(pnode &now, pnode lft, pnode rt)
    {
        push(lft), push(rt);
        if (!lft || !rt) now = lft ? lft : rt;
        else if (lft->prior > rt->prior) merge(
            lft->rt, lft->rt, rt), now = lft;
        else merge(rt->lft, lft, rt->lft), now =
            rt;
        update_sz(now), combine(now);
    }
    void insert(pnode &now, pnode notun) {
        if (!now) return void(now = notun);
        push(now);
        if (notun->prior > now->prior) split(now
            , notun->lft, notun->rt, notun->val)
            , now = notun;
        else insert(notun->val < now->val ? now
            ->lft : now->rt, notun);
        update_sz(now), combine(now);
    }
    void erase(pnode &now, int val) {
        push(now);
        if (now->val == val) {
            pnode temp = now;
            merge(now, now->lft, now->rt);
            delete(temp);
        } else erase(val < now->val ? now->lft :
            now->rt, val);
        update_sz(now), combine(now);
    }
    int get_idx(pnode &now, int val) {
        if (!now) return INT_MIN;
        else if (now->val == val) return 1 +
            get_sz(now->lft);
        else if (val < now->val) return get_idx(
            now->lft, val);
        else return (1 + get_sz(now->lft) +
            get_idx(now->rt, val));
    }
    int find_kth(pnode &now, int k) {
        if (k < 1 || k > get_sz(now)) return -1;
        if (get_sz(now->lft) + 1 == k) return
            now->val;
        if (k <= get_sz(now->lft)) return
            find_kth(now->lft, k);
        return find_kth(now->rt, k - get_sz(now
            ->lft) - 1);
    }
    ll prefix_sum(pnode &now, int k) {
        if (k < 1 || k > get_sz(now)) return -
            inf;
        if (get_sz(now->lft) + 1 == k) return
            get(now->lft) + now->val;
        if (k <= get_sz(now->lft)) return
            prefix_sum(now->lft, k);
        return get(now->lft) + now->val +
            prefix_sum(now->rt, k - get_sz(now
            ->lft) - 1);
    }
    pnode get_rng(int l, int r) { //gets all
        l <= values <= r
        pnode lft, rt, mid;
        split(root, lft, mid, l);
        split(mid, mid, rt, r + 1);
        merge(root, lft, rt);
        return mid;
    }
    void output(pnode now, vector<int>&v) {
        if (!now) return;
        output(now->lft, v);

```



```

    v.pb(now->val);
    output(now->rt, v);
}
vector<int>get_arr() {
    vector<int>ret;
    output(root, ret);
    return ret;
}
};

```

3.11 DSU With Rollbacks

```

struct Rollback_DSU {
    int n;
    vector<int> par, sz;
    vector<pair<int, int>> op;
    Rollback_DSU(int n) : par(n), sz(n, 1) {
        iota(par.begin(), par.end(), 0);
        op.reserve(n);
    }
    int Anc(int node) {
        for (; node != par[node]; node = par[
            node])
            ; // no path compression
        return node;
    }
    void Unite(int x, int y) {
        if (sz[x = Anc(x)] < sz[y = Anc(y)])
            swap(x, y);
        op.emplace_back(x, y);
        par[y] = x;
        sz[x] += sz[y];
    }
    void Undo(int t) {
        for (; op.size() > t; op.pop_back()) {
            par[op.back().second] = op.back().
                second;
            sz[op.back().first] -= sz[op.back().
                second];
        }
    }
};

```

3.12 Binary Trie

```

const int N = 1e7 + 5, b = 30;
int tc = 1;
struct node {
    int vis = 0;
    int to[2] = {0, 0};
    int val[2] = {0, 0};
    void update() {
        to[0] = to[1] = 0;
        val[0] = val[1] = 0;
        vis = tc;
    }
} T[N + 2];
node *root = T;
int ptr = 0;
node *nxt(node *cur, int x) {
    if (cur->to[x] == 0) cur->to[x] = ++ptr;
    assert(ptr < N);
    int idx = cur->to[x];
    if (T[idx].vis < tc) T[idx].update();
    return T + idx;
}
int query(int j, int aj) {
    int ans = 0, jaj = j ^ aj;
    node *cur = root;
    for (int k = b - 1; ~k; k--) {
        maximize(ans, nxt(cur, (jaj >> k & 1) ^
            1)->val[1 ^ (aj >> k & 1)]);
        cur = nxt(cur, (jaj >> k & 1));
    }
    return ans;
}
void insert(int j, int aj, int val) {
    int jaj = j ^ aj;
    node *cur = root;
    for (int k = b - 1; ~k; k--) {
        cur = nxt(cur, (jaj >> k & 1));
        maximize(cur->val[j >> k & 1], val);
    }
}
void clear() {

```

```

    tc++;
    ptr = 0;
    root->update();
}

```

4 Geometry

4.1 Point

```

typedef double Tf;
typedef double Ti; /// use long long for
    exactness
const Tf PI = acos(-1), EPS = 1e-9;
int dcmp(Tf x) { return abs(x) < EPS ? 0 : (
    x < 0 ? -1 : 1); }

struct Point {
    Ti x, y;
    Point(Ti x = 0, Ti y = 0) : x(x), y(y) {}

    Point operator+(const Point& u) const {
        return Point(x + u.x, y + u.y); }
    Point operator-(const Point& u) const {
        return Point(x - u.x, y - u.y); }
    Point operator*(const LL u) const { return
        Point(x * u, y * u); }
    Point operator*(const Tf u) const { return
        Point(x * u, y * u); }
    Point operator/(const Tf u) const { return
        Point(x / u, y / u); }

    bool operator==(const Point& u) const {
        return dcmp(x - u.x) == 0 && dcmp(y - u.
            y) == 0;
    }
    bool operator!=(const Point& u) const {
        return !(*this == u); }
    bool operator<(const Point& u) const {
        return dcmp(x - u.x) < 0 || (dcmp(x - u.
            x) == 0 && dcmp(y - u.y) < 0);
    }
};
Ti dot(Point a, Point b) { return a.x * b.x
    + a.y * b.y; }
Ti cross(Point a, Point b) { return a.x * b.
    y - a.y * b.x; }
Tf length(Point a) { return sqrt(dot(a, a)); }
Ti sqLength(Point a) { return dot(a, a); }
Tf distance(Point a, Point b) { return
    length(a - b); }
Tf angle(Point u) { return atan2(u.y, u.x); }

// returns angle between oa, ob in (-PI, PI]
Tf angleBetween(Point a, Point b) {
    Tf ans = angle(b) - angle(a);
    return ans <= -PI ? ans + 2 * PI : (ans >
        PI ? ans - 2 * PI : ans);
}
// Rotate a ccw by rad radians, Tf Ti same
Point rotate(Point a, Tf rad) {
    return Point(a.x * cos(rad) - a.y * sin(
        rad),
        a.x * sin(rad) + a.y * cos(rad
        ));
}
// rotate a ccw by angle th with cos(th) =
    co && sin(th) = si, Tf Ti same
Point rotatePrecise(Point a, Tf co, Tf si) {
    return Point(a.x * co - a.y * si, a.y * co
        + a.x * si);
}
Point rotate90(Point a) { return Point(-a.y,
    a.x); }
// scales vector a by s such that length of
    a becomes s, Tf Ti same
Point scale(Point a, Tf s) { return a /
    length(a) * s; }
// returns an unit vector perpendicular to
    vector a, Tf Ti same
Point normal(Point a) {
    Tf l = length(a);
    return Point(-a.y / l, a.x / l);
}

```

```

// returns 1 if c is left of ab, 0 if on ab
    && -1 if right of ab
int orient(Point a, Point b, Point c) {
    return dcmp(cross(b - a, c - a)); }
/// Use as sort(v.begin(), v.end(),
    polarComp(0, dir))
/// Polar comparator around 0 starting at
    direction dir
struct polarComp {
    Point O, dir;
    polarComp(Point O = Point(0, 0), Point dir
        = Point(1, 0)) : O(O), dir(dir) {}
    bool half(Point p) {
        return dcmp(cross(dir, p)) < 0 ||
            (dcmp(cross(dir, p)) == 0 && dcmp(
                dot(dir, p)) > 0);
    }
    bool operator()(Point p, Point q) {
        return make_tuple(half(p), 0) <
            make_tuple(half(q), cross(p, q));
    }
};
struct Segment {
    Point a, b;
    Segment(Point aa, Point bb) : a(aa), b(bb)
        {}
};
typedef Segment Line;
struct Circle {
    Point o;
    Tf r;
    Circle(Point o = Point(0, 0), Tf r = 0) :
        o(o), r(r) {}
    // returns true if point p is in || on the
        circle
    bool contains(Point p) { return dcmp(
        sqLength(p - o) - r * r) <= 0; }
    // returns a point on the circle rad
        radians away from +X CCW
    Point point(Tf rad) {
        static_assert(is_same<Tf, Ti>::value);
        return Point(o.x + cos(rad) * r, o.y +
            sin(rad) * r);
    }
    // area of a circular sector with central
        angle rad
    Tf area(Tf rad = PI + PI) { return rad * r
        * r / 2; }
    // area of the circular sector cut by a
        chord with central angle alpha
    Tf sector(Tf alpha) { return r * r * 0.5 *
        (alpha - sin(alpha)); }
};

```

4.2 Linear

```

// **** LINE LINE INTERSECTION START ****
// returns true if point p is on segment s
bool onSegment(Point p, Segment s) {
    return dcmp(cross(s.a - p, s.b - p)) == 0
        && dcmp(dot(s.a - p, s.b - p)) <= 0;
}
// returns true if segment p && q touch or
    intersect
bool segmentsIntersect(Segment p, Segment q)
    {
    if (onSegment(p.a, q) || onSegment(p.b, q)
        ) return true;
    if (onSegment(q.a, p) || onSegment(q.b, p)
        ) return true;

    Ti c1 = cross(p.b - p.a, q.a - p.a);
    Ti c2 = cross(p.b - p.a, q.b - p.a);
    Ti c3 = cross(q.b - q.a, p.a - q.a);
    Ti c4 = cross(q.b - q.a, p.b - q.a);
    return dcmp(c1) * dcmp(c2) < 0 && dcmp(c3)
        * dcmp(c4) < 0;
}
bool linesParallel(Line p, Line q) {
    return dcmp(cross(p.b - p.a, q.b - q.a))
        == 0;
}
// lines are represented as a ray from a
    point: (point, vector)

```

```
// returns false if two lines (p, v) && (q,
// w) are parallel or collinear
// true otherwise, intersection point is
// stored at o via reference, Tf Ti Same
bool lineLineIntersection(Point p, Point v,
    Point q, Point w, Point& o) {
    if (dcmp(cross(v, w)) == 0) return false;
    Point u = p - q;
    o = p + v * (cross(w, u) / cross(v, w));
    return true;
}
// returns false if two lines p && q are
// parallel or collinear
// true otherwise, intersection point is
// stored at o via reference
bool lineLineIntersection(Line p, Line q,
    Point& o) {
    return lineLineIntersection(p.a, p.b - p.a,
        q.a, q.b - q.a, o);
}
// returns the distance from point a to line
// l
// **** LINE LINE INTERSECTION FINISH ****
Tf distancePointLine(Point p, Line l) {
    return abs(cross(l.b - l.a, p - l.a) /
        length(l.b - l.a));
}
// returns the shortest distance from point
// a to segment s
Tf distancePointSegment(Point p, Segment s)
{
    if (s.a == s.b) return length(p - s.a);
    Point v1 = s.b - s.a, v2 = p - s.a, v3 = p
        - s.b;
    if (dcmp(dot(v1, v2)) < 0)
        return length(v2);
    else if (dcmp(dot(v1, v3)) > 0)
        return length(v3);
    else
        return abs(cross(v1, v2) / length(v1));
}
// returns the shortest distance from
// segment p to segment q
Tf distanceSegmentSegment(Segment p, Segment
    q) {
    if (segmentsIntersect(p, q)) return 0;
    Tf ans = distancePointSegment(p.a, q);
    ans = min(ans, distancePointSegment(p.b, q
        ));
    ans = min(ans, distancePointSegment(q.a, p
        ));
    ans = min(ans, distancePointSegment(q.b, p
        ));
    return ans;
}
// returns the projection of point p on line
// l, Tf Ti Same
Point projectPointLine(Point p, Line l) {
    Point v = l.b - l.a;
    return l.a + v * ((Tf)dot(v, p - l.a) /
        dot(v, v));
}
}
```

4.3 Circular

```
// Extremely inaccurate for finding near
// touches
// compute intersection of line l with
// circle c
// The intersections are given in order of
// the ray (l.a, l.b), Tf Ti same
vector<Point> circleLineIntersection(Circle
    c, Line l) {
    vector<Point> ret;
    Point b = l.b - l.a, a = l.a - c.o;
    Tf A = dot(b, b), B = dot(a, b);
    Tf C = dot(a, a) - c.r * c.r, D = B * B -
        A * C;
    if (D < -EPS) return ret;
    ret.push_back(l.a + b * (-B - sqrt(D + EPS
        )) / A);
    if (D > EPS) ret.push_back(l.a + b * (-B +
        sqrt(D)) / A);
    return ret;
}
}
```

```
// signed area of intersection of circle(c.o
// , c.r) &&
// triangle(c.o, s.a, s.b) [cross(a-o, b-o)
// /2]
Tf circleTriangleIntersectionArea(Circle c,
    Segment s) {
    using Linear::distancePointSegment;
    Tf OA = length(c.o - s.a);
    Tf OB = length(c.o - s.b);
    // sector
    if (dcmp(distancePointSegment(c.o, s) - c.
        r) >= 0)
        return angleBetween(s.a - c.o, s.b - c.o
            ) * (c.r * c.r) / 2.0;
    // triangle
    if (dcmp(OA - c.r) <= 0 && dcmp(OB - c.r)
        <= 0)
        return cross(c.o - s.b, s.a - s.b) /
            2.0;
    // three part: (A, a) (a, b) (b, B)
    vector<Point> Sect =
        circleLineIntersection(c, s);
    return circleTriangleIntersectionArea(c,
        Segment(s.a, Sect[0])) +
        circleTriangleIntersectionArea(c,
            Segment(Sect[0], Sect[1])) +
        circleTriangleIntersectionArea(c,
            Segment(Sect[1], s.b));
}
// area of intersecion of circle(c.o, c.r)
// && simple polyson(p[])
Tf circlePolyIntersectionArea(Circle c,
    Polygon p) {
    Tf res = 0;
    int n = p.size();
    for (int i = 0; i < n; ++i)
        res += circleTriangleIntersectionArea(c,
            Segment(p[i], p[(i + 1) % n]));
    return abs(res);
}
// locates circle c2 relative to c1
// interior (d < R - r)
// ----> -2
// interior tangents (d = R - r) ---->
// -1
// concentric (d = 0)
// secants (R - r < d < R + r)
// ----> 0
// exterior tangents (d = R + r) ---->
// 1
// exterior (d > R + r)
// ----> 2
int circleCirclePosition(Circle c1, Circle
    c2) {
    Tf d = length(c1.o - c2.o);
    int in = dcmp(d - abs(c1.r - c2.r)), ex =
        dcmp(d - (c1.r + c2.r));
    return in < 0 ? -2 : in == 0 ? -1 : ex ==
        0 ? 1 : ex > 0 ? 2 : 0;
}
// compute the intersection points between
// two circles c1 && c2, Tf Ti same
vector<Point> circleCircleIntersection(
    Circle c1, Circle c2) {
    vector<Point> ret;
    Tf d = length(c1.o - c2.o);
    if (dcmp(d) == 0) return ret;
    if (dcmp(c1.r + c2.r - d) < 0) return ret;
    if (dcmp(abs(c1.r - c2.r) - d) > 0) return
        ret;

    Point v = c2.o - c1.o;
    Tf co = (c1.r * c1.r + sqLength(v) - c2.r
        * c2.r) / (2 * c1.r * length(v));
    Tf si = sqrt(abs(1.0 - co * co));
    Point p1 = scale(rotatePrecise(v, co, -si)
        , c1.r) + c1.o;
    Point p2 = scale(rotatePrecise(v, co, si),
        c1.r) + c1.o;

    ret.push_back(p1);
    if (p1 != p2) ret.push_back(p2);
    return ret;
}
}
```

```
// intersection area between two circles c1,
// c2
Tf circleCircleIntersectionArea(Circle c1,
    Circle c2) {
    Point AB = c2.o - c1.o;
    Tf d = length(AB);
    if (d >= c1.r + c2.r) return 0;
    if (d + c1.r <= c2.r) return PI * c1.r *
        c1.r;
    if (d + c2.r <= c1.r) return PI * c2.r *
        c2.r;

    Tf alpha1 = acos((c1.r * c1.r + d * d - c2
        .r * c2.r) / (2.0 * c1.r * d));
    Tf alpha2 = acos((c2.r * c2.r + d * d - c1
        .r * c1.r) / (2.0 * c2.r * d));
    return c1.sector(2 * alpha1) + c2.sector(2
        * alpha2);
}
// returns tangents from a point p to circle
// c, Tf Ti same
vector<Point> pointCircleTangents(Point p,
    Circle c) {
    vector<Point> ret;
    Point u = c.o - p;
    Tf d = length(u);
    if (d < c.r)
        ;
    else if (dcmp(d - c.r) == 0) {
        ret = {rotate(u, PI / 2)};
    } else {
        Tf ang = asin(c.r / d);
        ret = {rotate(u, -ang), rotate(u, ang)};
    }
    return ret;
}
// returns the points on tangents that
// touches the circle, Tf Ti Same
vector<Point> pointCircleTangencyPoints(
    Point p, Circle c) {
    Point u = p - c.o;
    Tf d = length(u);
    if (d < c.r)
        return {};
    else if (dcmp(d - c.r) == 0)
        return {c.o + u};
    else {
        Tf ang = acos(c.r / d);
        u = u / length(u) * c.r;
        return {c.o + rotate(u, -ang), c.o +
            rotate(u, ang)};
    }
}
// for two circles c1 && c2, returns two
// list of points a && b
// such that a[i] is on c1 && b[i] is c2 &&
// for every i
// Line(a[i], b[i]) is a tangent to both
// circles
// CAUTION: a[i] = b[i] in case they touch |
// -1 for c1 = c2
int circleCircleTangencyPoints(Circle c1,
    Circle c2, vector<Point> &a,
    vector<Point> &b) {
    a.clear(), b.clear();
    int cnt = 0;
    if (dcmp(c1.r - c2.r) < 0) {
        swap(c1, c2);
        swap(a, b);
    }
    Tf d2 = sqLength(c1.o - c2.o);
    Tf rdif = c1.r - c2.r, rsum = c1.r + c2.r;
    if (dcmp(d2 - rdif * rdif) < 0) return 0;
    if (dcmp(d2) == 0 && dcmp(c1.r - c2.r) ==
        0) return -1;

    Tf base = angle(c2.o - c1.o);
    if (dcmp(d2 - rdif * rdif) == 0) {
        a.push_back(c1.point(base));
        b.push_back(c2.point(base));
        cnt++;
        return cnt;
    }
}
```

```

Tf ang = acos((c1.r - c2.r) / sqrt(d2));
a.push_back(c1.point(base + ang));
b.push_back(c2.point(base + ang));
cnt++;
a.push_back(c1.point(base - ang));
b.push_back(c2.point(base - ang));
cnt++;

if (dcmp(d2 - rsum * rsum) == 0) {
    a.push_back(c1.point(base));
    b.push_back(c2.point(PI + base));
    cnt++;
} else if (dcmp(d2 - rsum * rsum) > 0) {
    Tf ang = acos((c1.r + c2.r) / sqrt(d2));
    a.push_back(c1.point(base + ang));
    b.push_back(c2.point(PI + base + ang));
    cnt++;
    a.push_back(c1.point(base - ang));
    b.push_back(c2.point(PI + base - ang));
    cnt++;
}
return cnt;
}

```

4.4 Convex

```

// minkowski sum of two polygons in O(n)
Polygon minkowskiSum(Polygon A, Polygon B) {
    int n = A.size(), m = B.size();
    rotate(A.begin(), min_element(A.begin(), A.end()), A.end());
    rotate(B.begin(), min_element(B.begin(), B.end()), B.end());

    A.push_back(A[0]);
    B.push_back(B[0]);
    for (int i = 0; i < n; i++) A[i] = A[i + 1] - A[i];
    for (int i = 0; i < m; i++) B[i] = B[i + 1] - B[i];

    Polygon C(n + m + 1);
    C[0] = A.back() + B.back();
    merge(A.begin(), A.end() - 1, B.begin(), B.end() - 1, C.begin() + 1,
        polarComp(Point(0, 0), Point(0, -1)));
    for (int i = 1; i < C.size(); i++) C[i] = C[i] + C[i - 1];
    C.pop_back();
    return C;
}

// finds the rectangle with minimum area enclosing a convex polygon and
// the rectangle with minimum perimeter enclosing a convex polygon
// Tf Ti Same
pair<Tf, Tf> rotatingCalipersBoundingBox(const Polygon &p) {
    using Linear::distancePointLine;
    int n = p.size();
    int l = 1, r = 1, j = 1;
    Tf area = 1e100;
    Tf perimeter = 1e100;
    for (int i = 0; i < n; i++) {
        Point v = (p[(i + 1) % n] - p[i]) / length(p[(i + 1) % n] - p[i]);
        while (dcmp(dot(v, p[r % n] - p[i]) - dot(v, p[(r + 1) % n] - p[i])) < 0)
            r++;
        while (j < r || dcmp(cross(v, p[j % n] - p[i]) - cross(v, p[(j + 1) % n] - p[i])) < 0)
            j++;
        while (l < j || dcmp(dot(v, p[l % n] - p[i]) - dot(v, p[(l + 1) % n] - p[i])) > 0)
            l++;
        Tf w = dot(v, p[r % n] - p[i]) - dot(v, p[l % n] - p[i]);
        Tf h = distancePointLine(p[j % n], Line(p[i], p[(i + 1) % n]));
    }
}

```

```

    area = min(area, w * h);
    perimeter = min(perimeter, 2 * w + 2 * h);
}
return make_pair(area, perimeter);
}

// returns the left side of polygon u after cutting it by ray a->b
Polygon cutPolygon(Polygon u, Point a, Point b) {
    using Linear::lineLineIntersection;
    using Linear::onSegment;

    Polygon ret;
    int n = u.size();
    for (int i = 0; i < n; i++) {
        Point c = u[i], d = u[(i + 1) % n];
        if (dcmp(cross(b - a, c - a)) >= 0) ret.push_back(c);
        if (dcmp(cross(b - a, d - c)) != 0) {
            Point t;
            lineLineIntersection(a, b - a, c, d - c, t);
            if (onSegment(t, Segment(c, d))) ret.push_back(t);
        }
    }
    return ret;
}

// returns true if point p is in or on triangle abc
bool pointInTriangle(Point a, Point b, Point c, Point p) {
    return dcmp(cross(b - a, p - a)) >= 0 && dcmp(cross(c - b, p - b)) >= 0 && dcmp(cross(a - c, p - c)) >= 0;
}

// pt must be in ccw order with no three collinear points
// returns inside = -1, on = 0, outside = 1
int pointInConvexPolygon(const Polygon &pt, Point p) {
    int n = pt.size();
    assert(n >= 3);

    int lo = 1, hi = n - 1;
    while (hi - lo > 1) {
        int mid = (lo + hi) / 2;
        if (dcmp(cross(pt[mid] - pt[0], p - pt[0])) > 0)
            lo = mid;
        else
            hi = mid;
    }

    bool in = pointInTriangle(pt[0], pt[lo], pt[hi], p);
    if (!in) return 1;

    if (dcmp(cross(pt[lo] - pt[lo - 1], p - pt[lo - 1])) == 0) return 0;
    if (dcmp(cross(pt[hi] - pt[lo], p - pt[lo])) == 0) return 0;
    if (dcmp(cross(pt[hi] - pt[(hi + 1) % n], p - pt[(hi + 1) % n])) == 0) return 0;
    return -1;
}

// Extreme Point for a direction is the farthest point in that direction
// u is the direction for extremeness
int extremePoint(const Polygon &poly, Point u) {
    int n = (int)poly.size();
    int a = 0, b = n;
    while (b - a > 1) {
        int c = (a + b) / 2;
        if (dcmp(dot(poly[c] - poly[(c + 1) % n], u)) >= 0 && dcmp(dot(poly[c] - poly[(c - 1) % n], u)) >= 0) {
            return c;
        }
    }
}

```

```

bool a_up = dcmp(dot(poly[(a + 1) % n] - poly[a], u)) >= 0;
bool c_up = dcmp(dot(poly[(c + 1) % n] - poly[c], u)) >= 0;
bool a_above_c = dcmp(dot(poly[a] - poly[c], u)) > 0;

if (a_up && !c_up)
    b = c;
else if (!a_up && c_up)
    a = c;
else if (a_up && c_up) {
    if (a_above_c)
        b = c;
    else
        a = c;
} else {
    if (!a_above_c)
        b = c;
    else
        a = c;
}

if (dcmp(dot(poly[a] - poly[(a + 1) % n], u)) > 0 && dcmp(dot(poly[a] - poly[(a - 1) % n], u)) > 0)
    return a;
return b % n;
}

// For a convex polygon p and a line l, returns a list of segments of p that touch or intersect line l.
// the i'th segment is considered (p[i], p[(i + 1) modulo |p|])
// #1 If a segment is collinear with the line, only that is returned
// #2 Else if l goes through i'th point, the i'th segment is added
// Complexity: O(lg |p|)
vector<int> lineConvexPolyIntersection(const Polygon &p, Line l) {
    assert((int)p.size() >= 3);
    assert(l.a != l.b);

    int n = p.size();
    vector<int> ret;

    Point v = l.b - l.a;
    int lf = extremePoint(p, rotate90(v));
    int rt = extremePoint(p, rotate90(v) * Ti(-1));
    int olf = orient(l.a, l.b, p[lf]);
    int ort = orient(l.a, l.b, p[rt]);

    if (!olf || !ort) {
        int idx = (!olf ? lf : rt);
        if (orient(l.a, l.b, p[(idx - 1) % n]) == 0)
            ret.push_back((idx - 1) % n);
        else
            ret.push_back(idx);
        return ret;
    }
    if (olf == ort) return ret;

    for (int i = 0; i < 2; ++i) {
        int lo = i ? rt : lf;
        int hi = i ? lf : rt;
        int olo = i ? ort : olf;

        while (true) {
            int gap = (hi - lo + n) % n;
            if (gap < 2) break;

            int mid = (lo + gap / 2) % n;
            int omid = orient(l.a, l.b, p[mid]);
            if (!omid) {
                lo = mid;
                break;
            }
            if (omid == olo)
                lo = mid;
        }
    }
}

```



```

    else
        hi = mid;
    }
    ret.push_back(lo);
}
return ret;
}
// Calculate [ACW, CW] tangent pair from an
// external point
constexpr int CW = -1, ACW = 1;
bool isGood(Point u, Point v, Point Q, int
    dir) {
    return orient(Q, u, v) != -dir;
}
Point better(Point u, Point v, Point Q, int
    dir) {
    return orient(Q, u, v) == dir ? u : v;
}
Point pointPolyTangent(const Polygon &pt,
    Point Q, int dir, int lo, int hi) {
    while (hi - lo > 1) {
        int mid = (lo + hi) / 2;
        bool pvs = isGood(pt[mid], pt[mid - 1],
            Q, dir);
        bool nxt = isGood(pt[mid], pt[mid + 1],
            Q, dir);

        if (pvs && nxt) return pt[mid];
        if (!(pvs || nxt)) {
            Point p1 = pointPolyTangent(pt, Q, dir,
                mid + 1, hi);
            Point p2 = pointPolyTangent(pt, Q, dir,
                lo, mid - 1);
            return better(p1, p2, Q, dir);
        }

        if (!pvs) {
            if (orient(Q, pt[mid], pt[lo]) == dir)
                hi = mid - 1;
            else if (better(pt[lo], pt[hi], Q, dir)
                == pt[lo])
                hi = mid - 1;
            else
                lo = mid + 1;
        }
        if (!nxt) {
            if (orient(Q, pt[mid], pt[lo]) == dir)
                lo = mid + 1;
            else if (better(pt[lo], pt[hi], Q, dir)
                == pt[lo])
                hi = mid - 1;
            else
                lo = mid + 1;
        }
    }

    Point ret = pt[lo];
    for (int i = lo + 1; i <= hi; i++) ret =
        better(ret, pt[i], Q, dir);
    return ret;
}
// [ACW, CW] Tangent
pair<Point, Point> pointPolyTangents(const
    Polygon &pt, Point Q) {
    int n = pt.size();
    Point acw_tan = pointPolyTangent(pt, Q,
        ACW, 0, n - 1);
    Point cw_tan = pointPolyTangent(pt, Q, CW,
        0, n - 1);
    return make_pair(acw_tan, cw_tan);
}

```

4.5 Polygon

```

typedef vector<Point> Polygon;
// removes redundant colinear points
// polygon can't be all colinear points
Polygon RemoveCollinear(const Polygon &poly)
{
    Polygon ret;
    int n = poly.size();
    for (int i = 0; i < n; i++) {
        Point a = poly[i];
        Point b = poly[(i + 1) % n];
        Point c = poly[(i + 2) % n];

```

```

        if (dcmp(cross(b - a, c - b)) != 0 && (
            ret.empty() || b != ret.back()))
            ret.push_back(b);
    }
    return ret;
}
// returns the signed area of polygon p of n
// vertices
Tf signedPolygonArea(const Polygon &p) {
    Tf ret = 0;
    for (int i = 0; i < (int)p.size() - 1; i
        ++){
        ret += cross(p[i] - p[0], p[i + 1] - p
            [0]);
    }
    return ret / 2;
}
// given a polygon p of n vertices,
// generates the convex hull in in CCW
// Tested on https://acm.timus.ru/problem.
// asp?space=1&num=1185
// Caution: when all points are colinear AND
// removeRedundant == false
// output will be contain duplicate points (
// from upper hull) at back
Polygon convexHull(Polygon p, bool
    removeRedundant) {
    int check = removeRedundant ? 0 : -1;
    sort(p.begin(), p.end());
    p.erase(unique(p.begin(), p.end(), p.end
        ());
    int n = p.size();
    Polygon ch(n + n);
    int m = 0; // preparing lower hull
    for (int i = 0; i < n; i++) {
        while (m > 1 &&
            dcmp(cross(ch[m - 1] - ch[m - 2],
                p[i] - ch[m - 1])) <= check)
            m--;
        ch[m++] = p[i];
    }
    int k = m; // preparing upper hull
    for (int i = n - 2; i >= 0; i--) {
        while (m > k &&
            dcmp(cross(ch[m - 1] - ch[m - 2],
                p[i] - ch[m - 2])) <= check)
            m--;
        ch[m++] = p[i];
    }
    if (n > 1) m--;
    ch.resize(m);
    return ch;
}
// returns inside = -1, on = 0, outside = 1
int pointInPolygon(const Polygon &p, Point o
    ) {
    using Linear::onSegment;
    int wn = 0, n = p.size();
    for (int i = 0; i < n; i++) {
        int j = (i + 1) % n;
        if (onSegment(o, Segment(p[i], p[j])) ||
            o == p[i]) return 0;
        int k = dcmp(cross(p[j] - p[i], o - p[i]
            ));
        int d1 = dcmp(p[i].y - o.y);
        int d2 = dcmp(p[j].y - o.y);
        if (k > 0 && d1 <= 0 && d2 > 0) wn++;
        if (k < 0 && d2 <= 0 && d1 > 0) wn--;
    }
    return wn ? -1 : 1;
}
// Given a simple polygon p, and a line l,
// returns (x, y)
// x = longest segment of l in p, y = total
// length of l in p.
pair<Tf, Tf> linePolygonIntersection(Line l,
    const Polygon &p) {
    using Linear::lineLineIntersection;
    int n = p.size();
    vector<pair<Tf, int>> ev;
    for (int i = 0; i < n; ++i) {
        Point a = p[i], b = p[(i + 1) % n], z =
            p[(i - 1 + n) % n];

```

```

        int ora = orient(l.a, l.b, a), orb =
            orient(l.a, l.b, b),
            orz = orient(l.a, l.b, z);
        if (!ora) {
            Tf d = dot(a - l.a, l.b - l.a);
            if (orz && orb) {
                if (orz != orb) ev.emplace_back(d,
                    0);
                // else // Point Touch
            } else if (orz)
                ev.emplace_back(d, orz);
            else if (orb)
                ev.emplace_back(d, orb);
        } else if (ora == -orb) {
            Point ins;
            lineLineIntersection(l, Line(a, b),
                ins);
            ev.emplace_back(dot(ins - l.a, l.b - l
                .a), 0);
        }
    }
    sort(ev.begin(), ev.end());

    Tf ans = 0, len = 0, last = 0, tot = 0;
    bool active = false;
    int sign = 0;
    for (auto &qq : ev) {
        int tp = qq.second;
        Tf d = qq.first; // current Segment is
            (last, d)
        if (sign) { // On Border
            len += d - last;
            tot += d - last;
            ans = max(ans, len);
            if (tp != sign) active = !active;
            sign = 0;
        } else {
            if (active) { // Strictly Inside
                len += d - last;
                tot += d - last;
                ans = max(ans, len);
            }
            if (tp == 0)
                active = !active;
            else
                sign = tp;
        }
        last = d;
        if (!active) len = 0;
    }
    ans /= length(l.b - l.a);
    tot /= length(l.b - l.a);
    return {ans, tot};
}

```

4.6 Intersecting Segments

```

// Given a list of segments v, finds a pair
// (i, j)
// st v[i], v[j] intersects. If none,
// returns {-1, -1}
// Tested Timus 1469, CF 1359F
struct Event {
    Tf x;
    int tp, id;
    bool operator<(const Event &p) const {
        if (dcmp(x - p.x)) return x < p.x;
        return tp > p.tp;
    }
};
pair<int, int> anyIntersection(const vector<
    Segment> &v) {
    using Linear::segmentsIntersect;
    static_assert(is_same<Tf, Tf>::value);

    vector<Event> ev;
    for (int i = 0; i < v.size(); i++) {
        ev.push_back({min(v[i].a.x, v[i].b.x),
            +1, i});
        ev.push_back({max(v[i].a.x, v[i].b.x),
            -1, i});
    }
    sort(ev.begin(), ev.end());

    auto comp = [&v](int i, int j) {

```

```

Segment p = v[i], q = v[j];
Tf x = max(min(p.a.x, p.b.x), min(q.a.x,
    q.b.x));
auto yvalSegment = [&x](const Line &s) {
    if (dcmp(s.a.x - s.b.x) == 0) return s
        .a.y;
    return s.a.y + (s.b.y - s.a.y) * (x -
        s.a.x) / (s.b.x - s.a.x);
};
return dcmp(yvalSegment(p) - yvalSegment
    (q)) < 0;
};

multiset<int, decltype(comp)> st(comp);
typedef decltype(st)::iterator iter;
auto prev = [&st](iter it) { return it ==
    st.begin() ? st.end() : --it; };
auto next = [&st](iter it) { return it ==
    st.end() ? st.end() : ++it; };

vector<iter> pos(v.size());
for (auto &cur : ev) {
    int id = cur.id;
    if (cur.tp == 1) {
        iter nxt = st.lower_bound(id);
        iter pre = prev(nxt);
        if (pre != st.end() &&
            segmentsIntersect(v[*pre], v[id])
        )
            return {*pre, id};
        if (nxt != st.end() &&
            segmentsIntersect(v[*nxt], v[id])
        )
            return {*nxt, id};
        pos[id] = st.insert(nxt, id);
    } else {
        iter nxt = next(pos[id]);
        iter pre = prev(pos[id]);
        if (pre != st.end() && nxt != st.end()
            &&
            segmentsIntersect(v[*pre], v[*nxt])
        )
            return {*pre, *nxt};
        st.erase(pos[id]);
    }
}
return {-1, -1};
}

```

5 Graph

5.1 Link Cut Tree

```

struct SplayTree {
    struct node {
        int ch[2] = {0, 0}, p = 0;
        ll self = 0, path = 0;
        ll sub = 0, extra = 0;
        bool rev = false;
    };
    vector<node> T;
    SplayTree(int n) : T(n + 1) {}
    void push(int x) {
        if (!x) return;
        int l = T[x].ch[0], r = T[x].ch[1];
        if (T[x].rev) {
            T[l].rev ^= true, T[r].rev ^= true;
            swap(T[x].ch[0], T[x].ch[1]);
            T[x].rev = false;
        }
    }
    void pull(int x) {
        int l = T[x].ch[0], r = T[x].ch[1];
        push(l), push(r);
        T[x].path = T[x].self + T[l].path + T[r]
            .path;
        T[x].sub = T[x].self + T[x].extra + T[l]
            .sub + T[r].sub;
    }
    void set(int parent, int child, int d) {
        T[parent].ch[d] = child;
        T[child].p = parent;
        pull(parent);
    }
    int dir(int x) {

```

```

        int parent = T[x].p;
        if (!parent) return -1;
        return (T[parent].ch[0] == x) ? 0 : (T[
            parent].ch[1] == x) ? 1 : -1;
    }
    void rotate(int x) {
        int parent = T[x].p, gparent = T[parent
            ].p;
        int dx = dir(x), dp = dir(parent);
        set(parent, T[x].ch[!dx], dx);
        set(x, parent, !dx);
        if (~dp) set(gparent, x, dp);
        T[x].p = gparent;
    }
    void splay(int x) {
        push(x);
        while (~dir(x)) {
            int parent = T[x].p;
            int gparent = T[parent].p;
            push(gparent), push(parent), push(x);
            int dx = dir(x), dp = dir(parent);
            if (~dp) rotate(dx != dp ? x : parent)
                ;
            rotate(x);
        }
    };
    struct LinkCut : SplayTree {
        LinkCut(int n) : SplayTree(n) {}
        void cut_right(int x) {
            splay(x);
            int r = T[x].ch[1];
            T[x].extra += T[r].sub;
            T[x].ch[1] = 0, pull(x);
        }
        int access(int x) {
            int u = x, v = 0;
            for (; u; v = u, u = T[u].p) {
                cut_right(u);
                T[u].extra -= T[v].sub;
                T[u].ch[1] = v, pull(u);
            }
            return splay(x), v;
        }
        void make_root(int x) {
            access(x);
            T[x].rev ^= true, push(x);
        }
        void link(int u, int v) {
            make_root(v), access(u);
            T[u].extra += T[v].sub;
            T[v].p = u, pull(u);
        }
        void cut(int u) {
            access(u);
            T[u].ch[0] = T[T[u].ch[0]].p = 0;
            pull(u);
        }
        void cut(int u, int v) {
            make_root(u), access(v);
            T[v].ch[0] = T[u].p = 0, pull(v);
        }
        int find_root(int u) {
            access(u), push(u);
            while (T[u].ch[0]) {
                u = T[u].ch[0], push(u);
            }
            return splay(u), u;
        }
        int lca(int u, int v) {
            if (u == v) return u;
            access(u);
            int ret = access(v);
            return T[u].p ? ret : 0;
        }
        // subtree query of u if v is the root
        ll subtree(int u, int v) {
            make_root(v), access(u);
            return T[u].self + T[u].extra;
        }
        ll path(int u, int v) {
            make_root(u), access(v);
            return T[v].path;
        }
    };
}

```

```

// point update
void update(int u, ll val) {
    access(u);
    T[u].self = val, pull(u);
}
}

```

5.2 Graph Template

```

struct edge {
    int u, v;
    edge(int u = 0, int v = 0) : u(u), v(v) {}
    int to(int node) { return u ^ v ^ node; }
};
struct graph {
    int n;
    vector<vector<int>> adj;
    vector<edge> edges;
    graph(int n = 0) : n(n), adj(n) {}
    void addEdge(int u, int v, bool dir = 1) {
        adj[u].push_back(edges.size());
        if (dir) adj[v].push_back(edges.size());
        edges.emplace_back(u, v);
    }
    int addNode() {
        adj.emplace_back();
        return n++;
    }
    edge &operator()(int idx) { return edges[
        idx]; }
    vector<int> &operator[](int u) { return
        adj[u]; }
};

```

5.3 LCA, ETT, VT

```

struct lca_table {
    tree &T;
    int n, LOG = 20;
    vector<vector<int>> anc;
    vector<int> level;

    void setupLifting(int node, int par) {
        for (int v : T[node])
            if (v != par) {
                anc[v][0] = node, level[v] = level[
                    node] + 1;
                for (int k = 1; k < LOG; k++) anc[v]
                    [k] = anc[anc[v][k - 1]][k -
                        1];
                setupLifting(v, node);
            }
    }
    lca_table(tree &T, int root = 0) : T(T), n
        (T.n) {
        LOG = 33 - __builtin_clz(n);
        anc.assign(n, vector<int>(LOG, root));
        level.resize(n);
        setupLifting(root, root);
    }
    int lca(int u, int v) {
        if (level[u] > level[v]) swap(u, v);
        for (int k = LOG - 1; ~k; k--)
            if (level[u] + (1 << k) <= level[v]) v
                = anc[v][k];
        if (u == v) return u;
        for (int k = LOG - 1; ~k; k--)
            if (anc[u][k] != anc[v][k]) u = anc[u]
                [k], v = anc[v][k];
        return anc[u][0];
    }
    int getAncestor(int node, int ht) {
        for (int k = 0; k < LOG; k++)
            if (ht & (1 << k)) node = anc[node][k]
                ;
        return node;
    }
    int distance(int u, int v) {
        int g = lca(u, v);
        return level[u] + level[v] - 2 * level[g]
            ;
    }
};
struct euler_tour {
    int time = 0;

```

```

tree &T;
int n;
vector<int> start, finish, level, par;
euler_tour(tree &T, int root = 0)
    : T(T), n(T.n), start(n), finish(n),
      level(n), par(n) {
    time = 0;
    call(root);
}

void call(int node, int p = -1) {
    if (p != -1) level[node] = level[p] + 1;
    start[node] = time++;
    for (int e : T[node])
        if (e != p) call(e, node);
    par[node] = p;
    finish[node] = time++;
}

bool isAncestor(int node, int par) {
    return start[par] <= start[node] and
           finish[par] >= finish[node];
}

int subtreeSize(int node) { return finish[
    node] - start[node] + 1 >> 1; }

};

tree virtual_tree(vector<int> &nodes,
    lca_table &table, euler_tour &tour) {
    sort(nodes.begin(), nodes.end(),
        [&](int x, int y) { return tour.start
            [x] < tour.start[y]; });
    int n = nodes.size();
    for (int i = 0; i + 1 < n; i++)
        nodes.push_back(table.lca(nodes[i],
            nodes[i + 1]));
    sort(nodes.begin(), nodes.end());
    nodes.erase(unique(nodes.begin(), nodes.
        end()), nodes.end());
    sort(nodes.begin(), nodes.end(),
        [&](int x, int y) { return tour.start
            [x] < tour.start[y]; });
    n = nodes.size();
    stack<int> st;
    st.push(0);
    tree ans(n);
    for (int i = 1; i < n; i++) {
        while (!tour.isAncestor(nodes[i], nodes[
            st.top()]))) st.pop();
        ans.addEdge(st.top(), i);
        st.push(i);
    }
    return ans;
}

set<int> getCenters(tree &T) {
    int n = T.n;
    vector<int> deg(n), q;
    set<int> s;
    for (int i = 0; i < n; i++) {
        deg[i] = T[i].size();
        if (deg[i] == 1) q.push_back(i);
        s.insert(i);
    }
    for (vector<int> t; s.size() > 2; q = t) {
        for (auto x : q) {
            for (auto e : T[x])
                if (--deg[e] == 1) t.push_back(e);
            s.erase(x);
        }
    }
    return s;
}

```

5.4 SCC

```

typedef long long LL;
const LL N = 1e6 + 7;

bool vis[N];
vector<int> adj[N], adjr[N];
vector<int> order, component;
// tp = 0 ,finding topo order, tp = 1 ,
// reverse edge traversal

void dfs(int u, int tp = 0) {
    vis[u] = true;
    if (tp) component.push_back(u);
    auto& ad = (tp ? adjr : adj);

```

```

    for (int v : ad[u])
        if (!vis[v]) dfs(v, tp);
    if (!tp) order.push_back(u);
}

int main() {
    for (int i = 1; i <= n; i++) {
        if (!vis[i]) dfs(i);
    }
    memset(vis, 0, sizeof vis);
    reverse(order.begin(), order.end());
    for (int i : order) {
        if (!vis[i]) {
            // one component is found
            dfs(i, 1), component.clear();
        }
    }
}

```

5.5 Euler Tour on Edge

```

// for simplicity, G[idx] contains the
// adjacency list of a node
// while G(e) is a reference to the e-th
// edge.

const int N = 2e5 + 5;
int in[N], out[N], fwd[N], bck[N];
int t = 0;
void dfs(graph &G, int node, int par) {
    out[node] = t;
    for (int e : G[node]) {
        int v = G(e).to(node);
        if (v == par) continue;
        fwd[e] = t++;
        dfs(G, v, node);
        bck[e] = t++;
    }
    in[node] = t - 1;
}

void init(graph &G, int node) {
    t = 0;
    dfs(G, node, node);
}

```

5.6 LCA In O(1)

```

/* LCA in O(1)
 * depth calculates weighted distance
 * level calculates distance by number of
 * edges
 * Preprocessing in NlongN */
LL depth[N];
int level[N];

int st[N], en[N], LOG[N], par[N];
int a[N], id[N], table[L][N];

vector<PII> adj[N];
int n, root, Time, cur;

void init(int nodes, int root_) {
    n = nodes, root = root_, LOG[0] = LOG[1] =
        0;
    for (int i = 2; i <= n; i++) LOG[i] = LOG[
        i >> 1] + 1;
    for (int i = 0; i <= n; i++) adj[i].clear
        ();
}

void addEdge(int u, int v, int w) {
    adj[u].push_back(PII(v, w));
    adj[v].push_back(PII(u, w));
}

int lca(int u, int v) {
    if (en[u] > en[v]) swap(u, v);
    if (st[v] <= st[u] && en[u] <= en[v])
        return v;

    int l = LOG[id[v] - id[u] + 1];
    int p1 = id[u], p2 = id[v] - (1 << l) + 1;
    int d1 = level[table[l][p1]], d2 = level[
        table[l][p2]];

    if (d1 < d2)
        return par[table[l][p1]];
}

```

```

    else
        return par[table[l][p2]];
}

LL dist(int u, int v) {
    int l = lca(u, v);
    return (depth[u] + depth[v] - (depth[l] *
        2));
}

/* Euler tour */
void dfs(int u, int p) {
    st[u] = ++Time, par[u] = p;

    for (auto [v, w] : adj[u]) {
        if (v == p) continue;
        depth[v] = depth[u] + w;
        level[v] = level[u] + 1;
        dfs(v, u);
    }

    en[u] = ++Time;
    a[++cur] = u, id[u] = cur;
}

/* RMQ */
void pre() {
    cur = Time = 0, dfs(root, root);
    for (int i = 1; i <= n; i++) table[0][i] =
        a[i];

    for (int l = 0; l < L - 1; l++) {
        for (int i = 1; i <= n; i++) {
            table[l + 1][i] = table[l][i];

            bool C1 = (1 << l) + i <= n;
            bool C2 = level[table[l][i] + (1 << l)
                ] < level[table[l][i]];

            if (C1 && C2) table[l + 1][i] = table[
                l][i + (1 << l)];
        }
    }
}

```

5.7 HLD

```

const int N = 1e6 + 7;
template <typename DT>
struct Segtree {
    // write lazy segtree here
};

Segtree<int> tree(N);
vector<int> adj[N];
int depth[N], par[N], pos[N];
int head[N], heavy[N], cnt;

int dfs(int u, int p) {
    int SZ = 1, mxsz = 0, heavy;
    depth[u] = depth[p] + 1;

    for (auto v : adj[u]) {
        if (v == p) continue;
        par[v] = u;
        int subsz = dfs(v, u);
        if (subsz > mxsz) heavy[u] = v, mxsz =
            subsz;
        SZ += subsz;
    }
    return SZ;
}

void decompose(int u, int h) {
    head[u] = h, pos[u] = ++cnt;
    if (heavy[u] != -1) decompose(heavy[u], h)
        ;

    for (int v : adj[u]) {
        if (v == par[u]) continue;
        if (v != heavy[u]) decompose(v, v);
    }
}

int query(int a, int b) {
    int ret = 0;
    for (; head[a] != head[b]; b = par[head[b]
        ]) {

```

```

    if (depth[head[a]] > depth[head[b]])
        swap(a, b);
    ret += tree.query(1, 0, cnt, pos[head[b]
    ], pos[b]);
}

if (depth[a] > depth[b]) swap(a, b);
ret += tree.query(1, 0, cnt, pos[a], pos[b
]);
return ret;
}

```

5.8 Centroid Decomposition

```

class Centroid_Decomposition {
    vector<bool> blocked;
    vector<int> CompSize;
    int CompDFS(tree &T, int node, int par) {
        CompSize[node] = 1;
        for (int &e : T[node])
            if (e != par and !blocked[e]) CompSize
                [node] += CompDFS(T, e, node);
        return CompSize[node];
    }
    int FindCentroid(tree &T, int node, int
        par, int sz) {
        for (int &e : T[node])
            if (e != par and !blocked[e])
                if (CompSize[e] > sz / 2) return
                    FindCentroid(T, e, node, sz);
        return node;
    }
    pair<int, int> GetCentroid(tree &T, int
        entry) {
        int sz = CompDFS(T, entry, entry);
        return {FindCentroid(T, entry, entry, sz
        ), sz};
    }
    c_vector<LL> left[2], right[2];
    int GMin, GMax;
    void dfs(tree &T, int node, int par, int
        Min, int Max, int sum) {
        if (blocked[node]) return;
        right[Max < sum or Min > sum][sum]++;
        Max = max(Max, sum), Min = min(Min, sum)
        ;
        GMin = min(GMin, sum), GMax = max(GMax,
            sum);
        for (int i = 0; i < T[node].size(); i++)
            if (T[node][i] != par) {
                dfs(T, T[node][i], node, Min, Max,
                    sum + T.col[node][i]);
            }
    }
    LL solve(tree &T, int c, int sz) {
        LL ans = 0;
        left[0].clear(-sz, sz), left[1].clear(-
            sz, sz);
        for (int i = 0; i < T[c].size(); i++) {
            GMin = 1, GMax = -1;
            dfs(T, T[c][i], c, GMin, GMax, T.col[c
            ][i]);
            ans += right[0][0] + left[1][0] *
                right[1][0];
            for (int j : {0, 1})
                for (int k = GMin; k <= GMax; k++) {
                    ans += right[j][k] * (left[0][
                        -k] +
                        (j == 0) * left[1][-k]);
                }
            for (int j : {0, 1})
                for (int k = GMin; k <= GMax; k++) {
                    left[j][k] += right[j][k];
                    right[j][k] = 0;
                }
        }
        return ans;
    }
}

```

```

public:
LL operator()(tree &T, int entry) {
    blocked.resize(T.n);
    CompSize.resize(T.n);
    for (int i : {0, 1})
        left[i].resize(2 * T.n + 5), right[i].
            resize(2 * T.n + 5);
}

```

```

    auto [c, sz] = GetCentroid(T, entry);
    LL ans = solve(T, c, sz);
    blocked[c] = true;
    for (int e : T[c])
        if (!blocked[e]) ans += (*this)(T, e);
    return ans;
}
};

```

5.9 Dinic Max Flow

```

// flow with demand(lower bound) only for
// DAG
// create new src and sink
// add_edge(new src, u, sum(in_demand[u]))
// add_edge(u, new sink, sum(out_demand[u]))
// add_edge(old sink, old src, inf)
// if (sum of lower bound == flow) then
//     demand satisfied
// flow in every edge i = demand[i] + e.flow

using Ti = long long;
const Ti INF = 1LL << 60;
struct edge {
    int v, u;
    Ti cap, flow = 0;
    edge(int v, int u, Ti cap) : v(v), u(u),
        cap(cap) {}
};
vector<edge> edges;
vector<int> adj[N];
int m = 0, n;
int level[N], ptr[N];
queue<int> q;
bool bfs(int s, int t) {
    for (q.push(s), level[s] = 0; !q.empty();
        q.pop()) {
        for (int id : adj[q.front()]) {
            auto &ed = edges[id];
            if (ed.cap - ed.flow > 0 and level[ed.
                u] == -1)
                level[ed.u] = level[ed.v] + 1, q.
                    push(ed.u);
        }
    }
    return level[t] != -1;
}
Ti dfs(int v, Ti pushed, int t) {
    if (pushed == 0) return 0;
    if (v == t) return pushed;
    for (int &cid = ptr[v]; cid < adj[v].size
        (); cid++) {
        int id = adj[v][cid];
        auto &ed = edges[id];
        if (level[v] + 1 != level[ed.u] || ed.
            cap - ed.flow < 1) continue;
        Ti tr = dfs(ed.u, min(pushed, ed.cap -
            ed.flow), t);
        if (tr == 0) continue;
        ed.flow += tr;
        edges[id ^ 1].flow -= tr;
        return tr;
    }
    return 0;
}
void init(int nodes) {
    m = 0, n = nodes;
    for (int i = 0; i < n; i++) level[i] = -1,
        ptr[i] = 0, adj[i].clear();
}
void addEdge(int v, int u, Ti cap) {
    edges.emplace_back(v, u, cap), adj[v].
        push_back(m++);
    edges.emplace_back(u, v, 0), adj[u].
        push_back(m++);
}
Ti maxFlow(int s, int t) {
    Ti f = 0;
    for (auto &ed : edges) ed.flow = 0;
    for (; bfs(s, t); memset(level, -1, n * 4)
        ) {
        for (memset(ptr, 0, n * 4); Ti pushed =
            dfs(s, INF, t); f += pushed)
            ;
    }
}

```

```

}
return f;
}

```

5.10 Min Cost Max Flow

```

mt19937 rnd(chrono::steady_clock::now().
    time_since_epoch().count());
const LL inf = 1e9;
struct edge {
    int v, rev;
    LL cap, cost, flow;
    edge() {}
    edge(int v, int rev, LL cap, LL cost)
        : v(v), rev(rev), cap(cap), cost(cost)
        , flow(0) {}
};
struct mcmf {
    int src, sink, n;
    vector<int> par, idx, Q;
    vector<bool> inq;
    vector<LL> dis;
    vector<vector<edge>> g;
    mcmf() {}
    mcmf(int src, int sink, int n)
        : src(src),
          sink(sink),
          n(n),
          par(n),
          idx(n),
          inq(n),
          dis(n),
          g(n),
          Q(10000005) {} // use Q(n) if not
          using random
    void addEdge(int u, int v, LL cap, LL
        cost, bool directed = true) {
        edge _u = edge(v, g[v].size(), cap, cost
        );
        edge _v = edge(u, g[u].size(), 0, -cost)
        ;
        g[u].pb(_u);
        g[v].pb(_v);
        if (!directed) addEdge(v, u, cap, cost,
            true);
    }
    bool spfa() {
        for (int i = 0; i < n; i++) {
            dis[i] = inf, inq[i] = false;
        }
        int f = 0, l = 0;
        dis[src] = 0, par[src] = -1, Q[l++] =
            src, inq[src] = true;
        while (f < l) {
            int u = Q[f++];
            for (int i = 0; i < g[u].size(); i++)
                {
                    edge &e = g[u][i];
                    if (e.cap <= e.flow) continue;
                    if (dis[e.v] > dis[u] + e.cost) {
                        dis[e.v] = dis[u] + e.cost;
                        par[e.v] = u, idx[e.v] = i;
                        if (!inq[e.v]) inq[e.v] = true, Q[l
                            ++] = e.v;
                        // if (!inq[e.v]) {
                        //     inq[e.v] = true;
                        //     if (f && rnd() & 7) Q[--f] = e
                            .v;
                        //     else Q[l++] = e.v;
                        // }
                }
            inq[u] = false;
        }
        return (dis[sink] != inf);
    }
}
pair<LL, LL> solve() {
    LL mincost = 0, maxflow = 0;
    while (spfa()) {
        LL bottleneck = inf;
        for (int u = par[sink], v = idx[sink];
            u != -1; v = idx[u], u = par[u])
            {
                edge &e = g[u][v];
            }
    }
}

```



```

        bottleneck = min(bottleneck, e.cap -
            e.flow);
    }
    for (int u = par[sink], v = idx[sink];
        u != -1; v = idx[u], u = par[u])
    {
        edge &e = g[u][v];
        e.flow += bottleneck;
        g[e.v][e.rev].flow -= bottleneck;
    }
    mincost += bottleneck * dis[sink],
    maxflow += bottleneck;
}
return make_pair(mincost, maxflow);
}
};
// want to minimize cost and don't care
// about flow
// add edge from sink to dummy sink (cap =
// inf, cost = 0)
// add edge from source to sink (cap = inf,
// cost = 0)
// run mcmf, cost returned is the minimum
// cost

```

5.11 StoerWanger

/* for finding the min cut of a graph without specifying the source and the sink. all the edges are directed and no need to make any edge bidirectional. */

```

const int N = 1407;
// O(n^3) but faster, 1 indexed

```

```

mt19937 rnd(chrono::steady_clock::now().
    time_since_epoch().count());

```

```

struct StoerWagner {
    int n, idx[N];
    LL G[N][N], dis[N];
    bool vis[N];
    const LL inf = 1e18;

```

```

    StoerWagner() {}
    StoerWagner(int _n) {
        n = _n;
        memset(G, 0, sizeof G);
    }
    void add_edge(
        int u, int v,
        LL w) { // undirected edge, multiple
        edges are merged into one edge
        if (u != v) G[u][v] += w, G[v][u] += w;
    }

    LL solve() {
        LL ans = inf;
        for (int i = 0; i < n; ++i) idx[i] = i + 1;
        shuffle(idx, idx + n, rnd);

        while (n > 1) {
            int t = 1, s = 0;
            for (int i = 1; i < n; ++i) {
                dis[idx[i]] = G[idx[0]][idx[i]];
                if (dis[idx[i]] > dis[idx[t]]) t = i;
            };
            ;

            memset(vis, 0, sizeof vis);
            vis[idx[0]] = true;

            for (int i = 1; i < n; ++i) {
                if (i == n - 1) {
                    if (ans > dis[idx[t]])
                        ans =
                            dis[idx[t]]; // idx[s] - idx[
                            t] is in two halves of
                            the mincut
                    if (ans == 0) return 0;
                    for (int j = 0; j < n; ++j) {
                        G[idx[s]][idx[j]] += G[idx[j]][
                            idx[t]];
                        G[idx[j]][idx[s]] += G[idx[j]][
                            idx[t]];

```

```

        }
        idx[t] = idx[--n];
    }

    vis[idx[t]] = true;
    s = t, t = -1;

    for (int j = 1; j < n; ++j) {
        if (!vis[idx[j]]) {
            dis[idx[j]] += G[idx[s]][idx[j]];
            if (t == -1 || dis[idx[t]] < dis[
                idx[j]]) t = j;
        }
    }
}
return ans;
}
};

```

5.12 Hungarian

/* For max cost, negate cost matrix and negate output.

Complexity: $O(n^2 m)$. n must not be greater than m .
 Input: $(n+1) \times (m+1)$ cost matrix. (0th row and column are useless)
 Output: (ans, ml), where ml[i] = match for node i on the left. */

```

#include <bits/stdc++.h>
using namespace std;

```

```

template <typename T>
pair<T, vector<int>> Hungarian(const vector<
    vector<T>> &cost) {
    const T INF = numeric_limits<T>::max();
    int n = cost.size() - 1, m = cost[0].size() - 1;
    vector<T> U(n + 1), V(n + 1);
    vector<int> mr(m + 1), way(m + 1), ml(n + 1);

```

```

    for (int i = 1; i <= n; i++) {
        mr[0] = i;
        int lastJ = 0;
        vector<T> minV(m + 1, INF);
        vector<bool> used(m + 1);
        do {
            used[lastJ] = true;
            int lastI = mr[lastJ], nextJ;
            T delta = INF;
            for (int j = 1; j <= m; j++) {
                if (used[j]) continue;
                T diffCost = cost[lastI][j] - U[
                    lastI] - V[j];
                if (diffCost < minV[j]) minV[j] =
                    diffCost, way[j] = lastJ;
                if (minV[j] < delta) delta = minV[
                    j], nextJ = j;
            }
            for (int j = 0; j <= m; j++) {
                if (used[j])
                    U[mr[j]] += delta, V[j] -= delta;
                else
                    minV[j] -= delta;
            }
            lastJ = nextJ;
        } while (mr[lastJ] != 0);
        do {
            int prevJ = way[lastJ];
            mr[lastJ] = mr[prevJ];
            lastJ = prevJ;
        } while (lastJ != 0);
        for (int i = 1; i <= m; i++) ml[mr[i]] = i;
        return {-V[0], ml};
    }
}

```

```

int main() {
    ios::sync_with_stdio(0);
    cin.tie(0);

    int n;

```

```

    cin >> n;

    vector<vector<long long>> cost(n + 1,
        vector<long long>(n + 1));
    for (int i = 1; i <= n; i++)
        for (int j = 1; j <= n; j++) cin >> cost[
            i][j];

    auto [ans, match] = Hungarian(cost);
    cout << ans << endl;
    for (int i = 1; i <= n; i++) cout << match[
        i] - 1 << " ";
}

```

5.13 Block Cut Tree

```

vector<vector<int>> components;
vector<int> cutpoints, start, low;
vector<bool> is_cutpoint;
stack<int> st;
void find_cutpoints(int node, graph &G, int
    par = -1, int d = 0) {
    low[node] = start[node] = d++;
    st.push(node);
    int cnt = 0;
    for (int e : G[node])
        if (int to = G(e).to(node); to != par) {
            if (start[to] == -1) {
                find_cutpoints(to, G, node, d + 1);
                cnt++;
                if (low[to] >= start[node]) {
                    is_cutpoint[node] = par != -1 or
                        cnt > 1;
                    components.push_back({node}); //
                        starting a new block with the
                        point
                    while (st.top() != node)
                        components.back().push_back(st.
                            top()), st.pop();
                }
            }
            low[node] = min(low[node], low[to]);
        }
}

```

```

graph tree;
vector<int> id;
void init(graph &G) {
    int n = G.n;
    start.assign(n, -1), low.resize(n),
        is_cutpoint.resize(n), id.assign(n,
            -1);
    find_cutpoints(0, G);
    for (int u = 0; u < n; ++u)
        if (is_cutpoint[u]) id[u] = tree.addNode(
            0);
    for (auto &comp : components) {
        int node = tree.addNode();
        for (int u : comp)
            if (!is_cutpoint[u])
                id[u] = node;
            else
                tree.addEdge(node, id[u]);
    }
    if (id[0] == -1) // corner - 1
        id[0] = tree.addNode();
}

```

5.14 Bridge Tree

```

vector<vector<int>> components;
vector<int> depth, low;
stack<int> st;
vector<int> id;
vector<edge> bridges;
graph tree;
void find_bridges(int node, graph &G, int
    par = -1, int d = 0) {
    low[node] = depth[node] = d;
    st.push(node);
    for (int id : G[node]) {
        int to = G(id).to(node);
        if (par != to) {
            if (depth[to] == -1) {
                find_bridges(to, G, node, d + 1);
                if (low[to] > depth[node]) {

```



```

    bridges.emplace_back(node, to);
    components.push_back({});
    for (int x = -1; x != to; x = st.
        top(), st.pop())
        components.back().push_back(st.
            top());
    }
}
low[node] = min(low[node], low[to]);
}
}
if (par == -1) {
    components.push_back({});
    while (!st.empty()) components.back().
        push_back(st.top(), st.pop());
}
}

graph &create_tree() {
    for (auto &comp : components) {
        int idx = tree.addNode();
        for (auto &e : comp) id[e] = idx;
    }
    for (auto &[l, r] : bridges) tree.addEdge(
        id[l], id[r]);
    return tree;
}

void init(graph &G) {
    int n = G.n;
    depth.assign(n, -1), id.assign(n, -1), low
        .resize(n);
    for (int i = 0; i < n; i++)
        if (depth[i] == -1) find_bridges(i, G);
}

```

5.15 Tree Isomorphism

```

mp["01"] = 1;
ind = 1;
int dfs(int u, int p) {
    int cnt = 0;
    vector<int> vs;
    for (auto v : g1[u]) {
        if (v != p) {
            int got = dfs(v, u);
            vs.pb(got);
            cnt++;
        }
    }
    if (!cnt) return 1;

    sort(vs.begin(), vs.end());
    string s = "0";
    for (auto i : vs) s += to_string(i);
    vs.clear();
    s.pb('1');
    if (mp.find(s) == mp.end()) mp[s] = ++ind;
    int ret = mp[s];
    return ret;
}

```

6 Math

6.1 Adaptive Simpsons

```

/*
    For finding the length of an arc in a
    range
    L = integrate(ds) from start to end of
    range
    where ds = sqrt(1+(d/dy(x))^2)dy
*/
const double SIMPSON_TERMINAL_EPS = 1e-12;
/// Function whose integration is to be
    calculated
double F(double x);
double simpson(double minx, double maxx) {
    return (maxx - minx) / 6 * (F(minx) + 4 *
        F((minx + maxx) / 2.) + F(maxx));
}
double adaptive_simpson(double minx, double
    maxx, double c, double EPS) {
    // if(maxx - minx <
        SIMPSON_TERMINAL_EPS) return 0;

    double midx = (minx + maxx) / 2;
    double a = simpson(minx, midx);

```

```

    double b = simpson(midx, maxx);
    if (fabs(a + b - c) < 15 * EPS) return a +
        b + (a + b - c) / 15.0;

    return adaptive_simpson(minx, midx, a, EPS
        / 2.) +
        adaptive_simpson(midx, maxx, b, EPS
            / 2.);
}
double adaptive_simpson(double minx, double
    maxx, double EPS) {
    return adaptive_simpson(minx, maxx,
        simpson(minx, maxx, i), EPS);
}

```

6.2 Berlekamp Massey

```

struct berlekamp_massey { // for linear
    recursion
    typedef long long LL;
    static const int SZ = 2e5 + 5;
    static const int MOD = 1e9 + 7; /// mod
        must be a prime
    LL m, a[SZ], h[SZ], t_[SZ], s[SZ], t[
        SZ];
    // bigmod goes here
    inline vector<LL> BM( vector<LL> &x ) {
        LL lf, ld;
        vector<LL> ls, cur;
        for (int i = 0; i < int(x.size()); ++i
            ) {
            LL t = 0;
            for (int j = 0; j < int(cur.size());
                ++j) t = (t + x[i - j - 1] * cur
                    [j]) % MOD;
            if ( (t - x[i]) % MOD == 0 ) continue;
            if (!cur.size()) {
                cur.resize( i + 1 );
                lf = i; ld = (t - x[i]) % MOD;
                continue;
            }
            LL k = -(x[i] - t) * bigmod( ld, MOD
                - 2, MOD ) % MOD;
            vector<LL> c(i - lf - 1);
            c.push_back( k );
            for (int j = 0; j < int(ls.size());
                ++j) c.push_back(-ls[j] * k %
                    MOD);
            if ( c.size() < cur.size() ) c.resize(
                cur.size() );
            for (int j = 0; j < int(cur.size());
                ++j) c[j] = (c[j] + cur[j]) %
                MOD;
            if (i - lf + (int)ls.size() >= (int)
                cur.size() ) ls = cur, lf = i, ld
                = (t - x[i]) % MOD;
            cur = c;
        }
        for (int i = 0; i < int(cur.size()); ++
            i) cur[i] = (cur[i] % MOD + MOD) %
                MOD;
        return cur;
    }
    inline void mull( LL *p, LL *q ) {
        for (int i = 0; i < m + m; ++i) t_[i]
            = 0;
        for (int i = 0; i < m; ++i) if ( p[i]
            )
            for (int j = 0; j < m; ++j) t_[i +
                j] = (t_[i + j] + p[i] * q[j])
                    % MOD;
        for (int i = m + m - 1; i >= m; --i)
            if ( t_[i] )
                for (int j = m - 1; ~j; --j) t_[i
                    - j - 1] = (t_[i - j - 1] + t_[i
                        ] * h[j]) % MOD;
        for (int i = 0; i < m; ++i) p[i] = t_[
            i];
    }
    inline LL calc( LL K ) {
        for (int i = m; ~i; --i) s[i] = t[i] =
            0;
        s[0] = 1; if ( m != 1 ) t[1] = 1; else t
            [0] = h[0];

```

```

    while ( K ) {
        if ( K & 1 ) mull( s, t );
        mull( t, t ); K >>= 1;
    }
    LL su = 0;
    for ( int i = 0; i < m; ++i ) su = (su +
        s[i] * a[i]) % MOD;
    return (su % MOD + MOD) % MOD;
}
/// already calculated upto k, now
    calculate upto n.
inline vector<LL> process( vector<LL> &x
    , int n, int k ) {
    auto re = BM( x );
    x.resize( n + 1 );
    for ( int i = k + 1; i <= n; i++ ) {
        for ( int j = 0; j < re.size(); j++ )
            {
                x[i] += 1LL * x[i - j - 1] % MOD *
                    re[j] % MOD; x[i] %= MOD;
            }
    }
    return x;
}
inline LL work( vector<LL> &x, LL n ) {
    if ( n < int(x.size()) ) return x[n] %
        MOD;
    vector<LL> v = BM( x ); m = v.size();
    if (!m) return 0;
    for ( int i = 0; i < m; ++i ) h[i] = v[i
        ], a[i] = x[i];
    return calc( n ) % MOD;
}
} rec;
vector<LL> v;
void solve() {
    int n;
    cin >> n;
    cout << rec.work(v, n - 1) << endl;
}

```

6.3 Fractional Binary Search

```

/**
    Given a function f and n, finds the smallest
    fraction p / q in [0, 1] or [0,n]
    such that f(p / q) is true, and p, q <= n.
    Time: O(log(n))
*/
struct frac { long long p, q; };
bool f(frac x) {
    return 6 + 8 * x.p >= 17 * x.q + 12;
}
frac fracBS(long long n) {
    bool dir = 1, A = 1, B = 1;
    frac lo{0, 1}, hi{1, 0}; // Set hi to 1/0
        to search within [0, n] and {1, 1} to
        search within [0, 1]
    if (f(lo)) return lo;
    assert(f(hi)); //checking if any solution
        exists or not
    while (A || B) {
        long long adv = 0, step = 1; // move hi
            if dir, else lo
        for (int si = 0; step; (step *= 2) >>=
            si) {
            adv += step;
            frac mid{lo.p * adv + hi.p, lo.q * adv
                + hi.q};
            if (abs(mid.p) > n || mid.q > n || dir
                == !f(mid)) {
                adv -= step; si = 2;
            }
        }
        hi.p += lo.p * adv;
        hi.q += lo.q * adv;
        dir = !dir;
        swap(lo, hi);
        A = B; B = !adv;
    }
    return dir ? hi : lo;
}

```

6.4 Gaussian Elimination

```
double gaussian_elimination(int row, int col) {
    int basis[30];
    for (int j = 0; j < row; j++) {
        MAT[j][j + col] = 1;
    }
    memset(basis, -1, sizeof basis);
    double det = 1;
    for (int i = 0; i < col; i++) {
        for (int p = 0; p < row; p++) {
            for (int q = 0; q < col; q++) cout <<
                MAT[p][q] << ' ';
            cout << '\n';
        }
        int x = -1;
        for (int k = 0; k < row; k++) {
            if (abs(MAT[k][i]) > eps and basis[k] == -1) {
                x = k, det *= MAT[k][i], basis[x] = i;
                break;
            }
        }
        if (x < 0) continue;
        for (int j = 0; j < col; j++)
            if (j != i)
                for (int k = 0; k < row; k++)
                    if (k != x) MAT[k][j] -= (MAT[k][i] / MAT[x][i] * MAT[x][j]) / MAT[x][i];
        for (int k = 0; k < col; k++)
            if (k != i) MAT[x][k] /= MAT[x][i];
        for (int j = 0; j < row; j++) MAT[j][i] = (j == i);
    }
    for (int i = 0; i < row; i++) {
        for (int j = 0; j < col; j++) cout <<
            MAT[i][j] << ' ';
        cout << '\n';
    }
    for (int k = 0; k < row; k++)
        if (basis[k] == -1) return 0;
    return det;
}
```

6.5 Green Hackenbush

```
// Green Hackenbush
// Description:
// Consider a two player game on a graph
// with a specified vertex (root).
// In each turn, a player eliminates one
// edge.
// Then, if a subgraph that is
// disconnected from the root, it is
// removed.
// If a player cannot select an edge (i.e
// ., the graph is singleton),
// he will lose.
// Compute the Grundy number of the given
// graph.
// Algorithm:
// We use two principles:
// 1. Colon Principle: Grundy number of
// a tree is the xor of
// Grundy number of child subtrees.
// (Proof: easy).
// 2. Fusion Principle: Consider a pair
// of adjacent vertices u, v
// that has another path (i.e., they
// are in a cycle). Then,
// we can contract u and v without
// changing Grundy number.
// (Proof: difficult)
// We first decompose graph into two-edge
// connected components.
// Then, by contracting each components by
// using Fusion Principle,
// we obtain a tree (and many self loops)
// that has the same Grundy
// number to the original graph. By using
// Colon Principle, we can
```

```
// compute the Grundy number.
// Complexity:
// O(m + n).
// Verified:
// SPOJ 1477: Play with a Tree
// IPSC 2003 G: Got Root?

#define fst first
#define snd second
#define all(c) ((c).begin(), ((c).end()))
struct hackenbush {
    int n;
    vector<vector<int>> adj;
    hackenbush(int n) : n(n), adj(n) {}
    void add_edge(int u, int v) {
        adj[u].push_back(v);
        if (u != v) adj[v].push_back(u);
    }
    // r is the only root connecting to the
    // ground
    int Grundy(int r) {
        vector<int> num(n), low(n);
        int t = 0;
        function<int(int, int)> dfs = [&](int p,
            int u) {
            num[u] = low[u] = ++t;
            int ans = 0;
            for (int v : adj[u]) {
                if (v == p) {
                    p += 2 * n;
                    continue;
                }
                if (num[v] == 0) {
                    int res = dfs(u, v);
                    low[u] = min(low[u], low[v]);
                    if (low[v] > num[u])
                        ans ^= (1 + res) ^ 1; // bridge
                    else
                        ans ^= res; // non bridge
                } else
                    low[u] = min(low[u], num[v]);
            }
            if (p > n) p -= 2 * n;
            for (int v : adj[u])
                if (v != p && num[u] <= num[v]) ans
                    ^= 1;
            return ans;
        };
        return dfs(-1, r);
    };
};
```

6.6 Lagrange

```
// p is a polynomial with n points.
// p(0), p(1), p(2), ... p(n-1) are given.
// Find p(x).
LL Lagrange(vector<LL> &p, LL x) {
    LL n = p.size(), L, i, ret;
    if (x < n) return p[x];
    L = 1;
    for (i = 1; i < n; i++) {
        L = (L * (x - i)) % MOD;
        L = (L * bigmod(MOD - i, MOD - 2)) % MOD;
    }
    ret = (L * p[0]) % MOD;
    for (i = 1; i < n; i++) {
        L = (L * (x - i + 1)) % MOD;
        L = (L * bigmod(x - i, MOD - 2)) % MOD;
        L = (L * bigmod(i, MOD - 2)) % MOD;
        L = (L * (MOD + i - n)) % MOD;
        ret = (ret + L * p[i]) % MOD;
    }
    return ret;
}
```

6.7 Matrix Exponentiation

```
typedef vector<vector<LL>> Mat;
Mat Mul(Mat A, Mat B) {
    Mat ret(A.size(), vector<LL>(B[0].size()))
    ;
```

```
LL i, j, k;
for (i = 0; i < ret.size(); i++) {
    for (j = 0; j < ret[0].size(); j++) {
        for (k = 0; k < A[0].size(); k++)
            ret[i][j] = (ret[i][j] + (A[i][k] *
                B[k][j]) % MOD) % MOD;
    }
}
return ret;
}
Mat Pow(Mat A, LL p) {
    Mat ret(A.size(), vector<LL>(A[0].size()))
    ;
    for (LL i = 0; i < ret.size(); i++) ret[i]
        [i] = 1;
    while (p) {
        if (p & 1) ret = Mul(ret, A);
        A = Mul(A, A);
        p >>= 1;
    }
    return ret;
}
```

6.8 Pollard Rho

```
LL mul(LL a, LL b, LL mod) {
    return (__int128)a * b % mod;
    // LL ans = a * b - mod * (LL) (1.L / mod
    // * a * b);
    // return ans + mod * (ans < 0) - mod * (
    // ans >= (LL) mod);
}
LL bigmod(LL num, LL pow, LL mod) {
    LL ans = 1;
    for (; pow > 0; pow >>= 1, num = mul(num,
        num, mod))
        if (pow & 1) ans = mul(ans, num, mod);
    return ans;
}
bool is_prime(LL n) {
    if (n < 2 or n % 6 % 4 != 1) return (n |
        1) == 3;
    LL a[] = {2, 325, 9375, 28178, 450775,
        9780504, 1795265022};
    LL s = __builtin_ctzll(n - 1), d = n >> s;
    for (LL x : a) {
        LL p = bigmod(x % n, d, n), i = s;
        for (; p != 1 and p != n - 1 and x % n
            and i--; p = mul(p, p, n))
            ;
        if (p != n - 1 and i != s) return false;
    }
    return true;
}
LL get_factor(LL n) {
    auto f = [&](LL x) { return mul(x, x, n) +
        1; };
    LL x = 0, y = 0, t = 0, prod = 2, i = 2, q
        ;
    for (; t++ % 40 or gcd(prod, n) == 1; x =
        f(x), y = f(f(y))) {
        (x == y) ? x = i++, y = f(x) : 0;
        prod = (q = mul(prod, max(x, y) - min(x,
            y), n)) ? q : prod;
    }
    return gcd(prod, n);
}
map<LL, int> factorize(LL n) {
    map<LL, int> res;
    if (n < 2) return res;
    LL small_primes[] = {2, 3, 5, 7, 11, 13,
        17, 19, 23, 29, 31, 37, 41,
        43, 47, 53, 59, 61, 67,
        71, 73, 79, 83,
        89, 97};
    for (LL p : small_primes)
        for (; n % p == 0; n /= p, res[p]++)
            ;
    auto _factor = [&](LL n, auto &_factor) {
        if (n == 1) return;
        if (is_prime(n))
            res[n]++;
        else {
            LL x = get_factor(n);
```

```

_factor(x, _factor);
_factor(n / x, _factor);
}
};
_factor(n, _factor);
return res;
}

```

6.9 Shanks' Baby Step, Giant Step

// Finds $a^x = b \pmod{p}$

```
LL bigmod(LL b, LL p, LL m) {}
```

```
LL babyStepGiantStep(LL a, LL b, LL p) {
    LL i, j, c, sq = sqrt(p);
    map<LL, LL> babyTable;
```

```

    for (j = 0, c = 1; j <= sq; j++, c = (c * a) % p) babyTable[c] = j;

    LL giant = bigmod(a, sq * (p - 2), p);

    for (i = 0, c = 1; i <= sq; i++, c = (c * giant) % p) {
        if (babyTable.find((c * b) % p) != babyTable.end())
            return i * sq + babyTable[(c * b) % p];
    }

```

```
    return -1;
}

```

6.10 Stirling Numbers

//stirling number 2nd kind variation(number of ways to place n marbles in k boxes so that each box has at least x marbles)

```

ll solve(int marble, int box) {
    if (marble < 1ll * box * x) return 0;
    if (box == 1 && marble >= x) return 1;
    if (vis[marble][box] == cs) return dp[marble][box];
    vis[marble][box] = cs;
    ll a = ( 1ll * box * solve(marble - 1, box) ) % MOD;
    ll b = ( 1ll * box * ncr(marble - 1, x - 1) ) % MOD;
    b = (b * solve(marble - x, box - 1)) % MOD;
    ll ret = (a + b) % MOD;
    return dp[marble][box] = ret;
}

```

//number of ways to place n marbles in k boxes so that no box is empty

```

ll stir(ll n, ll k) {
    ll ret = 0;
    for (int i = 0; i <= k; i++) {
        ll v = ncr(k, i) * bigmod(i, n) % MOD;
        if ( (k - i) % 2 == 0 ) ret = (ret + v) % MOD;
        else ret = (ret - v + MOD) % MOD;
    }
    return ret;
}

```

6.11 Xor Basis

```

struct XorBasis {
    static const int sz = 64;
    array<ULL, sz> base = {0}, back;
    array<int, sz> pos;
    void insert(ULL x, int p) {
        ULL cur = 0;
        for (int i = sz - 1; ~i; i--)
            if (x >> i & 1) {
                if (!base[i]) {
                    base[i] = x, back[i] = cur, pos[i] = p;
                    break;
                } else x ^= base[i], cur |= 1ULL << i;
            }
    }
}

```

```

pair<ULL, vector<int>> construct(ULL mask)
{
    ULL ok = 0, x = mask;
    for (int i = sz - 1; ~i; i--)
        if (mask >> i & 1 and base[i]) mask ^= base[i], ok |= 1ULL << i;
    vector<int> ans;
    for (int i = 0; i < sz; i++)
        if (ok >> i & 1) {
            ans.push_back(pos[i]);
            ok ^= back[i];
        }
    return {x ^ mask, ans};
}

```

6.12 Combi

```

array<int, N + 1> fact, inv, inv_fact;
void init() {
    fact[0] = inv_fact[0] = 1;
    for (int i = 1; i <= N; i++) {
        inv[i] = i == 1 ? 1 : (LL)inv[i - 1] * mod % i * (mod / i + 1) % mod;
        fact[i] = (LL)fact[i - 1] * i % mod;
        inv_fact[i] = (LL)inv_fact[i - 1] * inv[i] % mod;
    }
}
LL C(int n, int r) {
    return (r < 0 or r > n) ? 0 : (LL)fact[n] * inv_fact[r] % mod * inv_fact[n - r] % mod;
}

```

6.13 Linear Sieve

```

const int N = 1e7;
vector<int> primes;
int spf[N + 5], phi[N + 5], NOD[N + 5], cnt[N + 5], POW[N + 5];
bool prime[N + 5];
int SOD[N + 5];
void init() {
    fill(prime + 2, prime + N + 1, 1);
    SOD[1] = NOD[1] = phi[1] = spf[1] = 1;
    for (LL i = 2; i <= N; i++) {
        if (prime[i]) {
            primes.push_back(i), spf[i] = i;
            phi[i] = i - 1;
            NOD[i] = 2, cnt[i] = 1;
            SOD[i] = i + 1, POW[i] = i;
        }
        for (auto p : primes) {
            if (p * i > N or p > spf[i]) break;
            prime[p * i] = false, spf[p * i] = p;
            if (i % p == 0) {
                phi[p * i] = p * phi[i];
                NOD[p * i] = NOD[i] / (cnt[i] + 1) * (cnt[i] + 2);
                cnt[p * i] = cnt[i] + 1;
                SOD[p * i] = SOD[i] / SOD[POW[i]] * (SOD[POW[i]] + p * POW[i]);
                POW[p * i] = p * POW[i];
                break;
            } else {
                phi[p * i] = phi[p] * phi[i];
                NOD[p * i] = NOD[p] * NOD[i], cnt[p * i] = 1;
                SOD[p * i] = SOD[p] * SOD[i], POW[p * i] = p;
            }
        }
    }
}

```

6.14 Chinese Remainder Theorem

```

// given a, b will find solutions for
// ax + by = 1
tuple<LL, LL, LL> EGCD(LL a, LL b) {
    if (b == 0)
        return {1, 0, a};
    else {
        auto [x, y, g] = EGCD(b, a % b);
        return {y, x - a / b * y, g};
    }
}

```

```

}
}
// given modulo equations, will apply CRT
PLL CRT(vector<PLL> &v) {
    LL V = 0, M = 1;
    for (auto &[v, m] : v) { // value % mod
        auto [x, y, g] = EGCD(M, m);
        if ((v - V) % g != 0) return {-1, 0};
        V += x * (v - V) / g % (m / g) * M, M *= m / g;
        V = (V % M + M) % M;
    }
    return make_pair(V, M);
}

```

6.15 Mobius Function

```

const int N = 1e6 + 5;
int mob[N];
void mobius() {
    memset(mob, -1, sizeof mob);
    mob[1] = 1;
    for (int i = 2; i < N; i++)
        if (mob[i]) {
            for (int j = i + i; j < N; j += i) mob[j] -= mob[i];
        }
}

```

6.16 FFT

```

using CD = complex<double>;
typedef long long LL;
const double PI = acos(-1.0L);

```

```

int N;
vector<int> perm;
vector<CD> wp[2];
void precalculate(int n) {
    assert((n & (n - 1)) == 0), N = n;
    perm = vector<int>(N, 0);
    for (int k = 1; k < N; k <= 1) {
        for (int i = 0; i < k; i++) {
            perm[i] <= 1;
            perm[i + k] = 1 + perm[i];
        }
    }
    wp[0] = wp[1] = vector<CD>(N);
    for (int i = 0; i < N; i++) {
        wp[0][i] = CD(cos(2 * PI * i / N), sin(2 * PI * i / N));
        wp[1][i] = CD(cos(2 * PI * i / N), -sin(2 * PI * i / N));
    }
}
void fft(vector<CD> &v, bool invert = false)
{
    if (v.size() != perm.size()) precalculate(v.size());
    for (int i = 0; i < N; i++)
        if (i < perm[i]) swap(v[i], v[perm[i]]);
    for (int len = 2; len <= N; len *= 2) {
        for (int i = 0, d = N / len; i < N; i += len) {
            for (int j = 0, idx = 0; j < len / 2; j++, idx += d) {
                CD x = v[i + j];
                CD y = wp[invert][idx] * v[i + j + len / 2];
                v[i + j] = x + y;
                v[i + j + len / 2] = x - y;
            }
        }
    }
    if (invert) {
        for (int i = 0; i < N; i++) v[i] /= N;
    }
}
void pairfft(vector<CD> &a, vector<CD> &b, bool invert = false) {
    int N = a.size();
    vector<CD> p(N);
    for (int i = 0; i < N; i++) p[i] = a[i] + b[i] * CD(0, 1);
    fft(p, invert);
}

```

```

p.push_back(p[0]);
for (int i = 0; i < N; i++) {
    if (invert) {
        a[i] = CD(p[i].real(), 0);
        b[i] = CD(p[i].imag(), 0);
    } else {
        a[i] = (p[i] + conj(p[N - i])) * CD(
            (0.5, 0);
        b[i] = (p[i] - conj(p[N - i])) * CD(0,
            -0.5);
    }
}
}
vector<LL> multiply(const vector<LL> &a,
    const vector<LL> &b) {
    int n = 1;
    while (n < a.size() + b.size()) n <= 1;
    vector<CD> fa(a.begin(), a.end()), fb(b.
        begin(), b.end());
    fa.resize(n);
    fb.resize(n);
    // fft(fa); fft(fb);
    pairfft(fa, fb);
    for (int i = 0; i < n; i++) fa[i] = fa[i]
        * fb[i];
    fft(fa, true);
    vector<LL> ans(n);
    for (int i = 0; i < n; i++) ans[i] = round
        (fa[i].real());
    return ans;
}
const int M = 1e9 + 7, B = sqrt(M) + 1;
vector<LL> anyMod(const vector<LL> &a, const
    vector<LL> &b) {
    int n = 1;
    while (n < a.size() + b.size()) n <= 1;
    vector<CD> al(n), ar(n), bl(n), br(n);
    for (int i = 0; i < a.size(); i++) al[i] =
        a[i] % M / B, ar[i] = a[i] % M % B;
    for (int i = 0; i < b.size(); i++) bl[i] =
        b[i] % M / B, br[i] = b[i] % M % B;
    pairfft(al, ar);
    pairfft(bl, br);
    // fft(al); fft(ar); fft(bl); fft(br
        );
    for (int i = 0; i < n; i++) {
        CD ll = (al[i] * bl[i]), lr = (al[i] *
            br[i]);
        CD rl = (ar[i] * bl[i]), rr = (ar[i] *
            br[i]);
        al[i] = ll;
        ar[i] = lr;
        bl[i] = rl;
        br[i] = rr;
    }
    pairfft(al, ar, true);
    pairfft(bl, br, true);
    // fft(al, true); fft(ar, true); fft
        (bl, true); fft(br, true);
    vector<LL> ans(n);
    for (int i = 0; i < n; i++) {
        LL right = round(br[i].real()), left =
            round(al[i].real());
        ;
        LL mid = round(round(bl[i].real()) +
            round(ar[i].real()));
        ans[i] = ((left % M) * B * B + (mid % M)
            * B + right) % M;
    }
    return ans;
}

```

6.17 NTT

```

const LL N = 1 << 18;
const LL MOD = 786433;

```

```

vector<LL> P[N];
LL rev[N], w[N | 1], a[N], b[N], inv_n, g;
LL Pow(LL b, LL p) {
    LL ret = 1;
    while (p) {
        if (p & 1) ret = (ret * b) % MOD;
        b = (b * b) % MOD;
        p >>= 1;
    }
}

```

```

}
return ret;
}
LL primitive_root(LL p) {
    vector<LL> factor;
    LL phi = p - 1, n = phi;
    for (LL i = 2; i * i <= n; i++) {
        if (n % i) continue;
        factor.emplace_back(i);
        while (n % i == 0) n /= i;
    }
    if (n > 1) factor.emplace_back(n);
    for (LL res = 2; res <= p; res++) {
        bool ok = true;
        for (LL i = 0; i < factor.size() && ok;
            i++)
            ok &= Pow(res, phi / factor[i]) != 1;
        if (ok) return res;
    }
    return -1;
}
void prepare(LL n) {
    LL sz = abs(31 - __builtin_clz(n));
    LL r = Pow(g, (MOD - 1) / n);
    inv_n = Pow(n, MOD - 2);
    w[0] = w[n] = 1;
    for (LL i = 1; i < n; i++) w[i] = (w[i -
        1] * r) % MOD;
    for (LL i = 1; i < n; i++)
        rev[i] = (rev[i >> 1] >> 1) | ((i & 1)
            << (sz - 1));
}
void NTT(LL *a, LL n, LL dir = 0) {
    for (LL i = 1; i < n - 1; i++)
        if (i < rev[i]) swap(a[i], a[rev[i]]);
    for (LL m = 2; m <= n; m <= 1) {
        for (LL i = 0; i < n; i += m) {
            for (LL j = 0; j < (m >> 1); j++) {
                LL &u = a[i + j], &v = a[i + j + (m
                    >> 1)];
                LL t = v * w[dir ? n - n / m * j : n
                    / m * j] % MOD;
                v = u - t < 0 ? u - t + MOD : u - t;
                u = u + t >= MOD ? u + t - MOD : u +
                    t;
            }
        }
    }
    if (dir)
        for (LL i = 0; i < n; i++) a[i] = (inv_n
            * a[i]) % MOD;
}
vector<LL> mul(vector<LL> p, vector<LL> q) {
    LL n = p.size(), m = q.size();
    LL t = n + m - 1, sz = 1;
    while (sz < t) sz <= 1;
    prepare(sz);
    for (LL i = 0; i < n; i++) a[i] = p[i];
    for (LL i = 0; i < m; i++) b[i] = q[i];
    for (LL i = n; i < sz; i++) a[i] = 0;
    for (LL i = m; i < sz; i++) b[i] = 0;
    NTT(a, sz);
    NTT(b, sz);
    for (LL i = 0; i < sz; i++) a[i] = (a[i] *
        b[i]) % MOD;
    NTT(a, sz, 1);
    vector<LL> c(a, a + sz);
    while (c.size() && c.back() == 0) c.
        pop_back();
    return c;
}

```

6.18 WalshHadamard

```

#include <bits/stdc++.h>
using namespace std;
typedef long long LL;
#define bitwiseXOR 1
// #define bitwiseAND 2
// #define bitwiseOR 3
const LL MOD = 30011;

```

```

LL BigMod(LL b, LL p) {
    LL ret = 1;
    while (p > 0) {
        if (p % 2 == 1) {
            ret = (ret * b) % MOD;
        }
        p = p / 2;
        b = (b * b) % MOD;
    }
    return ret % MOD;
}
void FWHT(vector<LL>& p, bool inverse) {
    LL n = p.size();
    assert((n & (n - 1)) == 0);
    for (LL len = 1; 2 * len <= n; len <= 1) {
        for (LL i = 0; i < n; i += len + len) {
            for (LL j = 0; j < len; j++) {
                LL u = p[i + j];
                LL v = p[i + len + j];
                #ifdef bitwiseXOR
                    p[i + j] = (u + v) % MOD;
                    p[i + len + j] = (u - v + MOD) % MOD;
                ;
                #endif // bitwiseXOR
                #ifdef bitwiseAND
                    if (!inverse) {
                        p[i + j] = v % MOD;
                        p[i + len + j] = (u + v) % MOD;
                    } else {
                        p[i + j] = (-u + v) % MOD;
                        p[i + len + j] = u % MOD;
                    }
                #endif // bitwiseAND
                #ifdef bitwiseOR
                    if (!inverse) {
                        p[i + j] = u + v;
                        p[i + len + j] = u;
                    } else {
                        p[i + j] = v;
                        p[i + len + j] = u - v;
                    }
                #endif // bitwiseOR
            }
        }
    }
    #ifdef bitwiseXOR
        if (inverse) {
            LL val = BigMod(n, MOD - 2); // Option
                2: Exclude
            for (LL i = 0; i < n; i++) {
                // assert(p[i]%n==0); //Option 2:
                    Include
                p[i] = (p[i] * val) % MOD; // Option
                    2: p[i]/=n;
            }
        }
    #endif // bitwiseXOR
}

```

7 String

7.1 Aho Corasick

```

const int sg = 26, N = 1e3 + 9;
struct aho_corasick {
    struct node {
        node *link, *out, *par;
        bool leaf;
        LL val;
        int cnt, last, len;
        char p_ch;
        array<node*, sg> to;
        node(node* par = NULL, char p_ch = '$',
            int len = 0) : par(par), p_ch(p_ch), len(len) {
            val = leaf = cnt = last = 0;
            link = out = NULL;
        }
    };
};

```



```

    }
};
vector<node> trie;
node* root;
aho_corasick() {
    trie.reserve(N), trie.emplace_back();
    root = &trie[0];
    root->link = root->out = root;
}
inline int f(char c) { return c - 'a'; }
inline node* add_node(node* par = NULL,
    char p_ch = '$', int len = 0) {
    trie.emplace_back(par, p_ch, len);
    return &trie.back();
}
void add_str(const string& s, LL val = 1)
{
    node* now = root;
    for (char c : s) {
        int i = f(c);
        if (!now->to[i]) now->to[i] = add_node
            (now, c, now->len + 1);
        now = now->to[i];
    }
    now->leaf = true, now->val++;
}
void push_links() {
    queue<node*> q;
    for (q.push(root); q.empty(); q.pop()) {
        node *cur = q.front(), *link = cur->
            link;
        cur->out = link->leaf ? link : link->
            out;
        int idx = 0;
        for (auto& next : cur->to) {
            if (next != NULL) {
                next->link = cur != root ? link->to
                    [idx++] : root;
                q.push(next);
            } else
                next = link->to[idx++];
        }
        cur->val += link->val;
    }
};

```

7.2 Double hash

```

ostream& operator<<(ostream& os, PLL hash) {
    return os << "(" << hash.ff << ", " <<
        hash.ss << ")";
}

```

```

PLL operator+(PLL a, LL x) { return PLL(a.ff
    + x, a.ss + x); }
PLL operator-(PLL a, LL x) { return PLL(a.ff
    - x, a.ss - x); }
PLL operator*(PLL a, LL x) { return PLL(a.ff
    * x, a.ss * x); }
PLL operator+(PLL a, PLL x) { return PLL(a.
    ff + x.ff, a.ss + x.ss); }
PLL operator-(PLL a, PLL x) { return PLL(a.
    ff - x.ff, a.ss - x.ss); }
PLL operator*(PLL a, PLL x) { return PLL(a.
    ff * x.ff, a.ss * x.ss); }
PLL operator%(PLL a, PLL m) { return PLL(a.
    ff % m.ff, a.ss % m.ss); }

```

```

PLL base(1949313259, 1997293877);
PLL mod(2091573227, 2117566807);

```

```

PLL power(PLL a, LL p) {
    if (!p) return PLL(1, 1);
    PLL ans = power(a, p / 2);
    ans = (ans * ans) % mod;
    if (p % 2) ans = (ans * a) % mod;
    return ans;
}

```

```

PLL inverse(PLL a) { return power(a, (mod.ff
    - 1) * (mod.ss - 1) - 1); }
PLL inv_base = inverse(base);

```

```

PLL val;

```

```

vector<PLL> P;
void hash_init(int n) {
    P.resize(n + 1);
    P[0] = PLL(1, 1);
    for (int i = 1; i <= n; i++) P[i] = (P[i -
        1] * base) % mod;
}
// appends c to string
PLL append(PLL cur, char c) { return (cur *
    base + c) % mod; }
// prepends c to string with size k
PLL prepend(PLL cur, int k, char c) { return
    (P[k] * c + cur) % mod; }
// replaces the i-th (0-indexed) character
// from right from a to b;
PLL replace(PLL cur, int i, char a, char b)
{
    cur = (cur + P[i] * (b - a)) % mod;
    return (cur + mod) % mod;
}
// Erases c from the back of the string
PLL pop_back(PLL hash, char c) {
    return ((hash - c) * inv_base) % mod +
        mod) % mod;
}
// Erases c from front of the string with
// size len
PLL pop_front(PLL hash, int len, char c) {
    return ((hash - P[len - 1] * c) % mod +
        mod) % mod;
}
// concatenates two strings where length of
// the right is k
PLL concat(PLL left, PLL right, int k) {
    return (left * P[k] + right) % mod; }
// Calculates hash of string with size len
// repeated cnt times
// This is O(log n). For O(1), pre-
// calculate inverses
PLL repeat(PLL hash, int len, LL cnt) {
    PLL mul = (P[len * cnt] - 1) * inverse(P[
        len] - 1);
    mul = (mul % mod + mod) % mod;
    PLL ret = (hash * mul) % mod;
    if (P[len].ff == 1) ret.ff = hash.ff * cnt
        ;
    if (P[len].ss == 1) ret.ss = hash.ss * cnt
        ;
    return ret;
}
PLL get(PLL hash) { return ((hash.ff << 32) ~
    hash.ss); }
struct hashlist {
    int len;
    vector<PLL> H, R;
    hashlist() {}
    hashlist(string& s) {
        len = (int)s.size();
        hash_init(len);
        H.resize(len + 1, PLL(0, 0)), R.resize(
            len + 2, PLL(0, 0));
        for (int i = 1; i <= len; i++) H[i] =
            append(H[i - 1], s[i - 1]);
        for (int i = len; i >= 1; i--) R[i] =
            append(R[i + 1], s[i - 1]);
    }
    // 1-indexed
    inline PLL range_hash(int l, int r) {
        int len = r - l + 1;
        return ((H[r] - H[l - 1] * P[len]) % mod
            + mod) % mod;
    }
    inline PLL reverse_hash(int l, int r) {
        int len = r - l + 1;

```

```

        return ((R[l] - R[r + 1] * P[len]) % mod
            + mod) % mod;
    }
    inline PLL concat_range_hash(int l1, int
        r1, int l2, int r2) {
        int len_2 = r2 - l2 + 1;
        return concat(range_hash(l1, r1),
            range_hash(l2, r2), len_2);
    }
    inline PLL concat_reverse_hash(int l1, int
        r1, int l2, int r2) {
        int len_1 = r1 - l1 + 1;
        return concat(reverse_hash(l2, r2),
            reverse_hash(l1, r1), len_1);
    }
};

```

7.3 Manacher's

```

vector<int> d1(n);
// d[i] = number of palindromes taking s[i]
// as center
for (int i = 0, l = 0, r = -1; i < n; i++) {
    int k = (i > r) ? 1 : min(d1[l + r - i], r
        - i + 1);
    while (0 <= i - k && i + k < n && s[i - k]
        == s[i + k]) k++;
    d1[i] = k--;
    if (i + k > r) l = i - k, r = i + k;
}

```

```

vector<int> d2(n);
// d[i] = number of palindromes taking s[i
// -1] and s[i] as center
for (int i = 0, l = 0, r = -1; i < n; i++) {
    int k = (i > r) ? 0 : min(d2[l + r - i +
        1], r - i + 1);
    while (0 <= i - k - 1 && i + k < n && s[i
        - k - 1] == s[i + k]) k++;
    d2[i] = k--;
    if (i + k > r) l = i - k - 1, r = i + k;
}

```

7.4 Palindromic Tree

```

struct state {
    int len, link;
    map<char, int> next;
};
state st[MAX];
int id, last;
string s;
ll ans[MAX];
void init() {
    for (int i = 0; i <= id; i++) {
        st[i].len = 0; st[i].link = 0;
        st[i].next.clear(); ans[i] = 0;
    }
    st[1].len = -1; st[1].link = 1;
    st[2].len = 0; st[2].link = 1;
    id = 2; last = 2;
}
void extend(int pos) {
    while (s[pos - st[last].len - 1] != s[pos
        ]) last = st[last].link;
    int newlink = st[last].link;
    char c = s[pos];
    while (s[pos - st[newlink].len - 1] != s[
        pos]) newlink = st[newlink].link;
    if (!st[last].next.count(c)) {
        st[last].next[c] = ++id;
        st[id].len = st[last].len + 2;
        st[id].link = (st[id].len == 1 ? 2 : st[
            newlink].next[c]);
        ans[id] += ans[st[id].link];
        if (st[id].len > 2) {
            int l = st[id].len / 2 + (st[id].len %
                2 ? 1 : 0);
            if (h.range_hash(pos - st[id].len + 1,
                pos - st[id].len + 1) == h.
                reverse_hash(pos - st[id].len +
                    1, pos - st[id].len + 1)) ans[id
                    ]++;

```



```

    }
}
last = st[last].next[c];
}

```

7.5 String Match FFT

```

//find occurrences of t in s where '?'s are
//automatically matched with any
//character
//res[i + m - 1] = sum_j=0 to m - 1_{s[i + j]
// * t[j] * (s[i + j] - t[j])}
vector<int> string_matching(string &s,
    string &t) {
    int n = s.size(), m = t.size();
    vector<int> s1(n), s2(n), s3(n);
    for(int i = 0; i < n; i++) s1[i] = s[i] ==
        '?' ? 0 : s[i] - 'a' + 1; //assign
        //any non zero number for non '?'s
    for(int i = 0; i < n; i++) s2[i] = s1[i] *
        s1[i];
    for(int i = 0; i < n; i++) s3[i] = s1[i] *
        s2[i];
    vector<int> t1(m), t2(m), t3(m);
    for(int i = 0; i < m; i++) t1[i] = t[i] ==
        '?' ? 0 : t[i] - 'a' + 1;
    for(int i = 0; i < m; i++) t2[i] = t1[i] *
        t1[i];
    for(int i = 0; i < m; i++) t3[i] = t1[i] *
        t2[i];
    reverse(t1.begin(), t1.end());
    reverse(t2.begin(), t2.end());
    reverse(t3.begin(), t3.end());
    vector<int> s1t3 = multiply(s1, t3);
    vector<int> s2t2 = multiply(s2, t2);
    vector<int> s3t1 = multiply(s3, t1);
    vector<int> res(n);
    for(int i = 0; i < n; i++) res[i] = s1t3[i]
        - s2t2[i] * 2 + s3t1[i];
    vector<int> oc;
    for(int i = m - 1; i < n; i++) if(res[i]
        == 0) oc.push_back(i - m + 1);
    return oc;
}

```

7.6 Suffix Array

```

/** Suffix Array Construction: O(NlogN)
    LCP Array Construction: O(NlogN)
    Suffix LCP: O(logN) */
typedef pair<int, int> PII;
typedef vector<int> VI;

// Equivalence Class INFO
vector<VI> c;
VI sort_cyclic_shifts(const string &s) {
    int n = s.size();
    const int alphabet = 256;
    VI p(n), cnt(alphabet, 0);

    c.clear();
    c.emplace_back();
    c[0].resize(n);

    for (int i = 0; i < n; i++) cnt[s[i]]++;
    for (int i = 1; i < alphabet; i++) cnt[i]
        += cnt[i - 1];
    for (int i = 0; i < n; i++) p[--cnt[s[i]]]
        = i;

    c[0][p[0]] = 0;
    int classes = 1;

    for (int i = 1; i < n; i++) {
        if (s[p[i]] != s[p[i - 1]]) classes++;
        c[0][p[i]] = classes - 1;
    }

    VI pn(n), cn(n);
    cnt.resize(n);

    for (int h = 0; (1 << h) < n; h++) {
        for (int i = 0; i < n; i++) {
            pn[i] = p[i] - (1 << h);
            if (pn[i] < 0) pn[i] += n;

```

```

        }
        fill(cnt.begin(), cnt.end(), 0);

        // radix sort
        for (int i = 0; i < n; i++) cnt[c[h][pn[i]]]++;
        for (int i = 1; i < classes; i++) cnt[i]
            += cnt[i - 1];
        for (int i = n - 1; i >= 0; i--) p[--cnt
            [c[h][pn[i]]]] = pn[i];

        cn[p[0]] = 0;
        classes = 1;

        for (int i = 1; i < n; i++) {
            PII cur = {c[h][p[i]], c[h][(p[i] + (1
                << h)) % n]};
            PII prev = {c[h][p[i - 1]], c[h][(p[i
                - 1] + (1 << h)) % n]};
            if (cur != prev) ++classes;
            cn[p[i]] = classes - 1;
        }
        c.push_back(cn);
    }
    return p;
}

VI suffix_array_construction(string s) {
    s += "!";
    VI sorted_shifts = sort_cyclic_shifts(s);
    sorted_shifts.erase(sorted_shifts.begin());
    return sorted_shifts;
}

// LCP between the ith and jth (i != j)
// suffix of the STRING
int suffixLCP(int i, int j) {
    assert(i != j);
    int log_n = c.size() - 1;

    int ans = 0;
    for (int k = log_n; k >= 0; k--) {
        if (c[k][i] == c[k][j]) {
            ans += 1 << k;
            i += 1 << k;
            j += 1 << k;
        }
    }
    return ans;
}

VI lcp_construction(const string &s, const
    VI &sa) {
    int n = s.size();
    VI rank(n, 0);
    VI lcp(n - 1, 0);

    for (int i = 0; i < n; i++) rank[sa[i]] =
        i;

    for (int i = 0, k = 0; i < n; i++) {
        if (rank[i] == n - 1) {
            k = 0;
            continue;
        }

        int j = sa[rank[i] + 1];
        while (i + k < n && j + k < n && s[i + k]
            == s[j + k]) k++;
        lcp[rank[i]] = k;
        if (k) k--;
    }
    return lcp;
}

const int MX = 1e6 + 7, K = 20;
int lg[MX];

void pre() {
    lg[1] = 0;
    for (int i = 2; i < MX; i++) lg[i] = lg[i
        / 2] + 1;
}

```

```

struct RMQ {
    int N;
    VI v[K];
    RMQ(const VI &a) {
        N = a.size();
        v[0] = a;

        for (int k = 0; (1 << (k + 1)) <= N; k
            ++){
            v[k + 1].resize(N);
            for (int i = 0; i - 1 + (1 << (k + 1))
                < N; i++) {
                v[k + 1][i] = min(v[k][i], v[k][i +
                    (1 << k)]);
            }
        }

        int findMin(int i, int j) {
            int k = lg[j - i + 1];
            return min(v[k][i], v[k][j + 1 - (1 << k
                )]);
        }
    };
};

```

7.7 Suffix Automata

```

/**
    Linear Time Suffix Automata construction.
    Build Complexity: O(n * alphabet)
    To achieve better build complexity and
    linear space,
    use map for transitions.
    */

#include<bits/stdc++.h>
using namespace std;

const int MAXN = 1e5+7, ALPHA = 26;
int len[2*MAXN], link[2*MAXN], nxt[2*MAXN][
    ALPHA];
int sz;
int last;

void sa_init() {
    memset(nxt, -1, sizeof nxt);

    len[0] = 0;
    link[0] = -1;
    sz = 1;
    last = 0;
}

void add(char ch) {
    int c = ch - 'a';

    int cur = sz++;
    //create new node
    len[cur] = len[last] + 1;

    int u = last;
    while (u != -1 && nxt[u][c] == -1) {
        nxt[u][c] = cur;
        u = link[u];
    }

    if (u == -1) {
        link[cur] = 0;
    }
    else {
        int v = nxt[u][c];
        if (len[v] == len[u] + 1) {
            link[cur] = v;
        }
        else {
            int clone = sz++;
            //create node by cloning
            len[clone] = 1 + len[u];
            link[clone] = link[v];

            for (int i=0; i<ALPHA; i++)
                nxt[clone][i] = nxt[v][i];

```

```

        while (u != -1 && nxt[u][c] == v)
        {
            nxt[u][c] = clone;
            u = link[u];
        }

        link[v] = link[cur] = clone;
    }
}
last = cur;
}

vector<int> edge[2*MAXN];
//Optional, Call after adding all
//characters
void makeEdge() {
    for (int i=0; i<sz; i++) {
        edge[i].clear();
        for (int j=0; j<ALPHA; j++)
            if (nxt[i][j]!=-1)
                edge[i].push_back(j);
    }
}

// The following code solves SPOJ SUBLEX
// Given a string S, you have to answer some
// queries:
// If all distinct substrings of string S
// were sorted
// lexicographically, which one will be the
// K-th smallest?

long long dp[2*MAXN];
bool vis[2*MAXN];

void dfs(int u) {
    if (vis[u]) return;
    vis[u] = 1;
    dp[u] = 1;
    for (int i: edge[u]) {
        if (nxt[u][i] == -1) continue;
        dfs(nxt[u][i]);
        dp[u] += dp[nxt[u][i]];
    }
}

void go(int u, long long rem, string &s) {
    if (rem == 1) return;
    long long sum = 1;
    for (int i: edge[u]) {
        if (nxt[u][i] == -1) continue;
        if (sum + dp[nxt[u][i]] < rem) {
            sum += dp[nxt[u][i]];
        }
        else {
            s += ('a' + i);
            go(nxt[u][i], rem-sum, s);
            return;
        }
    }
}

int main() {
    ios::sync_with_stdio(0);
    cin.tie(0);

    string s;
    cin>>s;

    sa_init();
    for (char c: s) add(c);
    makeEdge();

    dfs(0);
    int q;
    cin>>q;

    while (q--) {
        long long x;
        cin>>x;
        x++;
        string s;
        go(0, x, s);
    }
}

```

```

        cout<<s<<"\n";
    }
}

7.8 Z Algo

vector<int> calcz(string s) {
    int n = s.size();
    vector<int> z(n);
    int l, r; l = r = 0;
    for (int i = 1; i < n; i++) {
        if (i > r) {
            l = r = i;
            while (r < n && s[r] == s[r - 1])
                r++;
            z[i] = r - l; r--;
        } else {
            int k = i - l;
            if (z[k] < r - i + 1) z[i] = z[k];
            else {
                l = i;
                while (r < n && s[r] == s[r - 1]) r++;
                z[i] = r - l; r--;
            }
        }
    }
    return z;
}

```

8 Equations and Formulas

8.1 Catalan Numbers

$$C_n = \frac{1}{n+1} \binom{2n}{n} \quad C_0 = 1, C_1 = 1 \text{ and } C_n = \sum_{k=0}^{n-1} C_k C_{n-1-k}$$

The number of ways to completely parenthesize $n+1$ factors.

The number of triangulations of a convex polygon with $n+2$ sides (i.e. the number of partitions of polygon into disjoint triangles by using the diagonals).

The number of ways to connect the $2n$ points on a circle to form n disjoint i.e. non-intersecting chords.

The number of rooted full binary trees with $n+1$ leaves (vertices are not numbered). A rooted binary tree is full if every vertex has either two children or no children.

Number of permutations of $1, \dots, n$ that avoid the pattern 123 (or any of the other patterns of length 3); that is, the number of permutations with no three-term increasing sub-sequence. For $n = 3$, these permutations are 132, 213, 231, 312 and 321.

8.2 Stirling Numbers First Kind

The Stirling numbers of the first kind count permutations according to their number of cycles (counting fixed points as cycles of length one).

$S(n, k)$ counts the number of permutations of n elements with k disjoint cycles.

$$S(n, k) = (n-1) \cdot S(n-1, k) + S(n-1, k-1), \text{ where, } S(0, 0) = 1, S(n, 0) = S(0, n) = 0 \quad \sum_{k=0}^n S(n, k) = n!$$

The unsigned Stirling numbers may also be defined algebraically, as the coefficient of the rising factorial:

$$x^{\bar{n}} = x(x+1)\dots(x+n-1) = \sum_{k=0}^n S(n, k) x^k$$

Lets $[n, k]$ be the stirling number of the first kind, then

$$\left[\begin{matrix} n \\ k \end{matrix} \right] = \sum_{0 \leq i_1 < i_2 < \dots < i_k < n} i_1 i_2 \dots i_k.$$

8.3 Stirling Numbers Second Kind

Stirling number of the second kind is the number of ways to partition a set of n objects into k non-empty subsets.

$S(n, k) = k \cdot S(n-1, k) + S(n-1, k-1)$, where $S(0, 0) = 1, S(n, 0) = S(0, n) = 0$ $S(n, 2) = 2^{n-1} - 1$ $S(n, k) \cdot k! =$ number of ways to color n nodes using colors from 1 to k such that each color is used at least once.

An r -associated Stirling number of the second kind is the number of ways to partition a set of n objects into k subsets, with each subset containing at least r elements. It is denoted by $S_r(n, k)$ and obeys the recurrence relation. $S_r(n+1, k) =$

$$k S_r(n, k) + \binom{n}{r-1} S_r(n-r+1, k-1)$$

Denote the n objects to partition by the integers $1, 2, \dots, n$. Define the reduced Stirling numbers of the second kind, denoted $S^d(n, k)$, to be the number of ways to partition the integers $1, 2, \dots, n$ into k nonempty subsets such that all elements in each subset have pairwise distance at least d . That is, for any integers i and j in a given subset, it is required that $|i - j| \geq d$. It has been shown that these numbers satisfy, $S^d(n, k) = S(n-d+1, k-d+1), n \geq k \geq d$

8.4 Other Combinatorial Identities

$$\begin{aligned} \binom{n}{k} &= \frac{n}{k} \binom{n-1}{k-1} \\ \sum_{i=0}^k \binom{n+i}{i} &= \sum_{i=0}^k \binom{n+i}{n} = \binom{n+k+1}{k} \\ n, r \in N, n > r, \sum_{i=r}^n \binom{i}{r} &= \binom{n+1}{r+1} \end{aligned}$$

$$\text{If } P(n) = \sum_{k=0}^n \binom{n}{k} \cdot Q(k), \text{ then,}$$

$$Q(n) = \sum_{k=0}^n (-1)^{n-k} \binom{n}{k} \cdot P(k)$$

$$\text{If } P(n) = \sum_{k=0}^n (-1)^k \binom{n}{k} \cdot Q(k), \text{ then,}$$

$$Q(n) = \sum_{k=0}^n (-1)^k \binom{n}{k} \cdot P(k)$$

8.5 Different Math Formulas

Picks Theorem : $A = i + b/2 - 1$

Derangements : $d(i) = (i-1) \times (d(i-1) + d(i-2))$

$$\frac{n}{ab} - \left\{ \frac{bm}{a} \right\} - \left\{ \frac{a'n}{b} \right\} + 1$$

8.6 GCD and LCM

if m is any integer, then $\gcd(a + m \cdot b, b) = \gcd(a, b)$

The gcd is a multiplicative function in the following sense: if

a_1 and a_2 are relatively prime, then $\gcd(a_1 \cdot a_2, b) = \gcd(a_1, b) \cdot \gcd(a_2, b)$.

$$\gcd(a, \text{lcm}(b, c)) = \text{lcm}(\gcd(a, b), \gcd(a, c)).$$

$$\text{lcm}(a, \gcd(b, c)) = \gcd(\text{lcm}(a, b), \text{lcm}(a, c)).$$

For non-negative integers a and b , where a and b are not both zero, $\gcd(n^a - 1, n^b - 1) = n^{\gcd(a, b)} - 1$

$$\gcd(a, b) = \sum_{k|a \text{ and } k|b} \phi(k)$$

$$\sum_{i=1}^n [\gcd(i, n) = k] = \phi\left(\frac{n}{k}\right)$$

$$\sum_{k=1}^n \gcd(k, n) = \sum_{d|n} d \cdot \phi\left(\frac{n}{d}\right)$$

$$\sum_{k=1}^n x^{\gcd(k, n)} = \sum_{d|n} x^d \cdot \phi\left(\frac{n}{d}\right)$$

$$\sum_{k=1}^n \frac{1}{\gcd(k, n)} = \sum_{d|n} \frac{1}{d} \cdot \phi\left(\frac{n}{d}\right) = \frac{1}{n} \sum_{d|n} d \cdot \phi(d)$$

$$\sum_{k=1}^n \frac{k}{\gcd(k, n)} = \frac{n}{2} \cdot \sum_{d|n} \frac{1}{d} \cdot \phi\left(\frac{n}{d}\right) = \frac{n}{2} \cdot \frac{1}{n} \cdot \sum_{d|n} d \cdot \phi(d)$$

$$\sum_{k=1}^n \frac{n}{\gcd(k, n)} = 2 * \sum_{k=1}^n \frac{k}{\gcd(k, n)} - 1, \text{ for } n > 1$$

$$\sum_{i=1}^n \sum_{j=1}^n [\gcd(i, j) = 1] = \sum_{d=1}^n \mu(d) \left\lfloor \frac{n}{d} \right\rfloor^2$$

$$\sum_{i=1}^n \sum_{j=1}^n \gcd(i, j) = \sum_{d=1}^n \phi(d) \left\lfloor \frac{n}{d} \right\rfloor^2$$

$$\sum_{i=1}^n \sum_{j=1}^n i \cdot j [\gcd(i, j) = 1] = \sum_{i=1}^n \phi(i) i^2$$

$$F(n) = \sum_{i=1}^n \sum_{j=1}^n \text{lcm}(i, j) = \sum_{l=1}^n \left(\frac{(1 + \lfloor \frac{n}{l} \rfloor) (\lfloor \frac{n}{l} \rfloor)}{2} \right)^2 \sum_{d|l} \mu(d) l d$$