

SpringOne Platform

Spring 4 Web Apps

Rossen Stoyanchev

@rstoya05

Pivotal

About Me

Spring Framework committer

Focus on Spring MVC, WebSocket

Reactive effort

Spring Framework 4.3

Last 4.x feature release

Extended support life on JDK 6, 7, 8

Tomcat 6.0 - 8.5, WebSphere 7 - 9

Shortcut Annotations

@RequestMapping

@GetMapping

@PostMapping

@PutMapping

@DeleteMapping

```
@RequestMapping(path="/foos/{id}", method=RequestMethod.GET)  
public Foo getFoo(@PathVariable Long id) {  
    return retrieveFoo(id);  
}
```

```
@GetMapping("/foos/{id}")
```

```
@RequestMapping(path="/foos/{id}", method=RequestMethod.GET)
```

```
public Foo getFoo(@PathVariable Long id) {
```

```
    return retrieveFoo(id);
```

```
}
```

```
@Controller
@RequestMapping("/foos")
public class FooController {

    @GetMapping("{id}")
    public Foo getFoo(@PathVariable Long id) {
        return retrieveFoo(id);
    }

    // ...

}
```


@RequestScope

@SessionScope

@ApplicationScope

```
@Component
@Scope(scopeName = "session")
public class Foo {

    // ...

}
```

```
@Component
@SessionScope
@Scope(scopeName = "session")
public class Foo {

    // ...

}
```

@RequestAttribute

@SessionAttribute

```
@PostMapping("{id}")  
public void handle(@RequestAttribute Foo foo) {  
    // ...  
}
```

```
@PostMapping("{id}")  
public void handle(@SessionAttribute Foo foo) {  
    // ...  
}
```

Not to be confused with:

@SessionAttributeS

```
@Controller
@SessionAttributes("foo")
public class FooController {
```

```
    @GetMapping
    public Foo getFoo(@PathVariable Long id) {
        return new Foo();
    }
```

```
    @PostMapping("/{id}")
    public void handle(@ModelAttribute Foo foo) {
        // ...
    }
```

```
}
```


@RestControllerAdvice

@ModelAttribute (binding=false)

Pre-load **Foo** in the model

```
@ModelAttribute  
public Foo addFoo(@PathVariable Long id) {  
    return retrieveFoo(id);  
}
```

Form object
with binding

```
@PostMapping("/{id}")  
public void update(@Valid FooForm form,  
    @ModelAttribute(binding=false) Foo foo) {
```

```
// ...
```


```
}
```

Foo object without binding

HTTP OPTIONS, HEAD

automated handling

```
curl -v -X OPTIONS http://localhost:8080/foos/123
```



```
< HTTP/1.1 200 OK  
< Server: Apache-Coyote/1.1  
< Allow: GET,HEAD  
< Content-Length: 0
```

```
@GetMapping("/foos/{id}")  
public Foo getFoo(@PathVariable Long id) {  
    return retrieveFoo(id);  
}
```



```
curl --head http://localhost:8080/foos/123
```

```
HTTP/1.1 200 OK
```

```
Server: Apache-Coyote/1.1
```

```
Content-Type: application/json; charset=UTF-8
```

```
Content-Length: 155
```

```
@GetMapping("/foos/{id}")  
public Foo getFoo(@PathVariable Long id) {  
    return retrieveFoo(id);  
}
```

ForwardedHeaderFilter

Complements existing support

for “X-Forwarded-*” in

[Mvc | Servlet] UriComponentsBuilder

RestTemplate

default URI variable values

```
Map<String, String> defaultVars = new HashMap<>(2);  
defaultVars.put("host", "api.example.com");  
defaultVars.put("port", "443");
```

```
RestTemplate template = new RestTemplate();  
template.setDefaultUriVariables(defaultVars);
```

```
Map<String, Object> vars = new HashMap<>(1);  
vars.put("id", 123L);
```

```
String url = "https://{host}:{port}/v42/customers/{id}";  
template.getForObject(url, String.class, vars);
```

Client Mock REST Tests

expected count + order of requests

```
RestTemplate restTemplate = new RestTemplate();
```

```
MockRestServiceServer server = MockRestServiceServer  
    .bindTo(restTemplate).ignoreExpectOrder().build();
```

```
server.expect(times(2), requestTo("/foo")).andRespond(withSuccess());  
server.expect(times(3), requestTo("/bar")).andRespond(withSuccess());
```

```
// ...
```

```
server.verify();
```

Spring Framework 5

Spring Web Reactive

Lambda-style HTTP routing and processing

HTTP/2

SpringOne Platform

Thank You

@rstoya05



@springcentral
spring.io/blog



@pivotal
pivotal.io/blog



@pivotalcf
<http://engineering.pivotal.io>