

1,3-Butadiene

(C₄H₆)

A colorless, flammable, liquefied gas with a mildly aromatic odor.

GRADES & SPECIFICATIONS

Grade	% Purity	Butadiene Dimer	Other C ₄ 's	H ₂ O	Sulfur
Instrument	99.5%	≤400	≤4,000	≤5	≤1
Chemically Pure (CP)	99.0%	—	—	—	—

Concentrations given are ppm by volume unless otherwise specified.
Supplied stabilized to inhibit dimerization.
Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Instrument	350	129	510	B3-INST-350	21.4	0–25
	LP5	25	510	B3-INST-LP5	21.4	
Chemically Pure (CP)	350	129	510	B3-CP-350	21.4	Single-stage
	LP5	25	510	B3-CP-LP5	21.4	

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	54.09 g/mol	U.S. DOT Name	Butadienes, Stabilized
Specific Volume	7.15 cf/lb @ 70°F & 1 ATM	ID Number	UN 1010
Boiling Point	–4.4 °C	DOT Hazard Class	2.1 — Flammable Gas
Flammability in Air	Flammable — 2.0–12% in Air	CAS Registry Number	106-99-0

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.