

2-Butenes (2-C₄H₈)

A flammable, colorless liquefied gas.

GRADES & SPECIFICATIONS

Grade	% Purity
Chemically Pure (CP)	99.5%

Concentrations given are ppm by volume unless otherwise specified.
Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Chemically Pure (CP)	1/2 TON	523	510	2B-CP-12TON	15	0–25

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	56.1063 g/mol	U.S. DOT Name	Butylene
Specific Volume	6.90 cf/lb @ 70°F & 1 ATM	ID Number	UN 1012
Boiling Point	1.0 °C	DOT Hazard Class	2.1 — Flammable Gas
Flammability in Air	Flammable — 1.7–9.3% in Air	CAS Registry Number	107-01-7

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.