

Acetylene (C₂H₂)

A colorless, flammable gas with a garlic-like odor, dissolved in acetone. Do not discharge at pressures exceeding 15 psig.

GRADES & SPECIFICATIONS

Grade	Min. Purity	Phosphine	Total Sulfurs
Atomic Absorption (AA)	99.6%	≤25	≤25

Concentrations given are ppm by volume unless otherwise specified.

Warning: do not discharge this gas at pressures exceeding 15 psig. An acetylene filter is recommended for Atomic Absorption applications.

Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (ft ³)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Atomic Absorption (AA)	5	323	510	AC-AA-5	250	0–15
	4	132	510	AC-AA-4	250	

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	26.0373 g/mol
Specific Volume	14.24 cf/lb @ 70°F & 1 ATM
Boiling Point	–84 °C (sublimes)
Flammability in Air	Flammable — 2.5–100% in Air

U.S. DOT Name	Acetylene, Dissolved
ID Number	UN 1001
DOT Hazard Class	2.1 — Flammable Gas
CAS Registry Number	74-86-2

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.