

Air (Air)

A colorless, odorless, nonflammable synthetic blend of oxygen and nitrogen. Not for breathing applications.

GRADES & SPECIFICATIONS

Grade	% O ₂	H ₂ O	THC	CO ₂	CO	NO _x	SO ₂
Semiconductor	20–22	2	0.1	1 ⁽¹⁾	1 ⁽¹⁾	—	—
Continuous Emissions Monitoring (CEM)	20–21	0.1	1	0.5	0.1	0.1	—
Vehicle Emissions Zero	18–21	1	400	1	0.1	—	—
Vehicle Emissions Part 1065	20.5–21.5	0.05	10	1	0.02	—	—
Ultra Zero	20–22	2	0.1	1 ⁽¹⁾	1 ⁽¹⁾	—	—

Concentrations given are ppm by volume unless otherwise specified.

(1) Combined CO and CO₂ impurities not to exceed 1 ppm. First column indicates % O₂ content of the blend.

Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (ft ³)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Semiconductor	300	318	590	AI-SEMI-300	2,640	Single / 2-stage · 0–150
	200	238	590	AI-SEMI-200	2,200	
Continuous Emissions Monitoring (CEM)	300	318	590	AI-CEM-300	2,640	Single / 2-stage
	200	238	590	AI-CEM-200	2,200	
	150A	144	590	AI-CEM-150A	2,000	
	80A	84	590	AI-CEM-80A	2,200	
	33A	32	590	AI-CEM-33A	2,200	

Continued on page 2 → additional grades & Technical Data

Air (Air)

Continued — Ordering Information & Technical Data

— ORDERING INFORMATION (CONT.)

Product	Cyl. Size	Contents (ft ³)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Vehicle Emissions Zero	300	318	590	AI-VEZ-300	2,640	Single / 2-stage
	200	238	590	AI-VEZ-200	2,200	
	150A	144	590	AI-VEZ-150A	2,000	
	80A	84	590	AI-VEZ-80A	2,200	
	33A	32	590	AI-VEZ-33A	2,200	
Vehicle Emissions Part 1065	300	318	590	AI-VE-300	2,640	Single / 2-stage
	200	238	590	AI-VE-200	2,200	
	150A	144	590	AI-VE-150A	2,000	
	80A	84	590	AI-VE-80A	2,200	
	33A	32	590	AI-VE-33A	2,200	
Ultra Zero	300	318	590	AI-UZ-300	2,640	Single / 2-stage
	200	238	590	AI-UZ-200	2,200	
	80	94	590	AI-UZ-80	2,200	
	35	37	590	AI-UZ-35	2,200	

— TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	28.97 g/mol	U.S. DOT Name	Air, Compressed
Specific Volume	13.354 cf/lb @ 70°F & 1 ATM	ID Number	UN 1002
Boiling Point	-194.3 °C	DOT Hazard Class	2.2 — Nonflammable Gas
Flammability in Air	Nonflammable	CAS Registry Number	N/A

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.