

Argon (Ar)

A colorless, odorless, nonflammable gas — or a colorless, odorless, nonflammable cryogenic liquid.

GRADES & SPECIFICATIONS

Grade	% Purity	O ₂	H ₂ O	THC	CO	CO ₂	N ₂ ⁽³⁾
Research Ultra 6.0	99.9999	10 ppb	20 ppb	100 ppb	—	—	5
Research Plus 6.0	99.9999	0.1	0.2	0.1	0.1	0.1	2
Research 5.7 ⁽¹⁾	99.9997	0.2	0.5	0.2	0.5	0.5	3
Semiconductor 5.3	99.9993	1	1	0.5	1 ⁽²⁾	1 ⁽²⁾	5
Ultra-Pure Carrier (UPC)	99.9993	0.5	0.5	0.3	1 ⁽²⁾	1 ⁽²⁾	5
Ultra High Purity (UHP) 5.0	99.999	1	1	0.5	1 ⁽²⁾	1 ⁽²⁾	5
ICP-UHP Liquid	99.999	2	1	0.5	1	1	5
High Purity (HP)	99.998	4	—	—	—	—	3

Concentrations given are ppm by volume unless otherwise specified.

(1) Total impurities shall not exceed 3 ppm. (2) Total impurity CO + CO₂. (3) Nitrogen listed for reference only; not included in purity calculation.

Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (ft ³)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Research Ultra 6.0	300	336	580	AR-RU-300	2,640	2-stage · 2–75
Research Plus 6.0	300	336	580	AR-RP-300	2,640	2-stage · 0–150
	200	251	580	AR-RP-200	2,200	
	150A	152	580	AR-RP-150A	2,000	
Research 5.7	300	336	580	AR-RES-300	2,640	Single / 2-stage
	200	251	580	AR-RES-200	2,200	
	150A	152	580	AR-RES-150A	2,000	
	80	99	580	AR-RES-80	2,200	
	35	39	580	AR-RES-35	2,200	
Semiconductor 5.3	300	336	580	AR-SEMI-300	2,640	2-stage · 0–500
	200	251	580	AR-SEMI-200	2,200	
Ultra-Pure Carrier (UPC)	300	336	580	AR-UPC-300	2,640	Single-stage · 0–50
	200	251	580	AR-UPC-200	2,200	
	80	99	580	AR-UPC-80	2,200	
	35	39	580	AR-UPC-35	2,200	

Continued on page 2 → additional grades & Technical Data

Argon (Ar)

Continued — Ordering Information & Technical Data

— ORDERING INFORMATION (CONT.)

Product	Cyl. Size	Contents (ft ³)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Ultra High Purity (UHP) 5.0	300	336	580	AR-UHP-300	2,640	Single / 2-stage · 0–100
	200	251	580	AR-UHP-200	2,200	
	80	99	580	AR-UHP-80	2,200	
	35	39	580	AR-UHP-35	2,200	
ICP-UHP Liquid	180 L	4,884	580	AR-ICP-180L	230	Single-stage · 0–100
	230 L	6,073	580	AR-ICP-230L	230	
High Pressure (HP)	6K	566	677	AR-HP-6K	6,000	200–3,500
	3K	382	680	AR-HP-3K	3,500	300–1,500

— TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	39.948 g/mol
Specific Volume	9.68 cf/lb @ 70°F & 1 ATM
Boiling Point	–185.9 °C
Flammability in Air	Nonflammable

U.S. DOT Name	Argon, Compressed
ID Number	UN 1006
DOT Hazard Class	2.2 — Nonflammable Gas
CAS Registry Number	7440-37-1

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.