

Boron Trichloride

(BCl₃)

A colorless, corrosive, highly toxic, nonflammable liquefied gas with a pungent, irritating odor.

GRADES & SPECIFICATIONS

Grade	% Purity
Chemically Pure (CP)	99.9%

Concentrations given are ppm by volume unless otherwise specified.
Highly toxic and corrosive; use only positive-seal regulators with a cross-purge assembly.
Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Chemically Pure (CP)	200	70	660	BC-CP-200	4.4	0–100
	80	40	660	BC-CP-80	4.4	
	35	10	660	BC-CP-35	4.4	

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	117.170 g/mol
Specific Volume	3.30 cf/lb @ 70°F & 1 ATM
Boiling Point	12.6 °C
Flammability in Air	Nonflammable

U.S. DOT Name	Boron Trichloride
ID Number	UN 1741
DOT Hazard Class	2.3 — Inhalation Hazard, Poison Gas
CAS Registry Number	10294-34-5

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.