

Boron Trifluoride

(BF₃)

A colorless, highly toxic and corrosive, nonflammable gas with a strong, suffocating odor. Fumes strongly in moist air.

GRADES & SPECIFICATIONS

Grade	% Purity
Chemically Pure (CP)	99.9%

Concentrations given are ppm by volume unless otherwise specified.
Highly toxic and corrosive; use only positive-seal regulators with a cross-purge assembly. Fumes in moist air.
Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Chemically Pure (CP)	200	50	330	BF-CP-200	800	0–100
	35	6	330	BF-CP-35	800	

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	67.806 g/mol
Specific Volume	5.70 cf/lb @ 70°F & 1 ATM
Boiling Point	–100.3 °C
Flammability in Air	Nonflammable

U.S. DOT Name	Boron Trifluoride, Compressed
ID Number	UN 1008
DOT Hazard Class	2.3 — Inhalation Hazard, Poison Gas
CAS Registry Number	7637-07-2

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.