

Carbon Dioxide

(CO₂)

A colorless, odorless, nonflammable, liquefied gas.

GRADES & SPECIFICATIONS

Grade	% Purity	H ₂ O	THC	Ar	CO	N ₂	O ₂
SFE ⁽¹⁾	99.9995	1	0.5	1	1	5	1
SFC ⁽²⁾	99.999	3	1	1	1	5	1
Research Plus	99.999	2	0.5	4	—	—	1
Research	99.999	3	1	1	1	5	1
Semiconductor	99.995	5	5	—	—	—	—
Laser Plus - Ultra	99.996	5	1	—	—	10	—
Laser Plus	99.995	5	5	—	—	—	—
Laser	99.99	10	10	70	—	20	—
Pure Clean	99.995	5	5	—	—	—	—
Instrument	99.99	10	10	70	—	20	—
Refrigerant (R744)	99.99	10	—	—	—	—	—
Anaerobic	99.9	10	10	—	—	—	—
Bone Dry	99.9	10	—	—	—	—	—

Concentrations given are ppm by volume unless otherwise specified.

(1) SFE grade also carries a Halocarbon spec of ≤ 1 ppb. (2) SFC grade also carries a Halocarbon spec of ≤ 10 ppb. Total indicated components must be less than stated impurity.

Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
SFE	150A	39	320	CD-SFE-150A	835	N/A
SFC	150A	39	320	CD-SFC-150A	835	N/A
Research	200	60	320	CD-RES-200	835	Single / 2-stage · 0–500
	150A	39	320	CD-RES-150A	835	
Semiconductor	200	60	320	CD-SEMI-200	835	Single / 2-stage
	150A	39	320	CD-SEMI-150A	835	
Pure Clean	200	60	320	CD-PC-200	835	Single-stage

Continued on page 2 → additional grades & Technical Data

Carbon Dioxide

(CO₂)

Continued — Ordering Information & Technical Data

— ORDERING INFORMATION (CONT.)

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Instrument	200	60	320	CD-INST-200	835	Single-stage
	80	26	320	CD-INST-80	835	
Refrigerant (R744)	200	60	320	CD-REF-200	835	Single / 2-stage
	80	26	320	CD-REF-80	835	
Anaerobic	200	60	320	CD-AN-200	835	Single-stage
	80	26	320	CD-AN-80	835	
Bone Dry	200	60	320	CD-BD-200	835	Single-stage
	80	26	320	CD-BD-80	835	

— TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	44.0095 g/mol	U.S. DOT Name	Carbon Dioxide
Specific Volume	8.79 cf/lb @ 70°F & 1 ATM	ID Number	UN 1013
Boiling Point	-78.5 °C (sublimes)	DOT Hazard Class	2.2 — Nonflammable Gas
Flammability in Air	Nonflammable	CAS Registry Number	124-38-9

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.