

Carbon Monoxide

(CO)

A flammable, odorless, colorless and toxic gas.

GRADES & SPECIFICATIONS

Grade	% Purity	O ₂	H ₂ O	CO ₂	THC	H ₂	N ₂
Research Plus	99.999	2	2	2	2	1	5
Semiconductor	99.997	3	1	3	1	1	10
Research	99.99	5	3	5	1	—	40
Ultra High Purity (UHP) ⁽¹⁾	99.9	—	—	—	—	—	—
Chemically Pure (CP)	99.3	—	—	—	—	—	—

Concentrations given are ppm by volume unless otherwise specified.

⁽¹⁾ UHP grade: total impurities ≤ 1000 ppm. Semiconductor grade also carries Fe(CO)₅ ≤ 0.1 ppmw, Ni(CO)₄ ≤ 0.1 ppmw and sulfurs ≤ 0.5 ppm.

Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (ft ³)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Research Plus	300A	230	350	CM-RP-300A	2,000	Single / 2-stage · 0–500
	150A	140	350	CM-RP-150A	2,000	
	80A	75	350	CM-RP-80A	2,000	
Semiconductor	300A	230	350	CM-SEMI-300A	2,000	Single / 2-stage
	150A	140	350	CM-SEMI-150A	2,000	
Research	300	240	350	CM-RES-300	2,000	Single / 2-stage
	200	180	350	CM-RES-200	1,675	
	150A	140	350	CM-RES-150A	2,000	
	80	70	350	CM-RES-80	1,675	

Continued on page 2 → additional grades & Technical Data

Carbon Monoxide

(CO)

Continued — Ordering Information & Technical Data

— ORDERING INFORMATION (CONT.)

Product	Cyl. Size	Contents (ft ³)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Ultra High Purity (UHP)	300	240	350	CM-UHP-300	2,000	Single / 2-stage
	200	180	350	CM-UHP-200	1,675	
	150A	140	350	CM-UHP-150A	2,000	
	80	70	350	CM-UHP-80	1,675	
Chemically Pure (CP)	300	240	350	CM-CP-300	2,000	Single / 2-stage
	200	180	350	CM-CP-200	1,675	
	150A	140	350	CM-CP-150A	2,000	
	80	70	350	CM-CP-80	1,675	
Industrial	300	240	350	CM-IND-300	2,000	Single / 2-stage
	200	180	350	CM-IND-200	1,675	

— TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	28.010 g/mol
Specific Volume	13.81 cf/lb @ 70°F & 1 ATM
Boiling Point	-191.5 °C
Flammability in Air	Flammable — 12.5–74% in Air

U.S. DOT Name	Carbon Monoxide
ID Number	UN 1016
DOT Hazard Class	2.3 — Inhalation Hazard & Flammable Gas
CAS Registry Number	630-08-0

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.