

Chlorine (Cl₂)

A greenish-yellow liquefied gas with a choking odor. May react violently with ammonia, hydrocarbons and hydrogen.

GRADES & SPECIFICATIONS

Grade	% Purity	O ₂	CO	CO ₂	N ₂	THC
Electronic	99.99	50	5	5	—	1
Ultra High Purity (UHP)	99.9	100	50	—	100	—
High Purity (HP) ⁽¹⁾	99.5	—	—	—	—	—

Concentrations given are ppm by volume unless otherwise specified.

(1) HP grade: total impurities < 5000 ppm. Use only positive-seal regulators with a cross-purge or tee-purge assembly.

Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Semiconductor	200	90	660	CL-SEMI-200	85	0–100
	80	40	660	CL-SEMI-80	85	
Ultra High Purity (UHP)	200	90	660	CL-UHP-200	85	0–100
High Purity (HP)	200	90	660	CL-HP-200	85	0–100

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	70.906 g/mol
Specific Volume	5.46 cf/lb @ 70°F & 1 ATM
Boiling Point	–34.0 °C
Flammability in Air	Oxidizer

U.S. DOT Name	Chlorine
ID Number	UN 1017
DOT Hazard Class	2.3 (8) — Inhalation Hazard & Corrosive
CAS Registry Number	7782-50-5

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.