

Dimethylamine ((CH₃)₂NH)

A colorless, flammable liquefied gas with a characteristic fishy or ammonia-like odor.

GRADES & SPECIFICATIONS

Grade	% Purity
Chemically Pure (CP)	99.5%

Concentrations given are ppm by volume unless otherwise specified.
Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Chemically Pure (CP)	1/2 TON	550	705	DM-CP-12TON	26	Manual control valve
	350	125	705	DM-CP-350	26	

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	45.0837 g/mol	U.S. DOT Name	Dimethylamine, Anhydrous
Specific Volume	8.58 cf/lb @ 70°F & 1 ATM	ID Number	UN 1032
Boiling Point	6.9 °C	DOT Hazard Class	2.1 — Flammable Gas
Flammability in Air	Flammable — 2.8–14.4% in Air	CAS Registry Number	124-40-3

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.