

Ethane (C₂H₆)

A flammable, colorless liquefied gas.

GRADES & SPECIFICATIONS

Grade	% Purity	O ₂	H ₂ O	CO/CO ₂	Other HC	N ₂
Research Plus	99.999%	≤1	≤3	≤6	≤2	≤3
Research	99.99%	≤5	≤5	≤80	≤5	≤10
Technical	98.5%	—	—	—	—	—

Concentrations given are ppm by volume unless otherwise specified.
Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Research Plus	200	32	350	ET-RP-200	543	Single / 2-stage · 0–250
	80	11	350	ET-RP-80	543	
Research	200	32	350	ET-RES-200	543	Single / 2-stage
	80	11	350	ET-RES-80	543	
Technical	300	40	350	ET-TECH-300	543	Single / 2-stage
	200	32	350	ET-TECH-200	543	
	80	11	350	ET-TECH-80	543	

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	30.0690 g/mol	U.S. DOT Name	Ethane
Specific Volume	12.86 cf/lb @ 70°F & 1 ATM	ID Number	UN 1035
Boiling Point	–88.6 °C	DOT Hazard Class	2.1 — Flammable Gas
Flammability in Air	Flammable — 3.0–12.5% in Air	CAS Registry Number	74-84-0

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.