

Ethylene (C₂H₄)

A flammable, colorless liquefied gas.

GRADES & SPECIFICATIONS

Grade	% Purity	O ₂	H ₂ O	Other HC	CO	CO ₂	N ₂
Research Plus	99.9995%	≤1	≤1	≤4	≤1	≤1	≤1
Research	99.995%	≤2	≤5	≤40	≤2	≤5	≤5
Ultra High Purity (UHP)	99.9%	≤10	≤5	≤800	≤5	≤10	≤50
Chemically Pure (CP)	99.5%	≤1000	—	—	—	—	—
Plant Growth Regulator (PGR)	98.5%	≤1000	—	—	—	—	—

Concentrations given are ppm by volume unless otherwise specified.

PGR grade is FIFRA registered and labeled as a Plant Growth Regulator, recommended for produce ripening and degreening.

Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Research Plus	300	37	350	EY-RP-300	1,200	Single / 2-stage · 0–250
	200	30	350	EY-RP-200	1,200	
	80	11	350	EY-RP-80	1,200	
	35	4	350	EY-RP-35	1,200	
Research	300	37	350	EY-RES-300	1,200	Single / 2-stage
	200	30	350	EY-RES-200	1,200	
	80	11	350	EY-RES-80	1,200	
	35	4	350	EY-RES-35	1,200	
Ultra High Purity (UHP)	300	37	350	EY-UHP-300	1,200	Single / 2-stage
	200	30	350	EY-UHP-200	1,200	
	80	11	350	EY-UHP-80	1,200	
	35	4	350	EY-UHP-35	1,200	

Continued on page 2 → additional grades & Technical Data

Ethylene (C₂H₄)

Continued — Ordering Information & Technical Data

— ORDERING INFORMATION (CONT.)

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Plant Growth Regulator (PGR)	300	37	350	EY-PGR-300	1,200	Single / 2-stage
	200	30	350	EY-PGR-200	1,200	
	80	11	350	EY-PGR-80	1,200	
	35	4	350	EY-PGR-35	1,200	
Chemically Pure (CP)	300	37	350	EY-CP-300	1,200	Single / 2-stage
	200	30	350	EY-CP-200	1,200	
	80	11	350	EY-CP-80	1,200	
	35	4	350	EY-CP-35	1,200	

— TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	28.0532 g/mol
Specific Volume	13.79 cf/lb @ 70°F & 1 ATM
Boiling Point	-103.7 °C
Flammability in Air	Flammable — 2.7–36% in Air

U.S. DOT Name	Ethylene, Compressed
ID Number	UN 1962
DOT Hazard Class	2.1 — Flammable Gas
CAS Registry Number	74-85-1

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.