

Halocarbon-116 (C₂F₆)

Hexafluoroethane — a colorless, noncorrosive, nonflammable liquefied gas.

GRADES & SPECIFICATIONS

Grade	% Purity	O ₂	H ₂ O	Other Halo	HF	CO	CO ₂	N ₂	THC
Semiconductor	99.999	2	5	10	0.1 ppmw	1	1	8	1
Chemically Pure (CP) ⁽¹⁾	99.9	—	—	—	—	—	—	—	—

Concentrations given are ppm by volume unless otherwise specified.

(1) CP grade: total impurities not to exceed 1000 ppm.

Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Semiconductor	Y	950	660	H116-SEMI-Y	417	0–150
	200	95	660	H116-SEMI-200	417	
Chemically Pure (CP)	200	95	660	H116-CP-200	417	0–150

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	138.0118 g/mol	U.S. DOT Name	Hexafluoroethane, Compressed
Specific Volume	2.80 cf/lb @ 70°F & 1 ATM	ID Number	UN 2193
Boiling Point	–78.2 °C	DOT Hazard Class	2.2 — Nonflammable Gas
Flammability in Air	Nonflammable	CAS Registry Number	76-16-4

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.