

Halocarbon-1216 (C₃F₆)

Hexafluoropropylene — an odorless, colorless, noncombustible gas.

GRADES & SPECIFICATIONS

Grade	% Purity	O ₂	H ₂ O
Polymer	99.9%	50	20

Concentrations given are ppm by volume unless otherwise specified.
Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Polymer	1/2 TON	1,100	660	1216-PL-12TON	85	0–25

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	150.0225 g/mol
Specific Volume	2.58 cf/lb @ 70°F & 1 ATM
Boiling Point	–29.4 °C
Flammability in Air	Nonflammable

U.S. DOT Name	Hexafluoropropylene
ID Number	UN 1858
DOT Hazard Class	2.2 — Nonflammable Gas
CAS Registry Number	116-15-4

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.