

Halocarbon-14 (CF₄)

Tetrafluoromethane (Carbon Tetrafluoride) — a colorless, nonflammable, noncorrosive gas.

GRADES & SPECIFICATIONS

Grade	% Purity	O ₂	SF ₆	N ₂	CO	CO ₂	H ₂ O	HF	Other Halo	THC
Semiconductor	99.999	2	1	4	1	1	1	0.1 ppmw	2	1
Ultra High Purity (UHP)	99.99	15	1	60	5	5	1	0.25 ppmw	10	—
Chemically Pure (CP) ⁽¹⁾	99.9	—	—	—	—	—	—	—	—	—

Concentrations given are ppm by volume unless otherwise specified.

⁽¹⁾ CP grade: total impurities not to exceed 1000 ppm. Vapor phase analysis.

Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Semiconductor	Y	720	580	H14-SEMI-Y	1,875	0–100
	300	88	580	H14-SEMI-300	2,000	
	200	70	580	H14-SEMI-200	1,875	
Ultra High Purity (UHP)	200	70	580	H14-UHP-200	1,875	Single / 2-stage
Chemically Pure (CP)	200	70	580	H14-CP-200	1,875	Single / 2-stage

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	88.0043 g/mol	U.S. DOT Name	Tetrafluoromethane, Compressed
Specific Volume	4.40 cf/lb @ 70°F & 1 ATM	ID Number	UN 1982
Boiling Point	–128.0 °C	DOT Hazard Class	2.2 — Nonflammable Gas
Flammability in Air	Nonflammable	CAS Registry Number	75-73-0

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.