

Halocarbon- C318

(C₄F₈)

Octafluorocyclobutane — a colorless, odorless, nonflammable liquefied gas.

GRADES & SPECIFICATIONS

Grade	% Purity	O ₂	N ₂	H ₂ O	Other Halo	HF
Semiconductor	99.995	4	16	10	20	0.1 ppmw
Chemically Pure (CP)	99.98	20	80	50	50	0.1 ppmw

Concentrations given are ppm by volume unless otherwise specified.
Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Semiconductor	1/2 TON	1,100	660	C318-SEMI-12TON	25	0–25
	200	110	660	C318-SEMI-200	25	
Chemically Pure (CP)	1/2 TON	1,100	660	C318-CP-12TON	25	0–25
	200	110	660	C318-CP-200	25	

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	200.0300 g/mol	U.S. DOT Name	Octafluorocyclobutane
Specific Volume	1.93 cf/lb @ 70°F & 1 ATM	ID Number	UN 1976
Boiling Point	–6.0 °C	DOT Hazard Class	2.2 — Nonflammable Gas
Flammability in Air	Nonflammable	CAS Registry Number	115-25-3

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.