

Hydrogen Chloride

(HCl)

A colorless, toxic, corrosive, nonflammable liquefied gas with a sharp, suffocating odor.

GRADES & SPECIFICATIONS

Grade	% Purity	O ₂ +Ar	H ₂ O	THC	CO	CO ₂	N ₂	Iron	Metals
VLSI	99.999%	≤1	≤1	≤1	≤1	≤2	≤2	≤0.5	≤1
Electronic	99.997%	≤4	≤2	≤2	≤1	≤5	≤10	—	—
Technical / NG	99.5%	—	—	—	—	—	—	—	—

Concentrations given are ppm by volume unless otherwise specified.
Corrosive; use only positive-seal regulators with a cross-purge assembly.
Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
VLSI	Y	645	330	HC-VLSI-Y	611	0–50
	300	71	330	HC-VLSI-300	611	
	200	62	330	HC-VLSI-200	611	
Electronic	Y	645	330	HC-EL-Y	611	0–100
	300	71	330	HC-EL-300	611	
	200	62	330	HC-EL-200	611	
Technical / NG	Y	645	330	HC-NG-Y	611	Single-stage
	300	71	330	HC-NG-300	611	

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	36.461 g/mol
Specific Volume	10.61 cf/lb @ 70°F & 1 ATM
Boiling Point	–85.0 °C
Flammability in Air	Nonflammable

U.S. DOT Name	Hydrogen Chloride, Anhydrous
ID Number	UN 1050
DOT Hazard Class	2.3 (8) — Inhalation Hazard & Corrosive
CAS Registry Number	7647-01-0

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.