

Hydrogen Sulfide

(H₂S)

A flammable, colorless, liquefied gas with a rotten-egg-like odor.

GRADES & SPECIFICATIONS

Grade	% Purity
Chemically Pure (CP)	99.5%

Concentrations given are ppm by volume unless otherwise specified.

Toxic and flammable; use only positive-seal regulators with a cross-purge or tee-purge assembly.

Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Chemically Pure (CP)	200	60	330	HS-CP-200	247	0–150
	80	20	330	HS-CP-80	247	

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	34.081 g/mol
Specific Volume	11.35 cf/lb @ 70°F & 1 ATM
Boiling Point	–60.3 °C
Flammability in Air	Flammable — 4.0–44% in Air

U.S. DOT Name	Hydrogen Sulfide
ID Number	UN 1053
DOT Hazard Class	2.3 — Inhalation Hazard & Flammable Gas
CAS Registry Number	7783-06-4

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.