

Isobutylene (iso-C₄H₈)

A colorless, flammable liquefied gas with a detectable odor.

GRADES & SPECIFICATIONS

Grade	% Purity	Other HC	H ₂ O	Sulfur
Instrument	99.5%	≤4,500	≤3	≤1
Chemically Pure (CP)	99.0%	—	—	—

Concentrations given are ppm by volume unless otherwise specified.
Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Instrument	350	120	510	IY-INST-350	24	0–50
	LP5	24	510	IY-INST-LP5	24	
Chemically Pure (CP)	350	120	510	IY-CP-350	24	Single-stage
	LP5	24	510	IY-CP-LP5	24	

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	56.1063 g/mol	U.S. DOT Name	Isobutylene
Specific Volume	6.90 cf/lb @ 70°F & 1 ATM	ID Number	UN 1055
Boiling Point	–6.9 °C	DOT Hazard Class	2.1 — Flammable Gas
Flammability in Air	Flammable — 1.8–9.6% in Air	CAS Registry Number	115-11-7

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.