

Krypton (Kr)

A colorless, odorless, nonflammable, inert noble gas.

GRADES & SPECIFICATIONS

Grade	% Purity	O ₂	H ₂ O	THC	CO	CO ₂	N ₂	Xe	CF ₄
Research Plus	99.999	≤1	≤1	≤1	≤0.5	≤0.5	≤3	≤5	≤0.5
Research	99.995	≤2	≤1	≤1	≤1	≤0.5	≤15	≤20	—
Window	99.9	≤20	—	—	—	—	—	—	—

Concentrations given are ppm by volume unless otherwise specified.
Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (L)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Research Plus	300	9,000	580	KR-RP-300	2,085	Single / 2-stage · 0–100
	200	5,000	580	KR-RP-200	1,400	
	80	1,000	580	KR-RP-80	880	
Research	300	10,000	580	KR-RES-300	2,285	Single / 2-stage
	200	5,000	580	KR-RES-200	1,400	
	80	2,500	580	KR-RES-80	1,900	
	9A	250	580	KR-RES-9A	1,200	
	LB	50	580	KR-RES-LB	1,400	

Continued on page 2 → additional grades & Technical Data

Krypton (Kr)

Continued — Ordering Information & Technical Data

— ORDERING INFORMATION (CONT.)

Product	Cyl. Size	Contents (L)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Window	300	7,500	580	KR-WIN-300	1,800	Single-stage

— TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	83.798 g/mol
Specific Volume	4.62 cf/lb @ 70°F & 1 ATM
Boiling Point	-153.4 °C
Flammability in Air	Nonflammable

U.S. DOT Name	Krypton, Compressed
ID Number	UN 1056
DOT Hazard Class	2.2 — Nonflammable Gas
CAS Registry Number	7439-90-0

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.