

Neon (Ne)

A colorless, odorless, nonflammable, inert noble gas.

GRADES & SPECIFICATIONS

Grade	% Purity	O ₂	H ₂ O	THC	CO	CO ₂	Ar	N ₂	He
Semiconductor	99.999	0.5	1	0.5	0.5	0.5	1	2	8
Research	99.999	0.5	1	0.5	0.5	0.5	1	2	8
Ultra High Purity (UHP)	99.996	2	2	0.5	0.5	0.5	1	10	30

Concentrations given are ppm by volume unless otherwise specified.
Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (L)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Semiconductor	300	7,500	580	NE-SEMI-300	2,400	Single / 2-stage
	200	6,000	580	NE-SEMI-200	2,200	
Research	300	7,500	580	NE-RES-300	2,400	Single / 2-stage
	200	6,000	580	NE-RES-200	2,200	
	80	2,000	580	NE-RES-80	2,200	
	9A	100	580	NE-RES-9A	580	
	LB	50	580	NE-RES-LB	1,900	

Continued on page 2 → additional grades & Technical Data

Neon (Ne)

Continued — Ordering Information & Technical Data

— ORDERING INFORMATION (CONT.)

Product	Cyl. Size	Contents (L)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Ultra High Purity (UHP)	300	7,500	580	NE-UHP-300	2,400	Single / 2-stage
	200	6,000	580	NE-UHP-200	2,200	
	80	2,000	580	NE-UHP-80	2,200	
	9A	100	580	NE-UHP-9A	580	
	LB	50	580	NE-UHP-LB	1,900	

— TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	20.1797 g/mol
Specific Volume	19.17 cf/lb @ 70°F & 1 ATM
Boiling Point	-246.0 °C
Flammability in Air	Nonflammable

U.S. DOT Name	Neon, Compressed
ID Number	UN 1065
DOT Hazard Class	2.2 — Nonflammable Gas
CAS Registry Number	7440-01-9

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.