

# Nitric Oxide

(NO)

*A colorless, toxic, oxidizing and corrosive compressed gas.*

## GRADES & SPECIFICATIONS

| Grade                   | % Purity |
|-------------------------|----------|
| Ultra High Purity (UHP) | 99.9%    |
| Chemically Pure (CP)    | 99.5%    |

Concentrations given are ppm by volume unless otherwise specified.

Nitric Oxide is toxic and corrosive; use only stainless-steel regulators and purge lines with inert gas before and after use.

Individual or Batch Certificate of Analysis available upon request.

## ORDERING INFORMATION

| Product                 | Cyl. Size | Contents (ft <sup>3</sup> ) | Valve (CGA) | Product Number | Pressure @70°F (psig) | Delivery Range (psig) |
|-------------------------|-----------|-----------------------------|-------------|----------------|-----------------------|-----------------------|
| Ultra High Purity (UHP) | 150A      | 53                          | 660         | NC-UHP-150A    | 500                   | 0–100                 |
| Chemically Pure (CP)    | 200       | 53                          | 660         | NC-CP-200      | 500                   | Single-stage          |
|                         | 35        | 8                           | 660         | NC-CP-35       | 500                   |                       |

## TECHNICAL DATA & SHIPPING INFORMATION

|                     |                            |
|---------------------|----------------------------|
| Molecular Weight    | 30.0061 g/mol              |
| Specific Volume     | 12.89 cf/lb @ 70°F & 1 ATM |
| Boiling Point       | –151.7 °C                  |
| Flammability in Air | Oxidizer / Corrosive       |

|                     |                                                       |
|---------------------|-------------------------------------------------------|
| U.S. DOT Name       | Nitric Oxide, Compressed                              |
| ID Number           | UN 1660                                               |
| DOT Hazard Class    | 2.3 (5.1, 8) — Inhalation Hazard, Oxidizer, Corrosive |
| CAS Registry Number | 10102-43-9                                            |

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

**WSM Quality Policy.** The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.