

Nitrogen Trifluoride

(NF₃)

An odorless, colorless, noncombustible, oxidizing gas.

GRADES & SPECIFICATIONS

Grade	% Purity	O ₂ +Ar	N ₂	CF ₄	CO	CO ₂	N ₂ O	SF ₆	H ₂ O	Acidity (HF)
Semiconductor	99.995	3	5	40	1	5	5	5	1	1

Concentrations given are ppm by volume unless otherwise specified.
Supplied with DISS 640 valve outlet.
Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Semiconductor	300	50	640 (DISS)	NT-SEMI-300	1,450	0-100
	200	44	640 (DISS)	NT-SEMI-200	1,450	

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	71.002 g/mol
Specific Volume	5.426 cf/lb @ 70°F & 1 ATM
Boiling Point	-129.0 °C
Flammability in Air	Oxidizer

U.S. DOT Name	Nitrogen Trifluoride
ID Number	UN 2451
DOT Hazard Class	2.2 (5.1) — Nonflammable Gas, Oxidizer
CAS Registry Number	7783-54-2

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.