

Oxygen (O₂)

A colorless, odorless, oxidizing compressed gas.

GRADES & SPECIFICATIONS

Grade	% Purity	H ₂ O	THC	CO	CO ₂	Ar	N ₂	Kr
Research 5.0	99.999	0.5	0.2	0.5	0.5	3	5	2
Ultra-Pure Carrier (UPC)	99.996	1	0.5	1	1	20	10	—
Semiconductor	99.994	2	0.5	1	1	35	15	—
Ultra High Purity (UHP)	99.994	2	0.5	1	1	35	15	—

Concentrations given are ppm by volume unless otherwise specified.
Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (ft ³)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Research 5.0	300	337	540	OX-RES-300	2,640	Single-stage · 0–100
	200	251	540	OX-RES-200	2,200	
	80	85	540	OX-RES-80	2,200	
Ultra-Pure Carrier (UPC)	300	337	540	OX-UPC-300	2,640	Single-stage
	200	251	540	OX-UPC-200	2,200	
	80	85	540	OX-UPC-80	2,200	
Semiconductor	300	337	540	OX-SEMI-300	2,640	Single-stage
	200	251	540	OX-SEMI-200	2,200	
Ultra High Purity (UHP)	300	337	540	OX-UHP-300	2,640	Single-stage
	200	251	540	OX-UHP-200	2,200	
	80	85	540	OX-UHP-80	2,200	

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	31.9988 g/mol
Specific Volume	12.09 cf/lb @ 70°F & 1 ATM
Boiling Point	–183.0 °C
Flammability in Air	Oxidizer

U.S. DOT Name	Oxygen, Compressed
ID Number	UN 1072
DOT Hazard Class	2.2 — Nonflammable Gas & Oxidizer
CAS Registry Number	7782-44-7

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.