

Propane (C₃H₈)

A flammable, colorless liquefied gas.

GRADES & SPECIFICATIONS

Grade	% Purity	H ₂ O	O ₂	Other HC	C ₃ H ₆	N ₂	CO ₂
Semiconductor	99.999	1	1	1	1	1	1
Research	99.99	3	2	80 ⁽¹⁾	10	10	2
Instrument	99.5	5	100	4,000 ⁽¹⁾	400	400	100
Chemically Pure (CP)	99.0	—	—	—	—	—	—

Concentrations given are ppm by volume unless otherwise specified.
Non-odorized product, less than 1 ppm sulfurs. **(1)** Other HCs defined as Methane, Ethane and Ethylene.
Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Semiconductor	350	95	510	PR-SEMI-350	110	0–100
	LP5	19	510	PR-SEMI-LP5	110	
Research	350	95	510	PR-RES-350	110	Single-stage
	LP5	19	510	PR-RES-LP5	110	
	LP1	4	510	PR-RES-LP1	110	

Continued on page 2 → additional grades & Technical Data

Propane (C₃H₈)

Continued — Ordering Information & Technical Data

— ORDERING INFORMATION (CONT.)

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Instrument	1/2 Ton	400	510	PR-INST-12Ton	110	0–100
	350	95	510	PR-INST-350	110	
	LP5	19	510	PR-INST-LP5	110	
Chemically Pure (CP)	1/2 Ton	400	510	PR-CP-12Ton	110	Single-stage
	350	95	510	PR-CP-350	110	
	LP5	19	510	PR-CP-LP5	110	

— TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	44.0956 g/mol	U.S. DOT Name	Propane
Specific Volume	8.77 cf/lb @ 70°F & 1 ATM	ID Number	UN 1978
Boiling Point	–42.1 °C	DOT Hazard Class	2.1 — Flammable Gas
Flammability in Air	Flammable — 2.1–9.5% in Air	CAS Registry Number	74-98-6

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.