

Propylene (C₃H₆)

A flammable, colorless liquefied gas with a detectable odor.

GRADES & SPECIFICATIONS

Grade	% Purity	N ₂	Other HC	O ₂	H ₂ O	CO ₂
Semiconductor	99.99	5	90 ⁽¹⁾	1	2	1
Electronic	99.95	20	450 ⁽¹⁾	3	3	3
Polymer	99.5	50	4,500 ⁽¹⁾	5	5	5
Chemically Pure (CP) ⁽²⁾	99.0	—	—	—	—	—

Concentrations given are ppm by volume unless otherwise specified.

Non-odorized product, less than 1 ppm sulfurs. **(1)** Other HCs defined as Ethane, Propane, n-Butane, Isobutane. **(2)** Total impurities not to exceed 1%.

Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Semiconductor	350	99	510	PP-SEMI-350	138	0–50
Electronic	1/2 Ton	418	510	PP-EL-12Ton	138	Single-stage
	350	99	510	PP-EL-350	138	
Polymer	1/2 Ton	418	510	PP-PL-12Ton	138	Single-stage
	350	99	510	PP-PL-350	138	
Chemically Pure (CP)	1/2 Ton	418	510	PP-CP-12Ton	138	Single-stage
	350	99	510	PP-CP-350	138	

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	42.0797 g/mol
Specific Volume	9.19 cf/lb @ 70°F & 1 ATM
Boiling Point	–47.6 °C
Flammability in Air	Flammable — 2.4–11% in Air

U.S. DOT Name	Propylene
ID Number	UN 1077
DOT Hazard Class	2.1 — Flammable Gas
CAS Registry Number	115-07-1

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.