

Sulfur Dioxide

(SO₂)

A colorless, poisonous, corrosive, liquefied gas with a detectable odor.

GRADES & SPECIFICATIONS

Grade	% Purity
Anhydrous	99.98%

Concentrations given are ppm by volume unless otherwise specified.
Corrosive and toxic; use only stainless-steel positive-seal regulators and purge before and after use.
Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Anhydrous	Ton	1,240	660	SD-AH-Ton	34	0-15
	200	50	660	SD-AH-200	34	
	65	150	660	SD-AH-65	34	

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	64.064 g/mol
Specific Volume	6.04 cf/lb @ 70°F & 1 ATM
Boiling Point	-10.0 °C
Flammability in Air	Nonflammable

U.S. DOT Name	Sulfur Dioxide
ID Number	UN 1079
DOT Hazard Class	2.3 (8) — Inhalation Hazard & Corrosive
CAS Registry Number	7446-09-5

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.