

Sulfur Hexafluoride

(SF₆)

A colorless, odorless, nonflammable, non-reactive, nontoxic gas.

GRADES & SPECIFICATIONS

Grade	% Purity	Air (O ₂ +N ₂)	CF ₄	H ₂ O	Acidity (HF)
Electronic	99.999	10	2	3	0.1 ppmw
Semiconductor	99.99	75	25	5	0.1 ppmw
Instrument	99.99	75	25	5	0.1 ppmw
Chemically Pure / Dielectric ⁽¹⁾	99.8	500	500	8	0.3 ppmw

Concentrations given are ppm by volume unless otherwise specified.

(1) Dielectric Grade meets ASTM D-2472 specifications.

Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Electronic	300	130	590	SH-EL-300	298	0–100
	200	115	590	SH-EL-200	298	
	150A	77	590	SH-EL-150A	298	
	80	35	590	SH-EL-80	298	
	35	17	590	SH-EL-35	298	
Semiconductor	300	130	590	SH-SEMI-300	298	0–250
	200	115	590	SH-SEMI-200	298	

Continued on page 2 → additional grades & Technical Data

Sulfur Hexafluoride

(SF₆)

Continued — Ordering Information & Technical Data

— ORDERING INFORMATION (CONT.)

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Instrument	300	130	590	SH-INST-300	298	Single-stage
	200	115	590	SH-INST-200	298	
	80	35	590	SH-INST-80	298	
	35	17	590	SH-INST-35	298	
Chemically Pure / Dielectric	Y	1,100	590	SH-CP-Y	298	Single-stage
	300	130	590	SH-CP-300	298	
	200	115	590	SH-CP-200	298	
	80	35	590	SH-CP-80	298	
	35	17	590	SH-CP-35	298	

— TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	146.055 g/mol	U.S. DOT Name	Sulfur Hexafluoride
Specific Volume	2.65 cf/lb @ 70°F & 1 ATM	ID Number	UN 1080
Boiling Point	-63.8 °C (sublimes)	DOT Hazard Class	2.2 — Nonflammable Gas
Flammability in Air	Nonflammable	CAS Registry Number	2551-62-4

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.