

Xenon (Xe)

A colorless, odorless, nonflammable, inert noble gas.

GRADES & SPECIFICATIONS

Grade	% Purity	O ₂	H ₂ O	THC	CO	CO ₂	N ₂	Kr
Propulsion	99.9995	≤0.2	≤0.1	≤0.1	≤0.1	≤0.1	≤1	≤2
Research Plus	99.999	≤0.5	≤0.5	≤0.5	≤0.5	≤0.5	≤3	≤5
Research	99.995	≤1	≤1	≤1	≤1	≤1	≤5	≤25

Concentrations given are ppm by volume unless otherwise specified.
Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (L)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Propulsion	80A	2,500	580	XE-PROP-80A	900	Single / 2-stage
	33A	1,000	580	XE-PROP-33A	900	
	6A	100	580	XE-PROP-6A	855	
	LB	50	580	XE-PROP-LB	845	
Research Plus	80A	2,000	580	XE-RP-80A	900	Single / 2-stage
	33A	1,000	580	XE-RP-33A	900	
	9A	250	580	XE-RP-9A	790	
	LB	25	580	XE-RP-LB	845	

Continued on page 2 → additional grades & Technical Data

Xenon (Xe)

Continued — Ordering Information & Technical Data

— ORDERING INFORMATION (CONT.)

Product	Cyl. Size	Contents (L)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Research	200	5,000	580	XE-RES-200	900	Single-stage
	80	500	580	XE-RES-80	900	
	9A	250	580	XE-RES-9A	790	
	LB	50	580	XE-RES-LB	845	

— TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	131.293 g/mol	U.S. DOT Name	Xenon, Compressed
Specific Volume	2.95 cf/lb @ 70°F & 1 ATM	ID Number	UN 2036
Boiling Point	-108.1 °C	DOT Hazard Class	2.2 — Nonflammable Gas
Flammability in Air	Nonflammable	CAS Registry Number	7440-63-3

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.