

n-Butane

(C₄H₁₀)

A flammable, colorless, liquefied gas with a gasoline-like odor.

GRADES & SPECIFICATIONS

Grade	% Purity	N ₂	O ₂	Other HC	H ₂ O	Sulfurs
Research	99.99%	≤20	≤5	≤90	≤3	≤1
Instrument	99.5%	≤400	≤100	≤4,500	≤5	≤1
Chemically Pure (CP)	99.0%	—	—	—	—	—

Concentrations given are ppm by volume unless otherwise specified.

Analysis based on liquid phase. Other HCs defined as Isobutane, n-Pentane, Isopentane, Butene, Ethane and Propane.

Individual or Batch Certificate of Analysis available upon request.

ORDERING INFORMATION

Product	Cyl. Size	Contents (lbs)	Valve (CGA)	Product Number	Pressure @70°F (psig)	Delivery Range (psig)
Research	350	116	510	NB-RES-350	16	0–25
	LP5	23	510	NB-RES-LP5	16	
	LP1	5	510	NB-RES-LP1	16	
Instrument	1/2 TON	485	510	NB-INST-12TON	16	Single-stage
	350	116	510	NB-INST-350	16	
	LP5	23	510	NB-INST-LP5	16	
Chemically Pure (CP)	1/2 TON	485	510	NB-CP-12TON	16	Single-stage
	350	116	510	NB-CP-350	16	
	LP5	23	510	NB-CP-LP5	16	

TECHNICAL DATA & SHIPPING INFORMATION

Molecular Weight	58.1222 g/mol
Specific Volume	6.66 cf/lb @ 70°F & 1 ATM
Boiling Point	–0.5 °C
Flammability in Air	Flammable — 1.6–8.4% in Air

U.S. DOT Name	Butane
ID Number	UN 1011
DOT Hazard Class	2.1 — Flammable Gas
CAS Registry Number	106-97-8

WSM offers a wide range of gas supply modes, including high-pressure cylinders, liquid cylinders (dewars), MicroBulk and bulk. Your WSM specialty gas representative can help you select the option best suited to your operation, including automatic changeover systems for uninterrupted supply.

WSM Quality Policy. The purpose of the WSM Quality System is to continually improve our manufacturing and related processes to provide our customers with the highest product purity, consistency, and service.