

# Graph Algorithm

(Chapter 4.2, 5.3)


# Graph Algorithm

- ▶ Topological Sorting
  - Using DFS
  - Decrease by one
- ▶ Binary Tree Traversal
  - Preorder
  - Inorder
  - Postorder



# DAG's (Directed Acyclic Graphs)

- ▶ recall that a directed graph is a graph that uses arrows to show direction

- for example:



- ▶ a directed acyclic graph, aka **DAG**, is a directed graph that contains no cycles



# Topological Sort

- ▶ **Problem:** We have a set of tasks and a set of dependencies (precedence constraints) of form “task A must be done before task B”
- ▶ **Goal:** Find a linear ordering that satisfies all dependencies

# Topological Sort

- *Input might look like this ....*

2, 1  $\leftarrow$  ( task 2 must be done before task 1 )

4, 3  $\leftarrow$  ( task 4 must be done before task 3 )

1, 4  $\leftarrow$  ( task 1 must be done before task 4 )

5, 2  $\leftarrow$  ( task 5 must be done before task 2 )

one possible solution (topologically sorted order):

- 5 2 1 4 3 6

# Topo Sort Algo 1:DFS

To obtain a topological sort order for a set of items:

1. represent the items as a directed graph  $G$  such that:
  - a) vertices are the items that are tasks
  - b) edges are the dependencies (constraints) between tasks
    - an edge from  $v$  to  $w$  (eg:  $v \rightarrow w$ ) means that  $v$  is dependent on  $w$  ... ie ...  $v$  must be done before  $w$
2. apply the DFS algorithm to  $G$
3. the order in which vertices become dead ends gives the reverse topological sort order

*Note: Topological Sort produces no solution if the graph contains a cycle*


# Topo Sort Algo 1:DFS

Recall:

- the DFS implementation is recursive
- each time a recursive call is made is equivalent to "pushing a vertex on a stack"
- the "order in which vertices become dead ends" is given by the "order in which vertices are popped off the stack"

# Example 1: Work Tasks


- ▶ Assume you have a set of 6 tasks (a, b, c, d, e, f) with the following dependencies:
  - a must be done before b, e, f
  - b must be done before c
  - d must be done before b and c
  - e must be done before d
  - f must be done before c and e
- ▶ Step 1: Draw a directed graph to represent these dependencies.





# Example 1 (cont)

- ▶ Step 2: Apply DFS



Order vertices become dead ends:

c b d e f a

- ▶ Step 3:

Reverse this order for the solution:

a f e d b c

# Example 2: Work Tasks

2 1  $\leftarrow$  (2 before 1 ) 4 3  $\leftarrow$  (4 before 3 )

1 4  $\leftarrow$  (1 before 4 ) 5 2  $\leftarrow$  (5 before 2 )

2 3  $\leftarrow$  (2 before 3 ) 5 1  $\leftarrow$  (5 before 1 )

5 6  $\leftarrow$  (5 before 6 ) 6 3  $\leftarrow$  (6 before 3 )


2 4  $\leftarrow$  (2 before 4 ) 6 2  $\leftarrow$  (6 before 2 )

- ▶ Step 1: draw the graph (and verify it is a DAG)
- ▶ Step 2: apply DFS
- ▶ Step 3: find the order vertices were removed from stack, and reverse this order to get topological sort order

# Topo Sort Algo 2: Decrease by One

- ▶ Observe:
  - if a vertex  $v$  in the dependency graph  $G$  has no incoming arrows (ie:  $\text{in-degree}(v) = 0$ ), then  $v$  does not have any dependencies
  - it follows that any  $v$  that does not have dependencies is a candidate to be visited next in topographical order
- ▶ A Decrease-by-One approach:
  - identify a  $v \in V$  that has  $\text{in-degree} = 0$
  - delete  $v$  and all of its edges
  - when all vertices have been deleted, the topo sort order is given by the order of deletion
  - if there are  $v \in V$ , but no  $v$  has  $\text{in-degree} = 0$ , the graph  $G$  is not a DAG (no feasible solution exists)

# Example



# Topo Sort Algo 2: Decrease by One

- ▶ More detailed algorithm:
  - need a set to store the candidate  $v$ 's ( $\text{in-degree} = 0$ )
    - I will use a TreeSet. Any ordered set will do.
  - need an ordered list to store the delete order
    - I will use an ArrayList. Any ordered list will do.
- ▶ Then the algorithm is:


# Topo Sort Algo 2: Decrease by One

```
topo(G)
  create an empty ArrayList Soln
  create an empty TreeSet Candidates
  add all v with inDegree=0 to Candidates
  while Candidates is not empty
     $v \leftarrow \text{Candidates.first}()$ 
    add v to Soln
    for each vertex w adjacent to v
      remove edge (v,w) from G
      if w has inDegree=0
        add w to Candidates
    remove vertex v from G
  if there are vertices remaining in G
    no feasible solution exists
  else
    solution is in Soln
```

# Graph Algorithm


- ▶ Topological Sorting
  - Using DFS
  - Decrease by one
- ▶ Binary Tree Traversal
  - Preorder
  - Inorder
  - Postorder

# Binary Tree






# Preorder




a b c

# Example



Preorder: A B D E C F G

# Example




Preorder: A B D E C F G

# Preorder


```
public void preorderPrint(Node N) {  
  
    if (N == null) return;  
    System.out.println(N.value);  
    preorderPrint(N.leftChild);  
    preorderPrint(N.rightChild);  
}
```

# Inorder





b a c

# Example



Inorder: D B E A F C G

# Example




Inorder: D B E A F C G

# Inorder

```
public void inorderPrint(Node N) {  
  
    if (N == null) return;  
    inorderPrint(N.leftChild);  
    System.out.println(N.value);  
    inorderPrint(N.rightChild);  
}
```




# Postorder





b c a

# Example



postorder: D E B F G C A

# Example




Postorder: D E B F G C A

# postorder

```
public void postorderPrint(Node N) {  
  
    if (N == null) return;  
    postorderPrint(N.leftChild);  
    postorderPrint(N.rightChild);  
    System.out.println(N.value);  
}
```

# Example



# Try it/ homework

1. Chapter 4.2, page 142, question 1
2. Chapter 5.3, page 185, questions 5,6