

From the R2 router, how many ICMP messages are successful when pinging PC1?

R2>ping 172.30.1.10

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 172.30.1.10, timeout is 2 seconds:

.U!..!

Success rate is 40 percent (2/5), round-trip min/avg/max = 6/10/8 ms

Solamente 2

Step 3: Check the connectivity between the PCs.

From the PC1, is it possible to ping PC2? Es posible

What is the success rate? Se pueden enviar 3 paquetes de 4 75% success rate

From the PC1, is it possible to ping PC3? Es posible

What is the success rate? Se pueden enviar 2 paquetes de 4 50% success rate

From the PC1, is it possible to ping PC4? Es posible

What is the success rate? Se envían 4 paquetes de 4 100% success rate

From the PC4, is it possible to ping PC2? No es posible, el router dice Unreachable host

What is the success rate? No tiene, no se pueden enviar paquetes 0% success rate

From the PC4, is it possible to ping PC3? Si se puede

What is the success rate? Se envían 2 de 4 paquetes 50 % success rate

Use the output of the debug ip rip command to answer the following questions:

What entries are included in the RIP updates sent out from R3?

El router R3 está enviando actualizaciones RIP versión 2 (v2) a través de sus interfaces

Loopback0, Loopback1, Loopback2, y Serial0/0/1 a la dirección multicast 224.0.0.9, que es la dirección utilizada por RIP v2 para enviar actualizaciones a otros routers.

1. Loopback0 (IP: 172.30.110.1)

R3 anuncia las siguientes redes:

- 10.0.0.0/8, con métrica 2
- 172.30.100.0/24, métrica 1
- 172.30.200.16/28, métrica 1
- 172.30.200.32/28, métrica 1
- 209.165.200.0/24, métrica 1

2. Loopback1 (IP: 172.30.200.17)

R3 anuncia:

- 10.0.0.0/8, métrica 2
- 172.30.100.0/24, métrica 1
- 172.30.110.0/24, métrica 1
- 172.30.200.32/28, métrica 1
- 209.165.200.0/24, métrica 1

3. Loopback2 (IP: 172.30.200.33)

R3 anuncia:

- 10.0.0.0/8, métrica 2
- 172.30.100.0/24, métrica 1
- 172.30.110.0/24, métrica 1
- 172.30.200.16/28, métrica 1
- 209.165.200.0/24, métrica 1

4. Serial0/0/1 (IP: 209.165.200.234)

R3 anuncia una sola red:

- 172.30.0.0/16, métrica 1

También recibe desde esa interfaz (de 209.165.200.233) las siguientes redes:

- 10.0.0.0/8
- 209.165.200.228/30

On R2, what routes are in the RIP updates that are received from R3?

R2 está recibiendo actualizaciones RIP versión 2 desde R3 a través de la interfaz Serial0/0/1, que tiene la IP de origen 209.165.200.234.

72.30.0.0/16 via 0.0.0.0 in 1 hops

(Recibida en Serial0/0/1 desde 209.165.200.234)

(Y también se recibe la misma ruta en otra ocasión, lo cual es normal por la naturaleza periódica de RIP)

What entries are included in the RIP updates sent out from R1?

Las entradas incluidas en las actualizaciones RIP enviadas desde R1 son:

- 172.30.1.0/24 con métrica 1
- 172.30.2.0/24 con métrica 1

On R2, what routes are in the RIP updates that are received from R1?

Las rutas que R2 recibe en las actualizaciones RIP desde R1 son:

- 172.30.1.0/24 (1 salto)
- 172.30.2.0/24 (1 salto)

Are the subnet masks now included in the routing updates?

Yes, the subnet masks **are included** in the routing updates.

Step 1: Check connectivity between R2 router and PCs.

From R2, how many ICMP messages are successful when pinging PC1?

5/5 es decir un 100%

From R2, how many ICMP messages are successful when pinging PC4?

5/5 es decir un 100%

Step 2: Check the connectivity between the PCs.

From PC1, is it possible to ping PC2? Si

What is the success rate? success rate: 100%

From PC1, is it possible to ping PC3? si

What is the success rate? success rate: 100%

From PC1, is it possible to ping PC4? si

What is the success rate? success rate: 100%

From PC4, is it possible to ping PC2? si

What is the success rate? 100%

From PC4, is it possible to ping PC3? si

What is the success rate? 100%