

Práctica 12 — Despliegue y verificación de Gitea

Práctica 12 — Despliegue y verificación de Gitea

Resumen

Despliegue de Gitea usando Docker Compose en una VM Ubuntu y verificación completa: instalación, configuración inicial, creación de usuarios y repositorio privado, sincronización con Git, flujo de trabajo con ramas y Pull Request, copia de seguridad de datos, y acceso por SSH para Git (bonus). Las imágenes prueban cada paso.

Entorno

- VM: Ubuntu Server (Oracle VirtualBox) — Gitea en Docker
- Host: CachyOS — cliente Git/SSH y capturas
- URL web Gitea: <http://172.16.133.21:3000>

Contenido del informe (paso a paso)

1. Actualización del sistema y paquetes base

Comandos:

```
sudo apt update && sudo apt upgrade -y
sudo apt install -y docker.io docker-compose git openssh-server ufw curl ca-certificates
```

Prueba (capturas):

```
castor909@mus:~$ sudo apt update && sudo apt upgrade
Hit:1 http://es.archive.ubuntu.com/ubuntu noble InRelease
Hit:2 http://es.archive.ubuntu.com/ubuntu noble-updates InRelease
Hit:3 http://es.archive.ubuntu.com/ubuntu noble-backports InRelease
Hit:4 http://security.ubuntu.com/ubuntu noble-security InRelease
Hit:5 https://deb.nodesource.com/node_24.x nodistro InRelease
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
All packages are up to date.
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
Calculating upgrade... Done
The following packages were automatically installed and are no longer required:
  linux-headers-6.8.0-101 linux-headers-6.8.0-101-generic linux-headers-6.8.0-90 linux-headers-6.8.0-90-generic linux-image-6.8.0-101-generic
  linux-image-6.8.0-90-generic linux-modules-6.8.0-101-generic linux-modules-6.8.0-90-generic linux-modules-extra-6.8.0-101-generic
  linux-modules-extra-6.8.0-90-generic linux-tools-6.8.0-101 linux-tools-6.8.0-101-generic linux-tools-6.8.0-90 linux-tools-6.8.0-90-generic
Use 'sudo apt autoremove' to remove them.
0 upgraded, 0 newly installed, 0 to remove and 0 not upgraded.
castor909@mus:~$
```

```

castor909@mus:~$ sudo apt install -y docker.io docker-compose git openssh-server ufw curl ca-certificates
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
docker.io is already the newest version (29.1.3-0ubuntu3~24.04.2).
docker-compose is already the newest version (1.29.2-6ubuntu1).
git is already the newest version (1:2.43.0-1ubuntu7.3).
openssh-server is already the newest version (1:9.6p1-3ubuntu13.16).
ufw is already the newest version (0.36.2-6).
curl is already the newest version (8.5.0-2ubuntu10.9).
ca-certificates is already the newest version (20240203).
0 upgraded, 0 newly installed, 0 to remove and 0 not upgraded.
castor909@mus:~$ _

castor909@mus:~$ docker compose version
Docker Compose version v5.1.3
castor909@mus:~$ docker --version
Docker version 29.5.0, build 30f1464
castor909@mus:~$ docker compose version
Docker Compose version v5.1.3
castor909@mus:~$ sudo systemctl enable --now docker
Synchronizing state of docker.service with SysV service script with /usr/lib/systemd/systemd-sysv-install.
Executing: /usr/lib/systemd/systemd-sysv-install enable docker
castor909@mus:~$ sudo systemctl status docker --no-pager
● docker.service - Docker Application Container Engine
   Loaded: loaded (/usr/lib/systemd/system/docker.service; enabled; preset: enabled)
   Active: active (running) since Sun 2026-05-17 21:33:57 UTC; 17s ago
   TriggeredBy: ● docker.socket
   Docs: https://docs.docker.com
   Main PID: 22906 (dockerd)
   Tasks: 7
   Memory: 23.1M (peak: 23.7M)
   CPU: 235ms
   CGroup: /system.slice/docker.service
           └─22906 /usr/bin/dockerd -H fd:// --containerd=/run/containerd/containerd.sock

May 17 21:33:56 mus dockerd[22906]: time="2026-05-17T21:33:56.354120566Z" level=info msg="Restoring containers: start."
May 17 21:33:56 mus dockerd[22906]: time="2026-05-17T21:33:56.406253367Z" level=info msg="Deleting iptables IPv4 rules" error="exit status 1" output="br-9877ab894bce"
May 17 21:33:56 mus dockerd[22906]: time="2026-05-17T21:33:56.442538219Z" level=info msg="Deleting iptables IPv6 rules" error="exit status 1" output="br-9877ab894bce"
May 17 21:33:57 mus dockerd[22906]: time="2026-05-17T21:33:57.570864679Z" level=info msg="Loading containers: done."
May 17 21:33:57 mus dockerd[22906]: time="2026-05-17T21:33:57.58977925Z" level=info msg="Docker daemon" commit=ff8d90a containerd-snapshots=true version=29.5.0
May 17 21:33:57 mus dockerd[22906]: time="2026-05-17T21:33:57.58982413Z" level=info msg="Initializing buildkit"
May 17 21:33:57 mus dockerd[22906]: time="2026-05-17T21:33:57.597113742Z" level=info msg="Completed buildkit initialization"
May 17 21:33:57 mus dockerd[22906]: time="2026-05-17T21:33:57.665730938Z" level=info msg="Daemon has completed initialization"
May 17 21:33:57 mus dockerd[22906]: time="2026-05-17T21:33:57.665779413Z" level=info msg="API listen on /run/docker.sock"
May 17 21:33:57 mus systemd[1]: Started docker.service - Docker Application Container Engine.
Hint: Some lines were ellipsized, use -l to show in full.
castor909@mus:~$ _

castor909@mus:~/gitea$ hostname -I
172.16.133.21 172.17.0.1 172.18.0.1
castor909@mus:~/gitea$ ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host noprefixroute
        valid_lft forever preferred_lft forever
2: enp0s3: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen 1000
    link/ether 08:00:27:40:7e:81 brd ff:ff:ff:ff:ff:ff
    inet 172.16.133.21/20 metric 100 brd 172.16.143.255 scope global dynamic enp0s3
        valid_lft 14356sec preferred_lft 14356sec
    inet6 fe80::a00:27ff:fe40:7e81/64 scope link
        valid_lft forever preferred_lft forever
3: docker0: <NO-CARRIER,BROADCAST,MULTICAST,UP> mtu 1500 qdisc noqueue state DOWN group default
    link/ether de:98:ec:73:38:70 brd ff:ff:ff:ff:ff:ff
    inet 172.17.0.1/16 brd 172.17.255.255 scope global docker0
        valid_lft forever preferred_lft forever
4: br-9877ab894bce: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noqueue state UP group default
    link/ether d2:ea:66:95:b3:a7 brd ff:ff:ff:ff:ff:ff
    inet 172.18.0.1/16 brd 172.18.255.255 scope global br-9877ab894bce
        valid_lft forever preferred_lft forever
    inet6 fe80::d0ea:66ff:fe95:b3a7/64 scope link
        valid_lft forever preferred_lft forever
5: veth0b464b5eif2: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noqueue master br-9877ab894bce state UP group default
    link/ether 66:fa:66:91:00:df brd ff:ff:ff:ff:ff:ff link-netnsid 0
    inet6 fe80::64fa:66ff:fe91:df/64 scope link
        valid_lft forever preferred_lft forever
castor909@mus:~/gitea$

```

2. Firewall (UFW)

Comandos:

```

sudo ufw allow OpenSSH
sudo ufw allow 3000/tcp
sudo ufw allow 2222/tcp
sudo ufw enable
sudo ufw status verbose

```

Prueba:

3. Despliegue con Docker Compose (Gitea)

```

castor909@mus:~$ sudo ufw allow OpenSSH
Rule added
Rule added (v6)
castor909@mus:~$ sudo ufw allow 3000/tcp
Rule added
Rule added (v6)
castor909@mus:~$ sudo ufw allow 2222/tcp
Rule added
Rule added (v6)
castor909@mus:~$ sudo ufw enable
Firewall is active and enabled on system startup
castor909@mus:~$ sudo ufw status verbose
Status: active
Logging: on (low)
Default: deny (incoming), allow (outgoing), deny (routed)
New profiles: skip


```

To	Action	From
---	-----	----
22/tcp	ALLOW IN	Anywhere
389/tcp	ALLOW IN	Anywhere
80/tcp	ALLOW IN	Anywhere
22/tcp (OpenSSH)	ALLOW IN	Anywhere
3000/tcp	ALLOW IN	Anywhere
2222/tcp	ALLOW IN	Anywhere
22/tcp (v6)	ALLOW IN	Anywhere (v6)
389/tcp (v6)	ALLOW IN	Anywhere (v6)
80/tcp (v6)	ALLOW IN	Anywhere (v6)
22/tcp (OpenSSH (v6))	ALLOW IN	Anywhere (v6)
3000/tcp (v6)	ALLOW IN	Anywhere (v6)
2222/tcp (v6)	ALLOW IN	Anywhere (v6)

```

castor909@mus:~$ _

```

Figure 1: UFW status

Contenido de `docker-compose.yml`: puerto HTTP 3000, SSH Git 2222, volumen bind a host para persistencia.

Comandos:

```
docker compose up -d
docker compose ps
docker compose logs --tail=50
```

Prueba:

```
GNU nano 7.2 docker-compose.yml
services:
  gitea:
    image: gitea/gitea:latest
    container_name: gitea
    restart: unless-stopped
    ports:
      - "3000:3000"
      - "2222:22"
    volumes:
      - ./gitea:/data

castor909@mus: ~/gitea$ sudo docker compose up -d
[+] up 9/9
  Image gitea/gitea:latest Pulled
  Network gitea_default Created
  Container gitea Started
castor909@mus: ~/gitea$ _

castor909@mus: ~/gitea$ sudo docker compose ps
NAME                IMAGE                                COMMAND                  SERVICE  CREATED      STATUS      PORTS
gitea                gitea/gitea:latest                 "/usr/bin/entrypoint"   gitea    30 seconds ago Up 37 seconds 0.0.0.0:3000->3000/tcp, [::]:3000->3000/tcp, 0.0.0.0:2222->22
/tcp, [::]:2222->22/tcp
castor909@mus: ~/gitea$ sudo docker ps
CONTAINER ID        IMAGE                                COMMAND                  SERVICE  CREATED      STATUS      PORTS
fcd32ed7b174       gitea/gitea:latest                 "/usr/bin/entrypoint"   gitea    45 seconds ago Up 44 seconds 0.0.0.0:3000->3000/tcp, [::]:3000->3000/tcp, 0.0.0.0:2222->22
/tcp, [::]:2222->22/tcp
castor909@mus: ~/gitea$

castor909@mus: ~/gitea$ sudo docker compose logs --tail=50
gitea | Generating /data/ssh/ssh_host_ed25519_key...
gitea | Generating /data/ssh/ssh_host_rsa_key...
gitea | Generating /data/ssh/ssh_host_ecdsa_key...
gitea | Server listening on :: port 22.
gitea | Server listening on 0.0.0.0 port 22.
gitea | 2020-05-17 21:43:29 cmd.ueb.go:263:runWeb() [I] Starting Gitea on PID: 17
gitea | 2020-05-17 21:43:29 cmd.ueb.go:115:showWebStartupMessage() [I] Gitea version: 1.26.1 built with go1.26.2-X3:json2 : bindata, tinetsdata, sqlite, sqlite
_unlock_notify
gitea | 2020-05-17 21:43:29 cmd.ueb.go:116:showWebStartupMessage() [I] * RunMode: prod
gitea | 2020-05-17 21:43:29 cmd.ueb.go:117:showWebStartupMessage() [I] * AppPath: /usr/local/bin/gitea
gitea | 2020-05-17 21:43:29 cmd.ueb.go:118:showWebStartupMessage() [I] * WorkPath: /data/gitea
gitea | 2020-05-17 21:43:29 cmd.ueb.go:119:showWebStartupMessage() [I] * CustomPath: /data/gitea
gitea | 2020-05-17 21:43:29 cmd.ueb.go:120:showWebStartupMessage() [I] * ConfigFile: /data/gitea/conf/app.ini
gitea | 2020-05-17 21:43:29 cmd.ueb.go:121:showWebStartupMessage() [I] Prepare to run install page
gitea | 2020-05-17 21:43:29 cmd.ueb.go:329:listen() [I] Listen: http://0.0.0.0:3000
gitea | 2020-05-17 21:43:29 cmd.ueb.go:333:listen() [I] register URL: http://localhost:3000/
gitea | 2020-05-17 21:43:29 modules/graceful/server.go:52:NewServer() [I] Starting new Web server: tcp:0.0.0.0:3000 on PID: 17
castor909@mus: ~/gitea$ _
```

4. Configuración inicial via web (SQLite)

Accede a `http://172.16.133.21:3000` y completa la instalación: SQLite3, rutas de datos, Base URL y creación del administrador.

Prueba:

Initial Configuration

If you run Gitea inside Docker, please read the [documentation](#) before changing any settings.

Database Settings

Gitea requires MySQL, PostgreSQL, MSSQL, SQLite3 or TiDB (MySQL protocol).

Database Type *

Path *

File path for the SQLite3 database.
Enter an absolute path if you run Gitea as a service.

General Settings

Site Title *

You can enter your company name here.

Repository Root Path *

Remote Git repositories will be saved to this directory.

Git LFS Root Path

Files tracked by Git LFS will be stored in this directory. Leave empty to disable.

Run As Username

The operating system username that Gitea runs as, it must have write access to the data paths. This value is auto-detected and cannot be changed here. To use a different user, restart Gitea under that account.

Server Domain *

Optional host address for the server.

Log files will be written to this directory.

☐ Enable Update Checker
Checks for new version releases periodically by connecting to gitea.io.

Optional Settings

► Email Settings

► Server and Third-Party Service Settings

▼ Administrator Account Settings

Creating an administrator account is optional. The first registered user will automatically become an administrator.

Administrator Username

Castor909

Email Address

dunnage909@icloud.com

Password

.....

Confirm Password

.....

These configuration options will be written into: `/data/gitea/conf/app.ini`

Install Gitea

Powered by Gitea Version: 1.26.1 Page: 22ms Template: 22ms

Auto

English

Licenses

API



Installing now, please wait...

Powered by [Gitea](#) Version: 1.26.1 Page: 4260ms Template: 0ms

[Auto](#) [English](#) | [Licenses](#) | [API](#)

IssuesPull RequestsMilestonesExplore

Castor909

Repository

Organization

Repositories

+

There are no repositories yet.

0 contributions in the last 12 months

LessMore

No Activity

You are currently not following any repositories or users, so there is no content to display. You can explore repositories or users of interest from the links below.

Explore repositories

Explore users


Powered by Gitea Version: 1.26.1 Page: 4ms Template: 2ms

Auto

English

Licenses

API



5. Crear usuario normal y repositorio privado

Acciones en la UI: - Crear usuario `student_one` (no admin) - Crear repositorio privado `practica-gitea` bajo `student_one`

Prueba:

Issues

Pull Requests

Milestones

Explore

Admin Settings

Maintenance

Identity & Access

Authentication Sources

Organizations

User Accounts

Badges

User Email Addresses

Code Assets

Integrations

Actions

Configuration

System Notices

Monitoring

Create User Account

Authentication Source *Local

User visibility *Public

Username *Student One

Email Address *student01@example.com

Password *.....

☒ Require user to change password (recommended)

Create User Account

Powered by Gitea

Version: 1.26.1

Page: 4ms

Template: 3ms

Auto

English

Licenses

API

Admin Settings

Maintenance

Identity & Access

- Authentication Sources
- Organizations
- User Accounts
- Badges
- User Email Addresses

Code Assets

Integrations

Actions

Configuration

System Notices

Monitoring

The user account "student_one" has been created.

User Details

student_one

Authentication Source: Local

Activated: ✓

Disable Sign-In: X

Restricted: X

User visibility: Public

2FA: X

User Email Addresses (Total: 1)

student001@example.comPrimaryActivated

Repositories (Total: 0)

No matching results found.

Organizations (Total: 0)

No matching results found.

Powered by Gitea Version: 1.26.1 Page: 25ms Template: 23ms

AutoEnglishLicensesAPI

IssuesPull RequestsMilestonesExplore

student_one

Your password has been updated. Sign in using your new password from now on.

RepositoryOrganization

Repositories+

There are no repositories yet.

JunJulAugSepOctNovDecJanFebMarAprMay

Mon

Wed

Fri

0 contributions in the last 12 months

LessMore

No Activity

You are currently not following any repositories or users, so there is no content to display. You can explore repositories or users of interest from the links below.

Explore repositories · Explore users

Powered by Gitea Version: 1.26.1 Page: 4ms Template: 2ms

AutoEnglishLicensesAPI

IssuesPull RequestsMilestonesExplore

New Repository

A repository contains all project files, including revision history. Already hosting one elsewhere? [Migrate repository](#).

Owner *

student_one

Some organizations may not show up in the dropdown due to a maximum repository count limit.

Repository Name *

practica-gitea

Good repository names use short, memorable and unique keywords. A repository named "profile" or "profile-private" could be used to add a README.md for the user/organization profile.

Visibility

☒ Make repository private

Only the owner or the organization members, if they have rights, will be able to see it.

Description

Enter short description (optional)

Template

Select a template.

Issue Labels

Select an issue label set.

.gitignore

Select .gitignore templates.

Choose which files not to track from a list of templates for common languages. Typical artifacts generated by each language's build tools are included on .gitignore by default.

License

Select a license file.

A license governs what others can and can't do with your code. Not sure which one is right for your project? See [Choose a license](#).

README

Default

This is the place where you can write a complete description for your project.

☒ Initialize Repository (Adds .gitignore, License and README)

Default Branch

main

The default branch is the base branch for pull requests and code commits.

Object Format

sha1

Object format of the repository. Cannot be changed later. SHA1 is most compatible.


Template

☐ Make repository a template

Create Repository

Powered by Gitea · Version: 1.26.1 · Page: 9ms · Template: 7ms

AutoEnglishLicensesAPI



6. Sincronización Git (HTTP) — añadir archivos del proyecto

Comandos (cliente):

```
git clone http://172.16.133.21:3000/student_one/practica-gitea.git
cd practica-gitea
# crear index.html, style.css, README.md
git add .
git commit -m "Initial project files"
git push origin main
```

Prueba:

```
practica-gitea: fish — Konsole
New Tab Split View
Copy Paste Find

> git clone http://172.16.133.21:3000/student_one/practica-gitea.git
cd practica-gitea
Cloning into 'practica-gitea'...
Username for 'http://172.16.133.21:3000': student_one
Password for 'http://student_one@172.16.133.21:3000':
remote: Enumerating objects: 3, done.
remote: Counting objects: 100% (3/3), done.
remote: Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Receiving objects: 100% (3/3), done.

~/practica-gitea main 22s
> ls
drwxr-xr-x - castor909 18 may 16:35 .git
-rw-r--r-- 18 castor909 18 may 16:35 README.md

~/practica-gitea main
> git status
On branch main
Your branch is up to date with 'origin/main'.

Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   README.md

Untracked files:
  (use "git add <file>..." to include in what will be committed)
        index.html
        style.css

no changes added to commit (use "git add" and/or "git commit -a")

~/practica-gitea main*
> git add .
git commit -m "Initial project files"
git branch -M main
git push -u origin main
[main 127292b] Initial project files
 3 files changed, 13 insertions(+), 1 deletion(-)
 create mode 100644 index.html
 create mode 100644 style.css
Username for 'http://172.16.133.21:3000': student_one
Password for 'http://student_one@172.16.133.21:3000':
Enumerating objects: 7, done.
Counting objects: 100% (7/7), done.
Delta compression using up to 8 threads
Compressing objects: 100% (4/4), done.
Writing objects: 100% (5/5), 682 bytes | 682.00 KiB/s, done.
Total 5 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
remote: . Processing 1 references
remote: Processed 1 references in total
To http://172.16.133.21:3000/student_one/practica-gitea.git
 d250dd1..127292b main -> main
branch 'main' set up to track 'origin/main'.

~/practica-gitea main 11s
>
```

The screenshot shows the Gitea web interface for a repository named 'practica-gitea' under the user 'student_one'. The repository is private and has 1 branch (main) and 0 tags. The file list shows 'index.html', 'README.md', and 'style.css', all marked as 'Initial project files'. The README content is in Spanish, describing a Gitea practice repository with deployment instructions and Git commands. The language statistics show HTML at 84.3% and CSS at 15.7%. Below the repository view, a terminal window shows the execution of 'git remote -v', 'git log --oneline', and 'git add README.md'.

Repository: student_one / practica-gitea (Private)

2 Commits | 1 Branch | 0 Tags

Search code...

Description
No description provided

Languages
HTML 84.3% | CSS 15.7%

README.md

Práctica Gitea - practica-gitea

Descripción: Repositorio de práctica para Gitea.
Deploy: <http://172.16.133.21:3000> (port 3000)
Comandos Git: git add . git commit -m "Initial project files" git push origin main
Seguridad: repo privado, UFW permite 3000/2222, backup periódicos.

```
> git remote -v
origin http://172.16.133.21:3000/student_one/practica-gitea.git (fetch)
origin http://172.16.133.21:3000/student_one/practica-gitea.git (push)

~/practica-gitea main
> git log --oneline
127292b (HEAD -> main, origin/main, origin/HEAD) Initial project files
d250dd1 Initial commit

~/practica-gitea main
>
```

7. Ramas, Pull Request y Merge

Comandos:

```
git checkout -b mejora-readme
# editar README.md
git add README.md
```

```
git commit -m "Improve README with security notes"
git push -u origin mejora-readme
```

En la UI: crear PR desde mejora-readme hacia main y hacer merge.

Prueba:


```
> git checkout -b mejora-readme
Switched to a new branch 'mejora-readme'

~/practica-gitea mejora-readme
> nano README.md

~/practica-gitea mejora-readme* 20s
> git add README.md
> git commit -m "Improve README with security notes"
> git push -u origin mejora-readme
[mejora-readme c7e3c51] Improve README with security notes
1 file changed, 6 insertions(+)
Username for 'http://172.16.133.21:3000': student_one
Password for 'http://student_one@172.16.133.21:3000':
remote: Failed to authenticate user
fatal: Authentication failed for 'http://172.16.133.21:3000/student_one/practica-gitea.git/'

~/practica-gitea mejora-readme 14s
> git push -u origin mejora-readme
Username for 'http://172.16.133.21:3000': student_one
Password for 'http://student_one@172.16.133.21:3000':
Enumerating objects: 5, done.
Counting objects: 100% (5/5), done.
Delta compression using up to 8 threads
Compressing objects: 100% (3/3), done.
Writing objects: 100% (3/3), 544 bytes | 544.00 KiB/s, done.
Total 3 (delta 1), reused 0 (delta 0), pack-reused 0 (from 0)
remote:
remote: Create a new pull request for 'mejora-readme':
remote: http://172.16.133.21:3000/student_one/practica-gitea/pulls/new/mejora-readme
remote:
remote: . Processing 1 references
remote: Processed 1 references in total
To http://172.16.133.21:3000/student_one/practica-gitea.git
 * [new branch]      mejora-readme -> mejora-readme
branch 'mejora-readme' set up to track 'origin/mejora-readme'.

~/practica-gitea mejora-readme 10s
```



[Issues](#) [Pull Requests](#) [Milestones](#) [Explore](#)   

 **student_one / practica-gitea** Private   1  0  0

[Code](#) [Issues](#) [Pull Requests](#) 1 [Actions](#) [Packages](#) [Projects](#) [...](#)

Improve README with security notes #1

[Edit](#)

[Open](#) student_one wants to merge 1 commits from mejora-readme into main

[Conversation](#) 0 [Commits](#) 1 [Files Changed](#) 1 +6

0 / 1 files viewed

    [Review](#)

▼ README.md  +6 Viewed [...](#)

...	@@ -7,3 +7,9 @@ Comandos Git:
7	git commit -m "Initial project files"
8	git push origin main
9	Seguridad: repo privado, UFW permite 3000/2222, backup periódicos.
10	+
11	+ ## Seguridad básica aplicada
12	+ - Repositorio privado configurado
13	+ - UFW firewall habilitado con puertos SSH (22), web (3000) y Git SSH (2222)
14	+ - Backup periódicos de datos de Gitea
15	+ - Acceso controlado por usuario y rol

Powered by Gitea Version: 1.26.1 Page: 57ms Template: 10ms

 [English](#) [Licenses](#) [API](#)

Issues Pull Requests Milestones Explore

student_one / practica-gitea Private Unwatch 1 Star 0 Fork 0

<> Code Issues Pull Requests Actions Packages Projects Releases ...

Improve README with security notes #1

Merged student_one merged 1 commits from mejora-readme into main now

Conversation 0 Commits 1 Files Changed 1 +6

student_one commented 4 minutes ago
Owner

No description provided.

student_one added 1 commit 4 minutes ago
Improve README with secu... c7e3c510e2

student_one merged commit 6779557085 into main now

Pull request successfully merged and closed
The branch mejora-readme can now be deleted.
Delete Branch

Write Preview

Reviewers
No Reviewers

Labels
No Label

Milestone
No Milestone

Projects
No project

Assignees
No Assignees

1 Participants

Notifications
Unsubscribe

Time Tracker

```
> git checkout main
git pull
git log --oneline --decorate --graph -n 10
Switched to branch 'main'
Your branch is up to date with 'origin/main'.
Username for 'http://172.16.133.21:3000': student_one
Password for 'http://student_one@172.16.133.21:3000':
remote: Enumerating objects: 1, done.
remote: Counting objects: 100% (1/1), done.
remote: Total 1 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Unpacking objects: 100% (1/1), 306 bytes | 306.00 KiB/s, done.
From http://172.16.133.21:3000/student_one/practica-gitea
  127292b..6779557  main    -> origin/main
Updating 127292b..6779557
Fast-forward
 README.md | 6 +++++
 1 file changed, 6 insertions(+)
* 6779557 (HEAD -> main, origin/main, origin/HEAD) Merge pull request 'Improve README with security notes' (#1) from mejora-readme into main
* c7e3c51 (origin/mejora-readme, mejora-readme) Improve README with security notes
* 127292b Initial project files
* d250dd1 Initial commit
~/practica-gitea main 11s
```


8. Backup y persistencia de datos

Se confirmó que Gitea usa bind-mount a host: /home/castor909/gitea/gitea
-> /data. Se creó gitea-backup.tgz dentro del contenedor y se copió al host;
se verificó contenido.

Comandos (ejemplo):

```
docker compose exec -T gitea sh -c "tar -czf /tmp/gitea-backup.tgz /data/gitea"
CID=$(docker compose ps -q gitea)
docker cp ${CID}:/tmp/gitea-backup.tgz ./gitea-backup.tgz
tar -tzf gitea-backup.tgz | head -n 30
```

Prueba:



```
my_ubuntu_server [Running] - Oracle VirtualBox
File Machine View Input Devices Help

castor909@mus:~/gitea$ sudo docker compose ps
[sudo] password for castor909:
NAME        IMAGE        COMMAND                  SERVICE    CREATED        STATUS        PORTS
gitea       gitea/gitea:latest "/usr/bin/entrypoint"    gitea      17 hours ago   Up 17 hours   0.0.0.0:3000->3000/tcp, [::]:3000->3000/tcp, 0.0.0.0:2222->22/tcp, [::]:2222->22/tcp
castor909@mus:~/gitea$

castor909@mus:~/gitea$ sudo docker compose ps
[sudo] password for castor909:
NAME        IMAGE        COMMAND                  SERVICE    CREATED        STATUS        PORTS
gitea       gitea/gitea:latest "/usr/bin/entrypoint"    gitea      17 hours ago   Up 17 hours   0.0.0.0:3000->3000/tcp, [::]:3000->3000/tcp, 0.0.0.0:2222->22/tcp, [::]:2222->22/tcp
castor909@mus:~/gitea$ sudo docker compose -q gitea
unknown shorthand flag: 'q' in -q
castor909@mus:~/gitea$ sudo docker ps --filter "name=gitea" -q | head -n1
fcd32e07b174
castor909@mus:~/gitea$ sudo docker compose exec -T gitea sh -c "tar -czf /tmp/gitea-backup.tgz /data/gitea"
tar: removing leading '/' from member names
castor909@mus:~/gitea$ CID=fcd32e07b174
castor909@mus:~/gitea$ sudo docker cp ${CID}:/tmp/gitea-backup.tgz ./gitea-backup.tgz
CID: command not found
must specify at least one container source
castor909@mus:~/gitea$ echo $SHELL
/bin/bash
castor909@mus:~/gitea$ ps -p $$ -o comm=
bash
castor909@mus:~/gitea$ sudo docker ps --filter "name=gitea" --format "{{.ID}}\t\t{{.Names}}\t\t{{.Ports}}"
fcd32e07b174    gitea      0.0.0.0:3000->3000/tcp, [::]:3000->3000/tcp, 0.0.0.0:2222->22/tcp, [::]:2222->22/tcp
castor909@mus:~/gitea$ sudo docker exec gitea ls -lh /tmp/gitea-backup.tgz
-rw-r--r-- 1 root root 54.4K May 18 15:19 /tmp/gitea-backup.tgz
castor909@mus:~/gitea$ sudo docker cp gitea:/tmp/gitea-backup.tgz ./gitea-backup.tgz
Successfully copied 55.7kB (transferred 57.3kB) to /home/castor909/gitea/gitea-backup.tgz
castor909@mus:~/gitea$ ls -lh gitea-backup.tgz
-rw-r--r-- 1 root root 55K May 18 15:19 gitea-backup.tgz
castor909@mus:~/gitea$
```

```

> tar -tzf ~/Downloads/gitea-backup.tgz | head -n 30
data/gitea/
data/gitea/repo-avatars/
data/gitea/avatars/
data/gitea/avatars/684aefa5a85720ef3d0bc0a4a1328106
data/gitea/avatars/bb054fa6ce0705287e248bcd1a3ba676
data/gitea/avatars/tmp/
data/gitea/packages/
data/gitea/attachments/
data/gitea/sessions/
data/gitea/sessions/6/
data/gitea/sessions/6/f/
data/gitea/sessions/6/f/6f2505abaa99aa96
data/gitea/sessions/4/
data/gitea/sessions/4/0/
data/gitea/sessions/1/
data/gitea/sessions/1/b/
data/gitea/sessions/5/
data/gitea/sessions/5/6/
data/gitea/sessions/a/
data/gitea/sessions/a/6/
data/gitea/sessions/f/
data/gitea/sessions/f/9/
data/gitea/sessions/f/a/
data/gitea/sessions/d/
data/gitea/sessions/d/1/
data/gitea/repo-archive/
data/gitea/conf/
data/gitea/conf/app.ini
data/gitea/tmp/
data/gitea/tmp/local-repo/

~/practica-gitea main
> mkdir -p ~/tmp/gitea-backup-check
tar -xzf ~/Downloads/gitea-backup.tgz -C ~/tmp/gitea-backup-check
ls -la ~/tmp/gitea-backup-check | head -n 40
drwxr-xr-x - castor909 18 may 17:47 .
drwxr-xr-x - castor909 18 may 17:47 ..
drwxr-xr-x - castor909 18 may 17:47 data

~/practica-gitea main

```

6. Seguridad y persistencia (evidencias)

Estado del contenedor y del firewall (`docker compose ps + ufw status verbose`):

```
castor909@mus:~/gitea$ sudo docker compose ps
NAME                IMAGE              COMMAND                                SERVICE    CREATED        STATUS        PORTS
gitea               gitea/gitea:latest "/usr/bin/entrypoint"                gitea      18 hours ago   Up 18 hours   0.0.0.0:3000->3000, [::]:2222->22/tcp
castor909@mus:~/gitea$ sudo ufw status verbose
Status: active
Logging: on (low)
Default: deny (incoming), allow (outgoing), deny (routed)
New profiles: skip

To                        Action      From
--                        -
22/tcp                   ALLOW IN    Anywhere
389/tcp                  ALLOW IN    Anywhere
80/tcp                   ALLOW IN    Anywhere
22/tcp (OpenSSH)         ALLOW IN    Anywhere
3000/tcp                  ALLOW IN    Anywhere
2222/tcp                  ALLOW IN    Anywhere
22/tcp (v6)              ALLOW IN    Anywhere (v6)
389/tcp (v6)             ALLOW IN    Anywhere (v6)
80/tcp (v6)              ALLOW IN    Anywhere (v6)
22/tcp (OpenSSH (v6))    ALLOW IN    Anywhere (v6)
3000/tcp (v6)            ALLOW IN    Anywhere (v6)
2222/tcp (v6)            ALLOW IN    Anywhere (v6)
```

Estado del contenedor y firewall

Ubicación de los datos persistentes — `docker inspect` muestra el bind-mount `/home/castor909/gitea/gitea -> /data` ; ahí se guardan todos los datos de Gitea:

```
castor909@mus:~/gitea$ sudo docker inspect "$CID" --format '{{range .Mounts}}{{printf "%s %s -> %s\n" .Type .Source .Destination}}'
bind /home/castor909/gitea/gitea -> /data

castor909@mus:~/gitea$ ls -la /home/castor909/gitea/gitea
total 20
drwxr-xr-x  5 root    root      4096 May 17 21:43 .
drwxrwxr-x  3 castor909 castor909 4096 May 18 15:30 ..
drwxr-xr-x  5 castor909 castor909 4096 May 18 13:58 git
drwxr-xr-x 17 castor909 castor909 4096 May 18 15:04 gitea
drwx----- 2 root     root      4096 May 17 21:43 ssh
castor909@mus:~/gitea$ ls -la /home/castor909/gitea/gitea | head -n 40
total 20
drwxr-xr-x  5 root    root      4096 May 17 21:43 .
drwxrwxr-x  3 castor909 castor909 4096 May 18 15:30 ..
drwxr-xr-x  5 castor909 castor909 4096 May 18 13:58 git
drwxr-xr-x 17 castor909 castor909 4096 May 18 15:04 gitea
drwx----- 2 root     root      4096 May 17 21:43 ssh
castor909@mus:~/gitea$ du -sh /home/castor909/gitea/gitea
du: cannot read directory '/home/castor909/gitea/gitea/ssh': Permission denied
2.7M    /home/castor909/gitea/gitea
castor909@mus:~/gitea$ sudo du -sh /home/castor909/gitea/gitea
2.7M    /home/castor909/gitea/gitea
castor909@mus:~/gitea$ _
```

Datos persistentes (bind-mount)

Tabla resumen final

Usuario	Rol	Repositorio	Visibilidad	URL del servicio	Puertos
Castor909	Administrador	—	—	http://192.168.1.178:3000	3000 web · 2222 SSH Git
student_one	Usuario normal	practica-gitea	Privado	http://192.168.1.178:3000/student_one/practica-gitea	3000 web · 2222 SSH Git

Puertos: 3000/TCP interfaz web de Gitea; 2222/TCP acceso SSH de Git. **Persistencia:** los datos viven en el host en `~/gitea/gitea` (montado en `/data` del contenedor). Si se borra esa carpeta se pierden usuarios, repositorios y configuración. **Copia de seguridad:** `tar -czf backup-gitea.tar.gz ~/gitea/gitea`.

BONUS — Acceso por SSH con clave pública

Nota: este apartado se ha rehecho sobre la misma VM y el mismo Gitea, en la red doméstica actual, por lo que la IP del servidor aparece como 192.168.1.178 (en los apartados anteriores era 172.16.133.21, otra red). El servicio, el repositorio y el usuario son los mismos.

En el primer intento el clonado por SSH fallaba con `Permission denied (publickey)` porque el cliente no presentaba la clave correcta. Se solucionó añadiendo en `~/.ssh/config` un alias que apunta a `git@192.168.1.178:2222` con la clave `id_ed25519_gitea` (la clave pública ya estaba asociada al usuario `student_one`).

Clave y autenticación (puerto 2222, usuario `student_one`):

```
> cat ~/.ssh/config
ssh -T gitea

Host gitea
  HostName 192.168.1.178
  Port 2222
  User git
  IdentityFile ~/.ssh/id_ed25519_gitea
  IdentitiesOnly yes
Hi there, student_one! You've successfully authenticated with the key named CachyOS key, but Gitea does not provide shell access.
If this is unexpected, please log in with password and setup Gitea under another user.
```

Configuración SSH y autenticación correcta

Clonado del repositorio por SSH:

```
> cd ~
rm -rf practica-gitea-ssh
git clone gitea:student_one/practica-gitea.git practica-gitea-ssh
cd practica-gitea-ssh
git remote -v

Cloning into 'practica-gitea-ssh'...
remote: Enumerating objects: 18, done.
remote: Counting objects: 100% (18/18), done.
remote: Compressing objects: 100% (15/15), done.
Receiving objects: 100% (18/18), 2.19 KiB | 2.19 MiB/s, done.
remote: Total 18 (delta 3), reused 0 (delta 0), pack-reused 0 (from 0)
Resolving deltas: 100% (3/3), done.
origin gitea:student_one/practica-gitea.git (fetch)
origin gitea:student_one/practica-gitea.git (push)

~/practica-gitea-ssh main
```

Clonado por SSH

Cambio, commit y push por SSH (sin usuario ni contraseña):

```

> echo "Push de prueba por SSH - $(date)" >> README.md
git add README.md
git commit -m "Test push over SSH (clave ed25519)"
git push

[main 23b11e5] Test push over SSH (clave ed25519)
 1 file changed, 1 insertion(+)
Enumerating objects: 5, done.
Counting objects: 100% (5/5), done.
Delta compression using up to 8 threads
Compressing objects: 100% (3/3), done.
Writing objects: 100% (3/3), 414 bytes | 414.00 KiB/s, done.
Total 3 (delta 1), reused 0 (delta 0), pack-reused 0 (from 0)
remote: . Processing 1 references
remote: Processed 1 references in total
To gitea:student_one/practica-gitea.git
   28fb0e0..23b11e5  main -> main

~/practica-gitea-ssh main

```

Push por SSH

Confirmación en Gitea del commit subido mediante SSH:

The screenshot shows the Gitea web interface for a repository named 'student_one / practica-gitea'. The commit title is 'Test push over SSH (clave ed25519)'. The commit is attributed to 'Stepan Andreev' and was pushed 4 minutes ago. The commit hash is '23b11e5eb7', with a parent hash of '28fb0e0020'. The commit message is 'Push de prueba por SSH - dom 14 jun 2020 21:51:19 CEST'. The file 'README.md' is shown with a diff view, highlighting the new commit at line 18.

Commit por SSH en Gitea