

MARLET: Multi-Agent Retrieval for Learning-State-Aware Educational Tutoring

Anonymous Authors

Abstract—Large language models can generate fluent tutoring responses, but they need grounding that respects both instructional evidence and the learner’s current state. Classical retrieval-augmented generation (RAG) grounds generation through a fixed retrieve-then-read controller: the query is matched against a corpus, and the generator reads the returned passages. That design is often insufficient for tutoring, where the same surface question can require different evidence, scaffolding, or rubric constraints for different learners. We propose MARLET (Multi-Agent Retrieval for Learning-State-Aware Educational Tutoring), which integrates supervisory routing, planning, learner-state diagnosis, rubric analysis, conditional retrieval, tutoring, and bounded critique around a fixed tutor. MARLET builds a tutoring brief from the sample, inferred learning state, and answer criteria, then invokes retrieval only when the route indicates that external evidence is needed. Under matched backbones, corpus, reranker, and response budget on TutorEval and EduBench, MARLET improves fixed-tutor quality metrics while using fewer tokens; on EduBench it also reduces latency and backbone-call count. These results support the central claim: educational grounding should be controlled by pedagogical state and task regime, not by the surface query alone.

I. Introduction

Large language models (LLMs) are increasingly used as educational tutors because they can generate explanations, diagnose errors, and provide feedback [1], [2]. However, an LLM tutor cannot rely only on parametric knowledge. Knowledge-grounded dialogue has long shown the value of external evidence [3]; educational responses similarly need grounding in textbook chapters, course notes, rubrics, worked examples, or learner profiles to avoid fluent but misaligned guidance.

Classical retrieval-augmented generation (RAG) has therefore become the default grounding mechanism [4]. In classical RAG, the query is embedded, the top- k most similar passages are retrieved, and the LLM generates a response conditioned on those passages. Thus, relevance depends heavily on retrieval quality and query representation [5].

Educational tutoring is more complex than factual question answering. A student’s question is often only a partial signal: the appropriate response may depend on level, goals, weak points, recent confusion, dialogue, and likely misconceptions. We call this the learner’s personalized learning state. For example, an ordinary-differential-equation query may require high-school procedural scaffolding or college-level modeling context.

Submitted to the 2026 IEEE International Conference on Systems, Man, and Cybernetics (SMC). Single-blind review.

Therefore, tutoring retrieval must find evidence that is pedagogically appropriate for the learner, not merely topical.

Classical RAG can include explicit learner-state text when supplied, but appending learner state, dialogue, grading criteria, and task constraints forces one query embedding to compress topic, level, misconception, instructional goal, and response constraints. As constraints grow, search intent can blur. The issue is therefore how a tutoring system should organize constraints before retrieval and generation.

Therefore, we introduce MARLET (Multi-Agent Retrieval for Learning-State-Aware Educational Tutoring). Instead of letting the retriever act as the top-level controller, a supervisory router identifies the tutoring regime and decides whether retrieval is needed. A planner scopes search intent, a diagnoser summarizes visible learning state, and a rubric module states answer criteria; these modules run in parallel when possible, then are re-assembled with retrieved evidence into one tutor prompt. The framework integrates selective retrieval, tool-using agents, and tutoring-state modeling into one context-construction mechanism.

The experiments validate the framework rather than present a model leaderboard. We compare with classical retrieve-then-read RAG and Agentic RAG under shared backbone, corpus, reranker, response cap, tutor, and critic. Our validation on TutorEval and EduBench shows that the same tutor scores higher when fed context assembled by MARLET; on EduBench it also reduces latency and backbone calls.

Contributions. (i) We propose MARLET, a learning-state-aware multi-agent retrieval framework with a supervisory router, planner, diagnoser, rubric module, conditional retriever, tutor, and critic. (ii) We formalize the router and retrieval gate as transparent, training-free controls over learner state, rubric constraints, and external evidence. (iii) We validate against classical RAG and Agentic RAG baselines on two educational benchmarks under shared backbone, corpus, reranker, and response budget.

II. Related Work

Classical RAG fixes retrieval as the first controller: the query is matched to passages, and generation conditions on the returned evidence [4]. Selective and corrective RAG methods improve this controller. Self-RAG learns

when to retrieve, generate, and critique; CRAG evaluates retrieved documents and attempts correction when retrieval is unreliable; Adaptive-RAG and TARG vary retrieval behavior by query complexity or retrieval utility [6]–[9]. RAG diagnostics further emphasize separating retrieval, ranking, and generation errors [10]. These methods address whether passages retrieved for a query are necessary, sufficient, or reliable, but they do not infer learner stage before retrieval, separate rubric constraints from topic evidence, or decide whether external passages are the right source of grounding for a tutoring decision.

Agentic RAG and multi-agent LLM systems move beyond a single retrieve-then-read step. ReAct, AutoGen, CAMEL, and MetaGPT show that tool use and role decomposition can improve complex task execution [11]–[14]. MA-RAG uses multiple agents for query disambiguation, evidence extraction, and answer synthesis on ambiguous or multi-hop QA tasks [15]. These systems demonstrate coordination benefits, but their roles are designed for general task execution or ambiguous question answering. They do not define pedagogical regimes, infer visible learner state, or bind the final response to rubric-style answer criteria, so the educational reason for retrieving, skipping retrieval, or prioritizing rubric context remains implicit.

Recent educational work shows that tutoring quality requires more than answer accuracy. AgentTutor builds multi-turn personalized learning with learner assessment and memory [2]; adaptivity studies show that LLM tutors are sensitive to omitted student-context features [16]; and AI-tutor evaluation emphasizes pedagogy, mistake diagnosis, guidance quality, and learner support [1], [17]–[20]. These works define tutoring requirements, but they do not formulate retrieval as learner-state-aware control: when to retrieve, what evidence to retrieve, and how much context to allocate to evidence rather than learner-state and rubric information.

III. Methodology

MARLET turns one educational request into a grounded tutor response. It is a RAG controller rather than a set of independent answer agents: every intermediate output is converted into context for one final LLM tutor prompt. Its design follows three principles: route before retrieval, exchange typed records rather than free-form chat, and retrieve only when the tutoring brief needs external evidence. The flow is: standardize the entry, score routing cues, run active specialists in parallel, merge their outputs with retrieved evidence, serialize one augmented prompt, and run one critic revision if needed.

A. Input Entry and Prompt Budget

For one sample, MARLET first standardizes all visible fields into

$$x = (q, o, c, h, r, v, m). \quad (1)$$

TABLE I
Pseudocode for MARLET.

```
def MARLET(x, B, index, thresholds):
    q, o, c, h, r, v, m = x
    scores = cue_scores(concat(q, c, r, h))
    R, switches = route(scores, r, v, thresholds)
    z0 = Context(x=x, regime=R, budget=B)
    tasks = {planner(z0), diagnoser(z0)}
    if switches.rubric: tasks.add(rubric_agent(z0))
    p, ell, u = run_parallel(tasks)
    P = p.queries[:B.K]; z1 = merge(z0, p, ell, u)
    D = []
    if switches.retrieve:
        D = pack(rerank(dedup(search(index, P)), q), B.Q, B.L)
    y0 = tutor(prompt(q, o, h, p, ell, u, D, c))
    if not D and scores.evidence >= thresholds.fallback:
        D = pack(rerank(search(index, [q]), q), B.Q, B.L)
    y0 = tutor(prompt(q, o, h, p, ell, u, D, c))
    y = critic(y0, z1, D) if switches.critic else y0
    return y, {route=R, evidence=D, citations=ids(D)}
```

Here, q is the student question or task prompt; o is an optional answer-option list; c is optional inline context such as a chapter excerpt; h is recent dialogue; r is an optional rubric or answer-criteria list; v is an optional image list; and m stores metadata used for logging or formatting. Empty fields are allowed, so the same representation covers factual questions, grading requests, feedback requests, and planning requests.

The only student-facing output is the final tutor answer y . MARLET also stores internal records: a route record, which names the selected tutoring mode and which modules run; an evidence bundle D , which contains packed retrieved chunks; citation identifiers, which link chunks in D to their sources; and a cost log for token, latency, and call counts. These records are not answers. Planner output, learner-state summary, rubric summary, and D are assembled as prompt blocks before the LLM tutor generates y . The shared budget is

$$B = (K, Q, L, N),$$

where K is the maximum number of planner retrieval queries, Q is the maximum number of evidence chunks/tool calls, L is the character budget for packed evidence, and N is the response-token cap.

B. Supervisor Routing

The supervisor begins with a routing blob:

$$b(x) = \text{concat}(q, c, r, h), \quad (2)$$

where $\text{concat}(\cdot)$ means that the question, inline context, rubric text, and dialogue turns are joined into one normalized string. Images remain available to the tutor, but they are not converted into the textual routing score.

The router uses five cue families $j \in \{\text{ev}, \text{co}, \text{ru}, \text{pl}, \text{tu}\}$ for evidence, coordination, rubric, planning, and tutoring. Each family controls a different downstream decision: evidence cues open retrieval, coordination cues indicate that several constraints must be merged, rubric cues activate criterion checking, planning cues route to lesson sequencing, and tutoring cues activate learner-state adaptation. Each family has a keyword set W_j . Evidence cues include source, document, chapter, and verification; rubric cues include score, criteria, and comment;




Fig. 1. Main framework of MARLET. The router scores the entry, activates specialist modules, and decides whether retrieval is needed; specialist outputs and retrieved evidence are then assembled into one augmented tutor prompt.

Here o_{tok} is token overlap with q , o_{title} is title-token overlap, m_{phr} is an exact phrase-match flag, o_{num} is numeric overlap, b_{len} rewards moderate chunk length, and the α terms are fixed reranker weights. The learner summary ℓ affects retrieval through the route and planner queries, not these weights.

Evidence packing follows the relevance-diversity trade-off used in MMR-style selection [21]: the context should be useful, but repeated chunks should not consume the limited evidence budget. For each candidate chunk d , MARLET computes

$$\text{pack}(d) = \lambda \text{rank}(q, d) - (1 - \lambda) \text{repeat}(d). \quad (12)$$

Here $\text{repeat}(d)$ is the largest sentence overlap between d and selected chunks, and λ controls the relevance-diversity balance. The packer adds the remaining chunk with the highest $\text{pack}(d)$ score until Q chunks or the L character limit is reached, forming evidence bundle D .

E. Tutor Generation and Critic Revision

The final tutor context is

$$z_2 = (z_1, D). \quad (13)$$

This is where retrieval and agent outputs converge: z_1 supplies route, plan, learner-state, and rubric fields, while D supplies compact cited evidence. The retriever does not answer; its chunks become an evidence block. The final prompt contains task fields, pedagogical brief, evidence or inline context, and output requirements. The

tutor is the LLM-driven answer writer:

$$y_0 = A_{\text{tutor}}(z_2). \quad (14)$$

Its prompt contains q , optional answer options o , recent dialogue h , learner state ℓ , plan p , rubric summary u , and either retrieved evidence D or inline context c . The tutor is instructed to be correct, pedagogically useful, concise but not terse, include a next step when appropriate, and cite retrieved evidence with document markers.

The critic performs one bounded revision pass:

$$y = \begin{cases} A_{\text{crit}}(y_0, z_2), & I(y_0, z_2) > 0, \\ y_0, & I(y_0, z_2) = 0. \end{cases} \quad (15)$$

Here $I(y_0, z_2)$ is the number of issues found by the critic. Issues include missing citation markers when D is nonempty, uncovered rubric items from r , and answers that are too long for a beginner-facing state. If no issue is found, y_0 is returned unchanged; otherwise the critic rewrites once and the revised y becomes the final answer.

IV. Validation Experiments

We validate the framework on two public educational benchmarks. TutorEval [1] contains 834 expert-written science tutoring questions paired with long STEM chapters and teaching key points, so responses must explain, disambiguate, and stay chapter-grounded. EduBench [18] covers nine educational scenarios, including question answering, error correction, personalized support, emotional support, grading, teaching-material generation, and personalized content creation. Its rows

