

2026 Spray Booth Catalogue

Professional solutions for automotive refinishing and curing

ELECTRIC

NATURAL GAS

DIESEL

GBT-SB6900 SERIES

Electric · Natural Gas · Diesel | ECO · PLUS · PRO

3 heating systems | 3 specification levels

20 technical items for every model



PRODUCT IMAGE FOR SERIES PRESENTATION

Shanghai Gubot Automobile Technology Co., Ltd.

contact@gubotspraybooth.com · +86 133 8603 9948 · www.gubotspraybooth.com

SELECT BY PROJECT CONDITIONS

Choose the heating system first, then the specification level

Three heating systems and nine standard models, designed for applications from everyday refinishing to high-throughput professional workshops.

E

Electric Heating

For workshops with stable electrical capacity and no requirement for on-site fuel handling.

NG

Natural Gas Heating

For professional facilities with a suitable natural-gas supply and regular curing demand.

D

Diesel Heating

For projects without stable piped gas where compliant fuel supply and storage are available.

Compare ECO, PLUS and PRO

	ECO · Standard	PLUS · Enhanced	PRO · Professional
Best fit	A practical core specification for everyday refinishing work.	Upgraded structure, airflow and lighting for balanced productivity and durability.	A higher specification for frequent operation and professional workshops.
Booth body	50 mm EPS sandwich wall panels with 0.426 mm color-coated steel sheets on both sides; 0.7 mm galvanized roof panel, 0.8 mm top channel and 1.2 mm bottom channel. EPS core density is confirmed in the final technical agreement.	50 mm fire-resistant rock-wool composite wall panels with 0.426 mm color-coated steel sheets on both sides and 100 kg/m³ rock-wool density; 0.7 mm galvanized roof panel, 0.8 mm top channel and 1.2 mm bottom channel.	50 mm fire-resistant rock-wool composite wall panels with 0.5 mm color-coated steel sheets on both sides and 100 kg/m³ rock-wool density; 0.7 mm galvanized roof panel, 0.8 mm top channel and 1.2 mm bottom channel.
Base platform	Three rows of 2.3 mm checker plate and two rows of 3 × 30 steel grating, supported by bent galvanized-sheet brackets.	Three rows of 2.3 mm checker plate and two rows of 4 × 30 steel grating, supported by bent galvanized-sheet brackets.	Three rows of 2.3 mm checker plate and two rows of 5 × 30 steel grating, supported by No. 12 channel steel.
Ventilation	Aluminum-wound motors	Copper-wound motors	Copper-wound motors
Front door	Three-leaf main door with aluminum-alloy edging.	Three-leaf sheet-metal main door.	Four-leaf aluminum-alloy glazed main door.

MODEL CODE SYSTEM

GBT-SB6900-[E / NG / D]-[ECO / PLUS / PRO]

Custom dimensions and interfaces are available by project.

ELECTRIC HEATING | ECO · Standard

GBT-SB6900-E-ECO

01 / 09

Electric Heating Automotive Spray / Baking Booth



Product image for series presentation

WHY CHOOSE THIS MODEL

Electric Heating

For workshops with stable electrical capacity and no requirement for on-site fuel handling.

ECO · Standard

A practical core specification for everyday refinishing work.

ELECTRIC

Detailed technical configuration

20 complete technical items

Product	Electric Heating Automotive Spray / Baking Booth
Model	GBT-SB6900-E-ECO
Configuration level	Entry-level / ECO Standard
Internal size	6900 × 3900 × 2600 mm (L × W × H)
External size	7000 × 5100 × 3250 mm (L × W × H), single-side air box
Booth body	50 mm EPS sandwich wall panels with 0.426 mm color-coated steel sheets on both sides; 0.7 mm galvanized roof panel, 0.8 mm top channel and 1.2 mm bottom channel. EPS core density is confirmed in the final technical agreement.
Base platform	Three rows of 2.3 mm checker plate and two rows of 3 × 30 steel grating, supported by bent galvanized-sheet brackets.
Front door	Three-leaf main door with aluminum-alloy edging.
Service door	One side-mounted service door, 700 × 1800 mm (W × H), with aluminum-alloy edging, pressure lock and tempered-glass viewing window.
Plenum chamber	Welded reinforcing-rib and square-tube structure. The booth roof doubles as the plenum roof; filter supports and connectors are made from 0.6 mm bent galvanized sheet for convenient filter replacement.
Air supply system	Two YDW 3 kW supply fans with aluminum-wound motors, Tianyi or equivalent.

Exhaust system	One YDW 5.5 kW exhaust fan with aluminum-wound motor, Hengkang or equivalent.
Air box	40 × 40 mm powder-coated square-tube frame clad with 0.6 mm color-coated steel sheet.
Exhaust duct	Standard configuration includes two straight duct sections and one elbow.
Heating system	Eight infrared heating sets, 3 kW each, total heating power 24 kW.
Lighting system	Ceiling lighting: 8 sets × 4 tubes = 32 pcs 24 W LED tubes. No waist lights are fitted with the electric-heating layout. Light-box frames use 0.6 mm powder-coated galvanized sheet.
Filter system	Inlet pre-filter captures particles above 10 μm. SF-600G adhesive ceiling filter captures particles above 4 μm with at least 99% efficiency. Medium-efficiency fiberglass floor filter.
Electric control	CHINT or equivalent electrical components in an external rotary control box. The main circuit includes leakage, phase-loss, short-circuit, timing and overload protection.
Power requirement	380/220 V, 3 phase 4 wire, 50 Hz. Infrared heating load is 24 kW; final total connected load is confirmed by the project electrical drawing.
Project confirmation	Voltage, fuel connection, exhaust routing and local safety requirements must be confirmed in the mutually approved technical agreement before production.

ELECTRIC HEATING | PLUS · Enhanced

GBT-SB6900-E-PLUS

02 / 09

Electric Heating Automotive Spray / Baking Booth



Product image for series presentation

WHY CHOOSE THIS MODEL

Electric Heating

For workshops with stable electrical capacity and no requirement for on-site fuel handling.

PLUS · Enhanced

Upgraded structure, airflow and lighting for balanced productivity and durability.

ELECTRIC

Detailed technical configuration

20 complete technical items

Product	Electric Heating Automotive Spray / Baking Booth
Model	GBT-SB6900-E-PLUS
Configuration level	Mid-range / PLUS Enhanced
Internal size	6900 × 3900 × 2600 mm (L × W × H)
External size	7000 × 5100 × 3250 mm (L × W × H), single-side air box
Booth body	50 mm fire-resistant rock-wool composite wall panels with 0.426 mm color-coated steel sheets on both sides and 100 kg/m ³ rock-wool density; 0.7 mm galvanized roof panel, 0.8 mm top channel and 1.2 mm bottom channel.
Base platform	Three rows of 2.3 mm checker plate and two rows of 4 × 30 steel grating, supported by bent galvanized-sheet brackets.
Front door	Three-leaf sheet-metal main door.
Service door	One side-mounted service door, 700 × 1800 mm (W × H), with aluminum-alloy edging, pressure lock and tempered-glass viewing window.
Plenum chamber	Welded reinforcing-rib and square-tube structure. The booth roof doubles as the plenum roof; filter supports and connectors are made from 0.6 mm bent galvanized sheet for convenient filter replacement.
Air supply system	Two YDW 3 kW supply fans with copper-wound motors, Tianyi or equivalent.

Exhaust system	One YDW 5.5 kW exhaust fan with copper-wound motor, Henggang or equivalent.
Air box	40 × 40 mm powder-coated square-tube frame clad with 0.6 mm color-coated steel sheet.
Exhaust duct	Standard configuration includes two straight duct sections and one elbow.
Heating system	Eight upgraded luxury infrared heating sets, 3 kW each, total heating power 24 kW.
Lighting system	Ceiling lighting: 8 sets × 4 tubes = 32 pcs 24 W LED tubes. No waist lights are fitted with the electric-heating layout. Light-box frames use 0.6 mm powder-coated galvanized sheet.
Filter system	Inlet pre-filter captures particles above 10 μm. SF-700G adhesive ceiling filter captures particles above 4 μm with at least 99% efficiency. Medium-efficiency fiberglass floor filter.
Electric control	CHINT or equivalent electrical components in an external rotary control box. The main circuit includes leakage, phase-loss, short-circuit, timing and overload protection.
Power requirement	380/220 V, 3 phase 4 wire, 50 Hz. Infrared heating load is 24 kW; final total connected load is confirmed by the project electrical drawing.
Project confirmation	Voltage, fuel connection, exhaust routing and local safety requirements must be confirmed in the mutually approved technical agreement before production.

ELECTRIC HEATING | PRO · Professional

GBT-SB6900-E-PRO

03 / 09

Electric Heating Automotive Spray / Baking Booth



Product image for series presentation

WHY CHOOSE THIS MODEL

Electric Heating

For workshops with stable electrical capacity and no requirement for on-site fuel handling.

PRO · Professional

A higher specification for frequent operation and professional workshops.

ELECTRIC

Detailed technical configuration

20 complete technical items

Product	Electric Heating Automotive Spray / Baking Booth
Model	GBT-SB6900-E-PRO
Configuration level	High-end / PRO Professional
Internal size	6900 × 3900 × 2600 mm (L × W × H)
External size	7000 × 5100 × 3250 mm (L × W × H), single-side air box
Booth body	50 mm fire-resistant rock-wool composite wall panels with 0.5 mm color-coated steel sheets on both sides and 100 kg/m ³ rock-wool density; 0.7 mm galvanized roof panel, 0.8 mm top channel and 1.2 mm bottom channel.
Base platform	Three rows of 2.3 mm checker plate and two rows of 5 × 30 steel grating, supported by No. 12 channel steel.
Front door	Four-leaf aluminum-alloy glazed main door.
Service door	One side-mounted service door, 700 × 1800 mm (W × H), with aluminum-alloy edging, pressure lock and tempered-glass viewing window.
Plenum chamber	Welded reinforcing-rib and square-tube structure. The booth roof doubles as the plenum roof; filter supports and connectors are made from 0.6 mm bent galvanized sheet for convenient filter replacement.
Air supply system	Two YDW 3 kW supply fans with copper-wound motors.

Exhaust system	One YDW 5.5 kW exhaust fan with copper-wound motor.
Air box	40 × 40 mm powder-coated square-tube frame clad with 0.6 mm color-coated steel sheet.
Exhaust duct	Standard configuration includes two straight duct sections and one elbow.
Heating system	Eight upgraded luxury infrared heating sets, 3 kW each, total heating power 24 kW.
Lighting system	Ceiling lighting: 8 sets × 4 tubes = 32 pcs 24 W LED tubes. No waist lights are fitted with the electric-heating layout. Light-box frames use 0.6 mm powder-coated galvanized sheet.
Filter system	Inlet pre-filter captures particles above 10 μm. SF-700G adhesive ceiling filter captures particles above 4 μm with at least 99% efficiency. Medium-efficiency fiberglass floor filter.
Electric control	CHINT or equivalent electrical components in an external rotary control box. The main circuit includes leakage, phase-loss, short-circuit, timing and overload protection.
Power requirement	380/220 V, 3 phase 4 wire, 50 Hz. Infrared heating load is 24 kW; final total connected load is confirmed by the project electrical drawing.
Project confirmation	Voltage, fuel connection, exhaust routing and local safety requirements must be confirmed in the mutually approved technical agreement before production.

NATURAL GAS HEATING | ECO · Standard

GBT-SB6900-NG-ECO

04 / 09

Natural Gas Heating Automotive Spray / Baking Booth



Product image for series presentation

WHY CHOOSE THIS MODEL

Natural Gas Heating

For professional facilities with a suitable natural-gas supply and regular curing demand.

ECO · Standard

A practical core specification for everyday refinishing work.

NATURAL GAS

Detailed technical configuration

20 complete technical items

Product	Natural Gas Heating Automotive Spray / Baking Booth
Model	GBT-SB6900-NG-ECO
Configuration level	Entry-level / ECO Standard
Internal size	6900 × 3900 × 2600 mm (L × W × H)
External size	7000 × 5100 × 3250 mm (L × W × H), single-side air box
Booth body	50 mm EPS sandwich wall panels with 0.426 mm color-coated steel sheets on both sides; 0.7 mm galvanized roof panel, 0.8 mm top channel and 1.2 mm bottom channel. EPS core density is confirmed in the final technical agreement.
Base platform	Three rows of 2.3 mm checker plate and two rows of 3 × 30 steel grating, supported by bent galvanized-sheet brackets.
Front door	Three-leaf main door with aluminum-alloy edging.
Service door	One side-mounted service door, 700 × 1800 mm (W × H), with aluminum-alloy edging, pressure lock and tempered-glass viewing window.
Plenum chamber	Welded reinforcing-rib and square-tube structure. The booth roof doubles as the plenum roof; filter supports and connectors are made from 0.6 mm bent galvanized sheet for convenient filter replacement.
Air supply system	Two YDW 3 kW supply fans with aluminum-wound motors, Tianyi or equivalent.

Exhaust system	One YDW 5.5 kW exhaust fan with aluminum-wound motor, Hengkang or equivalent.
Air box	40 × 40 mm powder-coated square-tube frame clad with 0.6 mm color-coated steel sheet.
Exhaust duct	Standard configuration includes two straight duct sections and one elbow.
Heating system	Imported Italian Riello FS10 natural-gas burner.
Lighting system	Ceiling lighting: 8 sets × 4 tubes = 32 pcs 24 W LED tubes. Waist lighting: 16 sets × 2 tubes = 32 pcs 24 W LED tubes. Light-box frames use 0.6 mm powder-coated galvanized sheet.
Filter system	Inlet pre-filter captures particles above 10 μm. SF-600G adhesive ceiling filter captures particles above 4 μm with at least 99% efficiency. Medium-efficiency fiberglass floor filter.
Electric control	CHINT or equivalent electrical components in an external rotary control box. The main circuit includes leakage, phase-loss, short-circuit, timing and overload protection.
Power requirement	380/220 V, 3 phase 4 wire, 50 Hz. Reference electrical load is approx. 12 kW, excluding burner thermal output; final connected load is confirmed by the project electrical drawing.
Project confirmation	Voltage, fuel connection, exhaust routing and local safety requirements must be confirmed in the mutually approved technical agreement before production.

NATURAL GAS HEATING | PLUS · Enhanced

GBT-SB6900-NG-PLUS

05 / 09

Natural Gas Heating Automotive Spray / Baking Booth



Product image for series presentation

WHY CHOOSE THIS MODEL

Natural Gas Heating

For professional facilities with a suitable natural-gas supply and regular curing demand.

PLUS · Enhanced

Upgraded structure, airflow and lighting for balanced productivity and durability.

NATURAL GAS

Detailed technical configuration

20 complete technical items

Product	Natural Gas Heating Automotive Spray / Baking Booth
Model	GBT-SB6900-NG-PLUS
Configuration level	Mid-range / PLUS Enhanced
Internal size	6900 × 3900 × 2600 mm (L × W × H)
External size	7000 × 5100 × 3250 mm (L × W × H), single-side air box
Booth body	50 mm fire-resistant rock-wool composite wall panels with 0.426 mm color-coated steel sheets on both sides and 100 kg/m ³ rock-wool density; 0.7 mm galvanized roof panel, 0.8 mm top channel and 1.2 mm bottom channel.
Base platform	Three rows of 2.3 mm checker plate and two rows of 4 × 30 steel grating, supported by bent galvanized-sheet brackets.
Front door	Three-leaf sheet-metal main door.
Service door	One side-mounted service door, 700 × 1800 mm (W × H), with aluminum-alloy edging, pressure lock and tempered-glass viewing window.
Plenum chamber	Welded reinforcing-rib and square-tube structure. The booth roof doubles as the plenum roof; filter supports and connectors are made from 0.6 mm bent galvanized sheet for convenient filter replacement.
Air supply system	Two YDW 3 kW supply fans with copper-wound motors, Tianyi or equivalent.

Exhaust system	One YDW 5.5 kW exhaust fan with copper-wound motor, Hengkang or equivalent.
Air box	40 × 40 mm powder-coated square-tube frame clad with 0.6 mm color-coated steel sheet.
Exhaust duct	Standard configuration includes two straight duct sections and one elbow.
Heating system	Imported Italian Riello FS10 natural-gas burner.
Lighting system	Ceiling lighting: 8 sets × 4 tubes = 32 pcs 24 W LED tubes. Waist lighting: 16 sets × 2 tubes = 32 pcs 24 W LED tubes. Light-box frames use 0.6 mm powder-coated galvanized sheet.
Filter system	Inlet pre-filter captures particles above 10 μm. SF-700G adhesive ceiling filter captures particles above 4 μm with at least 99% efficiency. Medium-efficiency fiberglass floor filter.
Electric control	CHINT or equivalent electrical components in an external rotary control box. The main circuit includes leakage, phase-loss, short-circuit, timing and overload protection.
Power requirement	380/220 V, 3 phase 4 wire, 50 Hz. Reference electrical load is approx. 12 kW, excluding burner thermal output; final connected load is confirmed by the project electrical drawing.
Project confirmation	Voltage, fuel connection, exhaust routing and local safety requirements must be confirmed in the mutually approved technical agreement before production.

NATURAL GAS HEATING | PRO · Professional

GBT-SB6900-NG-PRO

06 / 09

Natural Gas Heating Automotive Spray / Baking Booth



Product image for series presentation

WHY CHOOSE THIS MODEL

Natural Gas Heating

For professional facilities with a suitable natural-gas supply and regular curing demand.

PRO · Professional

A higher specification for frequent operation and professional workshops.

NATURAL GAS

Detailed technical configuration

20 complete technical items

Product	Natural Gas Heating Automotive Spray / Baking Booth
Model	GBT-SB6900-NG-PRO
Configuration level	High-end / PRO Professional
Internal size	6900 × 3900 × 2600 mm (L × W × H)
External size	7000 × 5100 × 3250 mm (L × W × H), single-side air box
Booth body	50 mm fire-resistant rock-wool composite wall panels with 0.5 mm color-coated steel sheets on both sides and 100 kg/m ³ rock-wool density; 0.7 mm galvanized roof panel, 0.8 mm top channel and 1.2 mm bottom channel.
Base platform	Three rows of 2.3 mm checker plate and two rows of 5 × 30 steel grating, supported by No. 12 channel steel.
Front door	Four-leaf aluminum-alloy glazed main door.
Service door	One side-mounted service door, 700 × 1800 mm (W × H), with aluminum-alloy edging, pressure lock and tempered-glass viewing window.
Plenum chamber	Welded reinforcing-rib and square-tube structure. The booth roof doubles as the plenum roof; filter supports and connectors are made from 0.6 mm bent galvanized sheet for convenient filter replacement.
Air supply system	Two YDW 3 kW supply fans with copper-wound motors.

Exhaust system	One YDW 5.5 kW exhaust fan with copper-wound motor.
Air box	40 × 40 mm powder-coated square-tube frame clad with 0.6 mm color-coated steel sheet.
Exhaust duct	Standard configuration includes two straight duct sections and one elbow.
Heating system	Imported Italian Riello FS20 natural-gas burner.
Lighting system	Ceiling lighting: 8 sets × 4 tubes = 32 pcs 24 W LED tubes. Waist lighting: 16 sets × 2 tubes = 32 pcs 24 W LED tubes. Light-box frames use 0.6 mm powder-coated galvanized sheet.
Filter system	Inlet pre-filter captures particles above 10 μm. SF-700G adhesive ceiling filter captures particles above 4 μm with at least 99% efficiency. Medium-efficiency fiberglass floor filter.
Electric control	CHINT or equivalent electrical components in an external rotary control box. The main circuit includes leakage, phase-loss, short-circuit, timing and overload protection.
Power requirement	380/220 V, 3 phase 4 wire, 50 Hz. Reference electrical load is approx. 12 kW, excluding burner thermal output; final connected load is confirmed by the project electrical drawing.
Project confirmation	Voltage, fuel connection, exhaust routing and local safety requirements must be confirmed in the mutually approved technical agreement before production.

DIESEL HEATING | ECO · Standard

GBT-SB6900-D-ECO

07 / 09

Diesel Heating Automotive Spray / Baking Booth



Product image for series presentation

WHY CHOOSE THIS MODEL

Diesel Heating

For projects without stable piped gas where compliant fuel supply and storage are available.

ECO · Standard

A practical core specification for everyday refinishing work.

DIESEL

Detailed technical configuration

20 complete technical items

Product	Diesel Heating Automotive Spray / Baking Booth
Model	GBT-SB6900-D-ECO
Configuration level	Entry-level / ECO Standard
Internal size	6900 × 3900 × 2600 mm (L × W × H)
External size	7000 × 5100 × 3250 mm (L × W × H), single-side air box
Booth body	50 mm EPS sandwich wall panels with 0.426 mm color-coated steel sheets on both sides; 0.7 mm galvanized roof panel, 0.8 mm top channel and 1.2 mm bottom channel. EPS core density is confirmed in the final technical agreement.
Base platform	Three rows of 2.3 mm checker plate and two rows of 3 × 30 steel grating, supported by bent galvanized-sheet brackets.
Front door	Three-leaf main door with aluminum-alloy edging.
Service door	One side-mounted service door, 700 × 1800 mm (W × H), with aluminum-alloy edging, pressure lock and tempered-glass viewing window.
Plenum chamber	Welded reinforcing-rib and square-tube structure. The booth roof doubles as the plenum roof; filter supports and connectors are made from 0.6 mm bent galvanized sheet for convenient filter replacement.
Air supply system	Two YDW 3 kW supply fans with aluminum-wound motors, Tianyi or equivalent.

Exhaust system	One YDW 5.5 kW exhaust fan with aluminum-wound motor, Henggang or equivalent.
Air box	40 × 40 mm powder-coated square-tube frame clad with 0.6 mm color-coated steel sheet.
Exhaust duct	Standard configuration includes two straight duct sections and one elbow.
Heating system	Imported Italian Riello G10 diesel burner with 1.5 mm 201 stainless-steel heat exchanger.
Lighting system	Ceiling lighting: 8 sets × 4 tubes = 32 pcs 24 W LED tubes. Waist lighting: 16 sets × 2 tubes = 32 pcs 24 W LED tubes. Light-box frames use 0.6 mm powder-coated galvanized sheet.
Filter system	Inlet pre-filter captures particles above 10 μm. SF-600G adhesive ceiling filter captures particles above 4 μm with at least 99% efficiency. Medium-efficiency fiberglass floor filter.
Electric control	CHINT or equivalent electrical components in an external rotary control box. The main circuit includes leakage, phase-loss, short-circuit, timing and overload protection.
Power requirement	380/220 V, 3 phase 4 wire, 50 Hz. Reference electrical load is approx. 12 kW, excluding burner thermal output; final connected load is confirmed by the project electrical drawing.
Project confirmation	Voltage, fuel connection, exhaust routing and local safety requirements must be confirmed in the mutually approved technical agreement before production.

DIESEL HEATING | PLUS · Enhanced

GBT-SB6900-D-PLUS

08 / 09

Diesel Heating Automotive Spray / Baking Booth



Product image for series presentation

WHY CHOOSE THIS MODEL

Diesel Heating

For projects without stable piped gas where compliant fuel supply and storage are available.

PLUS · Enhanced

Upgraded structure, airflow and lighting for balanced productivity and durability.

DIESEL

Detailed technical configuration

20 complete technical items

Product	Diesel Heating Automotive Spray / Baking Booth
Model	GBT-SB6900-D-PLUS
Configuration level	Mid-range / PLUS Enhanced
Internal size	6900 × 3900 × 2600 mm (L × W × H)
External size	7000 × 5100 × 3250 mm (L × W × H), single-side air box
Booth body	50 mm fire-resistant rock-wool composite wall panels with 0.426 mm color-coated steel sheets on both sides and 100 kg/m ³ rock-wool density; 0.7 mm galvanized roof panel, 0.8 mm top channel and 1.2 mm bottom channel.
Base platform	Three rows of 2.3 mm checker plate and two rows of 4 × 30 steel grating, supported by bent galvanized-sheet brackets.
Front door	Three-leaf sheet-metal main door.
Service door	One side-mounted service door, 700 × 1800 mm (W × H), with aluminum-alloy edging, pressure lock and tempered-glass viewing window.
Plenum chamber	Welded reinforcing-rib and square-tube structure. The booth roof doubles as the plenum roof; filter supports and connectors are made from 0.6 mm bent galvanized sheet for convenient filter replacement.
Air supply system	Two YDW 3 kW supply fans with copper-wound motors, Tianyi or equivalent.

Exhaust system	One YDW 5.5 kW exhaust fan with copper-wound motor, Henggang or equivalent.
Air box	40 × 40 mm powder-coated square-tube frame clad with 0.6 mm color-coated steel sheet.
Exhaust duct	Standard configuration includes two straight duct sections and one elbow.
Heating system	Imported Italian Riello G10 diesel burner with 2.0 mm 201 stainless-steel heat exchanger.
Lighting system	Ceiling lighting: 8 sets × 4 tubes = 32 pcs 24 W LED tubes. Waist lighting: 16 sets × 2 tubes = 32 pcs 24 W LED tubes. Light-box frames use 0.6 mm powder-coated galvanized sheet.
Filter system	Inlet pre-filter captures particles above 10 μm. SF-700G adhesive ceiling filter captures particles above 4 μm with at least 99% efficiency. Medium-efficiency fiberglass floor filter.
Electric control	CHINT or equivalent electrical components in an external rotary control box. The main circuit includes leakage, phase-loss, short-circuit, timing and overload protection.
Power requirement	380/220 V, 3 phase 4 wire, 50 Hz. Reference electrical load is approx. 12 kW, excluding burner thermal output; final connected load is confirmed by the project electrical drawing.
Project confirmation	Voltage, fuel connection, exhaust routing and local safety requirements must be confirmed in the mutually approved technical agreement before production.

DIESEL HEATING | PRO · Professional

GBT-SB6900-D-PRO

09 / 09

Diesel Heating Automotive Spray / Baking Booth



Product image for series presentation

WHY CHOOSE THIS MODEL

Diesel Heating

For projects without stable piped gas where compliant fuel supply and storage are available.

PRO · Professional

A higher specification for frequent operation and professional workshops.

DIESEL

Detailed technical configuration

20 complete technical items

Product	Diesel Heating Automotive Spray / Baking Booth
Model	GBT-SB6900-D-PRO
Configuration level	High-end / PRO Professional
Internal size	6900 × 3900 × 2600 mm (L × W × H)
External size	7000 × 5100 × 3250 mm (L × W × H), single-side air box
Booth body	50 mm fire-resistant rock-wool composite wall panels with 0.5 mm color-coated steel sheets on both sides and 100 kg/m ³ rock-wool density; 0.7 mm galvanized roof panel, 0.8 mm top channel and 1.2 mm bottom channel.
Base platform	Three rows of 2.3 mm checker plate and two rows of 5 × 30 steel grating, supported by No. 12 channel steel.
Front door	Four-leaf aluminum-alloy glazed main door.
Service door	One side-mounted service door, 700 × 1800 mm (W × H), with aluminum-alloy edging, pressure lock and tempered-glass viewing window.
Plenum chamber	Welded reinforcing-rib and square-tube structure. The booth roof doubles as the plenum roof; filter supports and connectors are made from 0.6 mm bent galvanized sheet for convenient filter replacement.
Air supply system	Two YDW 3 kW supply fans with copper-wound motors.

Exhaust system	One YDW 5.5 kW exhaust fan with copper-wound motor.
Air box	40 × 40 mm powder-coated square-tube frame clad with 0.6 mm color-coated steel sheet.
Exhaust duct	Standard configuration includes two straight duct sections and one elbow.
Heating system	Imported Italian Riello G10 diesel burner with 2.0 mm 201 stainless-steel heat exchanger.
Lighting system	Ceiling lighting: 8 sets × 4 tubes = 32 pcs 24 W LED tubes. Waist lighting: 16 sets × 2 tubes = 32 pcs 24 W LED tubes. Light-box frames use 0.6 mm powder-coated galvanized sheet.
Filter system	Inlet pre-filter captures particles above 10 μm. SF-700G adhesive ceiling filter captures particles above 4 μm with at least 99% efficiency. Medium-efficiency fiberglass floor filter.
Electric control	CHINT or equivalent electrical components in an external rotary control box. The main circuit includes leakage, phase-loss, short-circuit, timing and overload protection.
Power requirement	380/220 V, 3 phase 4 wire, 50 Hz. Reference electrical load is approx. 12 kW, excluding burner thermal output; final connected load is confirmed by the project electrical drawing.
Project confirmation	Voltage, fuel connection, exhaust routing and local safety requirements must be confirmed in the mutually approved technical agreement before production.

PROJECT INFORMATION

Choose the right spray booth for your workshop

Send us the installation country and city, vehicle type, preferred heating system, available power supply and site dimensions. Our team will recommend a suitable configuration.

01

Installation site

Country, city, workshop length, width, height and available installation space.

02

Target vehicles

Passenger cars, SUVs, vans or other vehicle types, plus required door clearance.

03

Power and fuel

Voltage, phase, frequency, available electrical capacity and preferred heating source.

04

Exhaust route

Outdoor discharge point, duct direction and any local environmental requirements.

05

Daily workflow

Expected daily paint volume, curing frequency and preferred operating schedule.

06

Delivery scope

Destination, installation support requirements and requested optional equipment.

Contact GUBOT

Shanghai Gubot Automobile Technology Co., Ltd.

WhatsApp / Tel +86 133 8603 9948

Email contact@gubotspraybooth.com

Website www.gubotspraybooth.com

Address Changlin Road, Minhang District, Shanghai, China



WHATSAPP



WECHAT

This catalog is a product-selection reference and is not a binding quotation.

Final dimensions, voltage, fuel connections, optional equipment and delivery scope are confirmed in the signed technical agreement.