Computational Experiments for AGT-1: Resonance Windows, Emulator Milestones, and Prototype Protocols

Technology Program Draft

Draft skeleton

Abstract

This manuscript is the canonical computational-paper skeleton for the antigravity technology program. It anchors the clean numerical narrative to the legacy AGT toy-model line, the P3 digital emulator releases, and the hardware-facing protocol packages, while maintaining explicit scope and non-claim boundaries.

Contents

1 Scope and Computational Status **2**

2 Canonical Package Lineage **2**

3 Toy-Model Numerical Core **2**
3.1 Model inputs 2
3.2 Primary observables 2

4 Strip and Bubble Campaigns **2**
4.1 Strip resonance results 2
4.2 Bubble capture-proxy results 2

5 P3 Digital Emulator Line **2**
5.1 Run modes and configs 2
5.2 Acceptance and milestone ledger 3

6 Protocol Bridge to Physical Devices **3**
6.1 Observability and control map 3
6.2 Experimental protocol pathway 3

7 Reproducibility Contract **3**

8 Limitations and Non-Claims **3**

9 Forward Dependencies **3**

1 Scope and Computational Status

The AGT computational line provides toy-model evidence and engineering scaffolding only. It does not close the target theorem chain by itself. The purpose of this paper is to normalize the numerical observables, package lineage, and protocol bridge required for later reproducible code import and experimental handoff.

2 Canonical Package Lineage

This chapter will list the cleaned resonance reports, the live `agt_v11c` source tree, the P3 architecture and specification packages, the MVP release line, and the hardware-facing planning packages.

3 Toy-Model Numerical Core

This chapter will describe the 1D open-chain scattering reduction built on the local spectral-mass landscape.

3.1 Model inputs

Placeholder for backgrounds, spectral observables, interface-loss parameters, and scan grids.

3.2 Primary observables

Placeholder for dwell peaks, transmission, reflection, and absorption/capture proxies.

4 Strip and Bubble Campaigns

This chapter will normalize the strip and bubble experiment families and interpret their outputs in the same notation used by the theory paper.

4.1 Strip resonance results

Placeholder for the strip campaign summary and peak-extraction logic.

4.2 Bubble capture-proxy results

Placeholder for the bubble campaign summary and the role of absorption as a proxy observable.

5 P3 Digital Emulator Line

This chapter will organize the platform-architecture note, the software specification, the MVP definitions, and the release lineage through v0.2.2.

5.1 Run modes and configs

Placeholder for bulk, wall, bubble, and resonance run modes.

5.2 Acceptance and milestone ledger

Placeholder for the acceptance suite, milestone achievement statements, and recovery notes across releases.

6 Protocol Bridge to Physical Devices

This chapter will link the digital line to analog calibration, hardware testbench, first-session, and operator packages.

6.1 Observability and control map

Placeholder for the bridge from internal AGT variables to measurable bench outputs.

6.2 Experimental protocol pathway

Placeholder for digital-to-analog transfer, calibration workflow, testbench freeze, and operator runbooks.

7 Reproducibility Contract

This chapter will define the expected canonical source tree, config normalization, output contract, and minimum regression checks that must survive migration from the legacy package lineage to the canonical software tree.

8 Limitations and Non-Claims

This chapter will make explicit that the AGT computational line is still a toy and emulator program, not a proof of real antigravity transport.

9 Forward Dependencies

This chapter will specify what the canonical code import, tests, and Lean statement inventory must preserve.