

TravelX:
NLP model for a
task-oriented
Intelligent assistant

***Cărauşu Catrinel Ioana
Morariu Bogdan***

Contents:

1. Motivation
2. Theoretical background and Related work
3. Proposed solution and results



1.

Motivation

Original contribution

- Combine three AI models in order to create a task-oriented conversational AI
- Compare two different approaches for our NLP models
- Provide a user-friendly application that solves a real-world problem by means of our integrated models



Motivation and goals

- X Custom real-life application based on a relatively new NLP model (BERT)
- X Intuitive and user-friendly interface
- X Create a model and interface easy to extend and integrate with external parties (Amazon Alexa)



2.
Theoretical
background and
Related work

BERT

- Bidirectional Encoder Representation from Transformers
- Built on top of the Transformer Architecture
- State-of-the-art accuracy on 11 NLP tasks
- Brings state-of-the-art to regular users
- Fine-tuning vs feature based

BERT Pretrained model

- Masked Language Model

Input: The man went to the [MASK]₁ . He bought a [MASK]₂ of milk .
Labels: [MASK]₁ = store; [MASK]₂ = gallon

- Next Sentence prediction

Sentence A = The man went to the store.
Sentence B = He bought a gallon of milk.
Label = IsNextSentence

Sentence A = The man went to the store.
Sentence B = Penguins are flightless.
Label = NotNextSentence

Related work


Real-world Conversational AI for Hotel Bookings


- X Commercially used app in the real world
- X Intent Classifier - Bidirectional LSTM
- X Named Entity Recognition - SpaCy2
- X Top-1 Recall: 89% Top -3 Recall: 96%

3.


Proposed solution
and results

Proposed approach






Class diagram of the Backend application




State transitions example

Example of a conversation with our bot, with corresponding state transitions and model logic.




Implementation

- x Python model: ScyPy, pytorch, tensorflow, Keras, BERT
- x User interface: React, Electron, Axios



Experimental results



Our bert: 92.59%

Our bi-LSTM: 87.23%

State-of-the-art: 97.87%

Algorithm improvements

- X Memory footprint reduction: decrease resource utilization
- X Response time improvements:

3.8 seconds avg. -> 1.1 seconds avg.

(request completion-time measured in Chrome dev tools)





Conclusions and achievements

- ✓ **Real-life application** for a task-oriented chatbot
- ✓ **User-friendly** interface
- ✓ **Proof of concept** for further development
- ✓ Ability to **integrate** with other existing interfaces



Difficulties and limitations

- X Hardware resources
- X Complex dialog flows
- X Lack of free datasets for our problem, increased time of data collection and dataset construction



What's next? Future work

- X Support more complex dialog flows
- X Support more hotel features
- X Extends dataset
- X Detect the need to defer task to human
- X Performance improvement:
 - Model
 - Resource utilization
- X Integrate with speech recognition models / systems (Alexa)

To Do!

Bibliography

- X [1] Qian Chen, Zhu Zhuo, and Wen Wang. Bert for joint intent classification and slot filling. Technical report, Speech Lab, DAMO Academy, Alibaba Group, February 2019.
- X Alice Coucke, Alaa Saade, Adrien Ball, Theodore Bluche, Alexandre Caulier, David Leroy, Clement Doumour, Thibault Gisselbrecht, Francesco Caltagirone, Thibaut Lavril, Mael Primet, and Joseph Dureau. Snips voice platform: an embedded spoken language understanding system for private-by-design voice interfaces. Technical report, 2018.
- X Chih-Wen Goo, Guang Gao, Yun-Kai Hsu, Chih-Li Huo, Tsung-Chieh Chen, Keng-Wei Hsu, and YunNung Chen. Slot-gated modeling for joint slot filling and intent prediction. In NAACL-HLT, New Orleans, Louisiana, USA, June 1-6, 2018, Volume 2, pages 735–737, June 2018.
- X Daniel Guo, Gokhan Tur, Wen tau Yih, and Geoffrey Zweig. Joint semantic utterance classification and slot filling with recursive neural networks. In 2014 IEEE Spoken Language Technology Workshop, SLT 2014, South Lake Tahoe, NV, USA, pages 554–563, December 2014.
- X Dilek Hakkani-Tur, Gokhan Tur, Asli Çakırlmaz, Yun-Nung Chen, Jianfeng Gao, Li Deng, and YeYi Wang. Multi-domain joint semantic frame parsing using bi-directional rnn-lstm. In Interspeech 2016, San Francisco, CA, USA, pages 715–719, September 2016.



Thank you!

*Next:
Application Demo*