Distributed by:

JAMECO

ELECTRONICS

www.Jameco.com + 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Jameco Part Number 155433

Step Angle	1.8 ° ±5%
Insulation Resistant	500V DC 100MΩ Min
Insulation Strength	50Hz 1Minute 500V Min
Ambient Temperature	
Temperature Rise	80 Degree C Maximum
Radial Play	0.02 mm Maximum
End Play	0.1-0.3 mm

		Voltag				Holding	Moment of			Size	
Model	No. of Phase	e (VDC)	Current (A)	Resistance (O)	Inductance (mH)	Torque (g.cm)	inertia (g.cm²)	Weight (Kg)	Wiring Diagram	L0 (mm)	L1 (mm)
42BYG014	4	8.5	0.45	19	13	1300	20	0.2	WDG.B	33.5	5
42BYG016	4	12	0.16	70	44	950	20	0.2	WDG.B	33.5	17
42BYG017	2	6.3	0.42	15	16	1400	20	0.22	WDG.A	34	13
42BYG023	2	12	0.4	28.5	32	2000	20	0.22	WDG.A	33	5
42BYG205	4	9.5	0.16	75	65	1320	20	0.22	WDG.B	36	5
42BYG228	4	12	0.4	30	22	2000	20	0.22	WDG.B	38	5
42BYG022	2	9.6	0.24	100	46	1100	20	0.2	WDG.A	33	5



