

Tatami Grammatical Evolution for Feature Extraction with Multi Fitness Evaluation

Go Frendi Gunawan 1st Affiliation

Dept of Informatics, Faculty of Information Technology,
Institut Teknologi Sepuluh Nopember
Surabaya, Indonesia
gofrendiasgard@gmail.com

Joko Lianto Buliali

Dept of Informatics, Faculty of Information Technology,
Institut Teknologi Sepuluh Nopember
Surabaya, Indonesia
joko@its-sby.edu

Abstract

Feature Extraction is a significant topic in classification problem solving. Until now, there is no such a standard way to determine the best features of a data. In this research, grammatical evolution with multiple fitness evaluation approach (named as *GE Tatami*) has been developed in order to extract best features of the data. The method generate $n-1$ features which are able to separate data hierarchically, with n is number of classes.

Some methods has been evaluated in this research, including genetics algorithm, grammatical evolution with global fitness measurement, grammatical evolution with multi fitness measurement, grammatical evolution with Tatami fitness measurement, and Gavrilis's grammatical evolution.

It is shown in the experiment that Tatami method produces a better result compared to the four other methods for synthesis data using decision tree classifier. The synthesis data is hierarchically separable. However Tatami method shows a bad result when it is failed to determine ideal features or using SVM classifier.

Index Terms — Keywords: feature extraction, grammatical evolution, classification, multi-fitness.

I. INTRODUCTION

Feature Extraction is a process to determine transformation mapping of original features set into new features set that will produce better class separability [5]. Feature extraction is a significant topic in classification problem, since good feature set can boost classification accuracy, while bad feature set tend to make classification accuracy worse.

Some genetics algorithm based method has been in order to make good feature sets. In [3] and [4], grammatical evolution has been conducted for feature extraction purpose. The authors create a method that produces a set of new feature with classifier's accuracy as fitness function. In [5] and [6], similar method has also been used for different cases. However, sometime there are several irrelevant features also generated and attached to the feature set.

In [1], the authors create a new approach by measure per-feature accuracy rather than using a set of features altogether as a goodness measurement. However, this approach tends to produce bad accuracy since only one feature used to separate all classes.

In this paper, we propose a multi fitness evaluation to hierarchically separate the data. This multi fitness evaluation is named as Tatami Grammatical Evolution (GE Tatami) since it shows a figure looks like Japanese traditional *tatami*. Several previous methods also used as comparison.

II. DATA AND FEATURE SPACE

A data usually consists of several. Given a set of data, as in table 1.1, one can say that there are two features, x and y , and 3 classes (A, B and C).

Since the data consists of 2 original features, it is possible to plot it in *Cartesian Diagram* to produce better visualization. Figure 1.1 shows how the data plotted.

As shown in the figure 1.1, it is impossible to separate the data by using just one of the features. The two features should be used altogether, producing a feature space to make data separation possible.

Table 2.1 Example of Numeric Data

Original Features		Class
x	y	
0.3	0.5	A
0.4	0.9	B
0.6	0.2	A
0.9	1.0	C
1.0	0.3	C
0.8	0.2	B
...




Figure 2.1 Feature Space Produced by Original Features and Classification Process by Using RBF SVM

A commonly used classifier such as a SVM or neural network can use the feature space to separate the data very well. However the separation cannot be done linearly. The separator line should be a bit curvy which is mathematically more complex than a simple linear line.

III. FEATURE EXTRACTION

Feature Extraction is basically a mapping from original feature space to another one. The mapping can produce higher dimension, or lower dimension.

In classification problem, it is intuitive to map any inseparable (or difficultly separated) data into higher dimension. Higher dimension tend to produce more possibility to separate the data. However, this will also lead to more complex calculation as well.




Figure 3.1 Feature Space Produced by New Feature ($\sqrt{x}+\sqrt{y}$)

The goal of feature extraction is to produce a feature set that consist of as few features as possible. The generated feature set should also be able to produce good data separability in a relatively simple way (i.e.: such as using linear lines).

In order to explain the purpose of feature extraction, one can transform the data on table 2.1 which consists of 2 into features (x and y) into a new feature space containing just 1 feature, $\sqrt{x}+\sqrt{y}$. The feature space is shown as in figure 3.1

This transformation allows us to separate data by using a linear line, which is mathematically simpler than the previous one.

IV. GRAMMATICAL EVOLUTION

Grammatical Evolution is an evolutionary algorithm based on genetics algorithm. This method takes empowered by a predefined context free grammar to transform an individual into anything allowed by the grammar.

Each individual contains of a binary (or integer) string called genotype. The genotype is then transformed by using the grammar into a phenotype. The phenotype can be a mathematics operation, a function, or even a whole computer program, depend on the grammar used.

For example, one uses a grammar as defined in table 4.1. Let's say an individual contains an integer string 220, 203, 51, 123, 2, 45 as genotype. The process started by taking `<expr>` as start symbol. `<expr>` has 4 possible evolution rule, therefore, we take the first segment of the integer string (in this case 220), and do modulo operation. Since $220 \bmod 4$ produce 0, we then take the 0th rule. This make `<expr>` evolved into `<expr><op><expr>`. Next, we go with the second segment of integer string (which is 203) and choose the first non-terminal of `<expr><op><expr>` (which is `<expr>`). Again, we do a modulo operation. Since `<expr>` has 4 possible evolution rule, and $203 \bmod 4$ produce 3, we take the 3rd rule (which is `<var>`). Now we have `<var><op><expr>`. The process continued until we get `x*x` as phenotype. Figure 4.2 shows the complete transformation process.

After getting the phenotype, the process then continued as those in genetics algorithm. The phenotype's fitness measured by certain fitness function, producing a fitness value. The fitness value of each individual then used to determine individual's survival rate.

For feature extraction problem, classifier accuracy can be used as fitness value. Thus, each individual's fitness value shall ranged between 0 and 1.

Just as in genetics algorithm, after several generation, the most optimal individual will be found. The optimal individual is then used as problem solution.

Table 4.1 Grammar Example

Node	Production Rule	Index
<expr>	<expr><op><expr>	0
	(<expr><op><expr>)	1
	<pre-op><expr>	2
	<var>	3
<op>	+	0
	-	1
	*	2
	/	3
<pre-op>	Sin	0
	Cos	1
	Tan	2
var	x	0




Figure 4.1 Transformation Process

V. GE MULTI

Suppose there are n classes in the data, it is logical to think that one can have n features to separate data based on its classes. Each feature should be able to separate a certain class from others.

To achieve this, a simple grammatical evolution with single fitness value for each individual will not work. Therefore, we have developed a modification version of grammatical evolution which produces several fitness values for every individual. This modification version is named as GE Multi.

Let's say one has a data with n classes: $\{c_1, c_2, c_3, \dots, c_n\}$. In GE Multi, each individual has n fitness values: $\{f_1, f_2, f_3, \dots, f_n\}$. The first fitness value f_1 represents the goodness of individual's phenotype to separate c_1 and the others ($\{c_2, c_3, \dots, c_n\}$). The second fitness value f_2 represents the goodness of individual's phenotype to separate c_2 and the others ($\{c_1, c_3, \dots, c_n\}$). The n th fitness value f_n represents the goodness of

individual's phenotype to separate c_n and the others ($\{c_1, c_2, c_3, \dots, c_{n-1}\}$).

To calculate each fitness value of each individual, the data should be transformed so that it only has 2 classes. To measure the first fitness value, $\{c_2, c_3, \dots, c_n\}$ should be merged into one class, let's say c_{-1} . The classifier then works to separate c_1 and c_{-1} . The classifier's accuracy is then used as fitness value f_1 .

Using this approach, there will be n or less best individuals. Each represents the best fitness value for each class (i.e.: There will be an individual with the best f_1 value, there will be an individual with the best f_2 value, and so on). There is also a possibility, an individual has the best value for two or more fitness values. Therefore, using GE Multi as a feature extractor, one will get numerous features ranging from 0 to n , where n is the number of classes in the data.

VI. GE TATAMI

GE Tatami is an improvement of GE Multi which is designed for hierarchically separable data. For hierarchically separable data, the separation can also be done hierarchically. For example, if a data has n classes, $\{c_1, c_2, c_3, \dots, c_n\}$. Once c_1 is separated from the rest, c_1 can be ignored, so that in the next iteration, only $\{c_2, c_3, \dots, c_n\}$ are involved.

GE Tatami consists of $n-1$ iterations where n = number of classes. At each iteration, GE Multi is used to determine the best individuals. Maximum fitness values of all best individuals are then selected to determine which class is best separated from the others. The individual corresponding to the best separated class is then selected and added to the new features list. The process is then repeated with the best separated class omitted. On the last iteration, there will be only 2 classes left. The process ends after the best individual to separate the 2 classes is added to the new features list. Figure 6.1 shows the global flowchart of GE Tatami.

Using this approach, one will have a maximum of $n-1$ features. Figure 6.2 shows how 2 features produced by GE Tatami can separate 3 classes very well.

GE Tatami is very suitable for decision trees since both are designed to separate hierarchically separable data. The decision tree produced by using features generated by GE Tatami is shown in Figure 6.3.




Figure 6.1 Flowchart of GE Tatami




Figure 6.2 Feature Space Produced by GE Tatami




Figure 6.3 Decision Tree Using GE Tatami's Generated Feature

VII. RESULT AND ANALYSIS

To compare effectiveness of GE Multi and GE Tatami with the previous methods, we have conduct several experiments involving several datasets. The datasets consists of 3 synthesis data which is hierarchically separable and 3 commonly used datasets taken from UCI Machine Learning website (iris, balanced scale and E-Coli). In synthesis 03, the original features is hidden. The hidden features can be retrieved by mathematically fiddling with shown features.

For each dataset, we perform 5 fold cross-validation and another test which all data used as training set and testing set. The complete result of experiments is available freely at <https://github.com/goFrendiAsgard/feature-extractor/tree/master/RESULT>

The results are then resumed by calculating average of each case accuracy, producing table 7.1. By looking at the table, one can say that GE Tatami shows a very good result on hierarchically separable data (synthesis 01, synthesis 02, and synthesis 03). However, GE Multi generally shows better

accuracy in not only synthesis data, but also on other commonly used ones.

Figure 7.1 Experiment Result Average

Experiment		GA Select Feature		GE Global		GE Multi		GE Tatami		GE Gavrilis	
		Accuracy (%)	Features	Accuracy (%)	Features	Accuracy (%)	Features	Accuracy (%)	Features	Accuracy (%)	Features
Iris	Train	96.2	2	98.9	1	98.8	3	98.9	2	99.0	1
	Test	93.7		92.5		94.7		92.5		97.5	
	Total	95.7		97.6		98.0		97.6		98.7	
B. Sc ale	Train	71.3	3	88.6	1	96.2	1	93.3 7	2	82.7	25
	Test	69.8		79.0		81.6		81.5		75.4	
	Total	71.0		86.7		93.3		91.0		81.2	
E. Co li	Train	97.0	5	86.9	1	98.2	8	97.2	7	98.0	15
	Test	78.2		65.1		63.5		50.6		67.2	
	Total	93.4		82.7		91.5		88.2		92.0	
Sy nt he sis 01	Train	73.9	3	78.8	1	99.8	3	100	2	87.9	20
	Test	71.8		42.4		84.8		82.2		80.7	
	Total	73.5		71.7		96.9		96.5 2		86.5	
Sy nt he sis 02	Train	78.3	4	71.4	1	99.8	3	100	3	89.4	12
	Test	74.4		39.7		73.0		79.3		78.0	
	Total	77.5		65.2		94.5		95.9		87.2	
Sy nt he sis 03	Train	72.7	5	67.8	1	99.1	5	100	4	81.9	19
	Test	40.5		36.9		63.0		77.6		50.8	
	Total	66.3		61.7		92.0		95.5		75.8	
A V G	Train	81.6	3	82.1	1	98.6	3	98.2	3	89.8	15
	Test	71.4		59.3		76.8		77.3		74.9	
	Total	79.6		77.6		94.4		94.1		86.9	

VIII. CONCLUSION

The experiment conducted shows that using decision tree as classifier, GE Tatami shows a very good performance on hierarchically separated synthesis data. However, using the same classifier GE Multi shows generally good performance.

This also lead us to conclude that combining features generated by GE Tatami and GE Multi is possibly able to boost accuracy.

In the experiment conducted, classifier's accuracy is used to determine fitness value of each individual. Finding a better mechanism to measure fitness value will also probably make the calculation faster.

ACKNOWLEDGMENT

Some people has help the main author to finish this research. Not to mention, Mr. Joko Lianto, as supervisor. His suggestions inspire the main author to solve several problems and finish this research on time.

Some friends, such a Mr. Mukhlis Amien and Mr. Hendra Suprayogi also help the main authors by providing several out-of-the-box suggestions that sometimes useful and never thought before.

REFERENCES

- [1] Gunawan G. F., Gosaria S, Arifin A. Z. (2012). "Grammatical Evolution For Feature Extraction In Local Thresholding Problem", Jurnal Ilmu Komputer dan Informasi, Vol 5, No 2 (2012)
- [2] Harper R., Blair A. (2006). "Dynamically Define Functions in Grammatical Evolution", IEEE Congress of Evolutionary Computation, July 16-21, 2006
- [3] Gavrilis D., Tsoulous I. G., Georgoulas G., Glavas E. (2005). "Classification of Fetal Heart Rate Using Grammatical Evolution", IEEE Workshop on Signal Processing Systems Design and Implementation, 2005.
- [4] Gavrilis D., Tsoulous I. G., Dermatas E. (2008). "Selecting and Constructing Features Using Grammatical Evolution", Journal Pattern Recognition Letters Volume 29 Issue 9, July, 2008 Pages 1358-1365 .
- [5] Guo L., Rivero D., Dorado J., Munteanu C. R., Pazos A. (2011). "Automatic feature extraction using genetic programming: An application to epileptic EEG classification ", Expert Systems with Applications 38 Pages 10425-10436
- [6] Li B., Zhang P.Y., Tian H., Mi S.S., Liu D.S., Ruo G.Q. (2011). "A new feature extraction and selection scheme for hybrid fault diagnosis of gearbox", Expert Systems with Applications 38 Pages 10000-10009
- [7] Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V. , Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P. , Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M. and Duchesnay, E. (2011). "Scikit-learn: Machine Learning in Python", Journal of Machine Learning Research Vol. 12 Pages 2825-2830 Trans. Roy. Soc. London, vol. A247, pp. 529-551, April 1955. (*references*)