# **Bookworm vs Bullseye**

# **Table of Contents**

1 Colophon	4
2 Introduction	5
2.1 What's Not Covered	5
2.2 Requirements:	5
2.3 Conventions	6
3 Fallback to zeroconf	7
3.1 Make Network Manager Use DHCPCD	7
3.2 Use Multiple Connections For the Same Interface	8
3.3 Other Methods	9
4 Python, Pip, and Venvs	10
4.1 Does This Apply To Me?	11
4.2 Getting The Old Behaviour Back	12
4.3 Temporarily Overriding The New Behaviour	13
4.4 Using Your venv From Another User	
4.4.1 Activate The venv As The Alternate User	14
4.4.2 Use The venv Directly	
4.4.3 Use a Shebang Line and call the file directly	14
4.4.4 Other Options	
4.5 Cron, rc.local, and Systemd Services	16
4.5.1 Cron	16
4.5.2 rc.local	16
4.5.3 Systemd Services	17
4.5.4 An Alternativet	17
4.6 Shebangs and venvs	
4.6.1 #!/usr/bin/python	
4.6.2 #!/usr/bin/env python	18
4.6.3 An Alternative	18
5 No /var/log/syslog	
5.1 Option 1	
5.2 Option 2	
6 X11 vs Wayland/Wayfire	
6.1 Getting The Old Way Back	20
6.2 VNC Problems	21
6.2.1 Switching Between X11 and Wayland	21
6.2.2 Client Problems	21
6.3 The Autostart File	22
6.4 The Autostart Folders	23
7 /boot	
7.1 Viewed on RPiOS vs Other OS	24
7.2 Making Changes	25
7.2.1 Using Another OS or Computer	25
7.2.2 From Within The Running RPiOS	
7.2.2.1 config.txt and cmdline.txt	25
7.2.2.2 The overlays Directory	
7.2.2.3 Other Files and Directories	25

7.2.2.4 Programmatic Changes	25
8 Miscellaneous.	
8.1 User Home Directories	
8.2 Pi 5 Serial Ports (UARTs)	
9 Change Log	
o change 105	

# 1 Colophon

This document is Copyright 2023 and released under a Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International (CC BY-NC-SA 4.0) license (see https://creativecommons.org/licenses/by-nc-sa/4.0/)

### 2 Introduction

This is not an in depth and fully tested guide to migrating from Bullseye to Bookworm. Rather it is a repository of the issues I have encountered and potential solutions to them.

It is assumed that the reader is familiar with the Linux command line and at least one text editor. Desktop users will need to open a terminal to execute many of the commands in this guide.

#### 2.1 What's Not Covered

- OS installation.
- In place upgrade from Bullseye to Bookworm
- Quite a lot else, probably.

# 2.2 Requirements:

- An internet connection for software update and installation.
- Raspberry Pi (any model) with a configured and working network connection.
- For a headless<sup>1</sup> Pi, VNC or ssh enabled.

<sup>1</sup> I.E. no monitor, mouse, or keyboard connected.

### 2.3 Conventions

Text like this indicates input to or output from the command line.

Text like this also refers to full or partial commands but is not generally intended to be entered into the command line as is.

"SD card" refers equally to full size and micro SD cards. It should also be taken to refer to any boot storage medium in use.

Where "pi" occurs as a username, replace as appropriate.

Any mention of "python" refers equally to python 2 and python 3 unless explictly specified otherwise. On RPiOS Bookworm python and python3 are the same file.

All non system paths used in this guide follow the Filesystem Hierarchy Standard<sup>2</sup> though this is not mandatory.

<sup>2 &</sup>lt;a href="https://en.wikipedia.org/wiki/Filesystem">https://en.wikipedia.org/wiki/Filesystem</a> Hierarchy Standard

### 3 Fallback to zeroconf

With the switch from dhcpcd to Network Manager network connections/interfaces no longer fall back to a self assigned IP address in the link local/zeroconf subnet.<sup>34</sup> There are a number of ways to reinstate the old behaviour:

### 3.1 Make Network Manager Use DHCPCD

This is my preferred method as it's a one time change and works for all interfaces.

1. Update apt:

sudo apt update

2. Install dhcpcd:

sudo apt install -y dhcpcd

- 3. Open /etc/NetworkManager/NetworkManager.conf in your preferred text editor. You will need to be root or use sudo.
- 4. Add the folloowing line to the [main] section

dhcp=dhcpcd

- 5. Save and close
- 6. Reboot

<sup>3 169.254.0.0/16</sup> 

<sup>4</sup> A time of writing anyway.

# 3.2 Use Multiple Connections For the Same Interface

Network Manager supports multiple connection profiles (hence forth connections) for a network interface. These are attempted in descending order of priority.

Making use of this feature means no additional software is required and unlike 3.1 can be configured on a per interface basis. Unlike 3.1 it must be configured for each interface where fallback is required.

Do not apply this approach to loopback interfaces (e.g. lo). This has not been tested with WiFi interfaces and will likely break things if used on those.

1. Add a connection for DHCP:

sudo nmcli con add con-name eth0-dhcp ifname eth0 type ethernet connection.autoconnect-priority 100 connection.autoconnect-retries 2

2. Add a lower priority connection for zeroconf:

sudo nmcli con add con-name eth0-zeroconf type ethernet ifname eth0
 connection.autoconnect-priority 50 ipv4.method link-local ipv4.link local enabled

3. Make Network Manager reload its connections:

sudo nmcli con reload

4. Reboot.

Replace eth0 in the above with the name of the interface your are configuring.

Depending on configured timeout values falback to zeroconf may take longer than on Bullseye.

The shell script at <a href="https://github.com/thagrol/nm/blob/main/nm-setup.sh">https://github.com/thagrol/nm/blob/main/nm-setup.sh</a> can assist with the above.

### 3.3 Other Methods

Other possible methods include creating a fallback connection in Network Manager with a static IP address in the link local subnet, configuring the interface with a static IP address in /etc/network/interfaces<sup>5</sup>, using dhcpcd with a dhcp configured interface in /etc/network/interfaces.

<sup>5</sup> Network Manager is set to ignore any interfaces configured here.

### 4 Python, Pip, and Venvs

With Bookworm the default python configuration is that modules installed through pip must be installed into a virtual environment (A.K.A a venv). There are good reasons for this change and it was imposed upstream of Raspberry Pi Ltd.

Attempt to use pip install or sudo pip install without a venv will result in the following message:

error: externally-managed-environment

× This environment is externally managed

> To install Python packages system-wide, try apt install python3-xyz, where xyz is the package you are trying to install.

If you wish to install a non-Debian-packaged Python package, create a virtual environment using python3 -m venv path/to/venv. Then use path/to/venv/bin/python and path/to/venv/bin/pip. Make sure you have python3-full installed.

For more information visit http://rptl.io/venv

note: If you believe this is a mistake, please contact your Python installation or OS distribution provider. You can override this, at the risk of breaking your Python installation or OS, by passing --break-system-packages.

Third party installation scripts and out of date guides may also fail due to this change.

While not a tutorial on venvs the rest of this section should give you some ways to handle this change.

# 4.1 Does This Apply To Me?

In short, yes. But if you never install any additional python packages or only ever install packages using apt<sup>6</sup> you should never be impacted by this change.

<sup>6</sup> e.g. sudo apt update && sudo apt install python3-pygame -y

# 4.2 Getting The Old Behaviour Back

It is possible to get the old behaviour back but all this really achieves is pushing the problem further down the line. It also makes your system different from the RPiOS default and thus makes it harder for others to help you.

This is a system wide change and applies to all users.

To disable:

sudo mv /usr/lib/python3.11/EXTERNALLY-MANAGED /usr/lib/python3.11/EXTERNALLY-MANAGED.bak

To re-enable:

sudo mv /usr/lib/python3.11/EXTERNALLY-MANAGED.bak/usr/lib/python3.11/EXTERNALLY-MANAGED

# 4.3 Temporarily Overriding The New Behaviour

Pip has the command line option --break-system-packages that can be used to force installation of modules in the old manner.

To install a module for the current user:

pip install --break-system-packages SomeModule

To install a module for the all users:

sudo pip install --break-system-packages SomeModule

However, this is not recommended as it makes your system different from the RPiOS default and thus makes it harder for others to help you.

### 4.4 Using Your venv From Another User

Python venvs can be used by users other than their owner (e.g. to run your python program from /etc/rc.local). This is what is required when running with sudo, from rc.local, or from a systemd service as root.

In the examples below the user pi has a venv at /home/pi/.venv. The user ip has no venv but wants to run pi's code which relies on pi's venv.

#### 4.4.1 Activate The veny As The Alternate User

- 1. If you don't know it, find the location of the venv.
- 2. Activate the venv. e.g.:

```
source /home/pi/.venv/bin/activate
```

3. In the same shell or in a sub-shell of it run the python program, e.g.:

```
python /home/pi/SomeProgram.py
```

#### 4.4.2 Use The venv Directly

- 1. If you don't know it find the full path to the python binary inside the venv. With the venv active which python or which python3 should tell you e.g. /home/pi/, venv/bin/python.
- 2. Instead of calling the python program with the system binary call it with the one from the venv e.g.

```
/home/pi/.venv/bin/python /home/pi/SomeProgram.py
```

### 4.4.3 Use a Shebang Line and call the file directly

A shebang line as the first line in a python program tells the shell which python interpreter to use when the file is called directly. It is ignored by the python interpreter. In order to be useful the file must have execute permission<sup>7</sup>.

1. If you program does not have a shebang, add one as the first line of the file e.g.:

```
#!/home/pi/.venv/bin/python
```

If if has one change it as above.

2. Launch your program using

/home/pi/SomeProgram.py

<sup>7</sup> chmod +x SomeProgram.py

### **4.4.4 Other Options**

Other options include:

- Recreating and activating the venv under the target user.
- Creating a system wide venv usable by all users specific to the program in question.
- Creating a system wide venv usable and modifiable by all users.
- For python programs that require sudo: fix the issue that makes it require sudo and run as a normal user. This is the correct fix regardless of whether a venv is in use or not.

### 4.5 Cron, rc.local, and Systemd Services

Processes started under cron, rc.local, or as systemd services run under a different environment to processes started from a logged in shell. User logion scripts are not run and the actual user may not be the same as the development user.

#### 4.5.1 Cron

In general you will need to use one of the methods in 4.4 however as each cron job runs in its own shell the following, while tempting and seemingly correct will not work:

```
0 * * * * source /home/pi/.venv/bin/activate
1 * * * python /home/pi/SomeProgram.py
```

The environment set up in the first job is entirely separate to the environment of the second and will have been discarded prior to the second job starting.

Instead use the method from 4.4.2:

```
1 * * * * /home/pi/.venv/bin/python /home/pi/SomeProgram.py
```

or from 4.4.3:

```
1 * * * * /home/pi/SomeProgram.py
```

@reboot cron jobs work in the same manner.

#### 4.5.2 rc.local

The method in 4.4.1 needs a little care in that activating the venv must not be done as a background job.

```
source /home/pi/.venv/bin/activate &
python /home/pi/SomeProgram.py &
```

will fail as it will use the wrong python interpreter.8

```
source /home/pi/.venv/bin/activate
python /home/pi/SomeProgram.py &
```

will work as expected.

If you wish to start code that requires a different venv, deactivate the current one and activate the new one before calling that code.

4.4.2 and 4.4.3 should work as expected

<sup>8</sup> Background jobs are started in their own sub shell which, in this case is almost immediately discarded.

### 4.5.3 Systemd Services

I have yet to test venvs with systemd however I'd expect trying to activate one using

ExecStartPre=source /home/pi/.venv/bin/activate

to fail. I recommend using 4.4.2 or 4.4.3 in your ExecStart.

#### 4.5.4 An Alternativet

Instead of trying to activate the venv and call the python program directly a simple shell script can be used instead. This also has the benefit in rc.local of restricting the activated venv to that script only.

#!/bin/bash

source /home/pi/.venv/bin/activate

python /home/pi/SomeProgram.py

Call the bash script instead of calling the python program.<sup>9</sup>

<sup>9</sup> Don't forget to grant your script execute permission.

# 4.6 Shebangs and venvs

As mentioned above, shebangs tell the shell which python<sup>10</sup> interpreter to use to run the file's content.

The most common shebangs for python seem to be #!/usr/bin/python and #!/usr/bin/env python neither of which play well with venvs.

#### 4.6.1 #!/usr/bin/python

This will always use the python binary found at /usr/bin/python bypassing any venv whether active or not. Avoid this method where ever possible.

### 4.6.2 #!/usr/bin/env python

This uses your current environment<sup>11</sup> to finf which python interpreter to run. If a vrnv is active it will be used even if it is the wrong venv. If no venv is active the system interpreter will be used.

#### 4.6.3 An Alternative

See 4.4.3

<sup>10</sup> Not just python. Any text file can have one. It doesn't have to match the file extension either – a .py file could have a shebang pointing to bash.

<sup>11</sup> Via the env command.

# 5 No /var/log/syslog

Upstream Debian has removed syslog. All logging in now done through the systemd journal.

# **5.1 Option 1**

Learn to use journalctl. Reading the man page would be a good place to start.<sup>12</sup>

# **5.2 Option 2**

Install rsyslogd:

sudo apt update && sudo apt install -y rsyslog

Caution: this may leading to double logging and a consequent increase in disc space usage.

12 man journalctl

# 6 X11 vs Wayland/Wayfire

This is a significant change in Bookworm with major impact however it does not impact user of the lite images.

At time of writing Wayland is only the default on Pi 4 and Pi 5.<sup>13</sup> Earlier models still default to X11.

# **6.1** Getting The Old Way Back

The easiest way to get the old, pre-bookworm behaviour back is to switch back to X11 from Wayland:

1. Open a terminal

sudo raspi-config

- 2. Select 6 Advanced Options
- 3. Select A6 Wayland
- 4. Select *W1 X11*
- 5. Exit raspi-config and reboot

 $<sup>13 \</sup>quad See \ \underline{https://www.raspberrypi.com/news/bookworm-the-new-version-of-raspberry-pi-os/new-version-of-raspberry-pi-os/new-version-of-raspberry-pi-os/new-version-of-raspberry-pi-os/new-version-of-raspberry-pi-os/new-version-of-raspberry-pi-os/new-version-of-raspberry-pi-os/new-version-of-raspberry-pi-os/new-version-of-raspberry-pi-os/new-version-of-raspberry-pi-os/new-version-of-raspberry-pi-os/new-version-of-raspberry-pi-os/new-version-of-raspberry-pi-os/new-version-of-raspberry-pi-os/new-version-of-raspberry-pi-os/new-version-of-raspberry-pi-os/new-version-of-rasp$ 

### **6.2 VNC Problems**

### 6.2.1 Switching Between X11 and Wayland

Switching between X11 and Wayland<sup>14</sup> will disable the VNC server. You must enable it via sudo raspi-config in order to be able to connect even if it was previously enabled on the system you are switching to.

#### **6.2.2 Client Problems**

The VNC sever used under Wayland is know to cause problems with a significant number of VNC viewers. The current recommendation is to use the <u>TigerVNC</u> client.

<sup>14</sup> Or between Wayland and X11

# 6.3 The Autostart File

/etc/xdg/lxsession/LXDE-pi/autostart and

/home/pi/.config/lxsession/LXDE-pi/autostart are not used by Wayland/Wayfire. Any changes made to these will be ignored.

A similar functionality is provided in the [autostart] section \$HOME/.config/wayfire.ini. Unlike /etc/xdg/lxsession/LXDE-pi/autostart this is a per user configuration.

The format of each line is

```
[autostart]
unique-ID = some command
```

The ID doesn't matter except that it must be unique. Commands are run with sh so if you have a shell script that relies on features of a more advanced shell either use an appropriate shebang in your script or call the required shell and pass it your script name on the command line.

[auotstart] is required only once at the start of the section.

An example:

```
[autostart]
terminal = lxterminal
foo = $HOME/myscript.sh
bar = bash myotherscript.sh
```

Wayfire does not appear to support the same @ prefix feature<sup>15</sup> that LXDE does so you'll need to handle exit detection and restart your self, for example by wrapping the actual command in a small bash script such as this:

```
#!/bin bash
while true; do
    #your command goes here
    lxterminal
done
```

Changes made to wayfire.ini will be ignored if you later switch back to X11 from Wayland/Wayfire.

<sup>15</sup> Automatic restart if the process exits.

### **6.4** The Autostart Folders

Under X11 putting a .desktop  $file^{16}$  into /etc/xdg/lxsession/LXDE-pi/autostart, /home/pi/.config/lxsession/LXDE-pi/autostart, /etc/xdg/autostart, or /home/pi/.config/autostart caused the shortcut to be run at login.

/etc/xdg/lxsession/LXDE-pi/autostart and/home/pi/.config/lxsession/LXDE-pi/autostart are ignored by Wayland/Wayfire.

/etc/xdg/autostart, and /home/pi/.config/autostart are used by both systems. .desktop files placed here will be run regardless of your selection of X11 or Wayland.

<sup>16</sup> e.g. myprogram.desktop

### 7 /boot

On Bookworm the boot partition is no longer mounted on /boot but on /boot/firmware. Presumably to maintain backwards compatibility symbolic links for /boot/config.txt, /boot/cmdline.txt, and /boot/overlays have been provided.

This, however is an imperfect solution and may lead to some confusion.

#### 7.1 Viewed on RPiOS vs Other OS

When viewing the boot partition from a different OS (e.g. Windows) you will notice several differences compared to viewing /boot on RPiOS:

- There is no firmware directory
- overlays is a directory not a link.
- config.txt is a file not a link.
- cmdline.txt is a file not a link.
- Any changes made to /boot are not present.

The above are normal and as expected.

When viewed from within a running RPiOS all items immediately in /boot are on the root partition, the contents of /boot/firmware are the contents of the boot partition. If the boot partition is not mounted /boot/firmware will be empty.

## 7.2 Making Changes

### 7.2.1 Using Another OS or Computer

Changes made by mounting the boot partition on another OS or computer work as they did on previous releases.

#### 7.2.2 From Within The Running RPiOS

#### 7.2.2.1 config.txt and cmdline.txt

Most editors will handle editing /boot/config.txt and /boot/cmdline.txt without problems as will most shell commands and redirection (<, >, >>, etc.).

Copying from /boot/config.txt and /boot/cmdline.txt will also work as expected.

Copying to /boot/config.txt and /boot/cmdline.txt will not. Files will be copied onto the root partition and will replace the existing links. The actual config.txt or cmdline.txt present on the boot partition will not be changed. Copy the files to /boot/firmware/ instead.

#### 7.2.2.2 The overlays Directory

Most operations on /boot/overlays and its contents will behave as expected however deleting /boot/overlays will delete the link not the underlying directory.

#### 7.2.2.3 Other Files and Directories

Changes to other files and directories in the boot partition must be made via /boot/firmware. If changes are made in /boot they will not be visible to the boot loader and will not be acted on a boot.

### 7.2.2.4 Programmatic Changes

Programs and scripts that have not been updated for Bookworm should not be used. They may work as expected but they may write to the wrong place causing changes to be ignored or the system to be made unbootable.

If you need help with such a program contact its author.

### 8 Miscellaneous

### 8.1 User Home Directories

Default permissions on user home directories have change to permit access only by the owning user. The old permissions can be restored as follows:

- 1. Login as the required user
- 2. chmod a+rx  $\sim$

# 8.2 Pi 5 Serial Ports (UARTs)<sup>17</sup>

While not a general Bookworm issue it is included here as Bookworm is required for a Pi 5.

There is no /dev/serial1

/dev/serial0 points to the UART on the debug connector. It will do so even if the UART on GPIO 14 and 15 is enabled and regardless of the state of the UART connected to the Bluetooth controller.

The serial console is not routed to GPIO 14 and 15 so there is no need to disable the login on it to bale to use that UART.

<sup>17</sup> Advice here will be impacted if UART related changes are made to config.txt and/or cmdline.txt

# 9 Change Log

**2023-11-05** Initial release

**2023-11-22** Add sections 7 and 8. Moved change log to 9.