

Evaluating the Robustness of a 4D STEM Autoencoder to Noisy Inputs

Zhuo (Cecilia) Chen¹, Olivia Weng², Shuyu Qin³, Joshua Agar⁴, Nhan Tran⁵, Ryan Kastner²

1 – Computer Science Department, Bryn Mawr College 2 - Computer Science and Engineering Department, UC San Diego 3 – Computer Science Department, Lehigh University
4 - Department of Mechanical Engineering and Mechanics, Drexel University 5 - Fermi National Accelerator Lab

Submission 128

Why Evaluate NN's Robustness to noisy inputs?


- Neural Networks can assist 4D STEM dataset analysis [2][3][4].
- Reduce damage to the specimen → send less electron beams [5] → larger noise to the dataset
- What is the maximum noise level that the neural network can handle?
- How could we enhance the model's robustness?

CC-ST-AE

Data


In material science, 4D Scanning Transmission Electron Microscopy (4D STEM) is a dataset of images formed by electrons passing through a thin specimen [1] that material scientists can learn some structural properties.

A sample input image with different noise level, i.e. intensity of background noise



Model

Qin et al. proposed a neural network structure called cycle-consistent-spatial-transforming auto-encoders (CC-ST-AE) to extract spatial parameters like crystallographic strain, shear, and rotation to understand material properties [3], [4].




Results

Methods

Train and test the model with different noise levels to measure its robustness to noisy inputs.


Takeaways #1

The larger the noise level is, the worse the model's trains.




Takeaways #2

By injecting noise into the training set, we can improve the robustness of the model.



Takeaways #3

The model trained with the same noisy level as testing balances small spread with lower loss.



Future Work

- Data augmentation with training with a combination of various noise levels
- Hyper-parameter tuning for the learning rate, seed, and batch size
- Explore techniques such as regularization, pruning, and quantization to make this suitable for edge deployment.

References

- [1] I. 4D STEM — Gatan, "4d stem," 2024, <https://www.gatan.com/techniques/4d-stem> [Accessed: 9-1-2024].
- [2] M. P. Oxley, J. Yin, N. Borodnov, S. Somnath, M. Zlatkinov, A. R. Lupini, S. Jesse, R. K. Vasudevan, and S. V. Kalinin, "Deep learning of interface structures from simulated 4d stem data: cation intermixing vs. roughening," *Machine Learning: Science and Technology*, vol. 1, no. 4, p. 04LT01, 2020.
- [3] S. Qin, J. Agar, and N. Tran, "Extremely noisy 4d-TEM strain mapping using cycle consistent spatial transforming autoencoders," in *AI for Accelerated Materials Design - NeurIPS 2023 Workshop*, 2023. [Online]. Available: <https://openreview.net/forum?id=7y3N0u0W9>
- [4] S. Wang, T. B. Eldred, J. G. Smith, and W. Gao, "Autodisk: Automated diffraction processing and strain mapping in 4d-stem," *Ultramicroscopy*, vol. 236, p. 113513, 2022. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S0304399122000481>
- [5] K. C. Bustillo, S. E. Zellmann, M. Chen, J. Donohue, J. Ciston, C. Ophus, and A. M. Minor, "4d-stem of beam-sensitive materials," *Accounts of chemical research*, vol. 54, no. 11, pp. 2543–2551, 2021.