Index

A

abs() - Method in class dev.tamboui.layout.Fraction
Returns the absolute value of this fraction.

AbstractBackend - Class in dev.tamboui.terminal
Base class for terminal backends that produce ANSI output.

AbstractBackend() - Constructor for class dev.tamboui.terminal.AbstractBackend
Creates a new abstract backend.

action() - Method in class dev.tamboui.tui.event.ActionEvent
Returns the action name that was fired.

action() - Method in class dev.tamboui.tui.event.KeyEvent
Returns the action that this event matches, if any.

action() - Method in class dev.tamboui.tui.event.MouseEvent
Returns the action that this event matches, if any.

ActionEvent<T> - Class in dev.tamboui.tui.event
Represents a programmatically fired action, as opposed to a raw input event.

actionFor(Event) - Method in interface dev.tamboui.tui.bindings.Bindings
Returns the action that matches the event, if any.

actionFor(Event) - Method in class dev.tamboui.tui.bindings.DefaultBindings

actionHandler() - Method in class dev.tamboui.tui.TuiRunner.ConfiguredRunner
Returns the action handler, if auto-registration was enabled.

ActionHandler - Class in dev.tamboui.tui.bindings
Dispatches events to registered action handlers.

ActionHandler(Bindings) - Constructor for class dev.tamboui.tui.bindings.ActionHandler
Creates a new action handler with the given bindings.

ActionHandlerRegistrar<T> - Interface in dev.tamboui.tui.bindings
Service interface for registering action handlers from annotated classes.

actions() - Method in class dev.tamboui.tui.bindings.DefaultBindings
Returns all action names that have triggers defined.

Actions - Class in dev.tamboui.tui.bindings
String constants for common semantic actions.

active() - Static method in class dev.tamboui.internal.record.RecordingConfig
Returns the active recording config, or null if not recording.

add(int, int, Cell) - Method in class dev.tamboui.buffer.DiffResult
Adds a cell update to this diff result.

add(Fraction) - Method in class dev.tamboui.layout.Fraction
Returns the sum of this fraction and another.

add(TFxDuration) - Method in class dev.tamboui.tfx.TFxDuration
Adds another duration.

add(Element) - Method in class dev.tamboui.toolkit.element.ContainerElement
Adds a child element.

add(Element...) - Method in class dev.tamboui.toolkit.element.ContainerElement
Adds multiple child elements.

add(StyledElement) - Method in class dev.tamboui.toolkit.elements.ListElement
Adds a styled element item to the list.

add(TreeNode) - Method in class dev.tamboui.toolkit.elements.TreeElement
Adds a root node.

add(TreeNode) - Method in class dev.tamboui.widgets.tree.TreeNode
Adds a child node.

add(String) - Method in class dev.tamboui.toolkit.elements.ListElement
Adds a text item to the list.

add(String) - Method in class dev.tamboui.toolkit.elements.TabsElement
Adds a tab.

add(LocalDate, Style) - Method in class dev.tamboui.widgets.calendar.CalendarEventStore
Adds a date with the specified style.

addAll(Style, LocalDate...) - Method in class dev.tamboui.widgets.calendar.CalendarEventStore
Adds multiple dates with the same style.

addBar(long) - Method in class dev.tamboui.widgets.barchart.BarGroup.Builder
Adds a bar with the given value.

addBar(long, String) - Method in class dev.tamboui.widgets.barchart.BarGroup.Builder
Adds a bar with the given value and label.

addBar(Bar) - Method in class dev.tamboui.widgets.barchart.BarGroup.Builder
Adds a bar to this group.

addChangeListener(StyleEngine.StyleChangeListener) - Method in class dev.tamboui.css.engine.StyleEngine
Adds a listener to be notified when the active stylesheet changes.

addClass(String...) - Method in class dev.tamboui.toolkit.element.StyledElement
Adds one or more CSS classes to this element.

addConstraint(CassowaryConstraint) - Method in class dev.tamboui.layout.cassowary.Solver
Adds a constraint to the solver.

addConstraints(Iterable) - Method in class dev.tamboui.layout.cassowary.Solver
Adds multiple constraints to the solver.

addDataset(Dataset) - Method in class dev.tamboui.widgets.chart.Chart.Builder
Adds a dataset.

addEditVariable(Variable, Strength) - Method in class dev.tamboui.layout.cassowary.Solver
Adds an edit variable for interactive updates.

addEffect(Effect) - Method in class dev.tamboui.tfx.EffectManager
Adds an effect to be processed by the manager.

addEffect(Effect) - Method in class dev.tamboui.tfx.tui.TfxIntegration
Adds an effect to be processed.

addEffect(Effect, Rect) - Method in class dev.tamboui.tfx.tui.TfxIntegration
Adds an effect with a specific target area.

addEffect(Element, Effect) - Method in class dev.tamboui.tfx.toolkit.ElementEffectRegistry
Adds an effect that targets a specific element.

addEffect(Element, Effect) - Method in class dev.tamboui.tfx.toolkit.ToolkitEffects
Adds an effect that targets a specific element.

addEffect(String, Effect) - Method in class dev.tamboui.tfx.toolkit.ElementEffectRegistry
Adds an effect that targets a specific element by ID.

addEffect(String, Effect) - Method in class dev.tamboui.tfx.toolkit.ToolkitEffects
Adds an effect that targets a specific element by ID.

addEffectBySelector(String, Effect) - Method in class dev.tamboui.tfx.toolkit.ElementEffectRegistry
Adds an effect that targets elements matching a CSS-like selector.

addEffectBySelector(String, Effect) - Method in class dev.tamboui.tfx.toolkit.ToolkitEffects
Adds an effect that targets all elements matching a CSS-like selector.

addGlobalEffect(Effect) - Method in class dev.tamboui.tfx.toolkit.ElementEffectRegistry
Adds a global effect that applies to the entire frame area.

addGlobalEffect(Effect) - Method in class dev.tamboui.tfx.toolkit.ToolkitEffects
Adds a global effect that applies to the entire frame area.

addGlobalHandler(GlobalEventHandler) - Method in class dev.tamboui.toolkit.event.EventRouter
Adds a global event handler that is called before element-specific handlers.

addGlobalHandler(ActionHandler) - Method in class dev.tamboui.toolkit.event.EventRouter
Adds an action handler as a global event handler.

addGroup(BarGroup) - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Adds a single bar group.

addItem(SizedWidget) - Method in class dev.tamboui.widgets.list.ListWidget.Builder
Adds an item to the list.

addLabel(Span) - Method in class dev.tamboui.widgets.chart.Axis.Builder
Adds a label.

addLabel(String) - Method in class dev.tamboui.widgets.chart.Axis.Builder
Adds a label.

addModifier(Modifier) - Method in class dev.tamboui.css.cascade.CssStyleResolver.Builder
Adds a text modifier.

addModifier(Modifier) - Method in class dev.tamboui.style.Style
Returns a new style with the given modifier enabled.

addModifiers() - Method in class dev.tamboui.style.Style
Returns the modifiers explicitly added to this style.

addModifiers(Set) - Method in class dev.tamboui.css.cascade.CssStyleResolver.Builder
Adds multiple text modifiers.

addPoint(double, double) - Method in class dev.tamboui.widgets.chart.Dataset.Builder
Adds a single data point.

addRange(LocalDate, LocalDate, Style) - Method in class dev.tamboui.widgets.calendar.CalendarEventStore
Adds a range of dates with the specified style.

addRow(Row) - Method in class dev.tamboui.widgets.table.Table.Builder
Adds a row.

addStylesheet(String) - Method in class dev.tamboui.css.engine.StyleEngine
Adds an inline stylesheet from a CSS string.

addStylesheet(String, String) - Method in class dev.tamboui.css.engine.StyleEngine
Adds a named inline stylesheet.

addTitle(Line) - Method in class dev.tamboui.widgets.tabs.Tabs.Builder
Adds a tab title.

addTitle(String) - Method in class dev.tamboui.widgets.tabs.Tabs.Builder
Adds a tab title.

advance() - Method in class dev.tamboui.widgets.spinner.SpinnerState
Advances the tick by 1 and returns the new value.

advance() - Method in class dev.tamboui.widgets.wavetext.WaveTextState
Advances the tick by 1 and returns the new value.

advance(long) - Method in class dev.tamboui.widgets.spinner.SpinnerState
Advances the tick by the given amount.

advance(long) - Method in class dev.tamboui.widgets.wavetext.WaveTextState
Advances the tick by the given amount.

AeshBackend - Class in dev.tamboui.backend.aesh
Aesh Readline based backend for terminal operations.

AeshBackend() - Constructor for class dev.tamboui.backend.aesh.AeshBackend

Creates a new Aesh backend using a default TerminalConnection.

AeshBackend(Connection) - Constructor for class dev.tamboui.backend.aesh.AeshBackend
Creates a new Aesh backend using the provided Connection.

AeshBackendProvider - Class in dev.tamboui.backend.aesh
`BackendProvider` implementation for Aesh Readline.

AeshBackendProvider() - Constructor for class dev.tamboui.backend.aesh.AeshBackendProvider
Creates a new Aesh backend provider.

align(Rect, int, int) - Method in enum class dev.tamboui.layout.ContentAlignment
Computes the aligned sub-rect for a child within a container.

alignment() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the text alignment, if set.

alignment() - Method in class dev.tamboui.layout.stack.Stack
Returns the alignment for this stack.

alignment() - Method in class dev.tamboui.text.Line
Returns the alignment of this line, if set.

alignment() - Method in class dev.tamboui.text.Text
Returns the alignment of this text, if set.

alignment() - Method in class dev.tamboui.widgets.block.Title
Returns the title alignment.

alignment(Alignment) - Method in class dev.tamboui.css.cascade.CssStyleResolver.Builder
Sets the text alignment.

alignment(Alignment) - Method in class dev.tamboui.text.Line
Returns a new line with the given alignment.

alignment(Alignment) - Method in class dev.tamboui.text.Text
Returns a new text with the given alignment.

alignment(Alignment) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Sets the text alignment.

alignment(Alignment) - Method in class dev.tamboui.toolkit.elements.MarkupTextElement
Sets the text alignment.

alignment(Alignment) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Sets the text alignment.

alignment(Alignment) - Method in class dev.tamboui.toolkit.elements.RichTextElement
Sets the text alignment.

alignment(Alignment) - Method in class dev.tamboui.toolkit.elements.TextElement
Sets the text alignment.

alignment(Alignment) - Method in class dev.tamboui.widgets.block.Title
Returns a new title with the given alignment.

alignment(Alignment) - Method in class dev.tamboui.widgets.paragraph.Paragraph.Builder
Sets the text alignment.

alignment(ContentAlignment) - Method in class dev.tamboui.layout.stack.Stack.Builder
Sets how children are aligned within the stack.

alignment(ContentAlignment) - Method in class dev.tamboui.toolkit.elements.StackElement
Sets how children are aligned within the stack.

Alignment - Enum Class in dev.tamboui.layout
Alignment for text and widget content.

AlignmentConverter - Class in dev.tamboui.css.property
Converts CSS text-align values to Alignment enum.

AlignmentConverter - Class in dev.tamboui.style
Converts string values to `Alignment` enum values.

all() - Static method in class dev.tamboui.style.StandardProperties
Returns all registered property definitions.

all() - Method in interface dev.tamboui.style.StyledAreaRegistry
Returns all registered styled areas.

all() - Static method in class dev.tamboui.tfx.CellFilter
Selects every cell in the area (no filtering).

ALL - Static variable in enum class dev.tamboui.widgets.block.Borders
All borders.

allLayers() - Method in class dev.tamboui.widgets.canvas.Context
Returns the current grid plus all saved layers.

allMatch() - Static method in class dev.tamboui.css.cascade.PseudoClassState
Returns a state with all pseudo-classes matching.

allocateConsoleScreenBufferInfo(Arena) - Static method in class dev.tamboui.backend.panama.windows.Kernel32
Allocates a CONSOLE_SCREEN_BUFFER_INFO structure.

allocateInputRecord(Arena) - Static method in class dev.tamboui.backend.panama.windows.Kernel32
Allocates an INPUT_RECORD structure.

allocatePollfd(Arena) - Static method in class dev.tamboui.backend.panama.unix.LibC
Creates a new pollfd struct in the given arena.

allocateSigaction(Arena) - Static method in class dev.tamboui.backend.panama.unix.LibC
Allocates a sigaction structure in the given arena.

allocateTermios(Arena) - Static method in class dev.tamboui.backend.panama.unix.LibC
Creates a new termios struct in the given arena.

allocateWinsize(Arena) - Static method in class dev.tamboui.backend.panama.unix.LibC
Creates a new winsize struct in the given arena.

allOf(List) - Static method in class dev.tamboui.tfx.CellFilter
Selects cells that match ALL of the given filters (logical AND).

alpha() - Method in class dev.tamboui.tfx.EffectTimer
Computes the current alpha value based on the elapsed time and interpolation method.

alpha(float) - Method in enum class dev.tamboui.tfx.Interpolation
Applies the interpolation function to the given alpha value (0.0 to 1.0).

alpha(int) - Static method in class dev.tamboui.image.ImageData
Returns the alpha component of a pixel (0-255).

alpha(Position) - Method in class dev.tamboui.tfx.SlidingWindowAlpha
Calculates the alpha value for a given position.

alt() - Method in class dev.tamboui.tui.event.KeyModifiers
Returns whether the Alt modifier is active.

alt(char) - Static method in class dev.tamboui.tui.bindings.KeyTrigger
Creates a trigger for Alt+character.

ALT - Static variable in class dev.tamboui.tui.event.KeyModifiers
Only Alt pressed.

altClick() - Static method in class dev.tamboui.tui.bindings.MouseTrigger
Creates a trigger for Alt+left click.

alternateScreen() - Method in class dev.tamboui.tui.TuiConfig
Returns whether the alternate screen buffer is used.

alternateScreen(boolean) - Method in class dev.tamboui.tui.TuiConfig.Builder
Sets whether to use alternate screen buffer.

alternateScreen(boolean) - Method in class dev.tamboui.tui.TuiRunner.Builder
Sets whether to use alternate screen buffer.

ALWAYS - Enum constant in enum class dev.tamboui.widgets.common.ScrollBarPolicy
Always show the scrollbar.

ALWAYS - Enum constant in enum class dev.tamboui.widgets.table.Table.HighlightSpacing
Always allocate space for the highlight symbol.

ancestor() - Method in class dev.tamboui.css.selector.DescendantSelector
Returns the ancestor selector.

ancestors() - Method in class dev.tamboui.toolkit.element.ElementRegistry.ElementInfo
Builds the ancestor chain for selector matching.

and(Validator) - Method in interface dev.tamboui.widgets.form.Validator
Composes this validator with another, requiring both to pass.

ansi(AnsiColor) - Static method in interface dev.tamboui.style.Color
Creates an ANSI 16 color.

Ansi(AnsiColor) - Constructor for class dev.tamboui.style.Color.Ansi
Creates an ANSI color.

AnsiCellWriter - Class in dev.tamboui.terminal
Stateful cell-to-ANSI renderer that converts a sequence of `Cell` values into ANSI escape sequences and delivers them to a provided output sink.

AnsiCellWriter(Consumer) - Constructor for class dev.tamboui.terminal.AnsiCellWriter
Creates a new writer that sends ANSI output to the given sink.

AnsiColor - Enum Class in dev.tamboui.style
Standard ANSI 16 colors (8 normal + 8 bright).

AnsiStringBuilder - Class in dev.tamboui.terminal
Utility class for building ANSI-escaped strings from styled content.

AnsiTerminalCapture - Class in dev.tamboui.internal.record
Captures raw bytes written to System.out for recording inline demos.

ansiToRgb(AnsiColor) - Static method in interface dev.tamboui.style.Color
Converts an ANSI color to RGB using standard terminal colors.

anyOf(List) - Static method in class dev.tamboui.tfx.CellFilter
Selects cells that match ANY of the given filters (logical OR).

app(Object) - Method in class dev.tamboui.toolkit.app.ToolkitRunner.Builder
Sets the application object containing `@OnAction` annotated methods.

append(byte) - Method in class dev.tamboui.backend.panama.ByteArrayBuilder
Appends a single byte.

append(byte[]) - Method in class dev.tamboui.backend.panama.ByteArrayBuilder
Appends a byte array.

append(Line) - Method in class dev.tamboui.text.Line
Appends another line's spans to this line.

append(Line) - Method in class dev.tamboui.text.Text
Appends a line to this text.

append(Span) - Method in class dev.tamboui.text.Line
Appends a span to this line.

append(Text) - Method in class dev.tamboui.text.Text
Appends another text's lines to this text.

appendAscii(String) - Method in class dev.tamboui.backend.panama.ByteArrayBuilder
Appends an ASCII string without charset encoding.

appendInt(int) - Method in class dev.tamboui.backend.panama.ByteArrayBuilder
Appends a non-negative integer as ASCII digits.

appendUtf8(String) - Method in class dev.tamboui.backend.panama.ByteArrayBuilder
Appends a UTF-8 encoded string.

applyScrollToEnd(int, int) - Method in class dev.tamboui.widgets.list.ListState
Applies scroll-to-end mode (unconditional pin to bottom).

applyStickyScroll(int, int, int) - Method in class dev.tamboui.widgets.list.ListState
Applies sticky scroll logic.

ARC - Enum constant in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Arc spinner using quarter-circle characters.

area() - Method in class dev.tamboui.buffer.Buffer
Returns the area of this buffer.

area() - Method in class dev.tamboui.layout.Rect
Returns area (width * height).

area() - Method in class dev.tamboui.layout.Size
Returns the area (width * height).

area() - Method in class dev.tamboui.style.StyledAreaInfo
Returns the rectangular area where this styled content was rendered.

area() - Method in class dev.tamboui.terminal.CompletedFrame
Returns the area that was rendered.

area() - Method in class dev.tamboui.terminal.Frame
Returns the area available for rendering.

area() - Method in class dev.tamboui.terminal.Terminal
Returns the current terminal area.

area() - Method in class dev.tamboui.tfx.effects.DissolveShader

area() - Method in class dev.tamboui.tfx.effects.ExpandShader

area() - Method in class dev.tamboui.tfx.effects.FadeShader

area() - Method in class dev.tamboui.tfx.effects.PaintShader

area() - Method in class dev.tamboui.tfx.effects.ParallelEffect

area() - Method in class dev.tamboui.tfx.effects.SequentialEffect

area() - Method in class dev.tamboui.tfx.effects.SlideShader

area() - Method in class dev.tamboui.tfx.effects.StretchShader

area() - Method in class dev.tamboui.tfx.effects.SweepShader

area() - Method in interface dev.tamboui.tfx.Shader
Returns the area where the shader effect is applied, or null if not set.

area() - Method in class dev.tamboui.toolkit.element.ElementRegistry.ElementInfo
Returns the element's rendered area.

area() - Method in class dev.tamboui.toolkit.element.StyledSpan
Returns the area of this styled span.

area(Rect) - Static method in class dev.tamboui.tfx.CellFilter
Selects cells within the specified rectangular area.

area(String, Element) - Method in class dev.tamboui.toolkit.elements.GridElement
Assigns an element to a named area.

area(String, Widget) - Method in class dev.tamboui.layout.grid.Grid.AreaBuilder
Assigns a widget to a named area.

AreaBounds(int, int, int, int) - Constructor for class dev.tamboui.layout.grid.GridArea.AreaBounds
Creates area bounds.

areaCount() - Method in class dev.tamboui.layout.grid.GridArea

Returns the number of named areas.

Area Mode Example - Section in class dev.tamboui.layout.grid.Grid

areaNames() - Method in class dev.tamboui.layout.grid.GridArea
Returns all defined area names in declaration order.

arrowNavigation(boolean) - Method in class dev.tamboui.toolkit.elements.FormElement
Enables arrow key navigation between form fields.

arrowNavigation(boolean) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Enables arrow key navigation for this field.

ARROWS - Enum constant in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Rotating arrow spinner.

as(Format) - Method in class dev.tamboui.export.ExportRequest
Selects the export format and returns a step where options and destination can be set.

AS_NEEDED - Enum constant in enum class dev.tamboui.widgets.common.ScrollBarPolicy
Show the scrollbar only when content exceeds the viewport.

ASCII - Enum constant in enum class dev.tamboui.widgets.tree.GuideStyle
ASCII characters: +--, |, +--.

asMillis() - Method in class dev.tamboui.tfx.TFxDuration
Returns the duration in milliseconds.

asPostRenderProcessor() - Method in class dev.tamboui.tfx.toolkit.ToolkitEffects
Creates a post-render processor for use with ToolkitRunner.Builder.

asSecsF32() - Method in class dev.tamboui.tfx.TFxDuration
Returns the duration in seconds as a float.

attr(String, String) - Method in class dev.tamboui.toolkit.element.StyledElement
Sets a style attribute for attribute selector matching.

attribute() - Method in class dev.tamboui.css.selector.AttributeSelector
Returns the attribute name.

AttributeSelector - Class in dev.tamboui.css.selector
An attribute selector that matches elements by their style attributes.

AttributeSelector(String) - Constructor for class dev.tamboui.css.selector.AttributeSelector
Creates an attribute existence selector.

AttributeSelector(String, AttributeSelector.Operator, String) - Constructor for class dev.tamboui.css.selector.AttributeSelector
Creates an attribute selector with an operator and value.

AttributeSelector.Operator - Enum Class in dev.tamboui.css.selector
The operator for attribute matching.

AUTO_SCROLL - Enum constant in enum class dev.tamboui.widgets.list.ScrollMode
Automatically scroll to keep the selected item visible.

autoBindingRegistration(boolean) - Method in class dev.tamboui.tui.TuiRunner.Builder
Enables or disables automatic registration of action handlers.

autoMax() - Method in class dev.tamboui.toolkit.elements.BarChartElement
Uses auto-scaling based on data maximum.

autoMax() - Method in class dev.tamboui.toolkit.elements.SparklineElement
Uses auto-scaling based on data maximum.

autoMax() - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Clears the explicit max, using data maximum instead.

autoMax() - Method in class dev.tamboui.widgets.sparkline.Sparkline.Builder
Clears the explicit maximum value, using data maximum instead.

autoScroll() - Method in class dev.tamboui.toolkit.elements.ListElement

Enables auto-scroll to keep the selected item visible.

autoScroll(boolean) - Method in class dev.tamboui.toolkit.elements.ListElement
Sets whether auto-scroll is enabled.

Axis - Class in dev.tamboui.widgets.chart
An axis configuration for a `Chart`.

Axis.Builder - Class in dev.tamboui.widgets.chart
Builder for `Axis`.

B

b() - Method in class dev.tamboui.style.Color.Rgb
Returns the blue component.

backend() - Method in class dev.tamboui.terminal.Terminal
Returns the backend.

backend() - Method in class dev.tamboui.tui.TuiConfig
Returns the configured backend, or null if not set.

backend() - Method in class dev.tamboui.tui.TuiRunner
Returns the underlying backend.

backend(Backend) - Method in class dev.tamboui.tui.TuiConfig.Builder
Sets the backend to use.

Backend - Interface in dev.tamboui.terminal
Backend interface for terminal operations.

BackendException - Exception Class in dev.tamboui.terminal
Exception for backend errors.

BackendException(String) - Constructor for exception class dev.tamboui.terminal.BackendException
Creates a new backend exception with the given message.

BackendException(String, Throwable) - Constructor for exception class dev.tamboui.terminal.BackendException
Creates a new backend exception with the given message and cause.

BackendFactory - Class in dev.tamboui.terminal
Factory for creating `Backend` instances using the `ServiceLoader` mechanism.

BackendProvider - Interface in dev.tamboui.terminal
Service provider interface for creating `Backend` instances.

background() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the background color, if set.

background(Color) - Method in class dev.tamboui.css.cascade.CssStyleResolver.Builder
Sets the background color.

background(Color) - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Sets the background color programmatically.

background(Color) - Method in class dev.tamboui.widgets.block.Block.Builder
Sets the background color.

background(Color) - Method in class dev.tamboui.widgets.gauge.Gauge.Builder
Sets the background color programmatically.

background(Color) - Method in class dev.tamboui.widgets.gauge.LineGauge.Builder
Sets the background color programmatically.

background(Color) - Method in class dev.tamboui.widgets.input.TextArea.Builder
Sets the background color programmatically.

background(Color) - Method in class dev.tamboui.widgets.input.TextInput.Builder
Sets the background color programmatically.

background(Color) - Method in class dev.tamboui.widgets.paragraph.Paragraph.Builder

Sets the background color.

background(Color) - Method in class dev.tamboui.widgets.table.Table.Builder
Sets the background color programmatically.

background(Color) - Method in class dev.tamboui.widgets.tabs.Tabs.Builder
Sets the background color programmatically.

BACKGROUND - Static variable in class dev.tamboui.style.StandardProperties
The `background` property for background color.

BACKGROUND_COLOR - Static variable in class dev.tamboui.style.StandardProperties
The `background-color` property (alias for background).

backgroundColor(Color) - Method in class dev.tamboui.toolkit.elements.CanvasElement
Sets the background color.

backgroundColor(Color) - Method in class dev.tamboui.widgets.canvas.Canvas.Builder
Sets the background color.

BackIn - Enum constant in enum class dev.tamboui.tfx.Interpolation
Back easing - in

BackInOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Back easing - in-out

BackOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Back easing - out

BACKSPACE - Enum constant in enum class dev.tamboui.tui.event.KeyCode
Backspace key.

Bar - Class in dev.tamboui.widgets.barchart
A single bar in a `BarChart`.

BAR - Enum constant in enum class dev.tamboui.widgets.canvas.Marker
One point per cell in shape of a bar (▄).

BAR - Enum constant in enum class dev.tamboui.widgets.chart.Dataset.Marker
Bar marker: ▄

BAR - Enum constant in enum class dev.tamboui.widgets.chart.GraphType
Renders vertical bars from the X-axis to each data point.

BAR_COLOR - Static variable in class dev.tamboui.widgets.barchart.BarChart
Property key for the default bar color.

Bar.Builder - Class in dev.tamboui.widgets.barchart
Builder for `Bar`.

barChart() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty bar chart.

barChart(long...) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a bar chart with the given values.

BarChart - Class in dev.tamboui.widgets.barchart
A bar chart widget for displaying grouped data.

BarChart.BarSet - Class in dev.tamboui.widgets.barchart
Symbol set for rendering bar fills.

BarChart.Builder - Class in dev.tamboui.widgets.barchart
Builder for `BarChart`.

BarChartElement - Class in dev.tamboui.toolkit.elements
A DSL wrapper for the BarChart widget.

BarChartElement() - Constructor for class dev.tamboui.toolkit.elements.BarChartElement
Creates a new bar chart element with default settings.

barColor(Color) - Method in class dev.tamboui.toolkit.elements.BarChartElement
Sets the bar color.

barColor(Color) - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Sets the default bar color programmatically.

barGap(int) - Method in class dev.tamboui.toolkit.elements.BarChartElement
Sets the gap between bars in a group.

barGap(int) - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Sets the gap between bars in a group (default: 1).

BarGroup - Class in dev.tamboui.widgets.barchart
A group of `Bar`s in a `BarChart`.

BarGroup.Builder - Class in dev.tamboui.widgets.barchart
Builder for `BarGroup`.

bars() - Method in class dev.tamboui.widgets.barchart.BarGroup
Returns the bars in this group.

bars(Bar...) - Method in class dev.tamboui.widgets.barchart.BarGroup.Builder
Sets the bars in this group.

bars(List) - Method in class dev.tamboui.widgets.barchart.BarGroup.Builder
Sets the bars in this group.

barSet(BarChart.BarSet) - Method in class dev.tamboui.toolkit.elements.BarChartElement
Sets the bar character set.

barSet(BarChart.BarSet) - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Sets the bar symbol set.

barSet(Sparkline.BarSet) - Method in class dev.tamboui.toolkit.elements.SparklineElement
Sets the bar character set.

barSet(Sparkline.BarSet) - Method in class dev.tamboui.widgets.sparkline.Sparkline.Builder
Sets the bar symbol set.

BarSet(String, String, String, String, String, String, String, String, String) - Constructor for class dev.tamboui.widgets.barchart.BarChart.BarSet
Creates a new bar set with the given symbols for each fill level.

BarSet(String, String, String, String, String, String, String, String, String) - Constructor for class dev.tamboui.widgets.sparkline.Sparkline.BarSet
Creates a new bar set with the given symbols.

barStyle(Style) - Method in class dev.tamboui.toolkit.elements.BarChartElement
Sets the bar style.

barStyle(Style) - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Sets the default bar style.

barWidth(int) - Method in class dev.tamboui.toolkit.elements.BarChartElement
Sets the bar width.

barWidth(int) - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Sets the bar width (default: 1).

Basic Usage - Section in class dev.tamboui.toolkit.elements.FormElement

Basic Usage - Section in class dev.tamboui.toolkit.elements.FormFieldElement

begin() - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.SymbolSet
Returns the begin marker character.

begin(long, Event, String, int) - Static method in class dev.tamboui.toolkit.jfr.RoutingEvent
Starts a new routing duration event.

beginStyle(Style) - Method in class dev.tamboui.toolkit.elements.ScrollbarElement
Sets the begin marker style.

beginStyle(Style) - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.Builder
Sets the style for the begin marker.

beginSymbol(String) - Method in class dev.tamboui.toolkit.elements.ScrollbarElement
Sets the begin marker symbol.

beginSymbol(String) - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.Builder
Sets the begin marker symbol (e.g., up arrow for vertical scrollbar).

bestProtocol() - Method in class dev.tamboui.image.capability.TerminalImageCapabilities
Returns the best available image protocol implementation.

bestSupport() - Method in class dev.tamboui.image.capability.TerminalImageCapabilities
Returns the best available image support level.

bg() - Method in class dev.tamboui.style.Style
Returns the background color if set.

bg(Color) - Method in class dev.tamboui.style.Style
Returns a new style with the given background color.

bg(Color) - Method in class dev.tamboui.text.Line
Returns a new line with the given background color applied to all spans.

bg(Color) - Method in class dev.tamboui.text.Span
Returns a new span with the given background color.

bg(Color) - Method in class dev.tamboui.text.Text
Returns a new text with the given background color.

bg(Color) - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the background color.

bgCode() - Method in enum class dev.tamboui.style.AnsiColor
Returns the ANSI SGR code for background.

bgColor(Color) - Static method in class dev.tamboui.tfx.CellFilter
Selects cells with a matching background color.

bind(InputTrigger, String) - Method in interface dev.tamboui.tui.bindings.Bindings.Builder
Binds a trigger to an action.

bindings() - Method in class dev.tamboui.toolkit.element.DefaultRenderContext
Returns the current bindings.

bindings() - Method in class dev.tamboui.tui.bindings.ActionHandler
Returns the current bindings.

bindings() - Method in class dev.tamboui.tui.event.KeyEvent
Returns the bindings associated with this event.

bindings() - Method in class dev.tamboui.tui.event.MouseEvent
Returns the bindings associated with this event.

bindings() - Method in class dev.tamboui.tui.InlineTuiConfig
Returns the key bindings for semantic action matching.

bindings() - Method in class dev.tamboui.tui.TuiConfig
Returns the bindings used for semantic action matching.

bindings(Bindings) - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner.Builder
Sets the key bindings.

bindings(Bindings) - Method in class dev.tamboui.toolkit.app.ToolkitRunner.Builder
Sets the bindings to use for action matching.

bindings(Bindings) - Method in class dev.tamboui.tui.InlineTuiConfig.Builder
Sets the key bindings for semantic action matching.

bindings(Bindings) - Method in class dev.tamboui.tui.TuiConfig.Builder
Sets the bindings for semantic action matching.

bindings(Bindings) - Method in class dev.tamboui.tui.TuiRunner.Builder
Sets the bindings to use for action matching.

Bindings - Interface in dev.tamboui.tui.bindings

Maps input events to semantic actions.

Bindings.Builder - Interface in dev.tamboui.tui.bindings
Builder for creating custom bindings.

BindingSets - Class in dev.tamboui.tui.bindings
Factory for predefined binding sets.

black() - Method in class dev.tamboui.style.Style
Shorthand for `Style.fg(Color)` with `Color.BLACK`.

black() - Method in class dev.tamboui.text.Span
Returns a new span with black foreground color.

black() - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the foreground color to black.

BLACK - Enum constant in enum class dev.tamboui.style.AnsiColor
Black (palette index 0).

BLACK - Static variable in interface dev.tamboui.style.Color
Black.

block() - Method in class dev.tamboui.image.Image
Returns the block wrapper, if any.

block() - Method in class dev.tamboui.toolkit.elements.CanvasElement
Uses block marker.

block(Block) - Method in class dev.tamboui.image.Image.Builder
Wraps the image in a block (for borders, titles, etc.).

block(Block) - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Wraps the chart in a block.

block(Block) - Method in class dev.tamboui.widgets.calendar.Monthly
Returns a new calendar wrapped in a block.

block(Block) - Method in class dev.tamboui.widgets.calendar.Monthly.Builder
Wraps the calendar in a block.

block(Block) - Method in class dev.tamboui.widgets.canvas.Canvas.Builder
Wraps the canvas in a block.

block(Block) - Method in class dev.tamboui.widgets.chart.Chart.Builder
Wraps the chart in a block.

block(Block) - Method in class dev.tamboui.widgets.gauge.Gauge.Builder
Wraps the gauge in a block container.

block(Block) - Method in class dev.tamboui.widgets.input.TextArea.Builder
Wraps the text area in a block.

block(Block) - Method in class dev.tamboui.widgets.input.TextInput.Builder
Wraps the text input in a block.

block(Block) - Method in class dev.tamboui.widgets.list.ListWidget.Builder
Wraps the list in a block.

block(Block) - Method in class dev.tamboui.widgets.paragraph.Paragraph.Builder
Wraps the paragraph in a block.

block(Block) - Method in class dev.tamboui.widgets.sparkline.Sparkline.Builder
Wraps the sparkline in a block.

block(Block) - Method in class dev.tamboui.widgets.table.Table.Builder
Wraps the table in a block.

block(Block) - Method in class dev.tamboui.widgets.tabs.Tabs.Builder
Wraps the tabs in a block.

block(Block) - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Wraps the tree in a block.

Block - Class in dev.tamboui.widgets.block
A block is a container widget with optional borders and titles.

BLOCK - Enum constant in enum class dev.tamboui.widgets.canvas.Marker
One point per cell in shape of a block (█).

BLOCK - Enum constant in enum class dev.tamboui.widgets.chart.Dataset.Marker
Block marker: ▮

Block.Builder - Class in dev.tamboui.widgets.block
Builder for `Block`.

blue() - Method in class dev.tamboui.style.Style
Shorthand for `Style.fg(Color)` with `Color.BLUE`.

blue() - Method in class dev.tamboui.text.Span
Returns a new span with blue foreground color.

blue() - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the foreground color to blue.

blue(int) - Static method in class dev.tamboui.image.ImageData
Returns the blue component of a pixel (0-255).

BLUE - Enum constant in enum class dev.tamboui.style.AnsiColor
Blue (palette index 4).

BLUE - Static variable in interface dev.tamboui.style.Color
Blue.

bold() - Method in class dev.tamboui.style.Style
Enables bold text.

bold() - Method in class dev.tamboui.text.Line
Returns a new line with bold applied to all spans.

bold() - Method in class dev.tamboui.text.Span
Returns a new span with bold style.

bold() - Method in class dev.tamboui.text.Text
Returns a new text with bold style.

bold() - Method in class dev.tamboui.toolkit.element.StyledElement
Applies the bold modifier.

BOLD - Enum constant in enum class dev.tamboui.style.Modifier
Bold text.

booleanField(String) - Method in class dev.tamboui.widgets.form.FormState
Returns the BooleanFieldState for the given field name.

booleanField(String) - Method in class dev.tamboui.widgets.form.FormState.Builder
Adds a boolean field with false as the initial value.

booleanField(String, boolean) - Method in class dev.tamboui.widgets.form.FormState.Builder
Adds a boolean field with the given initial value.

BooleanFieldState - Class in dev.tamboui.widgets.form
State for a boolean form field (checkbox or toggle).

BooleanFieldState() - Constructor for class dev.tamboui.widgets.form.BooleanFieldState
Creates a new boolean field state with false as the initial value.

BooleanFieldState(boolean) - Constructor for class dev.tamboui.widgets.form.BooleanFieldState
Creates a new boolean field state with the given initial value.

booleanValue(String) - Method in class dev.tamboui.widgets.form.FormState
Returns the current boolean value for the given field name.

booleanValues() - Method in class dev.tamboui.widgets.form.FormState
Returns all boolean field values as a map.

BORDER_BOTTOM - Static variable in class dev.tamboui.widgets.block.Block

The `border-bottom` property for the bottom horizontal border character.

BORDER_BOTTOM_LEFT - Static variable in class dev.tamboui.widgets.block.Block
The `border-bottom-left` property for the bottom-left corner character.

BORDER_BOTTOM_RIGHT - Static variable in class dev.tamboui.widgets.block.Block
The `border-bottom-right` property for the bottom-right corner character.

BORDER_CHARS - Static variable in class dev.tamboui.widgets.block.Block
The `border-chars` property for custom border character sets.

BORDER_COLOR - Static variable in class dev.tamboui.widgets.block.Block
The `border-color` property.

BORDER_LEFT - Static variable in class dev.tamboui.widgets.block.Block
The `border-left` property for the left vertical border character.

BORDER_RIGHT - Static variable in class dev.tamboui.widgets.block.Block
The `border-right` property for the right vertical border character.

BORDER_TOP - Static variable in class dev.tamboui.widgets.block.Block
The `border-top` property for the top horizontal border character.

BORDER_TOP_LEFT - Static variable in class dev.tamboui.widgets.block.Block
The `border-top-left` property for the top-left corner character.

BORDER_TOP_RIGHT - Static variable in class dev.tamboui.widgets.block.Block
The `border-top-right` property for the top-right corner character.

BORDER_TYPE - Static variable in class dev.tamboui.widgets.block.Block
The `border-type` property for border style.

borderBottom() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the bottom border character, if set.

borderBottomLeft() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the bottom-left corner character, if set.

borderBottomRight() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the bottom-right corner character, if set.

BorderCharConverter - Class in dev.tamboui.style
Converter for border character properties.

borderChars() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the border-chars string, if set.

borderColor() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the border color, if set.

borderColor(Color) - Method in class dev.tamboui.toolkit.elements.BarChartElement
Sets the border color.

borderColor(Color) - Method in class dev.tamboui.toolkit.elements.CalendarElement
Sets the border color.

borderColor(Color) - Method in class dev.tamboui.toolkit.elements.CanvasElement
Sets the border color.

borderColor(Color) - Method in class dev.tamboui.toolkit.elements.ChartElement
Sets the border color.

borderColor(Color) - Method in class dev.tamboui.toolkit.elements.DialogElement
Sets the border color.

borderColor(Color) - Method in class dev.tamboui.toolkit.elements.FormElement
Sets the border color for all field inputs.

borderColor(Color) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Sets the border color for the input.

borderColor(Color) - Method in class dev.tamboui.toolkit.elements.GaugeElement

Sets the border color.

borderColor(Color) - Method in class dev.tamboui.toolkit.elements.ListElement
Sets the border color.

borderColor(Color) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Sets the border color.

borderColor(Color) - Method in class dev.tamboui.toolkit.elements.Panel
Sets the border color.

borderColor(Color) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Sets the border color.

borderColor(Color) - Method in class dev.tamboui.toolkit.elements.SparklineElement
Sets the border color.

borderColor(Color) - Method in class dev.tamboui.toolkit.elements.TableElement
Sets the border color.

borderColor(Color) - Method in class dev.tamboui.toolkit.elements.TabsElement
Sets the border color.

borderColor(Color) - Method in class dev.tamboui.toolkit.elements.TextAreaElement
Sets the border color.

borderColor(Color) - Method in class dev.tamboui.toolkit.elements.TextInputElement
Sets the border color.

borderColor(Color) - Method in class dev.tamboui.toolkit.elements.TreeElement
Sets the border color.

borderColor(Color) - Method in class dev.tamboui.widgets.block.Block.Builder
Sets the border color.

borderColor(Color) - Method in class dev.tamboui.widgets.error.ErrorDisplay.Builder
Sets the border color.

bordered() - Static method in class dev.tamboui.widgets.block.Block
Creates a block with all borders enabled.

borderLeft() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the left border character, if set.

borderless() - Method in class dev.tamboui.toolkit.elements.Panel
Makes this panel borderless.

borderRight() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the right border character, if set.

borders(EnumSet) - Method in class dev.tamboui.widgets.block.Block.Builder
Sets the borders to draw.

Borders - Enum Class in dev.tamboui.widgets.block
Which borders to draw on a block.

BorderSet - Class in dev.tamboui.widgets.block
Characters used to draw a border.

BorderSet(String, String, String, String, String, String, String, String) - Constructor for class dev.tamboui.widgets.block.BorderSet
Creates a border set with separate characters for each side.

BorderSet.Builder - Class in dev.tamboui.widgets.block
Builder for BorderSet.

BorderSetConverter - Class in dev.tamboui.css.property
Converts CSS border-chars values to BorderSet.

borderStyle(Style) - Method in class dev.tamboui.widgets.block.Block.Builder
Sets the border style.

borderTop() - Method in class dev.tamboui.css.cascade.CssStyleResolver

Returns the top border character, if set.

borderTopLeft() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the top-left corner character, if set.

borderTopRight() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the top-right corner character, if set.

borderType() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the border type, if set.

borderType(BorderType) - Method in class dev.tamboui.css.cascade.CssStyleResolver.Builder
Sets the border type.

borderType(BorderType) - Method in class dev.tamboui.toolkit.elements.DialogElement
Sets the border type.

borderType(BorderType) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Sets the border type.

borderType(BorderType) - Method in class dev.tamboui.toolkit.elements.Panel
Sets the border type.

borderType(BorderType) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Sets the border type.

borderType(BorderType) - Method in class dev.tamboui.widgets.block.Block.Builder
Sets the border type.

BorderType - Enum Class in dev.tamboui.widgets.block
Type of border to draw.

BorderTypeConverter - Class in dev.tamboui.css.property
Converts CSS border-type values to BorderType enum.

BorderTypeConverter - Class in dev.tamboui.widgets.block
Converts string values to `BorderType` enum values.

bottom() - Method in class dev.tamboui.layout.Margin
Returns the bottom margin.

bottom() - Method in class dev.tamboui.layout.Padding
Returns the bottom padding.

bottom() - Method in class dev.tamboui.layout.Rect
Returns the bottom edge (exclusive).

bottom(Element) - Method in class dev.tamboui.toolkit.elements.DockElement
Sets the bottom region element.

bottom(Element, Constraint) - Method in class dev.tamboui.toolkit.elements.DockElement
Sets the bottom region element with a height constraint.

bottom(Widget) - Method in class dev.tamboui.layout.dock.Dock.Builder
Sets the bottom region widget.

BOTTOM - Enum constant in enum class dev.tamboui.widgets.block.Borders
Bottom border.

BOTTOM - Enum constant in enum class dev.tamboui.widgets.chart.LegendPosition
Bottom center

BOTTOM_CENTER - Enum constant in enum class dev.tamboui.layout.ContentAlignment
Bottom center.

BOTTOM_LEFT - Enum constant in enum class dev.tamboui.layout.ContentAlignment
Bottom-left corner.

BOTTOM_LEFT - Enum constant in enum class dev.tamboui.widgets.chart.LegendPosition
Bottom left corner

BOTTOM_LEFT_TO_TOP_RIGHT - Enum constant in enum class
dev.tamboui.tfx.pattern.DiagonalPattern.DiagonalDirection

Sweeps diagonally from bottom-left corner to top-right corner

BOTTOM_ONLY - Static variable in enum class dev.tamboui.widgets.block.Borders
Bottom border only.

BOTTOM_RIGHT - Enum constant in enum class dev.tamboui.layout.ContentAlignment
Bottom-right corner.

BOTTOM_RIGHT - Enum constant in enum class dev.tamboui.widgets.chart.LegendPosition
Bottom right corner

BOTTOM_RIGHT_TO_TOP_LEFT - Enum constant in enum class dev.tamboui.tfx.pattern.DiagonalPattern.DiagonalDirection
Sweeps diagonally from bottom-right corner to top-left corner

bottomHeight(Constraint) - Method in class dev.tamboui.layout.dock.Dock.Builder
Sets the height constraint for the bottom region.

bottomHeight(Constraint) - Method in class dev.tamboui.toolkit.elements.DockElement
Sets the height constraint for the bottom region.

bottomHorizontal() - Method in class dev.tamboui.widgets.block.BorderSet
Returns the bottom horizontal border character.

bottomHorizontal(String) - Method in class dev.tamboui.widgets.block.BorderSet.Builder
Sets the bottom horizontal border character.

bottomLeft() - Method in class dev.tamboui.widgets.block.BorderSet
Returns the bottom-left corner character.

bottomLeft(String) - Method in class dev.tamboui.widgets.block.BorderSet.Builder
Sets the bottom-left corner character.

bottomLeftToTopRight() - Static method in class dev.tamboui.tfx.pattern.DiagonalPattern
Creates a diagonal pattern from bottom-left to top-right.

bottomMargin() - Method in class dev.tamboui.widgets.table.Row
Returns the bottom margin of this row.

bottomMargin(int) - Method in class dev.tamboui.widgets.table.Row
Returns a new row with the given bottom margin.

bottomRight() - Method in class dev.tamboui.widgets.block.BorderSet
Returns the bottom-right corner character.

bottomRight(String) - Method in class dev.tamboui.widgets.block.BorderSet.Builder
Sets the bottom-right corner character.

bottomRightToTopLeft() - Static method in class dev.tamboui.tfx.pattern.DiagonalPattern
Creates a diagonal pattern from bottom-right to top-left.

bottomTitle(Line) - Method in class dev.tamboui.toolkit.elements.Panel
Sets the bottom title with styled text.

bottomTitle(String) - Method in class dev.tamboui.toolkit.elements.Panel
Sets the bottom title.

BounceIn - Enum constant in enum class dev.tamboui.tfx.Interpolation
Bounce easing - in

BounceInOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Bounce easing - in-out

BounceOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Bounce easing - out

BOUNCING_BALL - Enum constant in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Bouncing ball spinner.

BOUNCING_BAR - Enum constant in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Bouncing bar spinner.

bounds() - Method in class dev.tamboui.widgets.chart.Axis

Returns the axis bounds [min, max].

bounds(double[]) - Method in class dev.tamboui.widgets.chart.Axis.Builder
Sets the axis bounds.

bounds(double, double) - Method in class dev.tamboui.widgets.chart.Axis.Builder
Sets the axis bounds [min, max].

bounds(double, double, double, double) - Method in class dev.tamboui.toolkit.elements.CanvasElement
Sets both axis bounds.

bounds(double, double, double, double) - Method in class dev.tamboui.toolkit.elements.ChartElement
Sets both axis bounds.

boundsFor(String) - Method in class dev.tamboui.layout.grid.GridArea
Returns the bounds for a named area.

braille() - Method in class dev.tamboui.toolkit.elements.CanvasElement
Uses Braille marker (highest resolution).

BRAILLE - Enum constant in enum class dev.tamboui.image.capability.TerminalImageProtocol
Unicode Braille pattern fallback.

BRAILLE - Enum constant in enum class dev.tamboui.widgets.canvas.Marker
Uses Unicode Braille Patterns for high-resolution rendering.

BRAILLE - Enum constant in enum class dev.tamboui.widgets.chart.Dataset.Marker
Braille patterns for high-resolution plotting

BrailleProtocol - Class in dev.tamboui.image.protocol
Renders images using Unicode Braille patterns.

BrailleProtocol() - Constructor for class dev.tamboui.image.protocol.BrailleProtocol
Creates a new Braille protocol instance with default percentile threshold.

BrailleProtocol(int) - Constructor for class dev.tamboui.image.protocol.BrailleProtocol
Creates a new Braille protocol instance with a custom percentile threshold.

branch() - Method in enum class dev.tamboui.widgets.tree.GuideStyle
Returns the branch connector string (for non-last children).

BRIGHT_BLACK - Enum constant in enum class dev.tamboui.style.AnsiColor
Bright black (palette index 8).

BRIGHT_BLUE - Enum constant in enum class dev.tamboui.style.AnsiColor
Bright blue (palette index 12).

BRIGHT_CYAN - Enum constant in enum class dev.tamboui.style.AnsiColor
Bright cyan (palette index 14).

BRIGHT_GREEN - Enum constant in enum class dev.tamboui.style.AnsiColor
Bright green (palette index 10).

BRIGHT_MAGENTA - Enum constant in enum class dev.tamboui.style.AnsiColor
Bright magenta (palette index 13).

BRIGHT_RED - Enum constant in enum class dev.tamboui.style.AnsiColor
Bright red (palette index 9).

BRIGHT_WHITE - Enum constant in enum class dev.tamboui.style.AnsiColor
Bright white (palette index 15).

BRIGHT_WHITE - Static variable in interface dev.tamboui.style.Color
Bright white.

BRIGHT_YELLOW - Enum constant in enum class dev.tamboui.style.AnsiColor
Bright yellow (palette index 11).

BRKINT - Static variable in class dev.tamboui.backend.panama.unix.LibC
Input flag: signal interrupt on break.

BRKINT - Static variable in class dev.tamboui.backend.panama.unix.PlatformConstants
Input flag: signal interrupt on break.

buffer() - Method in class dev.tamboui.backend.panama.ByteArrayBuilder
Returns the internal buffer.

buffer() - Method in class dev.tamboui.terminal.CompletedFrame
Returns the rendered buffer.

buffer() - Method in class dev.tamboui.terminal.Frame
Returns the underlying buffer.

Buffer - Class in dev.tamboui.buffer
A buffer that stores cells for a rectangular area.

build() - Method in class dev.tamboui.capability.CapabilityReportBuilder
Builds the capability report from the accumulated data.

build() - Method in class dev.tamboui.css.cascade.CssStyleResolver.Builder
Builds the CssStyleResolver.

build() - Method in class dev.tamboui.css.cascade.TypedPropertyMap.Builder
Builds the typed property map.

build() - Method in class dev.tamboui.image.Image.Builder
Builds the image widget.

build() - Method in class dev.tamboui.layout.columns.Columns.Builder
Builds the `Columns` widget.

build() - Method in class dev.tamboui.layout.dock.Dock.Builder
Builds the `Dock` widget.

build() - Method in class dev.tamboui.layout.flow.Flow.Builder
Builds the `Flow` widget.

build() - Method in class dev.tamboui.layout.grid.Grid.AreaBuilder
Builds the `Grid` widget.

build() - Method in class dev.tamboui.layout.grid.Grid.ChildrenBuilder
Builds the `Grid` widget.

build() - Method in class dev.tamboui.layout.stack.Stack.Builder
Builds the `Stack` widget.

build() - Method in class dev.tamboui.style.PropertyDefinition.Builder
Builds the property definition.

build() - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner.Builder
Builds and returns a configured InlineToolkitRunner.

build() - Method in class dev.tamboui.toolkit.app.ToolkitRunner.Builder
Builds and returns a configured ToolkitRunner.

build() - Method in interface dev.tamboui.tui.bindings.Bindings.Builder
Builds the bindings.

build() - Method in class dev.tamboui.tui.InlineTuiConfig.Builder
Builds the configuration.

build() - Method in class dev.tamboui.tui.TuiConfig.Builder
Builds the configuration.

build() - Method in class dev.tamboui.tui.TuiRunner.Builder
Builds the TuiRunner and returns an instance ready to run.

build() - Method in class dev.tamboui.widgets.barchart.Bar.Builder
Builds the bar.

build() - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Builds the bar chart.

build() - Method in class dev.tamboui.widgets.barchart.BarGroup.Builder
Builds the bar group.

build() - Method in class dev.tamboui.widgets.block.Block.Builder

Builds the block.

build() - Method in class dev.tamboui.widgets.block.BorderSet.Builder
Builds the BorderSet.

build() - Method in class dev.tamboui.widgets.calendar.Monthly.Builder
Builds the calendar.

build() - Method in class dev.tamboui.widgets.canvas.Canvas.Builder
Builds the canvas.

build() - Method in class dev.tamboui.widgets.chart.Axis.Builder
Builds the axis.

build() - Method in class dev.tamboui.widgets.chart.Chart.Builder
Builds the chart.

build() - Method in class dev.tamboui.widgets.chart.Dataset.Builder
Builds the dataset.

build() - Method in class dev.tamboui.widgets.checkbox.Checkbox.Builder
Builds the Checkbox instance.

build() - Method in class dev.tamboui.widgets.error.ErrorDisplay.Builder
Builds the ErrorDisplay.

build() - Method in class dev.tamboui.widgets.form.FormState.Builder
Builds the FormState.

build() - Method in class dev.tamboui.widgets.gauge.Gauge.Builder
Builds the gauge.

build() - Method in class dev.tamboui.widgets.gauge.LineGauge.Builder
Builds the line gauge.

build() - Method in class dev.tamboui.widgets.input.TextArea.Builder
Builds the text area.

build() - Method in class dev.tamboui.widgets.input.TextInput.Builder
Builds the text input.

build() - Method in class dev.tamboui.widgets.list.ListWidget.Builder
Builds the ListWidget.

build() - Method in class dev.tamboui.widgets.paragraph.Paragraph.Builder
Builds the paragraph.

build() - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.Builder
Builds the scrollbar.

build() - Method in class dev.tamboui.widgets.select.Select.Builder
Builds the Select instance.

build() - Method in class dev.tamboui.widgets.sparkline.Sparkline.Builder
Builds the sparkline.

build() - Method in class dev.tamboui.widgets.spinner.Spinner.Builder
Builds the Spinner widget.

build() - Method in class dev.tamboui.widgets.spinner.SpinnerFrameSet.Builder
Builds the SpinnerFrameSet.

build() - Method in class dev.tamboui.widgets.table.Table.Builder
Builds the table.

build() - Method in class dev.tamboui.widgets.tabs.Tabs.Builder
Builds the tabs.

build() - Method in class dev.tamboui.widgets.toggle.Toggle.Builder
Builds the Toggle instance.

build() - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Builds the TreeWidget.

build() - Method in class dev.tamboui.widgets.wavetext.WaveText.Builder
Builds the WaveText widget.

builder() - Static method in class dev.tamboui.css.cascade.CssStyleResolver
Creates a new builder.

builder() - Static method in class dev.tamboui.css.cascade.TypedPropertyMap
Creates a new builder for a typed property map.

builder() - Static method in class dev.tamboui.image.Image
Creates a new image builder.

builder() - Static method in class dev.tamboui.layout.columns.Columns
Creates a new builder.

builder() - Static method in class dev.tamboui.layout.dock.Dock
Creates a new builder.

builder() - Static method in class dev.tamboui.layout.flow.Flow
Creates a new builder.

builder() - Static method in class dev.tamboui.layout.grid.Grid
Creates a new builder.

builder() - Static method in class dev.tamboui.layout.stack.Stack
Creates a new builder.

builder() - Static method in class dev.tamboui.toolkit.app.ToolkitRunner
Creates a builder for configuring a ToolkitRunner.

builder() - Static method in class dev.tamboui.tui.bindings.DefaultBindings
Creates a new builder for constructing bindings.

builder() - Static method in class dev.tamboui.tui.TuiConfig
Returns a new builder with default values.

builder() - Static method in class dev.tamboui.tui.TuiRunner
Returns a new builder for constructing TuiRunner instances.

builder() - Static method in class dev.tamboui.widgets.barchart.Bar
Creates a new bar builder.

builder() - Static method in class dev.tamboui.widgets.barchart.BarChart
Creates a new bar chart builder.

builder() - Static method in class dev.tamboui.widgets.barchart.BarGroup
Creates a new bar group builder.

builder() - Static method in class dev.tamboui.widgets.block.Block
Creates a new block builder.

builder() - Static method in class dev.tamboui.widgets.block.BorderSet
Creates a new builder for BorderSet.

builder() - Static method in class dev.tamboui.widgets.canvas.Canvas
Creates a new canvas builder.

builder() - Static method in class dev.tamboui.widgets.chart.Axis
Creates a new axis builder.

builder() - Static method in class dev.tamboui.widgets.chart.Chart
Creates a new chart builder.

builder() - Static method in class dev.tamboui.widgets.chart.Dataset
Creates a new dataset builder.

builder() - Static method in class dev.tamboui.widgets.checkbox.Checkbox
Creates a new builder for Checkbox.

builder() - Static method in class dev.tamboui.widgets.error.ErrorDisplay
Creates a new builder.

builder() - Static method in class dev.tamboui.widgets.form.FormState

Creates a new builder for constructing a FormState.

builder() - Static method in class dev.tamboui.widgets.gauge.Gauge
Creates a new gauge builder.

builder() - Static method in class dev.tamboui.widgets.gauge.LineGauge
Creates a new line gauge builder.

builder() - Static method in class dev.tamboui.widgets.input.TextArea
Creates a new text area builder.

builder() - Static method in class dev.tamboui.widgets.input.TextInput
Creates a new text input builder.

builder() - Static method in class dev.tamboui.widgets.list.ListWidget
Creates a new builder for ListWidget.

builder() - Static method in class dev.tamboui.widgets.paragraph.Paragraph
Creates a new paragraph builder.

builder() - Static method in class dev.tamboui.widgets.scrollbar.Scrollbar
Creates a new scrollbar builder.

builder() - Static method in class dev.tamboui.widgets.select.Select
Creates a new builder for Select.

builder() - Static method in class dev.tamboui.widgets.sparkline.Sparkline
Creates a new sparkline builder.

builder() - Static method in class dev.tamboui.widgets.spinner.Spinner
Creates a new builder for Spinner.

builder() - Static method in class dev.tamboui.widgets.spinner.SpinnerFrameSet
Creates a new builder for SpinnerFrameSet.

builder() - Static method in class dev.tamboui.widgets.table.Table
Creates a new table builder.

builder() - Static method in class dev.tamboui.widgets.tabs.Tabs
Creates a new tabs builder.

builder() - Static method in class dev.tamboui.widgets.toggle.Toggle
Creates a new builder for Toggle.

builder() - Static method in class dev.tamboui.widgets.tree.TreeWidget
Creates a new builder for TreeWidget.

builder() - Static method in class dev.tamboui.widgets.wavetext.WaveText
Creates a new builder for WaveText.

builder(int) - Static method in class dev.tamboui.toolkit.app.InlineToolkitRunner
Returns a builder for configuring an InlineToolkitRunner.

builder(int) - Static method in class dev.tamboui.tui.InlineTuiConfig
Returns a builder for creating custom configurations.

builder(String, PropertyConverter) - Static method in class dev.tamboui.style.PropertyDefinition
Creates a new builder for a property definition.

builder(LocalDate, DateStyler) - Static method in class dev.tamboui.widgets.calendar.Monthly
Creates a builder for a calendar displaying the given month.

bulletStyle() - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Sets the checkbox to use bullet-style symbols (● / ○).

button() - Method in class dev.tamboui.tui.event.MouseEvent
Returns the button involved in the event.

byName(String) - Static method in class dev.tamboui.style.PropertyRegistry
Looks up a property definition by name.

byName(String) - Static method in class dev.tamboui.style.StandardProperties
Looks up a property definition by its name.

ByteArrayBuilder - Class in dev.tamboui.backend.panama
Efficient byte array builder optimized for terminal output.

ByteArrayBuilder(int) - Constructor for class dev.tamboui.backend.panama.ByteArrayBuilder
Creates a new ByteArrayBuilder with the specified initial capacity.

C

calendar() - Static method in class dev.tamboui.toolkit.Toolkit
Creates a calendar showing the current month.

calendar(LocalDate) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a calendar showing the given date's month.

CalendarElement - Class in dev.tamboui.toolkit.elements
A DSL wrapper for the Monthly calendar widget.

CalendarElement() - Constructor for class dev.tamboui.toolkit.elements.CalendarElement
Creates a new calendar element for the current month.

CalendarElement(LocalDate) - Constructor for class dev.tamboui.toolkit.elements.CalendarElement
Creates a new calendar element for the month of the given date.

CalendarEventStore - Class in dev.tamboui.widgets.calendar
A simple `DateStyler` implementation backed by a `HashMap`.

call() - Method in class dev.tamboui.picocli.TuiCommand

cancel() - Method in class dev.tamboui.toolkit.app.ToolkitRunner.ScheduledAction
Cancels the scheduled action.

CANCEL - Static variable in class dev.tamboui.tui.bindings.Actions
Cancel (Escape, emacs Ctrl+g, etc.).

CandidateEvent - Class in dev.tamboui.toolkit.jfr
JFR event emitted for each element candidate considered during event routing.

canScrollDown() - Method in class dev.tamboui.style.RichTextState
Returns true if there is content below the current viewport.

canScrollLeft() - Method in class dev.tamboui.style.RichTextState
Returns true if there is content to the left of the current viewport.

canScrollRight() - Method in class dev.tamboui.style.RichTextState
Returns true if there is content to the right of the current viewport.

canScrollUp() - Method in class dev.tamboui.style.RichTextState
Returns true if there is content above the current viewport.

canvas() - Static method in class dev.tamboui.toolkit.Toolkit
Creates a canvas with default bounds (0.0-1.0).

canvas(double, double, double, double) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a canvas with the given bounds.

Canvas - Class in dev.tamboui.widgets.canvas
A widget for drawing arbitrary shapes on a terminal grid.

Canvas.Builder - Class in dev.tamboui.widgets.canvas
Builder for `Canvas`.

CanvasElement - Class in dev.tamboui.toolkit.elements
A DSL wrapper for the Canvas widget.

CanvasElement() - Constructor for class dev.tamboui.toolkit.elements.CanvasElement
Creates a new canvas element with default bounds and Braille marker.

Capabilities - Class in dev.tamboui.capability
Convenience entrypoints for capability inspection.

CapabilityProvider - Interface in dev.tamboui.capability

Service-provider interface (SPI) for contributing capability information.

CapabilityReport - Class in dev.tamboui.capability
Aggregated capability information from all discovered `CapabilityProvider`s.

CapabilityReportBuilder - Class in dev.tamboui.capability
Builder for assembling a `CapabilityReport`.

CapabilityReportBuilder() - Constructor for class dev.tamboui.capability.CapabilityReportBuilder
Creates a new empty builder.

capacity() - Method in class dev.tamboui.buffer.DiffResult
Returns the current capacity of the internal arrays.

carriageReturn() - Method in class dev.tamboui.backend.aesh.AeshBackend

carriageReturn() - Method in class dev.tamboui.backend.jline3.JLineBackend

carriageReturn() - Method in class dev.tamboui.backend.panama.PanamaBackend

carriageReturn() - Method in interface dev.tamboui.terminal.Backend
Moves the cursor to the beginning of the current line (carriage return).

Cascade Order - Section in class dev.tamboui.css.engine.StyleEngine

CascadeResolver - Class in dev.tamboui.css.cascade
Resolves CSS cascade and specificity to produce final computed styles.

CascadeResolver() - Constructor for class dev.tamboui.css.cascade.CascadeResolver
Creates a new cascade resolver with default behavior (IGNORE unknown properties).

CascadeResolver(UnknownPropertyBehavior) - Constructor for class dev.tamboui.css.cascade.CascadeResolver
Creates a new cascade resolver with the specified unknown property behavior.

CassowaryConstraint - Class in dev.tamboui.layout.cassowary
A constraint in the Cassowary system.

CassowaryConstraint(Expression, Relation, Strength) - Constructor for class dev.tamboui.layout.cassowary.CassowaryConstraint
Creates a new constraint.

cause() - Method in class dev.tamboui.toolkit.elements.ErrorPlaceholder
Returns the exception that caused this placeholder.

cause() - Method in class dev.tamboui.tui.error.RenderError
Returns the original exception that caused the error.

ceil(float) - Static method in class dev.tamboui.tfx.TFxMath
Returns the smallest integer value greater than or equal to the argument.

cell() - Method in class dev.tamboui.tfx.CellIterator.CellEntry
Returns the cell value of this entry.

cell() - Method in class dev.tamboui.tfx.CellIterator.MutableCell
Returns the current cell value.

Cell - Class in dev.tamboui.buffer
A single cell in the terminal buffer.

Cell - Class in dev.tamboui.widgets.table
A cell in a `Table`.

Cell(String, Style) - Constructor for class dev.tamboui.buffer.Cell
Creates a cell with the given symbol and style.

cellFilter() - Method in class dev.tamboui.tfx.effects.DissolveShader

cellFilter() - Method in class dev.tamboui.tfx.effects.ExpandShader

cellFilter() - Method in class dev.tamboui.tfx.effects.FadeShader

cellFilter() - Method in class dev.tamboui.tfx.effects.PaintShader

cellFilter() - Method in class dev.tamboui.tfx.effects.ParallelEffect

cellFilter() - Method in class dev.tamboui.tfx.effects.SequentialEffect

cellFilter() - Method in class dev.tamboui.tfx.effects.SlideShader

cellFilter() - Method in class dev.tamboui.tfx.effects.StretchShader

cellFilter() - Method in class dev.tamboui.tfx.effects.SweepShader

cellFilter() - Method in interface dev.tamboui.tfx.Shader
Returns the cell filter for this shader, or null if none.

CellFilter - Class in dev.tamboui.tfx
A filter that enables effects to operate on specific cells based on various criteria.

CellIterator - Class in dev.tamboui.tfx
An iterator over terminal cells within a rectangular area.

CellIterator(Buffer, Rect) - Constructor for class dev.tamboui.tfx.CellIterator
Creates a new CellIterator over the specified area of a buffer.

CellIterator(Buffer, Rect, CellFilter) - Constructor for class dev.tamboui.tfx.CellIterator
Creates a new CellIterator over the specified area of a buffer with filtering.

CellIterator.CellEntry - Class in dev.tamboui.tfx
Represents a cell entry with its position and value.

CellIterator.CellMutator - Interface in dev.tamboui.tfx
A functional interface for mutating cells with primitive coordinates.

CellIterator.MutableCell - Class in dev.tamboui.tfx
A mutable cell wrapper that allows modifying cells in the buffer.

cells() - Method in class dev.tamboui.widgets.table.Row
Returns the cells in this row.

center() - Static method in class dev.tamboui.tfx.pattern.RadialPattern
Creates a radial pattern centered at the middle of the area.

center(Element) - Method in class dev.tamboui.toolkit.elements.DockElement
Sets the center region element.

center(Widget) - Method in class dev.tamboui.layout.dock.Dock.Builder
Sets the center region widget.

CENTER - Enum constant in enum class dev.tamboui.layout.Alignment
Center-aligned.

CENTER - Enum constant in enum class dev.tamboui.layout.ContentAlignment
Center (both horizontal and vertical).

CENTER - Enum constant in enum class dev.tamboui.layout.Flex
Center elements.

CENTER_LEFT - Enum constant in enum class dev.tamboui.layout.ContentAlignment
Center-left.

CENTER_RIGHT - Enum constant in enum class dev.tamboui.layout.ContentAlignment
Center-right.

centered() - Method in class dev.tamboui.text.Line
Returns a new line with center alignment.

centered() - Method in class dev.tamboui.text.Text
Returns a new text with center alignment.

centered() - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement

Centers the text horizontally.

centered() - Method in class dev.tamboui.toolkit.elements.MarkupTextElement
Centers the text horizontally.

centered() - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Centers the text horizontally.

centered() - Method in class dev.tamboui.toolkit.elements.RichTextElement
Centers the text horizontally.

centered() - Method in class dev.tamboui.toolkit.elements.TextElement
Centers the text horizontally.

centered() - Method in class dev.tamboui.widgets.block.Title
Returns a new center-aligned title.

centered() - Method in class dev.tamboui.widgets.paragraph.Paragraph.Builder
Sets center alignment.

ch(char) - Static method in class dev.tamboui.tui.bindings.KeyTrigger
Creates a trigger for a character (case-sensitive).

CHAR - Enum constant in enum class dev.tamboui.tui.event.KeyCode
Regular printable character - check `KeyEvent.character()`

character() - Method in class dev.tamboui.tui.event.KeyEvent
Returns the character for `KeyCode.CHAR` events, or `'\0'` otherwise.

chars() - Method in class dev.tamboui.style.Width
Returns the fixed character count.

chart() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty chart.

Chart - Class in dev.tamboui.widgets.chart
A chart widget for plotting datasets in a cartesian coordinate system.

Chart.Builder - Class in dev.tamboui.widgets.chart
Builder for `Chart`.

ChartElement - Class in dev.tamboui.toolkit.elements
A DSL wrapper for the Chart widget.

ChartElement() - Constructor for class dev.tamboui.toolkit.elements.ChartElement
Creates a new chart element with default settings.

CharWidth - Class in dev.tamboui.text
Utility for determining the display width of Unicode code points in a terminal.

CharWidth.TruncatePosition - Enum Class in dev.tamboui.text
Truncation position for ellipsis.

Checkbox - Class in dev.tamboui.widgets.checkbox
A checkbox widget that displays a toggleable checked/unchecked state.

CHECKBOX - Enum constant in enum class dev.tamboui.widgets.form.FieldType
Boolean checkbox for yes/no values.

Checkbox.Builder - Class in dev.tamboui.widgets.checkbox
Builder for `Checkbox`.

CheckboxState - Class in dev.tamboui.widgets.checkbox
State for the `Checkbox` widget, tracking checked/unchecked status.

CheckboxState() - Constructor for class dev.tamboui.widgets.checkbox.CheckboxState
Creates a new unchecked state.

CheckboxState(boolean) - Constructor for class dev.tamboui.widgets.checkbox.CheckboxState
Creates a new state with the given initial value.

CHECKED_COLOR - Static variable in class dev.tamboui.widgets.checkbox.Checkbox
CSS property for the checked state foreground color.

CHECKED_SYMBOL - Static variable in class dev.tamboui.widgets.checkbox.Checkbox
CSS property for the checked symbol.

checkedColor(Color) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Sets the color when checkbox is checked.

checkedColor(Color) - Method in class dev.tamboui.widgets.checkbox.Checkbox.Builder
Sets the foreground color when checked.

checkedSub(TFxDuration) - Method in class dev.tamboui.tfx.TFxDuration
Subtracts another duration, returning null if the result would be negative.

checkedSymbol() - Method in class dev.tamboui.widgets.checkbox.Checkbox
Returns the symbol used for checked state.

checkedSymbol(String) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Sets the symbol to display when checkbox is checked.

checkedSymbol(String) - Method in class dev.tamboui.widgets.checkbox.Checkbox.Builder
Sets the symbol to display when checked.

checkRenderThread() - Static method in class dev.tamboui.tui.RenderThread
Asserts that the current thread is the render thread.

chIgnoreCase(char) - Static method in class dev.tamboui.tui.bindings.KeyTrigger
Creates a trigger for a character (case-insensitive).

child() - Method in class dev.tamboui.css.selector.ChildSelector
Returns the child selector.

ChildPosition - Class in dev.tamboui.toolkit.element
Represents the position of a child element within its parent.

children - Variable in class dev.tamboui.toolkit.element.ContainerElement
The list of child elements in this container.

children() - Method in class dev.tamboui.toolkit.element.ContainerElement
Returns the list of children (for subclass access).

children() - Method in class dev.tamboui.widgets.tree.TreeNode
Returns the children of this node.

children(Element...) - Method in class dev.tamboui.toolkit.elements.InlineScopeElement
Adds child elements to this scope.

children(Widget...) - Method in class dev.tamboui.layout.columns.Columns.Builder
Sets the children widgets.

children(Widget...) - Method in class dev.tamboui.layout.grid.Grid.Builder
Creates a children-based grid layout with sequential placement.

children(Widget...) - Method in class dev.tamboui.layout.stack.Stack.Builder
Sets the children widgets.

children(TreeNode) - Method in class dev.tamboui.widgets.tree.TreeNode

children(Function) - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Sets the function to get children (functional shortcut).

children(List) - Method in class dev.tamboui.layout.columns.Columns.Builder
Sets the children widgets from a list.

children(List) - Method in class dev.tamboui.layout.grid.Grid.Builder
Creates a children-based grid layout with sequential placement.

children(List) - Method in class dev.tamboui.layout.stack.Stack.Builder
Sets the children widgets from a list.

children(T) - Method in interface dev.tamboui.widgets.tree.TreeModel
Returns the children of the given parent node.

childrenLoader(Supplier) - Method in class dev.tamboui.widgets.tree.TreeNode

Sets a lazy children loader.

Children Mode Example - Section in class dev.tamboui.layout.grid.Grid

ChildSelector - Class in dev.tamboui.css.selector
A child combinator selector that matches direct children.

ChildSelector(Selector, Selector) - Constructor for class dev.tamboui.css.selector.ChildSelector
Creates a child combinator selector.

childStyle(String) - Method in interface dev.tamboui.toolkit.element.RenderContext
Resolves CSS style for a child element.

childStyle(String, PseudoClassState) - Method in class dev.tamboui.toolkit.element.DefaultRenderContext

childStyle(String, PseudoClassState) - Method in interface dev.tamboui.toolkit.element.RenderContext
Resolves CSS style for a child element with a pseudo-class state.

childStyle(String, ChildPosition) - Method in interface dev.tamboui.toolkit.element.RenderContext
Resolves CSS style for a child element at a specific position.

childStyle(String, ChildPosition, PseudoClassState) - Method in class dev.tamboui.toolkit.element.DefaultRenderContext

childStyle(String, ChildPosition, PseudoClassState) - Method in interface dev.tamboui.toolkit.element.RenderContext
Resolves CSS style for a child element at a specific position with additional state.

chrome(boolean) - Method in class dev.tamboui.export.svg.SvgOptions
Sets whether to include window chrome (frame, title, traffic-light buttons).

CircIn - Enum constant in enum class dev.tamboui.tfx.Interpolation
Circular easing - in

CircInOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Circular easing - in-out

Circle - Class in dev.tamboui.widgets.canvas.shapes
A circle defined by center and radius.

Circle(double, double, double, Color) - Constructor for class dev.tamboui.widgets.canvas.shapes.Circle
Creates a circle centered at (x, y) with the given radius and color.

CIRCLE - Enum constant in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Circle spinner using clock-position characters.

CircOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Circular easing - out

clamp(Rect) - Method in class dev.tamboui.layout.Rect
Clamps another rectangle to fit within this one.

className() - Method in class dev.tamboui.css.selector.ClassSelector
Returns the CSS class name this selector matches.

ClassSelector - Class in dev.tamboui.css.selector
A class selector that matches elements by their CSS class.

ClassSelector(String) - Constructor for class dev.tamboui.css.selector.ClassSelector
Creates a class selector for the given CSS class name.

clear() - Method in class dev.tamboui.backend.aesh.AeshBackend

clear() - Method in class dev.tamboui.backend.jline3.JLineBackend

clear() - Method in class dev.tamboui.backend.panama.PanamaBackend

clear() - Method in class dev.tamboui.buffer.Buffer
Clears the buffer, resetting all cells to empty.

clear() - Method in class dev.tamboui.buffer.DiffResult

Clears this diff result, resetting the count to zero.

clear() - Method in class dev.tamboui.internal.record.RecordingBackend

clear() - Static method in class dev.tamboui.style.PropertyRegistry
Clears all registered properties.

clear() - Method in interface dev.tamboui.style.StyledAreaRegistry
Clears all registered areas.

clear() - Method in interface dev.tamboui.terminal.Backend
Clears the terminal screen.

clear() - Method in class dev.tamboui.terminal.Terminal
Clears the terminal and resets the buffers.

clear() - Method in class dev.tamboui.tfx.EffectManager
Clears all effects.

clear() - Method in class dev.tamboui.tfx.toolkit.ElementEffectRegistry
Clears all effects (pending, running, and global).

clear() - Method in class dev.tamboui.tfx.toolkit.ToolkitEffects
Clears all effects.

clear() - Method in class dev.tamboui.toolkit.element.ElementRegistry
Clears all registered elements.

clear() - Method in class dev.tamboui.toolkit.event.EventRouter
Clears all registered elements.

clear() - Static method in class dev.tamboui.widgets.Clear
Returns the singleton Clear widget instance.

clear() - Method in class dev.tamboui.widgets.input.TextAreaState
Clears all text and resets the cursor and scroll positions.

clear() - Method in class dev.tamboui.widgets.input.TextInputState
Clears all text and resets the cursor.

clear(Rect) - Method in class dev.tamboui.buffer.Buffer
Resets the buffer to empty cells within the given area.

Clear - Class in dev.tamboui.widgets
A widget that clears/resets the area it is rendered to.

clearAll() - Static method in class dev.tamboui.layout.cassowary.LayoutCache
Clears the cache for the current thread.

clearAllValidationResults() - Method in class dev.tamboui.widgets.form.FormState
Clears all validation results.

clearCursor() - Method in class dev.tamboui.terminal.Frame
Clears the cursor position, hiding the cursor.

clearEffects() - Method in class dev.tamboui.tfx.tui.TfxIntegration
Clears all effects.

clearFocus() - Method in class dev.tamboui.toolkit.focus.FocusManager
Clears the current focus.

clearFocusables() - Method in class dev.tamboui.toolkit.focus.FocusManager
Clears all registered focusable elements.

clearOnClose() - Method in class dev.tamboui.inline.InlineDisplay
Configures the display to clear the display area when closed.

clearOnClose() - Method in class dev.tamboui.tui.InlineTuiConfig
Returns whether the display should be cleared when closed.

clearOnClose(boolean) - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner.Builder
Configures whether to clear the display when closed.

clearOnClose(boolean) - Method in class dev.tamboui.tui.InlineTuiConfig.Builder
Configures whether to clear the display when closed.

clearSelection() - Method in class dev.tamboui.widgets.table.TableState
Clears the selection.

clearSelection() - Method in class dev.tamboui.widgets.tabs.TabsState
Clears the selection.

clearValidationResult(String) - Method in class dev.tamboui.widgets.form.FormState
Clears the validation result for the given field name.

click() - Static method in class dev.tamboui.tui.bindings.MouseTrigger
Creates a trigger for left mouse button click (press).

CLICK - Static variable in class dev.tamboui.tui.bindings.Actions
Primary click (left mouse button press).

clip() - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Convenience method to clip text at boundaries.

clip() - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Convenience method to clip text at boundaries.

CLIP - Enum constant in enum class dev.tamboui.style.Overflow
Silent truncation - text is clipped at the boundary with no indicator.

CLOCK - Enum constant in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Clock spinner using clock face characters.

close() - Method in class dev.tamboui.backend.aesh.AeshBackend

close() - Method in class dev.tamboui.backend.jline3.JLineBackend

close() - Method in class dev.tamboui.backend.panama.PanamaBackend

close() - Method in interface dev.tamboui.backend.panama.PlatformTerminal
Closes the terminal and releases resources.

close() - Method in class dev.tamboui.backend.panama.unix.UnixTerminal

close() - Method in class dev.tamboui.backend.panama.windows.WindowsTerminal

close() - Method in class dev.tamboui.inline.InlineDisplay

close() - Method in class dev.tamboui.internal.record.AnsiTerminalCapture

close() - Method in class dev.tamboui.internal.record.RecordingBackend

close() - Method in class dev.tamboui.terminal.AnsiCellWriter
Closes this writer by flushing any pending state and emitting the ANSI reset sequence (`AnsiStringBuilder.RESET`).

close() - Method in interface dev.tamboui.terminal.Backend
Closes this backend and releases any resources.

close() - Method in class dev.tamboui.terminal.Terminal
Closes the terminal and releases resources.

close() - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner

close() - Method in class dev.tamboui.toolkit.app.ToolkitRunner

close() - Method in class dev.tamboui.toolkit.event.EventRouter
Closes the event router and releases resources.

close() - Method in class dev.tamboui.tui.InlineTuiRunner
Closes this runner and releases resources.

close() - Method in class dev.tamboui.tui.TuiRunner

Closes this runner and releases resources.

close() - Method in class dev.tamboui.tui.TuiRunner.ConfiguredRunner

close(int) - Static method in class dev.tamboui.backend.panama.unix.LibC
Closes a file descriptor.

CloseBrace(Token.Position) - Constructor for class dev.tamboui.css.parser.Token.CloseBrace
Creates a closing brace token.

CloseBracket(Token.Position) - Constructor for class dev.tamboui.css.parser.Token.CloseBracket
Creates a closing bracket token.

CloseParen(Token.Position) - Constructor for class dev.tamboui.css.parser.Token.CloseParen
Creates a closing parenthesis token.

coalesce(long, Interpolation) - Static method in class dev.tamboui.tfx.Fx
Creates a coalesce effect (reverse dissolve) that coalesces text from random positions.

coalesce(EffectTimer) - Static method in class dev.tamboui.tfx.Fx
Creates a coalesce effect (reverse dissolve) that coalesces text from random positions.

coalesceFrom(Style, long, Interpolation) - Static method in class dev.tamboui.tfx.Fx
Creates a coalesce effect that coalesces from a specific style.

coalesceFrom(Style, EffectTimer) - Static method in class dev.tamboui.tfx.Fx
Creates a coalesce effect that coalesces from a specific style.

code() - Method in enum class dev.tamboui.style.AnsiColor
Returns the ANSI palette index (0-15).

code() - Method in enum class dev.tamboui.style.Modifier
Returns the ANSI SGR code to enable this modifier.

code() - Method in class dev.tamboui.tui.event.KeyEvent
Returns the key code.

coefficient() - Method in class dev.tamboui.layout.cassowary.Term
Returns the coefficient of this term.

collapseSelected() - Method in class dev.tamboui.toolkit.elements.TreeElement
Collapses the selected node, or moves to its parent if already collapsed.

CollectionUtil - Class in dev.tamboui.util
Small helpers to provide Java 9+ style collection factories while staying compatible with Java 8.

Colon(Token.Position) - Constructor for class dev.tamboui.css.parser.Token.Colon
Creates a colon token.

color() - Method in class dev.tamboui.style.Color.Ansi
Returns the ANSI color.

color() - Method in class dev.tamboui.widgets.canvas.shapes.Circle
Returns the color of the circle.

color() - Method in class dev.tamboui.widgets.canvas.shapes.Line
Returns the line color.

color() - Method in class dev.tamboui.widgets.canvas.shapes.Points
Returns the color for all points.

color() - Method in class dev.tamboui.widgets.canvas.shapes.Rectangle
Returns the color.

color() - Method in class dev.tamboui.widgets.wavetext.WaveText
Returns the base color.

color(Color) - Method in class dev.tamboui.toolkit.elements.SparklineElement
Sets the sparkline color.

color(Color) - Method in class dev.tamboui.toolkit.elements.WaveTextElement
Sets the base color for the wave effect.

color(Color) - Method in class dev.tamboui.widgets.wavetext.WaveText.Builder
Sets the base color for the text.

Color - Interface in dev.tamboui.style
Terminal colors supporting ANSI 16, 256-color indexed, and RGB true color modes.

COLOR - Static variable in class dev.tamboui.style.StandardProperties
The `color` property for foreground/text color.

Color.Ansi - Class in dev.tamboui.style
Standard ANSI 16 colors.

Color.Indexed - Class in dev.tamboui.style
256-color palette index (0-255).

Color.Named - Class in dev.tamboui.style
A named color reference that maps to a style resolver class.

Color.Reset - Class in dev.tamboui.style
Reset to default terminal color.

Color.Rgb - Class in dev.tamboui.style
RGB true color (24-bit).

ColorConverter - Class in dev.tamboui.style
Converts string color values to TamboUI Color objects.

colorSpace() - Method in class dev.tamboui.tfx.effects.FadeShader

colorSpace() - Method in class dev.tamboui.tfx.effects.ParallelEffect

colorSpace() - Method in class dev.tamboui.tfx.effects.SequentialEffect

colorSpace() - Method in class dev.tamboui.tfx.effects.SweepShader

colorSpace() - Method in interface dev.tamboui.tfx.Shader
Returns the color space for this shader, or null if not applicable.

column() - Method in class dev.tamboui.css.parser.Token.Position
Returns the 1-based column number.

column() - Method in class dev.tamboui.layout.grid.GridArea.AreaBounds
Returns the start column (0-based).

column() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty column.

column(Element...) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a vertical column layout.

column(Supplier) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a column with lazy content.

Column - Class in dev.tamboui.toolkit.elements
A vertical layout container that arranges children in a column.

Column() - Constructor for class dev.tamboui.toolkit.elements.Column
Creates a new empty column.

Column(Element...) - Constructor for class dev.tamboui.toolkit.elements.Column
Creates a new column with the given children.

COLUMN_COUNT - Static variable in class dev.tamboui.toolkit.elements.ColumnsElement
CSS property definition for the number of columns.

COLUMN_FIRST - Enum constant in enum class dev.tamboui.layout.columns.ColumnOrder
Items fill top-to-bottom, then left-to-right.

COLUMN_ORDER - Static variable in class dev.tamboui.toolkit.elements.ColumnsElement
CSS property definition for the column ordering mode.

columnConstraints(Constraint...) - Method in class dev.tamboui.layout.grid.Grid.AreaBuilder

Sets the width constraints for columns.

columnConstraints(Constraint...) - Method in class dev.tamboui.layout.grid.Grid.ChildrenBuilder
Sets the width constraints for columns.

columnConstraints(List) - Method in class dev.tamboui.layout.grid.Grid.AreaBuilder
Sets the width constraints for columns from a list.

columnConstraints(List) - Method in class dev.tamboui.layout.grid.Grid.ChildrenBuilder
Sets the width constraints for columns from a list.

columnCount(int) - Method in class dev.tamboui.layout.columns.Columns.Builder
Sets the number of columns.

columnCount(int) - Method in class dev.tamboui.layout.grid.Grid.ChildrenBuilder
Sets the number of columns.

columnCount(int) - Method in class dev.tamboui.toolkit.elements.ColumnsElement
Sets an explicit column count, overriding auto-detection.

columnFirst() - Method in class dev.tamboui.toolkit.elements.ColumnsElement
Convenience method to set column-first ordering.

ColumnOrder - Enum Class in dev.tamboui.layout.columns
Controls the ordering of children within a `Columns` layout.

ColumnOrderConverter - Class in dev.tamboui.toolkit.elements
Converts string values to `ColumnOrder` enum values.

columns() - Method in class dev.tamboui.layout.grid.GridArea
Returns the number of columns in the grid template.

columns() - Method in class dev.tamboui.layout.Rect
Returns an iterator over columns in this rectangle.

columns() - Method in class dev.tamboui.toolkit.elements.GridSize
Returns the number of columns.

columns() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty columns layout.

columns(int) - Static method in class dev.tamboui.toolkit.elements.GridSize
Creates a grid size with explicit columns and auto rows.

columns(Element...) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a multi-column grid layout.

columns(Collection) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a multi-column grid layout from a collection.

columns(Supplier) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a columns layout with lazy content.

Columns - Class in dev.tamboui.layout.columns
A grid layout widget that arranges children into columns.

Columns.Builder - Class in dev.tamboui.layout.columns
Builder for `Columns`.

ColumnsElement - Class in dev.tamboui.toolkit.elements
A multi-column grid layout container that arranges children into columns.

ColumnsElement() - Constructor for class dev.tamboui.toolkit.elements.ColumnsElement
Creates an empty columns layout.

ColumnsElement(Element...) - Constructor for class dev.tamboui.toolkit.elements.ColumnsElement
Creates a columns layout with the given children.

ColumnsElement(Collection) - Constructor for class dev.tamboui.toolkit.elements.ColumnsElement
Creates a columns layout with the given children.

columnSpacing(int) - Method in class dev.tamboui.toolkit.elements.TableElement
Sets the spacing between columns.

columnSpacing(int) - Method in class dev.tamboui.widgets.table.Table.Builder
Sets the spacing between columns.

columnSpan() - Method in class dev.tamboui.layout.grid.GridArea.AreaBounds
Returns the number of columns spanned.

columnWidths(Constraint...) - Method in class dev.tamboui.layout.columns.Columns.Builder
Sets the width constraints for columns.

columnWidths(List) - Method in class dev.tamboui.layout.columns.Columns.Builder
Sets the width constraints for columns from a list.

Comma(Token.Position) - Constructor for class dev.tamboui.css.parser.Token.Comma
Creates a comma token.

commit(long, int, EventResult) - Static method in class dev.tamboui.toolkit.jfr.GlobalHandlerEvent
Commits a new global handler event.

commit(long, String, boolean, String, String) - Static method in class dev.tamboui.toolkit.jfr.FocusNavigationEvent
Commits a new focus navigation event.

commit(long, String, String, int, int) - Static method in class dev.tamboui.toolkit.jfr.DragStateEvent
Commits a new drag state event.

commit(long, String, String, String) - Static method in class dev.tamboui.toolkit.jfr.FocusChangeEvent
Commits a new focus change event.

commit(long, String, String, String, String, String) - Static method in class dev.tamboui.toolkit.jfr.CandidateEvent
Commits a new candidate event.

compareTo(Fraction) - Method in class dev.tamboui.layout.Fraction

CompletedFrame - Class in dev.tamboui.terminal
Represents a completed frame after rendering.

CompletedFrame(Buffer, Rect) - Constructor for class dev.tamboui.terminal.CompletedFrame
Creates a completed frame with the given buffer and area.

Component<T> - Class in dev.tamboui.toolkit.component
Base class for stateful components with event handling.

Component() - Constructor for class dev.tamboui.toolkit.component.Component
Creates a new component.

CompoundSelector - Class in dev.tamboui.css.selector
A compound selector that combines multiple simple selectors.

CompoundSelector(List) - Constructor for class dev.tamboui.css.selector.CompoundSelector
Creates a compound selector from the given parts.

compute(int, int) - Method in class dev.tamboui.style.Width
Computes the actual width in characters given a container width.

computeIfAbsent(List, int, int, Flex, Supplier) - Method in class dev.tamboui.layout.cassowary.LayoutCache
Gets cached sizes for the given layout parameters, computing and caching if absent.

computeValue() - Method in class dev.tamboui.layout.cassowary.Strength
Computes the numeric value of this strength for use in the simplex objective.

config(TuiConfig) - Method in class dev.tamboui.toolkit.app.ToolkitRunner.Builder
Sets the TUI configuration.

configFile() - Method in class dev.tamboui.internal.record.RecordingConfig
Returns the config file path, or null if loaded from system properties.

Configuration Options - Section in class dev.tamboui.widgets.wavetext.WaveText

configure() - Method in class dev.tamboui.toolkit.app.ToolkitApp
Returns the TUI configuration for this application.

configure(int) - Method in class dev.tamboui.toolkit.app.InlineApp
Returns the TUI configuration for this application.

CONFIRM - Static variable in class dev.tamboui.tui.bindings.Actions
Confirm (Enter only).

CONSOLE_SCREEN_BUFFER_INFO_LAYOUT - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
Layout for CONSOLE_SCREEN_BUFFER_INFO structure.

constant() - Method in class dev.tamboui.layout.cassowary.Expression
Returns the constant part of this expression.

constant(long) - Static method in class dev.tamboui.layout.cassowary.Expression
Creates an expression with only a constant value.

constant(Fraction) - Static method in class dev.tamboui.layout.cassowary.Expression
Creates an expression with only a constant value.

constraint() - Method in exception class dev.tamboui.layout.cassowary.DuplicateConstraintException
Returns the duplicate constraint.

constraint() - Method in exception class dev.tamboui.layout.cassowary.UnknownConstraintException
Returns the unknown constraint.

constraint() - Method in exception class dev.tamboui.layout.cassowary.UnsatisfiableConstraintException
Returns the unsatisfiable constraint.

constraint() - Method in interface dev.tamboui.toolkit.element.Element
Returns the layout constraint for this element, if any.

constraint() - Method in class dev.tamboui.toolkit.element.StyledElement

constraint() - Method in class dev.tamboui.toolkit.elements.DialogElement

constraint() - Method in class dev.tamboui.toolkit.elements.InlineScopeElement

constraint() - Method in class dev.tamboui.toolkit.elements.LazyElement

constraint() - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement

constraint() - Method in class dev.tamboui.toolkit.elements.MarkupTextElement

constraint() - Method in class dev.tamboui.toolkit.elements.Panel

constraint() - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement

constraint() - Method in class dev.tamboui.toolkit.elements.RichTextElement

constraint() - Method in class dev.tamboui.toolkit.elements.Spacer

constraint() - Method in class dev.tamboui.toolkit.elements.TextElement
Returns the layout constraint for this text element.

constraint(Constraint) - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the layout constraint for this element.

Constraint - Interface in dev.tamboui.layout
Constraints for layout space allocation.

Constraint.Fill - Class in dev.tamboui.layout
Fill remaining space with given weight.

Constraint.Fit - Class in dev.tamboui.layout
Fit to content size.

Constraint.Length - Class in dev.tamboui.layout
Fixed size in cells.

Constraint.Max - Class in dev.tamboui.layout

Maximum size in cells.

Constraint.Min - Class in dev.tamboui.layout
Minimum size in cells.

Constraint.Percentage - Class in dev.tamboui.layout
Percentage of available space (0-100).

Constraint.Ratio - Class in dev.tamboui.layout
Ratio of available space (numerator/denominator).

ConstraintConverter - Class in dev.tamboui.css.property
Converts CSS constraint values to Constraint objects.

ConstraintConverter - Class in dev.tamboui.layout
Converts string values to `Constraint` objects.

ConstraintListConverter - Class in dev.tamboui.toolkit.elements
Converts a space-separated string of constraint tokens to a `List<Constraint>`.

constraints() - Method in class dev.tamboui.layout.Layout
Returns the constraints for the split.

constraints(Constraint...) - Method in class dev.tamboui.layout.Layout
Sets the constraints to apply when splitting.

constraints(List) - Method in class dev.tamboui.layout.Layout
Sets the constraints to apply when splitting.

ContainerElement<T> - Class in dev.tamboui.toolkit.element
Base class for container elements that hold children and forward events to them.

ContainerElement() - Constructor for class dev.tamboui.toolkit.element.ContainerElement
Creates a new container element.

contains(int, int) - Method in class dev.tamboui.layout.Rect
Returns true if the given coordinates lie inside this rectangle.

contains(Position) - Method in class dev.tamboui.layout.Rect
Returns true if the given position lies inside this rectangle.

contains(PropertyDefinition) - Method in class dev.tamboui.css.cascade.TypedPropertyMap
Returns true if this map contains a value for the given property.

contains(String) - Method in class dev.tamboui.style.Tags
Returns whether this Tags instance contains the given tag.

contains(String) - Method in class dev.tamboui.toolkit.element.ElementRegistry
Returns whether an element with the given ID is registered.

contains(LocalDate) - Method in class dev.tamboui.widgets.calendar.CalendarEventStore
Returns true if the given date has a style.

CONTAINS - Enum constant in enum class dev.tamboui.css.selector.AttributeSelector.Operator
Contains

containsEmojiCodes(String) - Static method in class dev.tamboui.text.MarkupParser
Returns true if the given text contains any emoji codes.

content() - Method in class dev.tamboui.text.Span
Returns the text content of this span.

content() - Method in class dev.tamboui.toolkit.elements.TextElement
Returns the text content.

content() - Method in class dev.tamboui.widgets.block.Title
Returns the title content.

content() - Method in class dev.tamboui.widgets.list.ListItem
Returns the item content.

content() - Method in class dev.tamboui.widgets.table.Cell
Returns the content of this cell.

CONTENT_ALIGN - Static variable in class dev.tamboui.toolkit.elements.StackElement
CSS property definition for the content alignment.

ContentAlignment - Enum Class in dev.tamboui.layout
Defines 2D alignment for positioning a child within a container area.

ContentAlignmentConverter - Class in dev.tamboui.layout
Converts string values to `ContentAlignment` enum values.

contentHeight() - Method in class dev.tamboui.style.RichTextState
Returns the total content height in lines.

contentLength() - Method in class dev.tamboui.widgets.scrollbar.ScrollbarState
Returns the total length of the scrollable content.

contentLength(int) - Method in class dev.tamboui.widgets.scrollbar.ScrollbarState
Sets the total length of the scrollable content.

contentWidth() - Method in class dev.tamboui.style.RichTextState
Returns the maximum content width (longest line).

context() - Method in class dev.tamboui.tui.event.ActionEvent
Returns the context associated with this action, if any.

Context - Class in dev.tamboui.widgets.canvas
The drawing context for a `Canvas`.

Context(int, int, double[], double[], Marker) - Constructor for class dev.tamboui.widgets.canvas.Context
Creates a new drawing context.

contextKey() - Method in class dev.tamboui.style.StyledAreaInfo
Returns the context key for this styled area.

CONTINUATION - Static variable in class dev.tamboui.buffer.Cell
A continuation cell placeholder for the trailing column(s) of a wide character.

contribute(CapabilityReportBuilder) - Method in interface dev.tamboui.capability.CapabilityProvider
Contribute information to the capability report.

contribute(CapabilityReportBuilder) - Method in class dev.tamboui.capability.core.CoreCapabilityProvider

contribute(CapabilityReportBuilder) - Method in class dev.tamboui.image.capability.ImageCapabilityProvider

convert(String) - Method in class dev.tamboui.layout.ConstraintConverter

convert(String) - Method in class dev.tamboui.layout.ContentAlignmentConverter

convert(String) - Method in class dev.tamboui.layout.DirectionConverter

convert(String) - Method in class dev.tamboui.layout.FlexConverter

convert(String) - Method in class dev.tamboui.layout.MarginConverter

convert(String) - Method in class dev.tamboui.layout.PaddingConverter

convert(String) - Method in class dev.tamboui.style.AlignmentConverter

convert(String) - Method in class dev.tamboui.style.BorderCharConverter

convert(String) - Method in class dev.tamboui.style.ColorConverter

convert(String) - Method in class dev.tamboui.style.DoubleConverter

convert(String) - Method in class dev.tamboui.style.IntegerConverter

convert(String) - Method in class dev.tamboui.style.ModifierConverter

convert(String) - Method in class dev.tamboui.style.OverflowConverter

convert(String) - Method in interface dev.tamboui.style.PropertyConverter
Converts a string value to the target type.

convert(String) - Method in class dev.tamboui.style.PropertyDefinition
Converts a string value to the target type using this definition's converter.

convert(String) - Method in class dev.tamboui.style.StringConverter

convert(String) - Method in class dev.tamboui.toolkit.elements.ColumnOrderConverter

convert(String) - Method in class dev.tamboui.toolkit.elements.ConstraintListConverter

convert(String) - Method in class dev.tamboui.toolkit.elements.GridAreaConverter

convert(String) - Method in class dev.tamboui.toolkit.elements.GridSizeConverter

convert(String) - Method in class dev.tamboui.toolkit.elements.GutterConverter

convert(String) - Method in class dev.tamboui.widgets.block.BorderTypeConverter

convert(String) - Method in class dev.tamboui.widgets.spinner.SpinnerFrameSetConverter

convert(String) - Method in class dev.tamboui.widgets.spinner.SpinnerStyleConverter

convert(String, Map) - Method in class dev.tamboui.css.property.AlignmentConverter

convert(String, Map) - Method in class dev.tamboui.css.property.BorderSetConverter

convert(String, Map) - Method in class dev.tamboui.css.property.BorderTypeConverter

convert(String, Map) - Method in class dev.tamboui.css.property.ConstraintConverter

convert(String, Map) - Method in class dev.tamboui.css.property.DirectionConverter

convert(String, Map) - Method in class dev.tamboui.css.property.FlexConverter

convert(String, Map) - Method in class dev.tamboui.css.property.IntegerConverter

convert(String, Map) - Method in class dev.tamboui.css.property.MarginConverter

convert(String, Map) - Method in class dev.tamboui.css.property.ModifierConverter

convert(String, Map) - Method in interface dev.tamboui.css.property.PropertyConverter
Converts a CSS value string to the target type.

convert(String, Map) - Method in class dev.tamboui.css.property.SpacingConverter

convert(String, Map) - Method in class dev.tamboui.css.property.WidthConverter

converter() - Method in class dev.tamboui.style.PropertyDefinition
Returns the converter for this property.

CONVERTER - Static variable in enum class dev.tamboui.widgets.common.ScrollBarPolicy
CSS property converter for scrollbar policy.

coords() - Method in class dev.tamboui.widgets.canvas.shapes.Points
Returns the coordinate pairs.

copy() - Method in class dev.tamboui.buffer.Buffer
Creates a deep copy of this buffer.

copy() - Method in class dev.tamboui.tfx.Effect
Creates a copy of this effect with a fresh internal state.

copy() - Method in class dev.tamboui.tfx.effects.DissolveShader

copy() - Method in class dev.tamboui.tfx.effects.ExpandShader

copy() - Method in class dev.tamboui.tfx.effects.FadeShader

copy() - Method in class dev.tamboui.tfx.effects.PaintShader

copy() - Method in class dev.tamboui.tfx.effects.ParallelEffect

copy() - Method in class dev.tamboui.tfx.effects.SequentialEffect

copy() - Method in class dev.tamboui.tfx.effects.SlideShader

copy() - Method in class dev.tamboui.tfx.effects.StretchShader

copy() - Method in class dev.tamboui.tfx.effects.SweepShader

copy() - Method in interface dev.tamboui.tfx.Shader
Creates a copy of this shader.

copyFrom(Bindings) - Method in interface dev.tamboui.tui.bindings.Bindings.Builder
Copies all triggers from another bindings instance.

CoreCapabilityProvider - Class in dev.tamboui.capability.core
Core capability contributor: prints what core assumes/uses and what it can infer from the environment.

CoreCapabilityProvider() - Constructor for class dev.tamboui.capability.core.CoreCapabilityProvider
Creates a new core capability provider.

cos(float) - Static method in class dev.tamboui.tfx.TFxMath
Computes the cosine of a float value in radians.

create() - Method in class dev.tamboui.backend.aesh.AeshBackendProvider

create() - Method in class dev.tamboui.backend.jline3.JLineBackendProvider

create() - Method in class dev.tamboui.backend.panama.PanamaBackendProvider

create() - Static method in class dev.tamboui.css.engine.StyleEngine
Creates a new StyleEngine with default configuration.

create() - Static method in class dev.tamboui.style.Style
Creates a new style builder.

create() - Static method in interface dev.tamboui.style.StyledAreaRegistry
Creates a new default StyledAreaRegistry implementation.

create() - Static method in class dev.tamboui.terminal.BackendFactory
Creates a new backend instance using the discovered provider.

create() - Method in interface dev.tamboui.terminal.BackendProvider
Creates a new backend instance.

create() - Static method in class dev.tamboui.toolkit.app.InlineToolkitRunner
Creates an InlineToolkitRunner with an initial height of 1.

create() - Static method in class dev.tamboui.toolkit.app.ToolkitRunner
Creates a ToolkitRunner with default configuration.

create() - Static method in class dev.tamboui.toolkit.id.IdGenerator
Creates a new ID generator instance with its own counter.

create() - Static method in class dev.tamboui.tui.TuiRunner
Creates a TuiRunner with default configuration.

create(int) - Static method in class dev.tamboui.inline.InlineDisplay
Creates an InlineDisplay with the specified height.

create(int) - Static method in class dev.tamboui.toolkit.app.InlineToolkitRunner
Creates an InlineToolkitRunner with the specified height.

create(int) - Static method in class dev.tamboui.tui.InlineTuiRunner
Creates an InlineTuiRunner with the specified height and default configuration.

create(int, int) - Static method in class dev.tamboui.inline.InlineDisplay
Creates an InlineDisplay with the specified height and fixed width.

create(long, long, long) - Static method in class dev.tamboui.layout.cassowary.Strength
Creates a custom strength with the given weights.

create(Fraction, Fraction, Fraction) - Static method in class dev.tamboui.layout.cassowary.Strength
Creates a custom strength with the given weights.

create(Motion, Rect, float, float) - Static method in class dev.tamboui.tfx.SlidingWindowAlpha
Creates a new sliding window alpha calculator.

create(InlineTuiConfig) - Static method in class dev.tamboui.toolkit.app.InlineToolkitRunner
Creates an InlineToolkitRunner with the specified configuration.

create(InlineTuiConfig) - Static method in class dev.tamboui.tui.InlineTuiRunner
Creates an InlineTuiRunner with the specified configuration.

create(TuiConfig) - Static method in class dev.tamboui.toolkit.app.ToolkitRunner
Creates a ToolkitRunner with the specified configuration.

create(TuiConfig) - Static method in class dev.tamboui.tui.TuiRunner
Creates a TuiRunner with the specified configuration.

createConfig() - Method in class dev.tamboui.picocli.TuiCommand
Creates the TuiConfig for this command.

createEmpty() - Static method in class dev.tamboui.toolkit.element.DefaultRenderContext
Creates an empty context for simple rendering without focus management.

createSignalHandler(Arena, IntConsumer) - Static method in class dev.tamboui.backend.panama.unix.LibC
Creates an upcall stub for a signal handler.

crop(int, int, int, int) - Method in class dev.tamboui.image.ImageData
Creates a cropped copy of this image.

crop(Rect) - Method in class dev.tamboui.export.ExportRequest
Limits export to the given rectangle (clipped to buffer bounds).

CROSSED_OUT - Enum constant in enum class dev.tamboui.style.Modifier
Crossed-out (strikethrough) text.

crossedOut() - Method in class dev.tamboui.style.Style
Enables strikethrough.

crossedOut() - Method in class dev.tamboui.text.Span
Returns a new span with crossed-out style.

crossedOut() - Method in class dev.tamboui.toolkit.element.StyledElement
Applies the crossed-out modifier.

CS8 - Static variable in class dev.tamboui.backend.panama.unix.LibC
Control flag: set character size to 8 bits.

CS8 - Static variable in class dev.tamboui.backend.panama.unix.PlatformConstants
Control flag: set character size to 8 bits.

CSBI_WINDOW_BOTTOM - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
VarHandle for the bottom coordinate of the console window rectangle.

CSBI_WINDOW_LEFT - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
VarHandle for the left coordinate of the console window rectangle.

CSBI_WINDOW_RIGHT - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
VarHandle for the right coordinate of the console window rectangle.

CSBI_WINDOW_TOP - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
VarHandle for the top coordinate of the console window rectangle.

csi() - Method in class dev.tamboui.backend.panama.ByteArrayBuilder
Appends the CSI (Control Sequence Introducer) escape sequence.

CSS Child Selectors - Section in class dev.tamboui.toolkit.elements.FormElement

CSS Child Selectors - Section in class dev.tamboui.toolkit.elements.FormFieldElement

CSS Child Selectors - Section in class dev.tamboui.toolkit.elements.GaugeElement

CSS Child Selectors - Section in class dev.tamboui.toolkit.elements.LineGaugeElement

CSS Child Selectors - Section in class dev.tamboui.toolkit.elements.RichTextAreaElement

CSS Child Selectors - Section in class dev.tamboui.toolkit.elements.ScrollbarElement

CSS Child Selectors - Section in class dev.tamboui.toolkit.elements.TextAreaElement

CSS Child Selectors - Section in class dev.tamboui.toolkit.elements.TextInputElement

CSS Child Selectors - Section in class dev.tamboui.toolkit.elements.TreeElement

cssClasses - Variable in class dev.tamboui.toolkit.element.StyledElement
The CSS classes applied to this element.

cssClasses() - Method in interface dev.tamboui.css.Styleable
Returns the CSS classes assigned to this element.

cssClasses() - Method in class dev.tamboui.toolkit.element.ElementRegistry.ElementInfo

cssClasses() - Method in class dev.tamboui.toolkit.element.StyledElement

cssClasses() - Method in class dev.tamboui.toolkit.element.StyledSpan

cssId() - Method in interface dev.tamboui.css.Styleable
Returns the element ID for ID selectors.

cssId() - Method in class dev.tamboui.toolkit.element.ElementRegistry.ElementInfo

cssId() - Method in class dev.tamboui.toolkit.element.StyledElement

cssId() - Method in class dev.tamboui.toolkit.element.StyledSpan

CssLexer - Class in dev.tamboui.css.parser
Lexer for Textual-style CSS.

CssLexer(String) - Constructor for class dev.tamboui.css.parser.CssLexer
Creates a new lexer for the given CSS input.

cssParent - Variable in class dev.tamboui.toolkit.element.StyledElement
The CSS parent for ancestor matching.

cssParent() - Method in interface dev.tamboui.css.Styleable
Returns the parent element in the style hierarchy.

cssParent() - Method in class dev.tamboui.toolkit.element.ElementRegistry.ElementInfo

cssParent() - Method in class dev.tamboui.toolkit.element.StyledElement

cssParent() - Method in class dev.tamboui.toolkit.element.StyledSpan

cssParent(Styleable) - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the CSS parent for ancestor matching.

CssParseException - Exception Class in dev.tamboui.css.parser
Exception thrown when CSS parsing fails.

CssParseException(String, Token.Position) - Constructor for exception class dev.tamboui.css.parser.CssParseException
Creates a new parse exception with a message and position.

CssParseException(String, Throwable) - Constructor for exception class dev.tamboui.css.parser.CssParseException

Creates a new parse exception with a message and cause.

CssParser - Class in dev.tamboui.css.parser
Recursive descent parser for Textual-style CSS.

CSS Properties - Section in class dev.tamboui.toolkit.elements.SpinnerElement

CSS Properties - Section in class dev.tamboui.toolkit.elements.TreeElement

CSS Properties - Section in class dev.tamboui.widgets.checkbox.Checkbox

CSS Properties - Section in class dev.tamboui.widgets.select.Select

CSS Properties - Section in class dev.tamboui.widgets.toggle.Toggle

CssStyleResolver - Class in dev.tamboui.css.cascade
Represents the computed style for an element after CSS cascade resolution.

CssStyleResolver.Builder - Class in dev.tamboui.css.cascade
Builder for CssStyleResolver.

ctrl() - Method in class dev.tamboui.tui.event.KeyModifiers
Returns whether the Ctrl modifier is active.

ctrl(char) - Static method in class dev.tamboui.tui.bindings.KeyTrigger
Creates a trigger for Ctrl+character.

CTRL - Static variable in class dev.tamboui.tui.event.KeyModifiers
Only Ctrl pressed.

ctrlClick() - Static method in class dev.tamboui.tui.bindings.MouseTrigger
Creates a trigger for Ctrl+left click.

CubicIn - Enum constant in enum class dev.tamboui.tfx.Interpolation
Cubic easing - in

CubicInOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Cubic easing - in-out

CubicOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Cubic easing - out

currentContextKey() - Method in class dev.tamboui.terminal.Frame
Returns the current context key (top of the stack).

currentElement() - Method in class dev.tamboui.toolkit.element.DefaultRenderContext
Returns the current element being rendered, if any.

currentResolver() - Method in class dev.tamboui.toolkit.element.DefaultRenderContext
Returns the current CSS resolver from the resolver stack, if any.

currentStyle() - Method in class dev.tamboui.toolkit.element.DefaultRenderContext

currentStyle() - Method in interface dev.tamboui.toolkit.element.RenderContext
Returns the current style from the style stack.

CURSOR_COLOR - Static variable in class dev.tamboui.widgets.input.TextArea
Property key for the cursor color.

CURSOR_COLOR - Static variable in class dev.tamboui.widgets.input.TextInput
Property key for the cursor color.

cursorCol() - Method in class dev.tamboui.widgets.input.TextAreaState
Returns the cursor column.

cursorColor(Color) - Method in class dev.tamboui.widgets.input.TextArea.Builder
Sets the cursor color programmatically.

cursorColor(Color) - Method in class dev.tamboui.widgets.input.TextInput.Builder
Sets the cursor color programmatically.

cursorPosition() - Method in class dev.tamboui.terminal.Frame

Returns the cursor position if set.

cursorPosition() - Method in class dev.tamboui.widgets.input.TextInputState
Returns the cursor position.

cursorRequiresFocus(boolean) - Method in class dev.tamboui.toolkit.elements.TextInputElement
Sets whether the cursor requires focus to be displayed.

cursorRow() - Method in class dev.tamboui.widgets.input.TextAreaState
Returns the cursor row.

cursorStyle(Style) - Method in class dev.tamboui.toolkit.elements.TextAreaElement
Sets the cursor style.

cursorStyle(Style) - Method in class dev.tamboui.toolkit.elements.TextInputElement
Sets the cursor style.

cursorStyle(Style) - Method in class dev.tamboui.widgets.input.TextArea.Builder
Sets the cursor style.

cursorStyle(Style) - Method in class dev.tamboui.widgets.input.TextInput.Builder
Sets the cursor style.

customBorderSet(BorderSet) - Method in class dev.tamboui.widgets.block.Block.Builder
Sets a custom border set with specific characters for each border element.

customResolver(MarkupParser.StyleResolver) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Sets a custom style resolver for tags not covered by built-in styles.

customResolver(MarkupParser.StyleResolver) - Method in class dev.tamboui.toolkit.elements.MarkupTextElement
Sets a custom style resolver for tags not covered by built-in styles.

cyan() - Method in class dev.tamboui.style.Style
Shorthand for `Style.fg(Color)` with `Color.CYAN`.

cyan() - Method in class dev.tamboui.text.Span
Returns a new span with cyan foreground color.

cyan() - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the foreground color to cyan.

CYAN - Enum constant in enum class dev.tamboui.style.AnsiColor
Cyan (palette index 6).

CYAN - Static variable in interface dev.tamboui.style.Color
Cyan.

D

DARK_GRAY - Static variable in interface dev.tamboui.style.Color
Dark gray (ANSI BRIGHT_BLACK renders as dark gray).

data() - Method in class dev.tamboui.image.Image
Returns the image data.

data() - Method in class dev.tamboui.widgets.chart.Dataset
Returns the data points as [x, y] pairs.

data() - Method in class dev.tamboui.widgets.tree.TreeNode
Returns the user data, or `null` if none.

data(double[][]) - Method in class dev.tamboui.widgets.chart.Dataset.Builder
Sets the data points as [x, y] pairs.

data(int...) - Method in class dev.tamboui.toolkit.elements.SparklineElement
Sets the data values from integers.

data(int...) - Method in class dev.tamboui.widgets.sparkline.Sparkline.Builder
Sets the data values from an int array.

data(long...) - Method in class dev.tamboui.toolkit.elements.BarChartElement
Adds data as simple values (single group).

data(long...) - Method in class dev.tamboui.toolkit.elements.SparklineElement
Sets the data values.

data(long...) - Method in class dev.tamboui.widgets.sparkline.Sparkline.Builder
Sets the data values to display.

data(ImageData) - Method in class dev.tamboui.image.Image.Builder
Sets the image data.

data(Bar...) - Method in class dev.tamboui.toolkit.elements.BarChartElement
Adds data as bars with labels.

data(BarGroup...) - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Adds bar groups to the chart.

data(Collection) - Method in class dev.tamboui.toolkit.elements.SparklineElement
Sets the data values from a collection.

data(List) - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Adds bar groups to the chart.

data(List) - Method in class dev.tamboui.widgets.chart.Dataset.Builder
Sets the data points from a list of [x, y] pairs.

data(List) - Method in class dev.tamboui.widgets.sparkline.Sparkline.Builder
Sets the data values from a list.

data(List, Function) - Method in class dev.tamboui.toolkit.elements.ListElement
Sets the data items and a renderer function.

dataset(Dataset) - Method in class dev.tamboui.toolkit.elements.ChartElement
Adds a dataset.

Dataset - Class in dev.tamboui.widgets.chart
A dataset to be plotted in a `Chart`.

Dataset.Builder - Class in dev.tamboui.widgets.chart
Builder for `Dataset`.

Dataset.Marker - Enum Class in dev.tamboui.widgets.chart
Marker symbols for data points.

datasets(Dataset...) - Method in class dev.tamboui.toolkit.elements.ChartElement
Sets all datasets.

datasets(Dataset...) - Method in class dev.tamboui.widgets.chart.Chart.Builder
Sets the datasets to plot.

datasets(List) - Method in class dev.tamboui.toolkit.elements.ChartElement
Sets all datasets from a list.

datasets(List) - Method in class dev.tamboui.widgets.chart.Chart.Builder
Sets the datasets to plot.

date(LocalDate) - Method in class dev.tamboui.toolkit.elements.CalendarElement
Sets the display date (determines which month to show).

dateStyler(DateStyler) - Method in class dev.tamboui.toolkit.elements.CalendarElement
Sets the date styler for customizing individual dates.

DateStyler - Interface in dev.tamboui.widgets.calendar
Provides styling for specific dates in a `Monthly` calendar.

DebugOverlay - Class in dev.tamboui.tui.overlay
Debug overlay that displays performance metrics and system information.

DebugOverlay(String, Duration, Duration) - Constructor for class dev.tamboui.tui.overlay.DebugOverlay
Creates a new debug overlay.

declarations() - Method in class dev.tamboui.css.model.Rule

Returns the property declarations of this rule.

DEFAULT - Static variable in class dev.tamboui.widgets.common.SizedWidget
Sentinel value meaning "use default" (fill for width, 1 for height).

DEFAULT_CHECKED_SYMBOL - Static variable in class dev.tamboui.widgets.checkbox.Checkbox
Default symbol for checked state.

DEFAULT_HTML_FORMAT - Static variable in class dev.tamboui.export.html.HtmlExporter
HTML template derived from Rich's `CONSOLE_HTML_FORMAT`.

DEFAULT_LEFT_INDICATOR - Static variable in class dev.tamboui.widgets.select.Select
Default left navigation indicator.

DEFAULT_OFF_LABEL - Static variable in class dev.tamboui.widgets.toggle.Toggle
Default off label (inline mode).

DEFAULT_OFF_SYMBOL - Static variable in class dev.tamboui.widgets.toggle.Toggle
Default symbol for off state (single mode).

DEFAULT_ON_LABEL - Static variable in class dev.tamboui.widgets.toggle.Toggle
Default on label (inline mode).

DEFAULT_ON_SYMBOL - Static variable in class dev.tamboui.widgets.toggle.Toggle
Default symbol for on state (single mode).

DEFAULT_POLL_TIMEOUT - Static variable in class dev.tamboui.tui.InlineTuiConfig
Default poll timeout for reading events (40ms).

DEFAULT_POLL_TIMEOUT - Static variable in class dev.tamboui.tui.TuiConfig
Default poll timeout in milliseconds.

DEFAULT_RESIZE_GRACE_PERIOD - Static variable in class dev.tamboui.tui.TuiConfig
Default grace period for resize events (250ms).

DEFAULT_RIGHT_INDICATOR - Static variable in class dev.tamboui.widgets.select.Select
Default right navigation indicator.

DEFAULT_SELECTED_INDICATOR - Static variable in class dev.tamboui.widgets.toggle.Toggle
Default indicator for selected option (inline mode).

DEFAULT_SEPARATOR - Static variable in class dev.tamboui.widgets.toggle.Toggle
Default separator between choices (inline mode).

DEFAULT_SVG_FORMAT - Static variable in class dev.tamboui.export.svg.SvgExporter
SVG template derived from Rich's `CONSOLE_SVG_FORMAT` with branding adjusted.

DEFAULT_TICK_RATE - Static variable in class dev.tamboui.tui.InlineTuiConfig
Default tick rate for animations (40ms, ~25fps).

DEFAULT_TICK_TIMEOUT - Static variable in class dev.tamboui.tui.TuiConfig
Default tick rate in milliseconds.

DEFAULT_UNCHECKED_SYMBOL - Static variable in class dev.tamboui.widgets.checkbox.Checkbox
Default symbol for unchecked state.

DEFAULT_UNSELECTED_INDICATOR - Static variable in class dev.tamboui.widgets.toggle.Toggle
Default indicator for unselected option (inline mode).

DefaultBindings - Class in dev.tamboui.tui.bindings
Default implementation of `Bindings` using a HashMap of actions to triggers.

defaultOptions() - Method in interface dev.tamboui.export.Format
Returns default options for this format.

defaultOptions() - Method in class dev.tamboui.export.html.HtmlFormat

defaultOptions() - Method in class dev.tamboui.export.svg.SvgFormat

defaultOptions() - Method in class dev.tamboui.export.text.TextFormat

DefaultRenderContext - Class in dev.tamboui.toolkit.element

Default implementation of RenderContext with internal framework methods.

DefaultRenderContext(FocusManager, EventRouter) - Constructor for class dev.tamboui.toolkit.element.DefaultRenderContext
Creates a new render context.

defaultRng() - Static method in class dev.tamboui.tfx.SimpleRng
Creates a new SimpleRng with a seed based on the current system time.

defaults() - Static method in class dev.tamboui.tui.bindings.BindingSets
Returns the default bindings.

defaults() - Static method in class dev.tamboui.tui.TuiConfig
Returns the default configuration.

defaults() - Static method in class dev.tamboui.widgets.chart.Axis
Creates an axis with default settings.

defaults(int) - Static method in class dev.tamboui.tui.InlineTuiConfig
Creates a default configuration for the given height.

defaultStyle(Style) - Method in class dev.tamboui.toolkit.elements.CalendarElement
Sets the default date style.

defaultStyle(Style) - Method in class dev.tamboui.widgets.calendar.Monthly.Builder
Sets the default style for dates.

defaultStyle(Style) - Method in class dev.tamboui.widgets.calendar.Monthly
Returns a new calendar with the default date style.

defaultValue() - Method in class dev.tamboui.style.Color.Named
Returns the default color value.

defaultValue() - Method in class dev.tamboui.style.PropertyDefinition
Returns the default value for this property, or null if none.

defaultValue(T) - Method in class dev.tamboui.style.PropertyDefinition.Builder
Sets the default value for this property.

DELETE - Enum constant in enum class dev.tamboui.tui.event.KeyCode
Delete key.

DELETE_BACKWARD - Static variable in class dev.tamboui.tui.bindings.Actions
Delete character backward (Backspace).

DELETE_FORWARD - Static variable in class dev.tamboui.tui.bindings.Actions
Delete character forward (Delete).

deleteBackward() - Method in class dev.tamboui.widgets.input.TextAreaState
Deletes the character before the cursor.

deleteBackward() - Method in class dev.tamboui.widgets.input.TextInputState
Deletes the character before the cursor.

deleteForward() - Method in class dev.tamboui.widgets.input.TextAreaState
Deletes the character after the cursor.

deleteForward() - Method in class dev.tamboui.widgets.input.TextInputState
Deletes the character after the cursor.

deleteLines(int) - Method in class dev.tamboui.backend.aesh.AeshBackend

deleteLines(int) - Method in class dev.tamboui.backend.jline3.JLineBackend

deleteLines(int) - Method in class dev.tamboui.backend.panama.PanamaBackend

deleteLines(int) - Method in interface dev.tamboui.terminal.Backend
Deletes N lines at the current cursor position, pulling lines below up.

Delim(char, Token.Position) - Constructor for class dev.tamboui.css.parser.Token.Delim
Creates a delimiter token.

denominator() - Method in class dev.tamboui.layout.Constraint.Ratio
Returns the denominator.

denominator() - Method in class dev.tamboui.layout.Fraction
Returns the denominator of this fraction.

depth() - Method in class dev.tamboui.widgets.tree.TreeWidget.FlatEntry
Returns the depth in the tree (0 for roots).

descendant() - Method in class dev.tamboui.css.selector.DescendantSelector
Returns the descendant selector.

DescendantSelector - Class in dev.tamboui.css.selector
A descendant combinator selector that matches nested elements.

DescendantSelector(Selector, Selector) - Constructor for class dev.tamboui.css.selector.DescendantSelector
Creates a descendant combinator selector.

describe() - Method in interface dev.tamboui.tui.bindings.InputTrigger
Returns a human-readable description of this trigger.

describe() - Method in class dev.tamboui.tui.bindings.KeyTrigger

describe() - Method in class dev.tamboui.tui.bindings.MouseTrigger

describeBindings(String) - Method in interface dev.tamboui.tui.bindings.Bindings
Returns a human-readable description of triggers for the action.

describeBindings(String) - Method in class dev.tamboui.tui.bindings.DefaultBindings

detect() - Static method in class dev.tamboui.capability.Capabilities
Detects capabilities from all discovered providers.

detect() - Static method in class dev.tamboui.image.capability.TerminalImageCapabilities
Detects terminal capabilities from the current environment.

dev.tamboui - package dev.tamboui

dev.tamboui.annotations.bindings - package dev.tamboui.annotations.bindings

dev.tamboui.backend.aesh - package dev.tamboui.backend.aesh

dev.tamboui.backend.jline3 - package dev.tamboui.backend.jline3

dev.tamboui.backend.panama - package dev.tamboui.backend.panama

dev.tamboui.backend.panama.unix - package dev.tamboui.backend.panama.unix

dev.tamboui.backend.panama.windows - package dev.tamboui.backend.panama.windows

dev.tamboui.buffer - package dev.tamboui.buffer

dev.tamboui.capability - package dev.tamboui.capability

dev.tamboui.capability.core - package dev.tamboui.capability.core

dev.tamboui.css - package dev.tamboui.css

dev.tamboui.css.cascade - package dev.tamboui.css.cascade

dev.tamboui.css.engine - package dev.tamboui.css.engine

dev.tamboui.css.model - package dev.tamboui.css.model

dev.tamboui.css.parser - package dev.tamboui.css.parser

dev.tamboui.css.property - package dev.tamboui.css.property

dev.tamboui.css.selector - package dev.tamboui.css.selector

dev.tamboui.error - package dev.tamboui.error

dev.tamboui.export - package dev.tamboui.export

dev.tamboui.export.html - package dev.tamboui.export.html

dev.tamboui.export.svg - package dev.tamboui.export.svg

dev.tamboui.export.text - package dev.tamboui.export.text

dev.tamboui.image - package dev.tamboui.image

dev.tamboui.image.capability - package dev.tamboui.image.capability

dev.tamboui.image.protocol - package dev.tamboui.image.protocol

dev.tamboui.inline - package dev.tamboui.inline

dev.tamboui.internal.record - package dev.tamboui.internal.record

dev.tamboui.jfr - package dev.tamboui.jfr

dev.tamboui.layout - package dev.tamboui.layout

dev.tamboui.layout.cassowary - package dev.tamboui.layout.cassowary

dev.tamboui.layout.columns - package dev.tamboui.layout.columns

dev.tamboui.layout.dock - package dev.tamboui.layout.dock

dev.tamboui.layout.flow - package dev.tamboui.layout.flow

dev.tamboui.layout.grid - package dev.tamboui.layout.grid

dev.tamboui.layout.stack - package dev.tamboui.layout.stack

dev.tamboui.picocli - package dev.tamboui.picocli

dev.tamboui.style - package dev.tamboui.style

dev.tamboui.symbols.merge - package dev.tamboui.symbols.merge

dev.tamboui.terminal - package dev.tamboui.terminal

dev.tamboui.text - package dev.tamboui.text

dev.tamboui.tfx - package dev.tamboui.tfx

dev.tamboui.tfx.effects - package dev.tamboui.tfx.effects

dev.tamboui.tfx.pattern - package dev.tamboui.tfx.pattern

dev.tamboui.tfx.toolkit - package dev.tamboui.tfx.toolkit

dev.tamboui.tfx.tui - package dev.tamboui.tfx.tui

dev.tamboui.toolkit - package dev.tamboui.toolkit

dev.tamboui.toolkit.app - package dev.tamboui.toolkit.app

dev.tamboui.toolkit.component - package dev.tamboui.toolkit.component

dev.tamboui.toolkit.element - package dev.tamboui.toolkit.element

dev.tamboui.toolkit.elements - package dev.tamboui.toolkit.elements

dev.tamboui.toolkit.event - package dev.tamboui.toolkit.event

dev.tamboui.toolkit.focus - package dev.tamboui.toolkit.focus

dev.tamboui.toolkit.id - package dev.tamboui.toolkit.id

dev.tamboui.toolkit.jfr - package dev.tamboui.toolkit.jfr

dev.tamboui.tui - package dev.tamboui.tui

dev.tamboui.tui.bindings - package dev.tamboui.tui.bindings

dev.tamboui.tui.bindings.processor - package dev.tamboui.tui.bindings.processor

dev.tamboui.tui.error - package dev.tamboui.tui.error

dev.tamboui.tui.event - package dev.tamboui.tui.event

dev.tamboui.tui.overlay - package dev.tamboui.tui.overlay

dev.tamboui.util - package dev.tamboui.util

dev.tamboui.widget - package dev.tamboui.widget

dev.tamboui.widgets - package dev.tamboui.widgets

dev.tamboui.widgets.barchart - package dev.tamboui.widgets.barchart

dev.tamboui.widgets.block - package dev.tamboui.widgets.block

dev.tamboui.widgets.calendar - package dev.tamboui.widgets.calendar

dev.tamboui.widgets.canvas - package dev.tamboui.widgets.canvas

dev.tamboui.widgets.canvas.shapes - package dev.tamboui.widgets.canvas.shapes

dev.tamboui.widgets.chart - package dev.tamboui.widgets.chart

dev.tamboui.widgets.checkbox - package dev.tamboui.widgets.checkbox
Checkbox widget for boolean input.

dev.tamboui.widgets.common - package dev.tamboui.widgets.common

dev.tamboui.widgets.error - package dev.tamboui.widgets.error

dev.tamboui.widgets.form - package dev.tamboui.widgets.form
Form state management and validation classes for TamboUI.

dev.tamboui.widgets.gauge - package dev.tamboui.widgets.gauge

dev.tamboui.widgets.input - package dev.tamboui.widgets.input

dev.tamboui.widgets.list - package dev.tamboui.widgets.list

dev.tamboui.widgets.logo - package dev.tamboui.widgets.logo

dev.tamboui.widgets.paragraph - package dev.tamboui.widgets.paragraph

dev.tamboui.widgets.scrollbar - package dev.tamboui.widgets.scrollbar

dev.tamboui.widgets.select - package dev.tamboui.widgets.select

dev.tamboui.widgets.sparkline - package dev.tamboui.widgets.sparkline

dev.tamboui.widgets.spinner - package dev.tamboui.widgets.spinner

dev.tamboui.widgets.table - package dev.tamboui.widgets.table

dev.tamboui.widgets.tabs - package dev.tamboui.widgets.tabs

dev.tamboui.widgets.toggle - package dev.tamboui.widgets.toggle
Toggle switch widget for on/off input.

dev.tamboui.widgets.tree - package dev.tamboui.widgets.tree
Tree widget for displaying hierarchical data.

dev.tamboui.widgets.wavetext - package dev.tamboui.widgets.wavetext

DiagonalPattern - Class in dev.tamboui.tfx.pattern
Diagonal pattern that sweeps diagonally across the area.

DiagonalPattern.DiagonalDirection - Enum Class in dev.tamboui.tfx.pattern
Direction variants for diagonal sweep patterns.

dialog() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty dialog.

dialog(Element...) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a dialog without a title.

dialog(String, Element...) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a dialog with a title and children.

DialogElement - Class in dev.tamboui.toolkit.elements
A dialog element that auto-centers in its parent area.

DialogElement() - Constructor for class dev.tamboui.toolkit.elements.DialogElement
Creates a new dialog element with default settings.

DialogElement(Element...) - Constructor for class dev.tamboui.toolkit.elements.DialogElement
Creates a new dialog element with the given children.

DialogElement(String, Element...) - Constructor for class dev.tamboui.toolkit.elements.DialogElement
Creates a new dialog element with the given title and children.

diff(Buffer, DiffResult) - Method in class dev.tamboui.buffer.Buffer
Calculates the differences between this buffer and another using a Data-Oriented Design approach with parallel arrays.

DiffResult - Class in dev.tamboui.buffer
A reusable container for buffer diff results using a Data-Oriented Design (DoD) layout.

DiffResult() - Constructor for class dev.tamboui.buffer.DiffResult
Creates a new diff result with the default initial capacity (256 updates).

DiffResult(int) - Constructor for class dev.tamboui.buffer.DiffResult
Creates a new diff result with the specified initial capacity.

dim() - Method in class dev.tamboui.style.Style
Enables dim text.

dim() - Method in class dev.tamboui.text.Span
Returns a new span with dim style.

dim() - Method in class dev.tamboui.toolkit.element.StyledElement
Applies the dim modifier.

DIM - Enum constant in enum class dev.tamboui.style.Modifier
Dim (faint) text.

DIM_FACTOR - Static variable in class dev.tamboui.widgets.wavetext.WaveText
The `wave-dim-factor` property for the dim factor (0.0-1.0).

dimFactor(double) - Method in class dev.tamboui.toolkit.elements.WaveTextElement

Sets the dim factor for non-peak characters.

dimFactor(double) - Method in class dev.tamboui.widgets.wavetext.WaveText.Builder
Sets the dim factor for the wave effect.

direction() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the layout direction, if set.

direction() - Method in class dev.tamboui.layout.Layout
Returns the layout direction.

direction(Direction) - Method in class dev.tamboui.css.cascade.CssStyleResolver.Builder
Sets the layout direction.

direction(Direction) - Method in class dev.tamboui.toolkit.elements.BarChartElement
Sets the direction.

direction(Direction) - Method in class dev.tamboui.toolkit.elements.DialogElement
Sets the layout direction for children.

direction(Direction) - Method in class dev.tamboui.toolkit.elements.Panel
Sets the layout direction for children.

direction(Direction) - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Sets the chart direction (default: VERTICAL).

direction(Sparkline.RenderDirection) - Method in class dev.tamboui.toolkit.elements.SparklineElement
Sets the render direction.

direction(Sparkline.RenderDirection) - Method in class dev.tamboui.widgets.sparkline.Sparkline.Builder
Sets the render direction.

Direction - Enum Class in dev.tamboui.layout
Layout direction for arranging elements.

DIRECTION - Static variable in class dev.tamboui.style.StandardProperties
The `direction` property for layout direction.

DirectionalVariance - Class in dev.tamboui.tfx
Generates random variances for directional effects.

DirectionConverter - Class in dev.tamboui.css.property
Converts CSS direction values to Direction enum.

DirectionConverter - Class in dev.tamboui.layout
Converts string values to `Direction` enum values.

disable(Backend) - Static method in class dev.tamboui.terminal.Mode2027Support
Disables Mode 2027 grapheme cluster mode on the terminal.

disableMouseCapture() - Method in class dev.tamboui.backend.aesh.AeshBackend

disableMouseCapture() - Method in class dev.tamboui.backend.jline3.JLineBackend

disableMouseCapture() - Method in class dev.tamboui.backend.panama.PanamaBackend

disableMouseCapture() - Method in class dev.tamboui.internal.record.RecordingBackend

disableMouseCapture() - Method in interface dev.tamboui.terminal.Backend
Disables mouse capture.

disableRawMode() - Method in class dev.tamboui.backend.aesh.AeshBackend

disableRawMode() - Method in class dev.tamboui.backend.jline3.JLineBackend

disableRawMode() - Method in class dev.tamboui.backend.panama.PanamaBackend

disableRawMode() - Method in interface dev.tamboui.backend.panama.PlatformTerminal
Disables raw mode and restores original terminal attributes.

disableRawMode() - Method in class dev.tamboui.backend.panama.unix.UnixTerminal

Disables raw mode and restores original terminal attributes.

disableRawMode() - Method in class dev.tamboui.backend.panama.windows.WindowsTerminal

disableRawMode() - Method in class dev.tamboui.internal.record.RecordingBackend

disableRawMode() - Method in interface dev.tamboui.terminal.Backend
Disables raw mode.

disableSequence() - Static method in class dev.tamboui.terminal.Mode2027Support
Constructs the disable sequence for Mode 2027.

dispatch(Event) - Method in class dev.tamboui.tui.bindings.ActionHandler
Dispatches an event to registered handlers.

dispatch(Event) - Method in class dev.tamboui.tui.TuiRunner
Dispatches an event into the event queue.

DISPLAY_AND_QUIT - Enum constant in enum class dev.tamboui.tui.error.ErrorAction
Display the error in the UI, wait for user dismissal, then quit.

displayAndQuit() - Static method in class dev.tamboui.tui.error.RenderErrorHandlers
Returns the default handler that displays the error in the UI.

displayOnly() - Method in class dev.tamboui.toolkit.elements.ListElement
Configures the list for display-only mode (non-interactive scrolling).

displayValue() - Method in class dev.tamboui.widgets.barchart.Bar
Returns the display string for this bar's value.

dissolve(long, Interpolation) - Static method in class dev.tamboui.tfx.Fx
Creates a dissolve effect that dissolves text over time.

dissolve(EffectTimer) - Static method in class dev.tamboui.tfx.effects.DissolveShader
Creates a dissolve shader that dissolves text over time.

dissolve(EffectTimer) - Static method in class dev.tamboui.tfx.Fx
Creates a dissolve effect that dissolves text over time.

DissolveShader - Class in dev.tamboui.tfx.effects
A dissolve effect that randomly dissolves text characters over time.

dissolveTo(Style, long, Interpolation) - Static method in class dev.tamboui.tfx.Fx
Creates a dissolve effect that dissolves text to a specific style.

dissolveTo(Style, EffectTimer) - Static method in class dev.tamboui.tfx.effects.DissolveShader
Creates a dissolve shader that dissolves to a specific style.

dissolveTo(Style, EffectTimer) - Static method in class dev.tamboui.tfx.Fx
Creates a dissolve effect that dissolves text to a specific style.

divide(long) - Method in class dev.tamboui.layout.cassowary.Expression
Divides this expression by a scalar.

divide(Fraction) - Method in class dev.tamboui.layout.cassowary.Expression
Divides this expression by a scalar.

divide(Fraction) - Method in class dev.tamboui.layout.Fraction
Returns the quotient of this fraction divided by another.

divider(Span) - Method in class dev.tamboui.widgets.tabs.Tabs.Builder
Sets the divider between tabs.

divider(String) - Method in class dev.tamboui.toolkit.elements.TabsElement
Sets the divider between tabs.

divider(String) - Method in class dev.tamboui.widgets.tabs.Tabs.Builder
Sets the divider between tabs.

dock() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty dock layout.

Dock - Class in dev.tamboui.layout.dock

A 5-region dock layout widget that arranges children into top, bottom, left, right, and center regions — the most common TUI application structure (header + sidebar + content + footer).

DOCK_BOTTOM_HEIGHT - Static variable in class dev.tamboui.toolkit.elements.DockElement
CSS property definition for the bottom region height.

DOCK_LEFT_WIDTH - Static variable in class dev.tamboui.toolkit.elements.DockElement
CSS property definition for the left region width.

DOCK_RIGHT_WIDTH - Static variable in class dev.tamboui.toolkit.elements.DockElement
CSS property definition for the right region width.

DOCK_TOP_HEIGHT - Static variable in class dev.tamboui.toolkit.elements.DockElement
CSS property definition for the top region height.

Dock.Builder - Class in dev.tamboui.layout.dock
Builder for `Dock`.

DockElement - Class in dev.tamboui.toolkit.elements
A 5-region dock layout element that arranges children into top, bottom, left, right, and center regions — the most common TUI application structure (header + sidebar + content + footer).

DockElement() - Constructor for class dev.tamboui.toolkit.elements.DockElement
Creates an empty dock layout.

done() - Method in class dev.tamboui.tfx.Effect
Returns true if the effect is done.

done() - Method in class dev.tamboui.tfx.effects.DissolveShader

done() - Method in class dev.tamboui.tfx.effects.ExpandShader

done() - Method in class dev.tamboui.tfx.effects.FadeShader

done() - Method in class dev.tamboui.tfx.effects.PaintShader

done() - Method in class dev.tamboui.tfx.effects.ParallelEffect

done() - Method in class dev.tamboui.tfx.effects.SequentialEffect

done() - Method in class dev.tamboui.tfx.effects.SlideShader

done() - Method in class dev.tamboui.tfx.effects.StretchShader

done() - Method in class dev.tamboui.tfx.effects.SweepShader

done() - Method in class dev.tamboui.tfx.EffectTimer
Returns true if the timer has completed.

done() - Method in interface dev.tamboui.tfx.Shader
Returns true if the shader effect is done.

dot() - Method in class dev.tamboui.toolkit.elements.CanvasElement
Uses dot marker.

DOT - Enum constant in enum class dev.tamboui.widgets.canvas.Marker
One point per cell in shape of a dot (•).

DOT - Enum constant in enum class dev.tamboui.widgets.chart.Dataset.Marker
Dot marker: •

dots() - Static method in class dev.tamboui.widgets.spinner.Spinner
Creates a simple spinner with default DOTS style.

DOTS - Enum constant in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Braille dot pattern spinner.

DOUBLE - Enum constant in enum class dev.tamboui.widgets.block.BorderType
Double-line border using double-line box-drawing characters.

DOUBLE - Static variable in class dev.tamboui.widgets.gauge.LineGauge
Line character set using double lines.

DOUBLE_HORIZONTAL - Static variable in class dev.tamboui.widgets.scrollbar.Scrollbar.SymbolSet
Horizontal scrollbar with double-line track and triangle arrows.

DOUBLE_VERTICAL - Static variable in class dev.tamboui.widgets.scrollbar.Scrollbar.SymbolSet
Vertical scrollbar with double-line track and triangle arrows.

doubleBorder() - Method in class dev.tamboui.toolkit.elements.DialogElement
Sets the border type to double.

doubleBorder() - Method in class dev.tamboui.toolkit.elements.Panel
Sets the border type to double.

DoubleConverter - Class in dev.tamboui.style
Converts string values to Double objects.

doubleLine() - Method in class dev.tamboui.toolkit.elements.LineGaugeElement
Uses double line characters.

doubleLine() - Method in class dev.tamboui.toolkit.elements.ScrollbarElement
Uses double-line symbols.

DOWN - Enum constant in enum class dev.tamboui.tui.event.KeyCode
Down arrow key.

DOWN_TO_UP - Enum constant in enum class dev.tamboui.tfx.Motion
Movement from bottom to top

downToUp(float) - Static method in class dev.tamboui.tfx.pattern.SweepPattern
Creates a down-to-up sweep pattern.

drag(MouseButton) - Static method in class dev.tamboui.tui.bindings.MouseTrigger
Creates a trigger for a drag event.

drag(MouseButton, int, int) - Static method in class dev.tamboui.tui.event.MouseEvent
Creates a mouse drag event.

DRAG - Enum constant in enum class dev.tamboui.tui.event.MouseEventKind
Mouse was moved while a button is held (drag).

draggable - Variable in class dev.tamboui.toolkit.element.StyledElement
Whether this element is draggable.

draggable(BiConsumer) - Method in class dev.tamboui.toolkit.element.StyledElement
Makes this element draggable with position callback.

draggingElement() - Method in class dev.tamboui.toolkit.event.EventRouter
Returns the element being dragged.

dragHandler - Variable in class dev.tamboui.toolkit.element.StyledElement
The drag handler for this element.

dragHandler() - Method in class dev.tamboui.toolkit.element.StyledElement
Returns the drag handler, if any.

DragHandler - Interface in dev.tamboui.toolkit.event
Handler for drag operations on an element.

DragStateEvent - Class in dev.tamboui.toolkit.jfr
JFR event emitted for drag state transitions (start/drag/end/cancel).

draw(DiffResult) - Method in class dev.tamboui.internal.record.RecordingBackend

draw(DiffResult) - Method in class dev.tamboui.terminal.AbstractBackend
Draws the given cell updates to the terminal using Data-Oriented Design.

draw(DiffResult) - Method in interface dev.tamboui.terminal.Backend
Draws the given cell updates to the terminal using a Data-Oriented Design approach.

draw(Painter) - Method in interface dev.tamboui.widgets.canvas.Shape

Draws this shape using the provided painter.

draw(Painter) - Method in class dev.tamboui.widgets.canvas.shapes.Circle

draw(Painter) - Method in class dev.tamboui.widgets.canvas.shapes.Line

draw(Painter) - Method in class dev.tamboui.widgets.canvas.shapes.Points

draw(Painter) - Method in class dev.tamboui.widgets.canvas.shapes.Rectangle

draw(Shape) - Method in class dev.tamboui.widgets.canvas.Context
Draws a shape on this context.

draw(Consumer) - Method in class dev.tamboui.terminal.Terminal
Draws a frame using the provided rendering function.

draw(Consumer) - Method in class dev.tamboui.tui.InlineTuiRunner
Draws the UI using the given renderer.

draw(Consumer) - Method in class dev.tamboui.tui.TuiRunner
Draws the UI using the given renderer.

DuplicateConstraintException - Exception Class in dev.tamboui.layout.cassowary
Thrown when attempting to add a constraint that already exists in the solver.

DuplicateConstraintException(CassowaryConstraint) - Constructor for exception class dev.tamboui.layout.cassowary.DuplicateConstraintException
Creates a new exception for the duplicate constraint.

duration() - Method in class dev.tamboui.tfx.EffectTimer
Returns the total duration.

E

ECHO - Static variable in class dev.tamboui.backend.panama.unix.LibC
Local flag: enable echo of input characters.

ECHO - Static variable in class dev.tamboui.backend.panama.unix.PlatformConstants
Local flag: enable echo of input characters.

Effect - Class in dev.tamboui.tfx
Represents an effect that can be applied to terminal cells.

effectCount() - Method in class dev.tamboui.tfx.tui.TfxIntegration
Returns the number of active effects.

effectiveModifiers() - Method in class dev.tamboui.style.Style
Returns the effective set of modifiers (add - sub).

EffectManager - Class in dev.tamboui.tfx
Manages a collection of terminal UI effects and their lifecycle.

EffectManager() - Constructor for class dev.tamboui.tfx.EffectManager
Creates a new EffectManager.

EffectTimer - Class in dev.tamboui.tfx
Manages the timing and interpolation of effects.

EINTR - Static variable in class dev.tamboui.backend.panama.unix.LibC
Errno value indicating an interrupted system call.

elapsed() - Method in class dev.tamboui.tui.event.TickEvent
Returns the time elapsed since the last tick.

elapsedMillis() - Method in class dev.tamboui.tui.event.TickEvent
Returns the elapsed time in milliseconds.

elapsedSeconds() - Method in class dev.tamboui.tui.event.TickEvent
Returns the elapsed time in seconds as a double.

ElasticIn - Enum constant in enum class dev.tamboui.tfx.Interpolation

Elastic easing - in

ElasticInOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Elastic easing - in-out

ElasticOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Elastic easing - out

Element - Interface in dev.tamboui.toolkit.element
Base interface for all DSL elements.

elementCount() - Method in class dev.tamboui.toolkit.event.EventRouter
Returns the number of registered elements (for debugging).

ElementEffectRegistry - Class in dev.tamboui.tfx.toolkit
Registry for effects that target specific elements by ID.

ElementEffectRegistry() - Constructor for class dev.tamboui.tfx.toolkit.ElementEffectRegistry
Creates a new ElementEffectRegistry.

elementId - Variable in class dev.tamboui.toolkit.element.StyledElement
The unique identifier for this element.

elementId() - Method in class dev.tamboui.toolkit.elements.ErrorPlaceholder
Returns the ID of the element that failed, if available.

elementRegistry() - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner
Returns the element registry.

elementRegistry() - Method in class dev.tamboui.toolkit.app.ToolkitRunner
Returns the element registry for ID-based area lookups.

elementRegistry() - Method in class dev.tamboui.toolkit.element.DefaultRenderContext
Returns the element registry for ID-based area lookups.

elementRegistry() - Method in class dev.tamboui.toolkit.event.EventRouter
Returns the element registry used by this router.

ElementRegistry - Class in dev.tamboui.toolkit.element
Registry that maps elements to their rendered areas with full CSS selector support.

ElementRegistry() - Constructor for class dev.tamboui.toolkit.element.ElementRegistry
Creates a new empty element registry.

ElementRegistry.ElementInfo - Class in dev.tamboui.toolkit.element
Information about a registered element.

elements(StyledElement...) - Method in class dev.tamboui.toolkit.elements.ListElement
Sets the list items from styled elements.

ellipsis() - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Convenience method to truncate with ellipsis at end.

ellipsis() - Method in class dev.tamboui.toolkit.elements.MarkupTextElement
Truncates with ellipsis at the end.

ellipsis() - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Convenience method to truncate with ellipsis at end.

ellipsis() - Method in class dev.tamboui.toolkit.elements.RichTextElement
Truncates with ellipsis at the end.

ellipsis() - Method in class dev.tamboui.toolkit.elements.TextElement
Convenience method to truncate with ellipsis at the end: "Long text..."

ellipsis() - Method in class dev.tamboui.widgets.block.Title
Truncate with ellipsis at end if title doesn't fit: "Long title..."

ELLIPSIS - Enum constant in enum class dev.tamboui.style.Overflow
Truncate with ellipsis at the end: "Long text..."

ELLIPSIS_MIDDLE - Enum constant in enum class dev.tamboui.style.Overflow
Truncate with ellipsis in the middle: "Long...text"

ELLIPSIS_START - Enum constant in enum class dev.tamboui.style.Overflow
Truncate with ellipsis at the start: "...ong text"

ellipsisMiddle() - Method in class dev.tamboui.toolkit.elements.RichTextElement
Truncates with ellipsis in the middle.

ellipsisMiddle() - Method in class dev.tamboui.toolkit.elements.TextElement
Convenience method to truncate with ellipsis in the middle: "Long...text"

ellipsisMiddle() - Method in class dev.tamboui.widgets.block.Title
Truncate with ellipsis in middle if title doesn't fit: "Long...itle"

ellipsisStart() - Method in class dev.tamboui.toolkit.elements.RichTextElement
Truncates with ellipsis at the start.

ellipsisStart() - Method in class dev.tamboui.toolkit.elements.TextElement
Convenience method to truncate with ellipsis at the start: "...ong text"

ellipsisStart() - Method in class dev.tamboui.widgets.block.Title
Truncate with ellipsis at start if title doesn't fit: "...ong title"

emacs() - Static method in class dev.tamboui.tui.bindings.BindingSets
Emacs-style binding set with Ctrl+n/p/f/b navigation.

email() - Static method in class dev.tamboui.widgets.form.Validators
Creates a validator that requires a valid email format.

email(String) - Static method in class dev.tamboui.widgets.form.Validators
Creates a validator that requires a valid email format with a custom message.

Emoji - Class in dev.tamboui.text
Replaces emoji codes (e.g.

emojis() - Static method in class dev.tamboui.text.Emoji
Returns the map of emoji shortcodes to Unicode emoji characters.

empty() - Static method in class dev.tamboui.css.cascade.CssStyleResolver
Creates an empty resolved style.

empty() - Static method in class dev.tamboui.css.cascade.TypedPropertyMap
Returns an empty property map.

empty() - Static method in class dev.tamboui.css.model.Stylesheet
Creates an empty stylesheet.

empty() - Static method in interface dev.tamboui.style.StylePropertyResolver
Returns an empty resolver that never resolves any properties.

empty() - Static method in class dev.tamboui.style.Tags
Returns an empty Tags instance.

empty() - Static method in class dev.tamboui.text.Line
Creates an empty line with no spans.

empty() - Static method in class dev.tamboui.text.Text
Creates an empty text with no lines.

empty() - Static method in interface dev.tamboui.toolkit.element.RenderContext
Creates an empty context for simple rendering without focus management.

empty() - Method in class dev.tamboui.widgets.barchart.BarChart.BarSet
Returns the empty symbol.

empty() - Static method in class dev.tamboui.widgets.block.Block
Creates an empty block with no borders.

empty() - Static method in class dev.tamboui.widgets.calendar.CalendarEventStore
Creates an empty event store.

empty() - Method in class dev.tamboui.widgets.sparkline.Sparkline.BarSet
Returns the empty symbol.

empty() - Static method in class dev.tamboui.widgets.table.Cell

Creates an empty cell.

empty() - Static method in class dev.tamboui.widgets.table.Row
Creates an empty row.

empty(Rect) - Static method in class dev.tamboui.buffer.Buffer
Creates an empty buffer filled with empty cells.

EMPTY - Static variable in class dev.tamboui.buffer.Cell
An empty cell containing a single space with no style.

EMPTY - Static variable in class dev.tamboui.style.Style
An empty style with no colors or modifiers set.

EMPTY_CELL - Static variable in class dev.tamboui.layout.grid.GridArea
Represents an empty cell in the area template.

enable(Backend) - Static method in class dev.tamboui.terminal.Mode2027Support
Enables Mode 2027 grapheme cluster mode on the terminal.

ENABLE_ECHO_INPUT - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
Console input mode flag: echo typed characters to the console.

ENABLE_LINE_INPUT - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
Console input mode flag: enable line-at-a-time input.

ENABLE_PROCESSED_INPUT - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
Console input mode flag: enable processing of control keys (Ctrl+C, etc.).

ENABLE_PROCESSED_OUTPUT - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
Console output mode flag: enable processing of output control sequences.

ENABLE_VIRTUAL_TERMINAL_INPUT - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
Console input mode flag: enable virtual terminal input sequences.

ENABLE_VIRTUAL_TERMINAL_PROCESSING - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
Console output mode flag: enable virtual terminal processing of ANSI escape sequences.

ENABLE_WINDOW_INPUT - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
Console input mode flag: report window buffer size changes as input events.

enabled() - Static method in class dev.tamboui.jfr.TerminalDrawEvent
Returns whether this event type is enabled.

enabled() - Static method in class dev.tamboui.toolkit.jfr.CandidateEvent
Returns whether this event type is enabled.

enabled() - Static method in class dev.tamboui.toolkit.jfr.DragStateEvent
Returns whether this event type is enabled.

enabled() - Static method in class dev.tamboui.toolkit.jfr.FocusChangeEvent
Returns whether this event type is enabled.

enabled() - Static method in class dev.tamboui.toolkit.jfr.FocusNavigationEvent
Returns whether this event type is enabled.

enabled() - Static method in class dev.tamboui.toolkit.jfr.GlobalHandlerEvent
Returns whether this event type is enabled.

enabled() - Static method in class dev.tamboui.toolkit.jfr.RoutingEvent
Returns whether this event type is enabled.

ENABLED - Enum constant in enum class dev.tamboui.terminal.Mode2027Status
Mode 2027 is currently enabled (Ps=1 or Ps=3 in DECRPM response).

enableMouseCapture() - Method in class dev.tamboui.backend.aesh.AeshBackend

enableMouseCapture() - Method in class dev.tamboui.backend.jline3.JLineBackend

enableMouseCapture() - Method in class dev.tamboui.backend.panama.PanamaBackend

enableMouseCapture() - Method in class dev.tamboui.internal.record.RecordingBackend

enableMouseCapture() - Method in interface dev.tamboui.terminal.Backend
Enables mouse capture.

enableRawMode() - Method in class dev.tamboui.backend.aesh.AeshBackend

enableRawMode() - Method in class dev.tamboui.backend.jline3.JLineBackend

enableRawMode() - Method in class dev.tamboui.backend.panama.PanamaBackend

enableRawMode() - Method in interface dev.tamboui.backend.panama.PlatformTerminal
Enables raw mode on the terminal.

enableRawMode() - Method in class dev.tamboui.backend.panama.unix.UnixTerminal
Enables raw mode on the terminal.

enableRawMode() - Method in class dev.tamboui.backend.panama.windows.WindowsTerminal

enableRawMode() - Method in class dev.tamboui.internal.record.RecordingBackend

enableRawMode() - Method in interface dev.tamboui.terminal.Backend
Enables raw mode (disables line buffering and echo).

enableSequence() - Static method in class dev.tamboui.terminal.Mode2027Support
Constructs the enable sequence for Mode 2027.

encode(Buffer, Rect, O, Appendable) - Method in interface dev.tamboui.export.Encoder
Encodes the given region of the buffer with the given options and appends the result to the output.

encoder() - Method in interface dev.tamboui.export.Format
Returns the encoder for this format.

encoder() - Method in class dev.tamboui.export.html.HtmlFormat

encoder() - Method in class dev.tamboui.export.svg.SvgFormat

encoder() - Method in class dev.tamboui.export.text.TextFormat

Encoder<O> - Interface in dev.tamboui.export
Encodes a region of a buffer to a format and writes to an `Appendable`.

end() - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.SymbolSet
Returns the end marker character.

END - Enum constant in enum class dev.tamboui.layout.Flex
Pack elements to the end.

END - Enum constant in enum class dev.tamboui.text.CharWidth.TruncatePosition
Truncate at end: "Hello..."

END - Enum constant in enum class dev.tamboui.tui.event.KeyCode
End key.

END - Static variable in class dev.tamboui.tui.bindings.Actions
Go to end (End, vim 'G', emacs Alt+>, etc.).

endColumn() - Method in class dev.tamboui.layout.grid.GridArea.AreaBounds
Returns the end column (exclusive).

endGroup() - Method in class dev.tamboui.toolkit.elements.FormElement
Ends the current field group.

endRow() - Method in class dev.tamboui.layout.grid.GridArea.AreaBounds
Returns the end row (exclusive).

ENDS_WITH - Enum constant in enum class dev.tamboui.css.selector.AttributeSelector.Operator
Ends with

endStyle(Style) - Method in class dev.tamboui.toolkit.elements.ScrollbarElement

Sets the end marker style.

endStyle(Style) - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.Builder
Sets the style for the end marker.

endSymbol(String) - Method in class dev.tamboui.toolkit.elements.ScrollbarElement
Sets the end marker symbol.

endSymbol(String) - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.Builder
Sets the end marker symbol (e.g., down arrow for vertical scrollbar).

ensureCursorVisible(int, int) - Method in class dev.tamboui.widgets.input.TextAreaState
Adjusts scroll offsets to keep the cursor visible.

ensureLineVisible(int) - Method in class dev.tamboui.style.RichTextState
Ensures the specified line is visible, scrolling if necessary.

ensureLineVisible(int) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Ensures the specified line is visible, scrolling if necessary.

ensureLineVisible(int) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Ensures the specified line is visible, scrolling if necessary.

ENTER - Enum constant in enum class dev.tamboui.tui.event.KeyCode
Enter key.

enterAlternateScreen() - Method in class dev.tamboui.backend.aesh.AeshBackend

enterAlternateScreen() - Method in class dev.tamboui.backend.jline3.JLineBackend

enterAlternateScreen() - Method in class dev.tamboui.backend.panama.PanamaBackend

enterAlternateScreen() - Method in class dev.tamboui.internal.record.RecordingBackend

enterAlternateScreen() - Method in interface dev.tamboui.terminal.Backend
Enters the alternate screen buffer.

env(String, String) - Method in class dev.tamboui.capability.CapabilityReportBuilder
Adds an environment key that should be printed (value resolved at print-time).

environmentBySource() - Method in class dev.tamboui.capability.CapabilityReport
Environment entries grouped by provider source.

EOF(Token.Position) - Constructor for class dev.tamboui.css.parser.Token.EOF
Creates an end-of-file token.

EQ - Enum constant in enum class dev.tamboui.layout.cassowary.Relation
Equality constraint: the expression must equal zero.

equals(Object) - Method in class dev.tamboui.buffer.Buffer

equals(Object) - Method in class dev.tamboui.buffer.Cell

equals(Object) - Method in class dev.tamboui.css.cascade.PseudoClassState

equals(Object) - Method in class dev.tamboui.css.cascade.TypedPropertyMap

equals(Object) - Method in class dev.tamboui.css.model.PropertyValue

equals(Object) - Method in class dev.tamboui.css.model.Rule

equals(Object) - Method in class dev.tamboui.css.model.Stylesheet

equals(Object) - Method in class dev.tamboui.css.parser.Token.Position

equals(Object) - Method in class dev.tamboui.css.selector.AttributeSelector

equals(Object) - Method in class dev.tamboui.css.selector.ChildSelector

equals(Object) - Method in class dev.tamboui.css.selector.ClassSelector

equals(Object) - Method in class dev.tamboui.css.selector.CompoundSelector

equals(Object) - Method in class dev.tamboui.css.selector.DescendantSelector

equals(Object) - Method in class dev.tamboui.css.selector.IdSelector

equals(Object) - Method in class dev.tamboui.css.selector.PseudoClassSelector

equals(Object) - Method in class dev.tamboui.css.selector.TypeSelector

equals(Object) - Method in class dev.tamboui.layout.cassowary.CassowaryConstraint

equals(Object) - Method in class dev.tamboui.layout.cassowary.Expression

equals(Object) - Method in class dev.tamboui.layout.cassowary.Strength

equals(Object) - Method in class dev.tamboui.layout.cassowary.Term

equals(Object) - Method in class dev.tamboui.layout.cassowary.Variable

equals(Object) - Method in class dev.tamboui.layout.Constraint.Fill

equals(Object) - Method in class dev.tamboui.layout.Constraint.Fit

equals(Object) - Method in class dev.tamboui.layout.Constraint.Length

equals(Object) - Method in class dev.tamboui.layout.Constraint.Max

equals(Object) - Method in class dev.tamboui.layout.Constraint.Min

equals(Object) - Method in class dev.tamboui.layout.Constraint.Percentage

equals(Object) - Method in class dev.tamboui.layout.Constraint.Ratio

equals(Object) - Method in class dev.tamboui.layout.Fraction

equals(Object) - Method in class dev.tamboui.layout.Margin

equals(Object) - Method in class dev.tamboui.layout.Padding

equals(Object) - Method in class dev.tamboui.layout.Position

equals(Object) - Method in class dev.tamboui.layout.Rect

equals(Object) - Method in class dev.tamboui.layout.Size

equals(Object) - Method in class dev.tamboui.layout.Spacing.Overlap

equals(Object) - Method in class dev.tamboui.layout.Spacing.Space

equals(Object) - Method in class dev.tamboui.style.Color.Ansi

equals(Object) - Method in class dev.tamboui.style.Color.Indexed

equals(Object) - Method in class dev.tamboui.style.Color.Named

equals(Object) - Method in class dev.tamboui.style.Color.Reset

equals(Object) - Method in class dev.tamboui.style.Color.Rgb

equals(Object) - Method in class dev.tamboui.style.Hyperlink

equals(Object) - Method in class dev.tamboui.style.PropertyDefinition

equals(Object) - Method in class dev.tamboui.style.Style

equals(Object) - Method in class dev.tamboui.style.Tags

equals(Object) - Method in class dev.tamboui.style.Width

equals(Object) - Method in class dev.tamboui.terminal.CompletedFrame

equals(Object) - Method in class dev.tamboui.text.Line

equals(Object) - Method in class dev.tamboui.text.Masked

equals(Object) - Method in class dev.tamboui.text.Span

equals(Object) - Method in class dev.tamboui.text.Text

equals(Object) - Method in class dev.tamboui.tfx.EffectTimer

equals(Object) - Method in class dev.tamboui.tfx.SimpleRng

equals(Object) - Method in class dev.tamboui.tfx.TFxDuration

equals(Object) - Method in class dev.tamboui.toolkit.element.ChildPosition

equals(Object) - Method in class dev.tamboui.toolkit.element.Size

equals(Object) - Method in class dev.tamboui.toolkit.elements.GridSize

equals(Object) - Method in class dev.tamboui.toolkit.elements.Gutter

equals(Object) - Method in class dev.tamboui.tui.bindings.KeyTrigger

equals(Object) - Method in class dev.tamboui.tui.bindings.MouseTrigger

equals(Object) - Method in class dev.tamboui.tui.event.ActionEvent

equals(Object) - Method in class dev.tamboui.tui.event.KeyEvent

equals(Object) - Method in class dev.tamboui.tui.event.KeyModifiers

equals(Object) - Method in class dev.tamboui.tui.event.MouseEvent

equals(Object) - Method in class dev.tamboui.tui.event.ResizeEvent

equals(Object) - Method in class dev.tamboui.tui.event.TickEvent

equals(Object) - Method in class dev.tamboui.tui.TuiConfig

equals(Object) - Method in class dev.tamboui.widgets.barchart.BarChart.BarSet

equals(Object) - Method in class dev.tamboui.widgets.block.BorderSet

equals(Object) - Method in class dev.tamboui.widgets.block.Title

equals(Object) - Method in class dev.tamboui.widgets.canvas.Painter.GridPoint

equals(Object) - Method in class dev.tamboui.widgets.canvas.shapes.Circle

equals(Object) - Method in class dev.tamboui.widgets.canvas.shapes.Line

equals(Object) - Method in class dev.tamboui.widgets.canvas.shapes.Points

equals(Object) - Method in class dev.tamboui.widgets.canvas.shapes.Rectangle

equals(Object) - Method in class dev.tamboui.widgets.form.ValidationResult

equals(Object) - Method in class dev.tamboui.widgets.gauge.LineGauge.LineSet

equals(Object) - Method in class dev.tamboui.widgets.list.ListItem

equals(Object) - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.SymbolSet

equals(Object) - Method in class dev.tamboui.widgets.sparkline.Sparkline.BarSet

equals(Object) - Method in class dev.tamboui.widgets.spinner.SpinnerFrameSet

EQUALS - Enum constant in enum class dev.tamboui.css.selector.AttributeSelector.Operator
Exact match

equalTo(long, Strength) - Method in class dev.tamboui.layout.cassowary.Expression
Creates an equality constraint: this == value.

equalTo(Expression, Strength) - Method in class dev.tamboui.layout.cassowary.Expression
Creates an equality constraint: this == other.

equalTo(Fraction, Strength) - Method in class dev.tamboui.layout.cassowary.Expression
Creates an equality constraint: this == value.

eraseToEndOfLine() - Method in class dev.tamboui.backend.aesh.AeshBackend

eraseToEndOfLine() - Method in class dev.tamboui.backend.jline3.JLineBackend

eraseToEndOfLine() - Method in class dev.tamboui.backend.panama.PanamaBackend

eraseToEndOfLine() - Method in interface dev.tamboui.terminal.Backend
Erases from the cursor to the end of the line.

error(Throwable) - Method in class dev.tamboui.widgets.error.ErrorDisplay.Builder
Sets the error to display.

ErrorAction - Enum Class in dev.tamboui.tui.error
Defines the actions that can be taken when a render error occurs.

errorBorderColor(Color) - Method in class dev.tamboui.toolkit.elements.FormElement
Sets the border color when validation fails.

errorBorderColor(Color) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Sets the border color when validation fails.

ErrorContext - Interface in dev.tamboui.tui.error
Context provided to error handlers when a render error occurs.

ErrorDisplay - Class in dev.tamboui.widgets.error
A widget that displays error information with a stack trace.

ErrorDisplay.Builder - Class in dev.tamboui.widgets.error
Builder for `ErrorDisplay`.

errorHandler() - Method in class dev.tamboui.tui.TuiConfig
Returns the error handler for render errors.

errorHandler(RenderErrorHandler) - Method in class dev.tamboui.tui.TuiConfig.Builder
Sets the error handler for render errors.

errorMessage() - Method in class dev.tamboui.widgets.form.ValidationResult
Returns the error message if validation failed.

errorOutput() - Method in interface dev.tamboui.tui.error.ErrorContext
Returns the output stream for logging fatal errors.

errorOutput() - Method in class dev.tamboui.tui.TuiConfig
Returns the output stream for error logging.

errorOutput(PrintStream) - Method in class dev.tamboui.toolkit.app.ToolkitRunner.Builder
Sets the output stream for error logging.

errorOutput(PrintStream) - Method in class dev.tamboui.tui.TuiConfig.Builder
Sets the output stream for error logging.

ErrorPlaceholder - Class in dev.tamboui.toolkit.elements
An element that displays an error placeholder when another element fails to render.

errorStyle(Style) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Sets the error message style.

ESCAPE - Enum constant in enum class dev.tamboui.tui.event.KeyCode
Escape key.

evalCell(Predicate) - Static method in class dev.tamboui.tfx.CellFilter
Selects cells using a custom cell-content-based predicate function.

Event - Interface in dev.tamboui.tui.event
Base interface for all TUI events.

eventHandler(EventHandler) - Method in class dev.tamboui.tui.TuiRunner.Builder
Sets the event handler for the application.

EventHandler - Interface in dev.tamboui.tui
Functional interface for handling TUI events.

EventParser - Class in dev.tamboui.tui.event
Parses raw terminal input into typed `Event` objects.

EventResult - Enum Class in dev.tamboui.toolkit.event
Result of handling an event.

eventRouter() - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner
Returns the event router.

eventRouter() - Method in class dev.tamboui.toolkit.app.ToolkitRunner
Returns the event router.

eventRouter() - Method in class dev.tamboui.toolkit.element.DefaultRenderContext
Returns the event router.

EventRouter - Class in dev.tamboui.toolkit.event
Routes events to elements based on focus and position.

EventRouter(FocusManager, ElementRegistry) - Constructor for class dev.tamboui.toolkit.event.EventRouter
Creates a new event router with tracing enabled when available.

EXACT - Enum constant in enum class dev.tamboui.symbols.merge.MergeStrategy
Merges symbols only if an exact composite unicode character exists.

Examples - Section in class dev.tamboui.widgets.logo.Logo

Example Usage - Section in class dev.tamboui.toolkit.elements.GenericWidgetElement

Example Usage - Section in class dev.tamboui.toolkit.elements.InlineScopeElement

exceptionType() - Method in class dev.tamboui.tui.error.RenderError
Returns the simple class name of the exception.

execute(TFxDuration, Rect, Buffer) - Method in class dev.tamboui.tfx.effects.DissolveShader

execute(TFxDuration, Rect, Buffer) - Method in class dev.tamboui.tfx.effects.ExpandShader

execute(TFxDuration, Rect, Buffer) - Method in class dev.tamboui.tfx.effects.FadeShader

execute(TFxDuration, Rect, Buffer) - Method in class dev.tamboui.tfx.effects.PaintShader

execute(TFxDuration, Rect, Buffer) - Method in class dev.tamboui.tfx.effects.SlideShader

execute(TFxDuration, Rect, Buffer) - Method in class dev.tamboui.tfx.effects.StretchShader

execute(TFxDuration, Rect, Buffer) - Method in class dev.tamboui.tfx.effects.SweepShader

execute(TFxDuration, Rect, Buffer) - Method in interface dev.tamboui.tfx.Shader
Executes the shader effect after the duration has been applied to the timer.

EXISTS - Enum constant in enum class dev.tamboui.css.selector.AttributeSelector.Operator
Attribute exists

expand(ExpandDirection, Style, long, Interpolation) - Static method in class dev.tamboui.tfx.Fx
Creates an expand effect that grows outward from the center in both directions.

expand(ExpandDirection, Style, EffectTimer) - Static method in class dev.tamboui.tfx.Fx
Creates an expand effect that grows outward from the center in both directions.

ExpandDirection - Enum Class in dev.tamboui.tfx
Direction for bidirectional expansion effects.

expanded() - Method in class dev.tamboui.widgets.tree.TreeNode
Sets this node to expanded state.

expanded(boolean) - Method in class dev.tamboui.widgets.tree.TreeNode
Sets this node's expanded state.

expandSelected() - Method in class dev.tamboui.toolkit.elements.TreeElement
Expands the selected node, or moves to the first child if already expanded.

expandSelectors(ElementRegistry) - Method in class dev.tamboui.tfx.toolkit.ElementEffectRegistry
Expands pending selector-based effects to individual effect instances.

expandSelectors(ElementRegistry, StyledAreaRegistry) - Method in class dev.tamboui.tfx.toolkit.ElementEffectRegistry
Expands pending selector-based effects to individual effect instances.

ExpandShader - Class in dev.tamboui.tfx.effects
A shader that applies bidirectional expansion effects using two opposing stretch shaders.

ExpandShader(ExpandDirection, Style, EffectTimer) - Constructor for class dev.tamboui.tfx.effects.ExpandShader
Creates a new expand effect with the specified direction, style, and timing.

expansionState(Predicate, BiConsumer) - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Sets custom functions to check and modify expansion state.

ExpoIn - Enum constant in enum class dev.tamboui.tfx.Interpolation
Exponential easing - in

ExpoInOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Exponential easing - in-out

ExpoOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Exponential easing - out

export(Buffer) - Static method in class dev.tamboui.export.ExportRequest
Starts an export request for the given buffer.

EXPORT_BACKGROUND - Static variable in class dev.tamboui.export.ExportProperties
Default background color for export when a style has no background (e.g.

EXPORT_FOREGROUND - Static variable in class dev.tamboui.export.ExportProperties
Default foreground color for export when a style has no foreground (e.g.

ExportOptions - Interface in dev.tamboui.export
Marker interface for format-specific export options.

ExportProperties - Class in dev.tamboui.export
Property definitions for export default colors.

ExportRequest - Class in dev.tamboui.export
Entry point for the fluent export API after selecting a buffer.

ExportStep<O> - Class in dev.tamboui.export
Fluent step after selecting a format.

expression() - Method in class dev.tamboui.layout.cassowary.CassowaryConstraint

Returns the expression (left-hand side) of this constraint.

Expression - Class in dev.tamboui.layout.cassowary
A linear expression of the form: constant + c1*v1 + c2*v2 + ...

extension(Class) - Method in class dev.tamboui.style.Style
Returns the extension value for the given type, if present.

extension(Class, T) - Method in class dev.tamboui.style.Style
Returns the extension value for the given type, or a default value.

F

F1 - Enum constant in enum class dev.tamboui.tui.event.KeyCode
F1 function key.

F10 - Enum constant in enum class dev.tamboui.tui.event.KeyCode
F10 function key.

F11 - Enum constant in enum class dev.tamboui.tui.event.KeyCode
F11 function key.

F12 - Enum constant in enum class dev.tamboui.tui.event.KeyCode
F12 function key.

F2 - Enum constant in enum class dev.tamboui.tui.event.KeyCode
F2 function key.

F3 - Enum constant in enum class dev.tamboui.tui.event.KeyCode
F3 function key.

F4 - Enum constant in enum class dev.tamboui.tui.event.KeyCode
F4 function key.

F5 - Enum constant in enum class dev.tamboui.tui.event.KeyCode
F5 function key.

F6 - Enum constant in enum class dev.tamboui.tui.event.KeyCode
F6 function key.

F7 - Enum constant in enum class dev.tamboui.tui.event.KeyCode
F7 function key.

F8 - Enum constant in enum class dev.tamboui.tui.event.KeyCode
F8 function key.

F9 - Enum constant in enum class dev.tamboui.tui.event.KeyCode
F9 function key.

fadeFrom(Color, Color, long, Interpolation) - Static method in class dev.tamboui.tfx.Fx
Creates a fade effect that transitions from the specified color.

fadeFrom(Color, Color, EffectTimer) - Static method in class dev.tamboui.tfx.Fx
Creates a fade effect that transitions from the specified color.

fadeFromFg(Color, long, Interpolation) - Static method in class dev.tamboui.tfx.Fx
Creates a fade effect that transitions the foreground color from the specified color.

fadeFromFg(Color, EffectTimer) - Static method in class dev.tamboui.tfx.Fx
Creates a fade effect that transitions the foreground color from the specified color.

FadeShader - Class in dev.tamboui.tfx.effects
Shader implementation for color fade effects.

fadeTo(Color, Color, long, Interpolation) - Static method in class dev.tamboui.tfx.Fx
Creates a fade effect that transitions from one color to another.

fadeTo(Color, Color, EffectTimer) - Static method in class dev.tamboui.tfx.effects.FadeShader
Creates a fade shader that transitions from one color to another.

fadeTo(Color, Color, EffectTimer) - Static method in class dev.tamboui.tfx.Fx

Creates a fade effect that transitions from one color to another.

fadeToFg(Color, long, Interpolation) - Static method in class dev.tamboui.tfx.Fx
Creates a fade effect that transitions the foreground color.

fadeToFg(Color, EffectTimer) - Static method in class dev.tamboui.tfx.Fx
Creates a fade effect that transitions the foreground color.

FAIL - Enum constant in enum class dev.tamboui.css.cascade.UnknownPropertyBehavior
Throw an exception when an unknown property is encountered.

faultTolerant(boolean) - Method in class dev.tamboui.toolkit.app.ToolkitRunner.Builder
Enables or disables fault-tolerant rendering.

feature(String, String) - Method in class dev.tamboui.capability.CapabilityReport
Looks up a feature value by source and key.

feature(String, String, Class) - Method in class dev.tamboui.capability.CapabilityReport
Looks up a feature by source and key, and returns it if it matches the requested type.

feature(String, String, Object) - Method in class dev.tamboui.capability.CapabilityReportBuilder
Adds a general capability/feature.

featuresBySource() - Method in class dev.tamboui.capability.CapabilityReport
Free-form capability/features map, grouped by provider source.

fg() - Method in class dev.tamboui.style.Style
Returns the foreground color if set.

fg(Color) - Method in class dev.tamboui.style.Style
Returns a new style with the given foreground color.

fg(Color) - Method in class dev.tamboui.text.Line
Returns a new line with the given foreground color applied to all spans.

fg(Color) - Method in class dev.tamboui.text.Span
Returns a new span with the given foreground color.

fg(Color) - Method in class dev.tamboui.text.Text
Returns a new text with the given foreground color.

fg(Color) - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the foreground color.

fgCode() - Method in enum class dev.tamboui.style.AnsiColor
Returns the ANSI SGR code for foreground.

fgColor(Color) - Static method in class dev.tamboui.tfx.CellFilter
Selects cells with a matching foreground color.

field(String, String) - Method in class dev.tamboui.toolkit.elements.FormElement
Adds a text field to the form.

field(String, String, FieldType) - Method in class dev.tamboui.toolkit.elements.FormElement
Adds a field with a specific type to the form.

field(String, String, FieldType, Validator...) - Method in class dev.tamboui.toolkit.elements.FormElement
Adds a field with a specific type and validators to the form.

field(String, String, Validator...) - Method in class dev.tamboui.toolkit.elements.FormElement
Adds a text field with validators to the form.

field(String, String, String) - Method in class dev.tamboui.toolkit.elements.FormElement
Adds a field with a placeholder.

fieldSpacing(int) - Method in class dev.tamboui.toolkit.elements.FormElement
Sets the vertical spacing between fields.

FieldType - Enum Class in dev.tamboui.widgets.form
The type of form field input.

fill() - Static method in interface dev.tamboui.layout.Constraint
Creates a fill constraint with weight 1.

fill() - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the constraint to fill available space.

fill() - Static method in class dev.tamboui.toolkit.elements.Spacer
Creates a spacer that fills available space.

fill() - Static method in class dev.tamboui.toolkit.Toolkit
Creates a fill constraint with weight 1.

fill(int) - Static method in interface dev.tamboui.layout.Constraint
Creates a fill constraint with a custom weight.

fill(int) - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the constraint to fill available space with the given weight.

fill(int) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a fill constraint with the given weight.

fill(Rect, Cell) - Method in class dev.tamboui.buffer.Buffer
Fills the given area with the specified cell.

Fill() - Constructor for class dev.tamboui.layout.Constraint.Fill
Creates a fill constraint with weight 1.

Fill(int) - Constructor for class dev.tamboui.layout.Constraint.Fill
Creates a fill constraint.

FILL - Enum constant in enum class dev.tamboui.image.ImageScaling
Scale the image to fill the bounds while maintaining aspect ratio.

FILL - Static variable in class dev.tamboui.style.Width
Width that fills the available container space.

filled() - Method in class dev.tamboui.widgets.gauge.LineGauge.LineSet
Returns the character used for the filled portion.

filled(Rect, Cell) - Static method in class dev.tamboui.buffer.Buffer
Creates a buffer filled with the given cell.

FILLED_COLOR - Static variable in class dev.tamboui.widgets.gauge.LineGauge
Property key for the filled portion color.

filledColor(Color) - Method in class dev.tamboui.toolkit.elements.LineGaugeElement
Sets the color for the filled portion.

filledColor(Color) - Method in class dev.tamboui.widgets.gauge.LineGauge.Builder
Sets the filled portion color programmatically.

filledStyle(Style) - Method in class dev.tamboui.toolkit.elements.LineGaugeElement
Sets the style for the filled portion.

filledStyle(Style) - Method in class dev.tamboui.widgets.gauge.LineGauge.Builder
Sets the style for the filled portion of the gauge.

fire(String) - Method in class dev.tamboui.tui.bindings.ActionHandler
Fires a named action without an originating event.

fire(String, Event) - Method in class dev.tamboui.tui.bindings.ActionHandler
Fires a named action directly, bypassing bindings resolution.

first() - Method in class dev.tamboui.widgets.scrollbar.ScrollbarState
Scrolls to the first position.

firstDayOfWeek(DayOfWeek) - Method in class dev.tamboui.toolkit.elements.CalendarElement
Sets the first day of the week.

firstDayOfWeek(DayOfWeek) - Method in class dev.tamboui.widgets.calendar.Monthly.Builder
Sets the first day of the week.

firstDayOfWeek(DayOfWeek) - Method in class dev.tamboui.widgets.calendar.Monthly
Returns a new calendar with the given first day of week.

fit() - Static method in interface dev.tamboui.layout.Constraint

Creates a fit-to-content constraint.

fit() - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the constraint to fit the element's preferred size.

fit() - Method in class dev.tamboui.toolkit.elements.Panel
Enables automatic height calculation to fit the panel's content.

FIT - Enum constant in enum class dev.tamboui.image.ImageScaling
Scale the image to fit within the bounds while maintaining aspect ratio.

FIT - Static variable in class dev.tamboui.style.Width
Width that fits the content.

fiveEighths() - Method in class dev.tamboui.widgets.barchart.BarChart.BarSet
Returns the five-eighths fill symbol.

fiveEighths() - Method in class dev.tamboui.widgets.sparkline.Sparkline.BarSet
Returns the five-eighths fill symbol.

fixed(int) - Static method in class dev.tamboui.style.Width
Creates a fixed character width.

flex() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the flex layout mode, if set.

flex() - Method in class dev.tamboui.layout.Layout
Returns the flex mode used to distribute extra space.

flex(Flex) - Method in class dev.tamboui.css.cascade.CssStyleResolver.Builder
Sets the flex layout mode.

flex(Flex) - Method in class dev.tamboui.layout.columns.Columns.Builder
Sets how remaining space is distributed among columns.

flex(Flex) - Method in class dev.tamboui.layout.grid.Grid.AreaBuilder
Sets how remaining space is distributed.

flex(Flex) - Method in class dev.tamboui.layout.grid.Grid.ChildrenBuilder
Sets how remaining space is distributed.

flex(Flex) - Method in class dev.tamboui.layout.Layout
Sets how remaining space is distributed.

flex(Flex) - Method in class dev.tamboui.toolkit.elements.Column
Sets how remaining space is distributed among children.

flex(Flex) - Method in class dev.tamboui.toolkit.elements.ColumnsElement
Sets how remaining space is distributed among columns.

flex(Flex) - Method in class dev.tamboui.toolkit.elements.DialogElement
Sets the flex layout mode for positioning children.

flex(Flex) - Method in class dev.tamboui.toolkit.elements.GridElement
Sets how remaining space is distributed when grid constraints don't fill the available area.

flex(Flex) - Method in class dev.tamboui.toolkit.elements.Panel
Sets the flex layout mode for positioning children.

flex(Flex) - Method in class dev.tamboui.toolkit.elements.Row
Sets how remaining space is distributed among children.

Flex - Enum Class in dev.tamboui.layout
Flex mode for distributing remaining space in layouts.

FLEX - Static variable in class dev.tamboui.style.StandardProperties
The `flex` property for flex layout mode.

FlexConverter - Class in dev.tamboui.css.property
Converts CSS flex values to Flex enum.

FlexConverter - Class in dev.tamboui.layout
Converts string values to `Flex` enum values.

flipped() - Method in enum class dev.tamboui.tfx.Interpolation
Returns the flipped version of this interpolation (in ↔ out).

flipped() - Method in enum class dev.tamboui.tfx.Motion
Returns the opposite direction of the current motion.

flipsTimer() - Method in enum class dev.tamboui.tfx.Motion
Determines whether this motion direction requires timer reversal.

floor(float) - Static method in class dev.tamboui.tfx.TFxMath
Returns the largest integer value less than or equal to the argument.

flow() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty flow layout.

flow(Element...) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a flow layout with the given children.

flow(Collection) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a flow layout from a collection.

Flow - Class in dev.tamboui.layout.flow
A wrap layout widget where items flow left-to-right and wrap to the next line when exceeding the available width.

FLOW_ROW_SPACING - Static variable in class dev.tamboui.toolkit.elements.FlowElement
CSS property definition for vertical spacing between rows.

Flow.Builder - Class in dev.tamboui.layout.flow
Builder for `Flow`.

FlowElement - Class in dev.tamboui.toolkit.elements
A wrap layout element where children flow left-to-right and wrap to the next line when exceeding the available width.

FlowElement() - Constructor for class dev.tamboui.toolkit.elements.FlowElement
Creates an empty flow layout.

FlowElement(Element...) - Constructor for class dev.tamboui.toolkit.elements.FlowElement
Creates a flow layout with the given children.

FlowElement(Collection) - Constructor for class dev.tamboui.toolkit.elements.FlowElement
Creates a flow layout with the given children.

FlowItem - Class in dev.tamboui.layout.flow
An item in a `Flow` layout with explicit width and height.

flush() - Method in class dev.tamboui.backend.aesh.AeshBackend

flush() - Method in class dev.tamboui.backend.jline3.JLineBackend

flush() - Method in class dev.tamboui.backend.panama.PanamaBackend

flush() - Method in class dev.tamboui.internal.record.AnsiTerminalCapture

flush() - Method in class dev.tamboui.internal.record.RecordingBackend

flush() - Method in interface dev.tamboui.terminal.Backend
Flushes any buffered output to the terminal.

FOCUS_NEXT - Enum constant in enum class dev.tamboui.toolkit.event.EventResult
Request to move focus to the next focusable element.

FOCUS_NEXT - Static variable in class dev.tamboui.tui.bindings.Actions
Move focus to next element (Tab).

FOCUS_PREVIOUS - Enum constant in enum class dev.tamboui.toolkit.event.EventResult
Request to move focus to the previous focusable element.

FOCUS_PREVIOUS - Static variable in class dev.tamboui.tui.bindings.Actions

Move focus to previous element (Shift+Tab).

focusable - Variable in class dev.tamboui.toolkit.element.StyledElement
Whether this element is focusable.

focusable() - Method in class dev.tamboui.toolkit.element.StyledElement
Makes this element focusable, allowing it to participate in TAB navigation.

focusable(boolean) - Method in class dev.tamboui.toolkit.element.StyledElement
Sets whether this element is focusable for TAB navigation.

focusable(boolean) - Method in class dev.tamboui.toolkit.elements.TextInputElement
Sets whether this text input is focusable.

Focusable - Interface in dev.tamboui.toolkit.focus
Interface for elements that can receive focus.

focusAt(int, int) - Method in class dev.tamboui.toolkit.focus.FocusManager
Attempts to focus the element at the given screen position.

FocusChangeEvent - Class in dev.tamboui.toolkit.jfr
JFR event emitted when focus changes during toolkit event routing.

focusedArea() - Method in class dev.tamboui.toolkit.focus.FocusManager
Returns the area of the focused element, if any.

focusedBorderColor(Color) - Method in class dev.tamboui.toolkit.elements.FormElement
Sets the border color when focused for all field inputs.

focusedBorderColor(Color) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Sets the border color when focused.

focusedBorderColor(Color) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Sets the border color when the element is focused.

focusedBorderColor(Color) - Method in class dev.tamboui.toolkit.elements.Panel
Sets the border color when focused.

focusedBorderColor(Color) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Sets the border color when the element is focused.

focusedBorderColor(Color) - Method in class dev.tamboui.toolkit.elements.TextAreaElement
Sets the border color to use when focused.

focusedBorderColor(Color) - Method in class dev.tamboui.toolkit.elements.TextInputElement
Sets the border color when focused.

focusedId() - Method in class dev.tamboui.toolkit.focus.FocusManager
Returns the ID of the currently focused element.

focusManager() - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner
Returns the focus manager.

focusManager() - Method in class dev.tamboui.toolkit.app.ToolkitRunner
Returns the focus manager.

focusManager() - Method in class dev.tamboui.toolkit.element.DefaultRenderContext
Returns the focus manager.

FocusManager - Class in dev.tamboui.toolkit.focus
Manages focus state for focusable elements.

FocusManager() - Constructor for class dev.tamboui.toolkit.focus.FocusManager
Creates a new focus manager with no focused element.

FocusNavigationEvent - Class in dev.tamboui.toolkit.jfr
JFR event emitted when performing focus navigation (Tab/Shift+Tab).

focusNext() - Method in class dev.tamboui.toolkit.focus.FocusManager
Moves focus to the next focusable element.

focusOrder() - Method in class dev.tamboui.toolkit.focus.FocusManager
Returns the list of focusable element IDs in tab order.

focusPrevious() - Method in class dev.tamboui.toolkit.focus.FocusManager
Moves focus to the previous focusable element.

fontAspectRatio(double) - Method in class dev.tamboui.export.svg.SvgOptions
Sets the font aspect ratio used for width calculations.

footer(Row) - Method in class dev.tamboui.toolkit.elements.TableElement
Sets the footer row.

footer(Row) - Method in class dev.tamboui.widgets.table.Table.Builder
Sets the footer row.

footer(String) - Method in class dev.tamboui.widgets.error.ErrorDisplay.Builder
Sets the footer shown at the bottom of the border.

footer(String...) - Method in class dev.tamboui.toolkit.elements.TableElement
Sets the footer row from strings.

forEachCell(BiConsumer) - Method in class dev.tamboui.tfx.CellIterator
Applies a function to each cell in the iterator's area.

forEachCellMutable(CellIterator.CellMutator) - Method in class dev.tamboui.tfx.CellIterator
Applies a function to each cell in the iterator's area, allowing mutation.

forEachCellMutable(BiConsumer) - Method in class dev.tamboui.tfx.CellIterator

> **Deprecated.**
> *Use `CellIterator.forEachCellMutable(CellMutator)` instead for better performance*

foreground() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the foreground color, if set.

foreground(Color) - Method in class dev.tamboui.css.cascade.CssStyleResolver.Builder
Sets the foreground color.

foreground(Color) - Method in class dev.tamboui.widgets.block.Block.Builder
Sets the foreground (text) color.

foreground(Color) - Method in class dev.tamboui.widgets.input.TextArea.Builder
Sets the foreground (text) color programmatically.

foreground(Color) - Method in class dev.tamboui.widgets.input.TextInput.Builder
Sets the foreground (text) color programmatically.

foreground(Color) - Method in class dev.tamboui.widgets.paragraph.Paragraph.Builder
Sets the foreground (text) color.

foreground(Color) - Method in class dev.tamboui.widgets.sparkline.Sparkline.Builder
Sets the foreground (bar) color programmatically.

form(FormState) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a form container with the given state.

Format<O> - Interface in dev.tamboui.export
A format for buffer export (e.g.

Formats - Class in dev.tamboui.export
Built-in export formats.

formattedStackTrace() - Method in class dev.tamboui.tui.error.RenderError
Returns a pre-formatted stack trace suitable for display.

FormElement - Class in dev.tamboui.toolkit.elements
A form container that manages multiple form fields with grouping support.

FormElement(FormState) - Constructor for class dev.tamboui.toolkit.elements.FormElement
Creates a new form element with the given state.

formField(String) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a form field with a label and new text input state.

formField(String, BooleanFieldState) - Static method in class dev.tamboui.toolkit.Toolkit

Creates a form field with a label and boolean state (checkbox).

formField(String, BooleanFieldState, FieldType) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a form field with a label, boolean state, and field type.

formField(String, SelectFieldState) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a form field with a label and select state.

formField(String, TextInputState) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a form field with a label and text input state.

FormFieldElement - Class in dev.tamboui.toolkit.elements
A form field element that pairs a label with an input control.

FormFieldElement(String) - Constructor for class dev.tamboui.toolkit.elements.FormFieldElement
Creates a new form field with the given label and a new text input state.

FormFieldElement(String, BooleanFieldState, FieldType) - Constructor for class dev.tamboui.toolkit.elements.FormFieldElement
Creates a new form field with the given label and boolean state.

FormFieldElement(String, SelectFieldState) - Constructor for class dev.tamboui.toolkit.elements.FormFieldElement
Creates a new form field with the given label and select state.

FormFieldElement(String, TextInputState) - Constructor for class dev.tamboui.toolkit.elements.FormFieldElement
Creates a new form field with the given label and text input state.

formState() - Method in class dev.tamboui.toolkit.elements.FormElement
Returns the FormState associated with this form.

formState(FormState, String) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Associates this field with a FormState for persistent validation state.

FormState - Class in dev.tamboui.widgets.form
Centralized state container for all fields in a form.

FormState.Builder - Class in dev.tamboui.widgets.form
Builder for constructing FormState instances.

forTesting(Buffer) - Static method in class dev.tamboui.terminal.Frame
Creates a frame for testing purposes.

fps() - Method in class dev.tamboui.internal.record.RecordingConfig
Returns the frames per second.

fpsOverlay(boolean) - Method in class dev.tamboui.tui.TuiConfig.Builder
Enables or disables the FPS overlay.

fpsOverlayEnabled() - Method in class dev.tamboui.tui.TuiConfig
Returns whether the FPS overlay is enabled.

Fraction - Class in dev.tamboui.layout
An immutable exact rational number represented as a fraction.

frame(int) - Method in class dev.tamboui.widgets.spinner.SpinnerFrameSet
Returns the frame at the given index (wrapping around).

frame(int) - Method in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Returns the frame at the given index (wrapping around).

frame(String) - Method in class dev.tamboui.widgets.spinner.SpinnerFrameSet.Builder
Adds a frame to the set.

Frame - Class in dev.tamboui.terminal
A frame represents a single render cycle.

frameCount() - Method in class dev.tamboui.tui.event.TickEvent
Returns the total number of frames elapsed.

frameCount() - Method in class dev.tamboui.widgets.spinner.SpinnerFrameSet

Returns the number of frames in this set.

frameCount() - Method in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Returns the number of frames in this style.

FrameInternal - Class in dev.tamboui.terminal
Utility class exposing internal Frame capabilities.

frames() - Method in class dev.tamboui.widgets.spinner.Spinner
Returns the frames used by this spinner.

frames() - Method in class dev.tamboui.widgets.spinner.SpinnerFrameSet
Returns all frames in this set.

frames() - Method in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Returns all frames for this spinner style.

frames(String...) - Method in class dev.tamboui.toolkit.elements.SpinnerElement
Sets custom frames for the spinner, overriding the style.

frames(String...) - Method in class dev.tamboui.widgets.spinner.Spinner.Builder
Sets custom frames for the spinner.

frames(String...) - Method in class dev.tamboui.widgets.spinner.SpinnerFrameSet.Builder
Adds multiple frames to the set.

frameSet() - Method in class dev.tamboui.widgets.spinner.Spinner
Returns the frame set used by this spinner.

frameSet() - Method in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Returns the frame set for this spinner style.

frameSet(SpinnerFrameSet) - Method in class dev.tamboui.toolkit.elements.SpinnerElement
Sets a custom frame set for the spinner, overriding the style.

frameSet(SpinnerFrameSet) - Method in class dev.tamboui.widgets.spinner.Spinner.Builder
Sets the frame set for the spinner.

from(int) - Static method in class dev.tamboui.layout.Spacing
Creates spacing from an integer value.

from(long...) - Static method in class dev.tamboui.widgets.sparkline.Sparkline
Creates a sparkline with the given data values.

from(Line) - Static method in class dev.tamboui.text.Text
Creates a text containing a single line.

from(Line) - Static method in class dev.tamboui.widgets.block.Title
Creates a left-aligned title from a line.

from(Line) - Static method in class dev.tamboui.widgets.list.ListItem
Creates a list item from a styled line.

from(Line) - Static method in class dev.tamboui.widgets.paragraph.Paragraph
Creates a paragraph from a line.

from(Line) - Static method in class dev.tamboui.widgets.table.Cell
Creates a cell from a line.

from(Line...) - Static method in class dev.tamboui.text.Text
Creates a text from one or more lines.

from(Line...) - Static method in class dev.tamboui.widgets.tabs.Tabs
Creates tabs from line titles.

from(Masked) - Static method in class dev.tamboui.text.Span
Creates a span from a masked string.

from(Span) - Static method in class dev.tamboui.text.Line
Creates a line from a single span.

from(Span) - Static method in class dev.tamboui.text.Text
Creates a text containing a single span on one line.

from(Span) - Static method in class dev.tamboui.widgets.block.Title
Creates a left-aligned title from a span.

from(Span) - Static method in class dev.tamboui.widgets.paragraph.Paragraph
Creates a paragraph from a span.

from(Span) - Static method in class dev.tamboui.widgets.table.Cell
Creates a cell from a span.

from(Span...) - Static method in class dev.tamboui.text.Line
Creates a line from multiple spans.

from(Text) - Static method in class dev.tamboui.widgets.list.ListItem
Creates a list item from a text.

from(Text) - Static method in class dev.tamboui.widgets.paragraph.Paragraph
Creates a paragraph from a text.

from(Text) - Static method in class dev.tamboui.widgets.table.Cell
Creates a cell from text.

from(Cell...) - Static method in class dev.tamboui.widgets.table.Row
Creates a row from cells.

from(String) - Static method in class dev.tamboui.text.Line
Creates a line from a plain text string.

from(String) - Static method in class dev.tamboui.text.Text
Creates a text from a string, splitting on newlines.

from(String) - Static method in class dev.tamboui.widgets.block.Title
Creates a left-aligned title from a string.

from(String) - Static method in class dev.tamboui.widgets.list.ListItem
Creates a list item from a string.

from(String) - Static method in class dev.tamboui.widgets.paragraph.Paragraph
Creates a paragraph from a string.

from(String) - Static method in class dev.tamboui.widgets.table.Cell
Creates a cell from a string.

from(String...) - Static method in class dev.tamboui.widgets.table.Row
Creates a row from strings (each string becomes a cell).

from(String...) - Static method in class dev.tamboui.widgets.tabs.Tabs
Creates tabs from string titles.

from(Throwable) - Static method in class dev.tamboui.toolkit.elements.ErrorPlaceholder
Creates an ErrorPlaceholder for the given exception.

from(Throwable) - Static method in class dev.tamboui.tui.error.RenderError
Creates a RenderError from the given exception.

from(Throwable) - Static method in class dev.tamboui.widgets.error.ErrorDisplay
Creates an ErrorDisplay for the given exception with default settings.

from(Throwable, String) - Static method in class dev.tamboui.toolkit.elements.ErrorPlaceholder
Creates an ErrorPlaceholder for the given exception.

from(List) - Static method in class dev.tamboui.text.Text
Creates a text from a list of lines.

from(List) - Static method in class dev.tamboui.text.Line
Creates a line from a list of spans.

from(List) - Static method in class dev.tamboui.widgets.table.Row
Creates a row from cells.

from(List) - Static method in class dev.tamboui.widgets.sparkline.Sparkline
Creates a sparkline with the given data values.

fromBufferedImage(BufferedImage) - Static method in class dev.tamboui.image.ImageData

Creates image data from a BufferedImage.

fromBytes(byte[]) - Static method in class dev.tamboui.image.ImageData
Loads image data from a byte array.

fromDouble(double) - Static method in class dev.tamboui.layout.Fraction
Creates a fraction from a double value.

fromHex(String) - Static method in class dev.tamboui.style.Color.Rgb
Creates an RGB color from a hex string (e.g.

fromHsl(float, float, float) - Static method in enum class dev.tamboui.tfx.TFxColorSpace
Creates a color from HSL (Hue, Saturation, Lightness) values.

fromHsv(float, float, float) - Static method in enum class dev.tamboui.tfx.TFxColorSpace
Creates a color from HSV (Hue, Saturation, Value) values.

fromJavaDuration(Duration) - Static method in class dev.tamboui.tfx.TFxDuration
Converts from java.time.Duration.

fromMillis(long) - Static method in class dev.tamboui.tfx.TFxDuration
Creates a duration from milliseconds.

fromMs(long, Interpolation) - Static method in class dev.tamboui.tfx.EffectTimer
Creates a new EffectTimer with the specified duration in milliseconds and interpolation.

fromPath(Path) - Static method in class dev.tamboui.image.Image
Creates an image widget from a file path.

fromPath(Path) - Static method in class dev.tamboui.image.ImageData
Loads image data from a file path.

fromResource(String) - Static method in class dev.tamboui.image.Image
Creates an image widget from a classpath resource.

fromResource(String) - Static method in class dev.tamboui.image.ImageData
Loads image data from a classpath resource.

fromSecs(long) - Static method in class dev.tamboui.tfx.TFxDuration
Creates a duration from seconds.

fromSecsF32(float) - Static method in class dev.tamboui.tfx.TFxDuration
Creates a duration from fractional seconds.

full() - Method in class dev.tamboui.widgets.barchart.BarChart.BarSet
Returns the full fill symbol.

full() - Method in class dev.tamboui.widgets.sparkline.Sparkline.BarSet
Returns the full fill symbol.

fullExceptionType() - Method in class dev.tamboui.tui.error.RenderError
Returns the full class name of the exception.

FUZZY - Enum constant in enum class dev.tamboui.symbols.merge.MergeStrategy
Merges symbols even if an exact composite unicode character doesn't exist, using the closest match.

Fx - Class in dev.tamboui.tfx
Factory class providing static methods for creating common effects.

G

g() - Method in class dev.tamboui.style.Color.Rgb
Returns the green component.

gauge() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty gauge.

gauge(double) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a gauge with the given ratio (0.0-1.0).

gauge(int) - Static method in class dev.tamboui.toolkit.Toolkit

Creates a gauge with the given percentage (0-100).

Gauge - Class in dev.tamboui.widgets.gauge
A progress bar widget that renders a bar filled according to the progress value.

GAUGE - Enum constant in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Gauge-style spinner using block fill characters (left to right).

GAUGE_COLOR - Static variable in class dev.tamboui.widgets.gauge.Gauge
Property key for the gauge (filled portion) color.

Gauge.Builder - Class in dev.tamboui.widgets.gauge
Builder for `Gauge`.

gaugeColor(Color) - Method in class dev.tamboui.toolkit.elements.GaugeElement
Sets the color for the filled portion.

gaugeColor(Color) - Method in class dev.tamboui.widgets.gauge.Gauge.Builder
Sets the gauge (filled portion) color programmatically.

GaugeElement - Class in dev.tamboui.toolkit.elements
A DSL wrapper for the Gauge widget.

GaugeElement() - Constructor for class dev.tamboui.toolkit.elements.GaugeElement
Creates a new gauge element with zero progress.

GaugeElement(double) - Constructor for class dev.tamboui.toolkit.elements.GaugeElement
Creates a new gauge element with the given progress ratio.

GaugeElement(int) - Constructor for class dev.tamboui.toolkit.elements.GaugeElement
Creates a new gauge element with the given percentage.

gaugeStyle(Style) - Method in class dev.tamboui.toolkit.elements.GaugeElement
Sets the style for the filled portion.

gaugeStyle(Style) - Method in class dev.tamboui.widgets.gauge.Gauge.Builder
Sets the style for the filled portion of the gauge.

GE - Enum constant in enum class dev.tamboui.layout.cassowary.Relation
Greater than or equal constraint: the expression must be >= 0.

gen() - Method in class dev.tamboui.tfx.SimpleRng
Generates the next pseudo-random int value.

generateId(Element) - Method in class dev.tamboui.toolkit.id.IdGenerator
Generates a unique ID for the given element.

GenericWidgetElement<T> - Class in dev.tamboui.toolkit.elements
A generic element that wraps any `Widget` and exposes it as a `StyledElement`.

genF32() - Method in class dev.tamboui.tfx.SimpleRng
Generates a pseudo-random float value in the range [0, 1).

genRange(float, float) - Method in class dev.tamboui.tfx.SimpleRng
Generates a random float value in the specified range [start, end).

genRange(int, int) - Method in class dev.tamboui.tfx.SimpleRng
Generates a random value in the specified range [start, end).

get(int, int) - Method in class dev.tamboui.buffer.Buffer
Gets the cell at the given position.

get(Position) - Method in class dev.tamboui.buffer.Buffer
Gets the cell at the given position.

get(PropertyDefinition) - Method in class dev.tamboui.css.cascade.CssStyleResolver
Retrieves a typed property value using the given property definition.

get(PropertyDefinition) - Method in class dev.tamboui.css.cascade.TypedPropertyMap
Retrieves the value for the given property definition.

get(PropertyDefinition) - Method in interface dev.tamboui.style.StylePropertyResolver
Retrieves the value for the given property definition.

getActiveStylesheet() - Method in class dev.tamboui.css.engine.StyleEngine
Returns the name of the active stylesheet.

getArea(String) - Method in class dev.tamboui.toolkit.element.ElementRegistry
Returns the rendered area for an element by ID.

getCell(int) - Method in class dev.tamboui.buffer.DiffResult
Returns the cell at the given index.

getCharset() - Method in interface dev.tamboui.backend.panama.PlatformTerminal
Returns the charset used for terminal I/O.

getCharset() - Method in class dev.tamboui.backend.panama.unix.UnixTerminal
Returns the charset used for terminal I/O.

getCharset() - Method in class dev.tamboui.backend.panama.windows.WindowsTerminal

getConsoleMode(MemorySegment, MemorySegment) - Static method in class dev.tamboui.backend.panama.windows.Kernel32
Gets the current input mode of a console's input buffer or output mode of a screen buffer.

getConsoleScreenBufferInfo(MemorySegment, MemorySegment) - Static method in class dev.tamboui.backend.panama.windows.Kernel32
Gets information about the specified console screen buffer.

getCursorPosition() - Method in class dev.tamboui.backend.aesh.AeshBackend

getCursorPosition() - Method in class dev.tamboui.backend.jline3.JLineBackend

getCursorPosition() - Method in class dev.tamboui.backend.panama.PanamaBackend

getCursorPosition() - Method in class dev.tamboui.internal.record.RecordingBackend

getCursorPosition() - Method in interface dev.tamboui.terminal.Backend
Gets the current cursor position.

getHeight() - Static method in class dev.tamboui.internal.record.AnsiTerminalCapture
Returns the configured height, or 24 if not installed.

getLastErrno() - Static method in class dev.tamboui.backend.panama.unix.LibC
Returns the errno from the last failed ioctl call.

getLastError() - Static method in class dev.tamboui.backend.panama.windows.Kernel32
Gets the last error code.

getLine(int) - Method in class dev.tamboui.widgets.input.TextAreaState
Returns the text of the line at the given row.

getNumberOfConsoleInputEvents(MemorySegment, MemorySegment) - Static method in class dev.tamboui.backend.panama.windows.Kernel32
Gets the number of unread input records in the console's input buffer.

getPoint(double, double) - Method in class dev.tamboui.widgets.canvas.Painter
Converts canvas coordinates to grid coordinates.

getPollTimeoutMs() - Method in class dev.tamboui.picocli.TuiMixin
Returns the poll timeout in milliseconds.

getPosition() - Method in exception class dev.tamboui.css.parser.CssParseException
Returns the position in the source where the error occurred.

getPropertyName() - Method in exception class dev.tamboui.css.cascade.UnknownCssPropertyException
Returns the unknown property name.

getPropertyValue() - Method in exception class dev.tamboui.css.cascade.UnknownCssPropertyException
Returns the property value.

getSigactionHandler(MemorySegment) - Static method in class dev.tamboui.backend.panama.unix.LibC
Gets the handler pointer from a sigaction structure.

getSize() - Method in interface dev.tamboui.backend.panama.PlatformTerminal

Gets the current terminal size.

getSize() - Method in class dev.tamboui.backend.panama.unix.UnixTerminal
Gets the current terminal size.

getSize() - Method in class dev.tamboui.backend.panama.windows.WindowsTerminal

getState() - Method in class dev.tamboui.toolkit.elements.TextAreaElement
Returns the current state.

getStdHandle(int) - Static method in class dev.tamboui.backend.panama.windows.Kernel32
Gets a handle to the specified standard device.

getStyle() - Method in class dev.tamboui.toolkit.element.StyledElement
Returns the current style.

getStyle(LocalDate) - Method in class dev.tamboui.widgets.calendar.CalendarEventStore

getStyle(LocalDate) - Method in interface dev.tamboui.widgets.calendar.DateStyler
Returns the style for the given date.

getStylesheetNames() - Method in class dev.tamboui.css.engine.StyleEngine
Returns the names of all loaded named stylesheets.

getTickRateMs() - Method in class dev.tamboui.picocli.TuiMixin
Returns the tick rate in milliseconds, or 0 if ticks are disabled.

getWidth() - Static method in class dev.tamboui.internal.record.AnsiTerminalCapture
Returns the configured width, or 80 if not installed.

getX(int) - Method in class dev.tamboui.buffer.DiffResult
Returns the x coordinate of the update at the given index.

getY(int) - Method in class dev.tamboui.buffer.DiffResult
Returns the y coordinate of the update at the given index.

GlobalEventHandler - Interface in dev.tamboui.toolkit.event
Handler for global events that are processed before element-specific handlers.

GlobalHandlerEvent - Class in dev.tamboui.toolkit.jfr
JFR event emitted for each global handler invocation during routing.

graphType() - Method in class dev.tamboui.widgets.chart.Dataset
Returns the graph type.

graphType(GraphType) - Method in class dev.tamboui.widgets.chart.Dataset.Builder
Sets the graph type.

GraphType - Enum Class in dev.tamboui.widgets.chart
The type of graph to render for a `Dataset`.

gray() - Method in class dev.tamboui.style.Style
Shorthand for `Style.fg(Color)` with `Color.GRAY`.

gray() - Method in class dev.tamboui.text.Span
Returns a new span with gray foreground color.

gray() - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the foreground color to gray.

GRAY - Static variable in interface dev.tamboui.style.Color
Gray (ANSI WHITE renders as light gray).

greaterThanOrEqual(long, Strength) - Method in class dev.tamboui.layout.cassowary.Expression
Creates a greater-than-or-equal constraint: this >= value.

greaterThanOrEqual(Expression, Strength) - Method in class dev.tamboui.layout.cassowary.Expression
Creates a greater-than-or-equal constraint: this >= other.

greaterThanOrEqual(Fraction, Strength) - Method in class dev.tamboui.layout.cassowary.Expression
Creates a greater-than-or-equal constraint: this >= value.

green() - Method in class dev.tamboui.style.Style

Shorthand for `Style.fg(Color)` with `Color.GREEN`.

green() - Method in class dev.tamboui.text.Span
Returns a new span with green foreground color.

green() - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the foreground color to green.

green(int) - Static method in class dev.tamboui.image.ImageData
Returns the green component of a pixel (0-255).

GREEN - Enum constant in enum class dev.tamboui.style.AnsiColor
Green (palette index 2).

GREEN - Static variable in interface dev.tamboui.style.Color
Green.

grid() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty grid layout.

grid(Element...) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a CSS Grid-inspired grid layout.

grid(Collection) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a grid layout from a collection.

grid(Supplier) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a grid layout with lazy content.

Grid - Class in dev.tamboui.layout.grid
A CSS Grid-inspired layout widget that arranges children into a grid with explicit control over grid dimensions, per-column/per-row sizing constraints, and gutter spacing.

GRID_COLUMNS - Static variable in class dev.tamboui.toolkit.elements.GridElement
CSS property definition for per-column constraints.

GRID_GUTTER - Static variable in class dev.tamboui.toolkit.elements.GridElement
CSS property definition for the gutter spacing.

GRID_ROWS - Static variable in class dev.tamboui.toolkit.elements.GridElement
CSS property definition for per-row constraints.

GRID_SIZE - Static variable in class dev.tamboui.toolkit.elements.GridElement
CSS property definition for the grid size.

GRID_TEMPLATE_AREAS - Static variable in class dev.tamboui.toolkit.elements.GridElement
CSS property definition for grid-template-areas.

Grid.AreaBuilder - Class in dev.tamboui.layout.grid
Builder for area-based grid layouts.

Grid.Builder - Class in dev.tamboui.layout.grid
Initial builder for `Grid`.

Grid.ChildrenBuilder - Class in dev.tamboui.layout.grid
Builder for children-based grid layouts.

GridArea - Class in dev.tamboui.layout.grid
Parses and validates CSS grid-template-areas style layout definitions.

GridArea.AreaBounds - Class in dev.tamboui.layout.grid
Bounds of a named area within the grid.

GridAreaConverter - Class in dev.tamboui.toolkit.elements
Converts CSS grid-template-areas value to `GridArea`.

gridAreas(String...) - Method in class dev.tamboui.layout.grid.Grid.Builder
Creates an area-based grid layout using CSS grid-template-areas style.

gridAreas(String...) - Method in class dev.tamboui.toolkit.elements.GridElement
Defines the grid layout using CSS grid-template-areas style strings.

gridColumns(Constraint...) - Method in class dev.tamboui.toolkit.elements.GridElement

Sets per-column width constraints.

GridElement - Class in dev.tamboui.toolkit.elements
A CSS Grid-inspired layout container that arranges children into a grid with explicit control over grid dimensions, per-column/per-row sizing constraints, and gutter spacing.

GridElement() - Constructor for class dev.tamboui.toolkit.elements.GridElement
Creates an empty grid layout.

GridElement(Element...) - Constructor for class dev.tamboui.toolkit.elements.GridElement
Creates a grid layout with the given children.

GridElement(Collection) - Constructor for class dev.tamboui.toolkit.elements.GridElement
Creates a grid layout with the given children.

GridPoint(int, int) - Constructor for class dev.tamboui.widgets.canvas.Painter.GridPoint
Creates a new grid point.

gridRows(Constraint...) - Method in class dev.tamboui.toolkit.elements.GridElement
Sets per-row height constraints.

gridSize(int) - Method in class dev.tamboui.toolkit.elements.GridElement
Sets the number of columns (rows auto-derived from children count).

gridSize(int, int) - Method in class dev.tamboui.toolkit.elements.GridElement
Sets the grid dimensions (columns and rows).

GridSize - Class in dev.tamboui.toolkit.elements
Immutable value object holding grid dimensions (columns and rows).

GridSizeConverter - Class in dev.tamboui.toolkit.elements
Converts CSS string values to `GridSize` objects.

group(BarGroup) - Method in class dev.tamboui.toolkit.elements.BarChartElement
Adds a bar group.

group(String) - Method in class dev.tamboui.toolkit.elements.FormElement
Starts a new field group.

groupGap(int) - Method in class dev.tamboui.toolkit.elements.BarChartElement
Sets the gap between groups.

groupGap(int) - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Sets the gap between groups (default: 1).

Grouping Fields - Section in class dev.tamboui.toolkit.elements.FormElement

groups(BarGroup...) - Method in class dev.tamboui.toolkit.elements.BarChartElement
Adds bar groups.

groups(List) - Method in class dev.tamboui.toolkit.elements.BarChartElement
Adds bar groups from a list.

groupTitleStyle(Style) - Method in class dev.tamboui.toolkit.elements.FormElement
Sets the style for group titles.

GROWING_DOTS - Enum constant in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Growing dots spinner using braille.

GUIDE_STYLE - Static variable in class dev.tamboui.toolkit.elements.TreeElement
CSS property for guide style.

guideStyle(GuideStyle) - Method in class dev.tamboui.toolkit.elements.TreeElement
Sets the guide style for tree branch characters.

guideStyle(GuideStyle) - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Sets the guide style for branch characters.

GuideStyle - Enum Class in dev.tamboui.widgets.tree
Style for tree guide/branch characters.

gutter(int) - Method in class dev.tamboui.toolkit.elements.GridElement

Sets uniform gutter spacing between cells.

gutter(int, int) - Method in class dev.tamboui.toolkit.elements.GridElement
Sets asymmetric gutter spacing between cells.

Gutter - Class in dev.tamboui.toolkit.elements
Immutable value object holding horizontal and vertical gutter spacing for grid layouts.

GutterConverter - Class in dev.tamboui.toolkit.elements
Converts CSS string values to `Gutter` objects.

H

half() - Method in class dev.tamboui.widgets.barchart.BarChart.BarSet
Returns the half fill symbol.

half() - Method in class dev.tamboui.widgets.sparkline.Sparkline.BarSet
Returns the half fill symbol.

HALF_BLOCK - Enum constant in enum class dev.tamboui.image.capability.TerminalImageProtocol
Unicode half-block character fallback.

HALF_BLOCK - Enum constant in enum class dev.tamboui.widgets.canvas.Marker
Uses Unicode block and half-block characters (▀, ▄, ▀).

halfBlock() - Method in class dev.tamboui.toolkit.elements.CanvasElement
Uses half-block marker.

HalfBlockProtocol - Class in dev.tamboui.image.protocol
Renders images using Unicode half-block characters.

HalfBlockProtocol() - Constructor for class dev.tamboui.image.protocol.HalfBlockProtocol
Creates a new half-block protocol instance.

handle(RenderError, ErrorContext) - Method in interface dev.tamboui.tui.error.RenderErrorHandler
Handles a render error.

handle(Event) - Method in interface dev.tamboui.toolkit.event.GlobalEventHandler
Handles an event.

handle(Event, InlineTuiRunner) - Method in interface dev.tamboui.tui.InlineEventHandler
Handles an event.

handle(Event, TuiRunner) - Method in interface dev.tamboui.tui.EventHandler
Handles an event.

handle(KeyEvent) - Method in interface dev.tamboui.toolkit.event.KeyEventHandler
Handles a key event.

handle(MouseEvent) - Method in interface dev.tamboui.toolkit.event.MouseEventHandler
Handles a mouse event.

HANDLED - Enum constant in enum class dev.tamboui.toolkit.event.EventResult
The event was handled and should not be propagated further.

handleKeyEvent(KeyEvent, boolean) - Method in class dev.tamboui.toolkit.component.Component
Called internally to handle key events.

handleKeyEvent(KeyEvent, boolean) - Method in class dev.tamboui.toolkit.element.ContainerElement
Handles key events by first trying custom handlers, then forwarding to children.

handleKeyEvent(KeyEvent, boolean) - Method in interface dev.tamboui.toolkit.element.Element
Handles a key event on this element.

handleKeyEvent(KeyEvent, boolean) - Method in class dev.tamboui.toolkit.element.StyledElement

handleKeyEvent(KeyEvent, boolean) - Method in class dev.tamboui.toolkit.elements.DialogElement
Handles key events for the dialog.

handleKeyEvent(KeyEvent, boolean) - Method in class dev.tamboui.toolkit.elements.FormFieldElement

handleKeyEvent(KeyEvent, boolean) - Method in class dev.tamboui.toolkit.elements.LazyElement

handleKeyEvent(KeyEvent, boolean) - Method in class dev.tamboui.toolkit.elements.ListElement

handleKeyEvent(KeyEvent, boolean) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement

handleKeyEvent(KeyEvent, boolean) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement

handleKeyEvent(KeyEvent, boolean) - Method in class dev.tamboui.toolkit.elements.TextAreaElement
Handles a key event for text area input.

handleKeyEvent(KeyEvent, boolean) - Method in class dev.tamboui.toolkit.elements.TextInputElement
Handles a key event for text input.

handleKeyEvent(KeyEvent, boolean) - Method in class dev.tamboui.toolkit.elements.TreeElement

handleMouseEvent(MouseEvent) - Method in class dev.tamboui.toolkit.component.Component
Called internally to handle mouse events.

handleMouseEvent(MouseEvent) - Method in class dev.tamboui.toolkit.element.ContainerElement
Handles mouse events by first trying custom handlers, then forwarding to children.

handleMouseEvent(MouseEvent) - Method in interface dev.tamboui.toolkit.element.Element
Handles a mouse event on this element.

handleMouseEvent(MouseEvent) - Method in class dev.tamboui.toolkit.element.StyledElement

handleMouseEvent(MouseEvent) - Method in class dev.tamboui.toolkit.elements.DockElement

handleMouseEvent(MouseEvent) - Method in class dev.tamboui.toolkit.elements.LazyElement

handleMouseEvent(MouseEvent) - Method in class dev.tamboui.toolkit.elements.ListElement

handleMouseEvent(MouseEvent) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement

handleMouseEvent(MouseEvent) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement

handleMouseEvent(MouseEvent) - Method in class dev.tamboui.toolkit.elements.TreeElement

handleTextInputKey(TextInputState, KeyEvent) - Static method in class dev.tamboui.toolkit.Toolkit
Handles common key events for text input.

has(String) - Method in class dev.tamboui.css.cascade.PseudoClassState
Checks if the given pseudo-class is active.

hasAlt() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if Alt modifier was pressed.

hasAny() - Method in class dev.tamboui.tui.event.KeyModifiers
Returns true if any modifier is pressed.

hasConstraint(CassowaryConstraint) - Method in class dev.tamboui.layout.cassowary.Solver
Checks if the solver contains a constraint.

hasCtrl() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if Ctrl modifier was pressed.

hasEditVariable(Variable) - Method in class dev.tamboui.layout.cassowary.Solver
Checks if a variable is an edit variable.

hasExplicitHeight() - Method in class dev.tamboui.widgets.common.SizedWidget
Returns whether an explicit height was specified.

hasExplicitWidth() - Method in class dev.tamboui.widgets.common.SizedWidget
Returns whether an explicit width was specified.

hasFocus() - Method in class dev.tamboui.toolkit.element.DefaultRenderContext

hasFocus() - Method in interface dev.tamboui.toolkit.element.RenderContext

Returns whether any element is currently focused.

Hash(String, Token.Position) - Constructor for class dev.tamboui.css.parser.Token.Hash
Creates a hash token.

hasHandlers(String) - Method in class dev.tamboui.tui.bindings.ActionHandler
Checks if any handlers are registered for the specified action.

hashCode() - Method in class dev.tamboui.buffer.Buffer

hashCode() - Method in class dev.tamboui.buffer.Cell

hashCode() - Method in class dev.tamboui.css.cascade.PseudoClassState

hashCode() - Method in class dev.tamboui.css.cascade.TypedPropertyMap

hashCode() - Method in class dev.tamboui.css.model.PropertyValue

hashCode() - Method in class dev.tamboui.css.model.Rule

hashCode() - Method in class dev.tamboui.css.model.Stylesheet

hashCode() - Method in class dev.tamboui.css.parser.Token.Position

hashCode() - Method in class dev.tamboui.css.selector.AttributeSelector

hashCode() - Method in class dev.tamboui.css.selector.ChildSelector

hashCode() - Method in class dev.tamboui.css.selector.ClassSelector

hashCode() - Method in class dev.tamboui.css.selector.CompoundSelector

hashCode() - Method in class dev.tamboui.css.selector.DescendantSelector

hashCode() - Method in class dev.tamboui.css.selector.IdSelector

hashCode() - Method in class dev.tamboui.css.selector.PseudoClassSelector

hashCode() - Method in class dev.tamboui.css.selector.TypeSelector

hashCode() - Method in class dev.tamboui.layout.cassowary.CassowaryConstraint

hashCode() - Method in class dev.tamboui.layout.cassowary.Expression

hashCode() - Method in class dev.tamboui.layout.cassowary.Strength

hashCode() - Method in class dev.tamboui.layout.cassowary.Term

hashCode() - Method in class dev.tamboui.layout.cassowary.Variable

hashCode() - Method in class dev.tamboui.layout.Constraint.Fill

hashCode() - Method in class dev.tamboui.layout.Constraint.Fit

hashCode() - Method in class dev.tamboui.layout.Constraint.Length

hashCode() - Method in class dev.tamboui.layout.Constraint.Max

hashCode() - Method in class dev.tamboui.layout.Constraint.Min

hashCode() - Method in class dev.tamboui.layout.Constraint.Percentage

hashCode() - Method in class dev.tamboui.layout.Constraint.Ratio

hashCode() - Method in class dev.tamboui.layout.Fraction

hashCode() - Method in class dev.tamboui.layout.Margin

hashCode() - Method in class dev.tamboui.layout.Padding

hashCode() - Method in class dev.tamboui.layout.Position

hashCode() - Method in class dev.tamboui.layout.Rect

hashCode() - Method in class dev.tamboui.layout.Size

hashCode() - Method in class dev.tamboui.layout.Spacing.Overlap

hashCode() - Method in class dev.tamboui.layout.Spacing.Space

hashCode() - Method in class dev.tamboui.style.Color.Ansi

hashCode() - Method in class dev.tamboui.style.Color.Indexed

hashCode() - Method in class dev.tamboui.style.Color.Named

hashCode() - Method in class dev.tamboui.style.Color.Reset

hashCode() - Method in class dev.tamboui.style.Color.Rgb

hashCode() - Method in class dev.tamboui.style.Hyperlink

hashCode() - Method in class dev.tamboui.style.PropertyDefinition

hashCode() - Method in class dev.tamboui.style.Style

hashCode() - Method in class dev.tamboui.style.Tags

hashCode() - Method in class dev.tamboui.style.Width

hashCode() - Method in class dev.tamboui.terminal.CompletedFrame

hashCode() - Method in class dev.tamboui.text.Line

hashCode() - Method in class dev.tamboui.text.Masked

hashCode() - Method in class dev.tamboui.text.Span

hashCode() - Method in class dev.tamboui.text.Text

hashCode() - Method in class dev.tamboui.tfx.EffectTimer

hashCode() - Method in class dev.tamboui.tfx.SimpleRng

hashCode() - Method in class dev.tamboui.tfx.TFxDuration

hashCode() - Method in class dev.tamboui.toolkit.element.ChildPosition

hashCode() - Method in class dev.tamboui.toolkit.element.Size

hashCode() - Method in class dev.tamboui.toolkit.elements.GridSize

hashCode() - Method in class dev.tamboui.toolkit.elements.Gutter

hashCode() - Method in class dev.tamboui.tui.bindings.KeyTrigger

hashCode() - Method in class dev.tamboui.tui.bindings.MouseTrigger

hashCode() - Method in class dev.tamboui.tui.event.ActionEvent

hashCode() - Method in class dev.tamboui.tui.event.KeyEvent

hashCode() - Method in class dev.tamboui.tui.event.KeyModifiers

hashCode() - Method in class dev.tamboui.tui.event.MouseEvent

hashCode() - Method in class dev.tamboui.tui.event.ResizeEvent

hashCode() - Method in class dev.tamboui.tui.event.TickEvent

hashCode() - Method in class dev.tamboui.tui.TuiConfig

hashCode() - Method in class dev.tamboui.widgets.barchart.BarChart.BarSet

hashCode() - Method in class dev.tamboui.widgets.block.BorderSet

hashCode() - Method in class dev.tamboui.widgets.block.Title

hashCode() - Method in class dev.tamboui.widgets.canvas.Painter.GridPoint

hashCode() - Method in class dev.tamboui.widgets.canvas.shapes.Circle

hashCode() - Method in class dev.tamboui.widgets.canvas.shapes.Line

hashCode() - Method in class dev.tamboui.widgets.canvas.shapes.Points

hashCode() - Method in class dev.tamboui.widgets.canvas.shapes.Rectangle

hashCode() - Method in class dev.tamboui.widgets.form.ValidationResult

hashCode() - Method in class dev.tamboui.widgets.gauge.LineGauge.LineSet

hashCode() - Method in class dev.tamboui.widgets.list.ListItem

hashCode() - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.SymbolSet

hashCode() - Method in class dev.tamboui.widgets.sparkline.Sparkline.BarSet

hashCode() - Method in class dev.tamboui.widgets.spinner.SpinnerFrameSet

hasKnownHeight() - Method in class dev.tamboui.toolkit.element.Size
Returns true if the height is known (non-negative).

hasKnownWidth() - Method in class dev.tamboui.toolkit.element.Size
Returns true if the width is known (non-negative).

hasLabels() - Method in class dev.tamboui.widgets.chart.Axis
Returns true if this axis has labels.

hasMarkers() - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.SymbolSet
Returns whether this set has begin/end markers.

hasName() - Method in class dev.tamboui.widgets.chart.Dataset
Returns true if this dataset has a name.

hasProperties() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns true if this style has any properties set.

hasShift() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if Shift modifier was pressed.

hasValidationErrors() - Method in class dev.tamboui.widgets.form.FormState
Returns true if any field has a validation error.

header(Row) - Method in class dev.tamboui.toolkit.elements.TableElement
Sets the header row.

header(Row) - Method in class dev.tamboui.widgets.table.Table.Builder
Sets the header row.

header(String...) - Method in class dev.tamboui.toolkit.elements.TableElement
Sets the header row from strings.

HEAVY_DOUBLE_DASHED - Enum constant in enum class dev.tamboui.widgets.block.BorderType
Heavy double-dashed border.

HEAVY_QUADRUPLE_DASHED - Enum constant in enum class dev.tamboui.widgets.block.BorderType
Heavy quadruple-dashed border.

HEAVY_TRIPLE_DASHED - Enum constant in enum class dev.tamboui.widgets.block.BorderType
Heavy triple-dashed border.

height() - Method in class dev.tamboui.buffer.Buffer
Returns the height of this buffer.

height() - Method in class dev.tamboui.image.ImageData
Returns the image height in pixels.

height() - Method in class dev.tamboui.inline.InlineDisplay
Returns the height of this display in lines.

height() - Method in class dev.tamboui.internal.record.RecordingConfig
Returns the recording height in rows.

height() - Method in class dev.tamboui.layout.flow.FlowItem
Returns the item height in cells.

height() - Method in class dev.tamboui.layout.Rect
Returns the height.

height() - Method in class dev.tamboui.layout.Size
Returns the height.

height() - Method in class dev.tamboui.terminal.Frame
Returns the terminal height.

height() - Method in class dev.tamboui.text.Text
Returns the height (number of lines).

height() - Method in class dev.tamboui.toolkit.app.InlineApp
Returns the initial height of the inline display in lines.

height() - Method in class dev.tamboui.toolkit.element.Size
Returns the preferred height.

height() - Method in class dev.tamboui.tui.event.ResizeEvent
Returns the new terminal height in rows.

height() - Method in class dev.tamboui.tui.InlineTuiConfig
Returns the height of the inline display in lines.

height() - Method in class dev.tamboui.tui.InlineTuiRunner
Returns the viewport height.

height() - Method in class dev.tamboui.widgets.canvas.shapes.Rectangle
Returns the height.

height() - Method in class dev.tamboui.widgets.common.SizedWidget
Returns the explicit height, or `SizedWidget.DEFAULT` for default behavior.

height() - Method in class dev.tamboui.widgets.list.ListItem
Returns the height of this item in lines.

height() - Method in class dev.tamboui.widgets.table.Cell
Returns the height of this cell (number of lines).

height() - Method in class dev.tamboui.widgets.table.Row
Returns the height of this row.

height(int) - Method in class dev.tamboui.widgets.table.Row
Returns a new row with the given height.

HEIGHT - Static variable in class dev.tamboui.style.StandardProperties

The `height` property for height constraint.

heightConstraint() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the height constraint (for vertical layouts), if set.

heightConstraint(Constraint) - Method in class dev.tamboui.css.cascade.CssStyleResolver.Builder
Sets the height constraint (for vertical layouts).

heightMultiplier() - Method in class dev.tamboui.image.protocol.ImageProtocol.Resolution
Returns the height multiplier.

heightOnly(int) - Static method in class dev.tamboui.toolkit.element.Size
Creates a size with known height and unknown width (fill horizontally).

heightOr(int) - Method in class dev.tamboui.toolkit.element.Size
Returns the height if known, otherwise returns the default value.

heightOr(int) - Method in class dev.tamboui.widgets.common.SizedWidget
Returns the height if explicitly set, or the given default value.

hex(String) - Static method in interface dev.tamboui.style.Color
Creates an RGB true-color value from a `#rrggbb` string.

hidden() - Method in class dev.tamboui.style.Style
Hides text.

HIDDEN - Enum constant in enum class dev.tamboui.style.Modifier
Hidden (invisible) text.

hide() - Method in class dev.tamboui.toolkit.elements.InlineScopeElement
Hides this scope (sets visibility to false).

hideCursor() - Method in class dev.tamboui.backend.aesh.AeshBackend

hideCursor() - Method in class dev.tamboui.backend.jline3.JLineBackend

hideCursor() - Method in class dev.tamboui.backend.panama.PanamaBackend

hideCursor() - Method in class dev.tamboui.internal.record.RecordingBackend

hideCursor() - Method in interface dev.tamboui.terminal.Backend
Hides the cursor.

hideCursor() - Method in class dev.tamboui.terminal.Terminal
Hides the cursor.

hideCursor() - Method in class dev.tamboui.tui.TuiConfig
Returns whether the cursor should be hidden.

hideCursor(boolean) - Method in class dev.tamboui.tui.TuiConfig.Builder
Sets whether to hide the cursor.

hideCursor(boolean) - Method in class dev.tamboui.tui.TuiRunner.Builder
Sets whether to hide the cursor.

hideLegend() - Method in class dev.tamboui.toolkit.elements.ChartElement
Hides the legend.

hideLegend() - Method in class dev.tamboui.widgets.chart.Chart.Builder
Hides the legend.

hideMarkers() - Method in class dev.tamboui.toolkit.elements.ScrollbarElement
Hides the begin/end markers.

HIGHLIGHT_COLOR - Static variable in class dev.tamboui.widgets.table.Table
Property key for the row highlight (selection) color.

HIGHLIGHT_COLOR - Static variable in class dev.tamboui.widgets.tabs.Tabs
Property key for the selected tab highlight color.

HIGHLIGHT_SYMBOL - Static variable in class dev.tamboui.toolkit.elements.ListElement
CSS property for highlight symbol shown before selected item.

HIGHLIGHT_SYMBOL - Static variable in class dev.tamboui.toolkit.elements.TreeElement
CSS property for highlight symbol shown before selected item.

highlightColor(Color) - Method in class dev.tamboui.toolkit.elements.ListElement
Sets the highlight color for selected items.

highlightColor(Color) - Method in class dev.tamboui.toolkit.elements.TableElement
Sets the highlight color for selected rows.

highlightColor(Color) - Method in class dev.tamboui.toolkit.elements.TabsElement
Sets the highlight color for the selected tab.

highlightColor(Color) - Method in class dev.tamboui.toolkit.elements.TreeElement
Sets the highlight color for the selected node.

highlightColor(Color) - Method in class dev.tamboui.widgets.table.Table.Builder
Sets the row highlight (selection) color programmatically.

highlightColor(Color) - Method in class dev.tamboui.widgets.tabs.Tabs.Builder
Sets the selected tab highlight color programmatically.

highlightSpacing(Table.HighlightSpacing) - Method in class dev.tamboui.widgets.table.Table.Builder
Sets when to allocate space for the highlight symbol.

highlightStyle(Style) - Method in class dev.tamboui.toolkit.elements.ListElement
Sets the highlight style for selected items.

highlightStyle(Style) - Method in class dev.tamboui.toolkit.elements.TableElement
Sets the highlight style for selected rows.

highlightStyle(Style) - Method in class dev.tamboui.toolkit.elements.TabsElement
Sets the highlight style for the selected tab.

highlightStyle(Style) - Method in class dev.tamboui.toolkit.elements.TreeElement
Sets the highlight style for the selected node.

highlightStyle(Style) - Method in class dev.tamboui.widgets.list.ListWidget.Builder
Sets the highlight style for selected items.

highlightStyle(Style) - Method in class dev.tamboui.widgets.table.Table.Builder
Sets the style for the selected row.

highlightStyle(Style) - Method in class dev.tamboui.widgets.tabs.Tabs.Builder
Sets the style for the selected tab.

highlightStyle(Style) - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Sets the highlight style for selected items.

highlightSymbol(Line) - Method in class dev.tamboui.widgets.list.ListWidget.Builder
Sets the highlight symbol shown before selected items.

highlightSymbol(Line) - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Sets the highlight symbol shown before selected items.

highlightSymbol(String) - Method in class dev.tamboui.toolkit.elements.ListElement
Sets the symbol displayed before the selected item.

highlightSymbol(String) - Method in class dev.tamboui.toolkit.elements.TableElement
Sets the symbol displayed before the selected row.

highlightSymbol(String) - Method in class dev.tamboui.toolkit.elements.TreeElement
Sets the symbol displayed before the selected node.

highlightSymbol(String) - Method in class dev.tamboui.widgets.list.ListWidget.Builder
Sets the highlight symbol as a string.

highlightSymbol(String) - Method in class dev.tamboui.widgets.table.Table.Builder
Sets the symbol displayed before the selected row.

highlightSymbol(String) - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Sets the highlight symbol as a string.

highlightToday(Color) - Method in class dev.tamboui.toolkit.elements.CalendarElement

Highlights today with the given color.

highlightToday(Style) - Method in class dev.tamboui.toolkit.elements.CalendarElement
Highlights today with the given style.

HOME - Enum constant in enum class dev.tamboui.tui.event.KeyCode
Home key.

HOME - Static variable in class dev.tamboui.tui.bindings.Actions
Go to beginning (Home, vim 'g', emacs Alt+<, etc.).

horizontal() - Static method in class dev.tamboui.layout.Layout
Creates a horizontal layout (left-to-right).

horizontal() - Method in class dev.tamboui.toolkit.elements.BarChartElement
Sets horizontal direction.

horizontal() - Method in class dev.tamboui.toolkit.elements.DialogElement
Sets the layout direction to horizontal.

horizontal() - Method in class dev.tamboui.toolkit.elements.Gutter
Returns the horizontal gutter (between columns).

horizontal() - Method in class dev.tamboui.toolkit.elements.Panel
Sets the layout direction to horizontal.

horizontal() - Method in class dev.tamboui.toolkit.elements.ScrollbarElement
Sets horizontal bottom-aligned orientation.

horizontal() - Static method in class dev.tamboui.widgets.scrollbar.Scrollbar
Creates a horizontal bottom-aligned scrollbar with default settings.

horizontal(int) - Static method in class dev.tamboui.layout.Margin
Returns a margin applied horizontally only.

horizontal(int) - Static method in class dev.tamboui.layout.Padding
Returns a padding applied horizontally only.

horizontal(String) - Method in class dev.tamboui.widgets.block.BorderSet.Builder
Sets both horizontal border characters (top and bottom).

HORIZONTAL - Enum constant in enum class dev.tamboui.layout.Direction
Horizontal direction (left-to-right).

HORIZONTAL - Enum constant in enum class dev.tamboui.tfx.ExpandDirection
Expands horizontally from center (left and right simultaneously).

HORIZONTAL - Static variable in class dev.tamboui.widgets.barchart.BarChart.BarSet
Horizontal bar set (left to right).

HORIZONTAL - Static variable in class dev.tamboui.widgets.scrollbar.Scrollbar.SymbolSet
Horizontal scrollbar with single-line track and arrows.

HORIZONTAL_BOTTOM - Enum constant in enum class dev.tamboui.widgets.scrollbar.ScrollbarOrientation
Horizontal scrollbar at the bottom of the content area.

HORIZONTAL_TOP - Enum constant in enum class dev.tamboui.widgets.scrollbar.ScrollbarOrientation
Horizontal scrollbar at the top of the content area.

horizontalGutter(int) - Method in class dev.tamboui.layout.grid.Grid.AreaBuilder
Sets the horizontal gutter between columns.

horizontalGutter(int) - Method in class dev.tamboui.layout.grid.Grid.ChildrenBuilder
Sets the horizontal gutter between columns.

horizontalSpacing(int) - Method in class dev.tamboui.layout.flow.Flow.Builder
Sets the horizontal gap between items on the same row.

horizontalTop() - Method in class dev.tamboui.toolkit.elements.ScrollbarElement
Sets horizontal top-aligned orientation.

horizontalTotal() - Method in class dev.tamboui.layout.Margin
Returns the sum of left and right margins.

horizontalTotal() - Method in class dev.tamboui.layout.Padding
Returns the sum of left and right padding.

HSL - Enum constant in enum class dev.tamboui.tfx.TFxColorSpace
HSL interpolation (default - balance of performance and perceptual quality)

HSV - Enum constant in enum class dev.tamboui.tfx.TFxColorSpace
HSV interpolation (similar to HSL but different perceptual model)

html() - Method in class dev.tamboui.export.ExportRequest
Shorthand for `as(Formats.HTML)`.

HTML - Static variable in class dev.tamboui.export.Formats
HTML format.

HtmlExporter - Class in dev.tamboui.export.html
Exports a `Buffer` to HTML in the same spirit as Rich's `Console.export_html`.

HtmlFormat - Class in dev.tamboui.export.html
HTML export format.

HtmlOptions - Class in dev.tamboui.export.html
Options for HTML export.

HtmlOptions() - Constructor for class dev.tamboui.export.html.HtmlOptions
Creates default HTML export options.

hyperlink() - Method in class dev.tamboui.style.Style
Returns the hyperlink attached to this style, if any.

hyperlink(Hyperlink) - Method in class dev.tamboui.style.Style
Returns a new style with the given hyperlink.

hyperlink(String) - Method in class dev.tamboui.style.Style
Returns a new style with the given hyperlink.

hyperlink(String) - Method in class dev.tamboui.text.Line
Returns a new line with a hyperlink applied to all spans.

hyperlink(String) - Method in class dev.tamboui.text.Span
Returns a new span with a hyperlink.

hyperlink(String) - Method in class dev.tamboui.text.Text
Returns a new text with a hyperlink.

hyperlink(String, String) - Method in class dev.tamboui.style.Style
Returns a new style with the given hyperlink and ID.

hyperlink(String, String) - Method in class dev.tamboui.text.Line
Returns a new line with a hyperlink and ID applied to all spans.

hyperlink(String, String) - Method in class dev.tamboui.text.Span
Returns a new span with a hyperlink and explicit ID.

hyperlink(String, String) - Method in class dev.tamboui.text.Text
Returns a new text with a hyperlink and explicit ID.

Hyperlink - Class in dev.tamboui.style
Represents a hyperlink that can be attached to a Style.

hyperlinkEnd() - Static method in class dev.tamboui.terminal.AnsiStringBuilder
Generates an OSC8 escape sequence to end a hyperlink.

hyperlinkStart(Hyperlink) - Static method in class dev.tamboui.terminal.AnsiStringBuilder
Generates an OSC8 hyperlink escape sequence to start a hyperlink.

I

ICANON - Static variable in class dev.tamboui.backend.panama.unix.LibC
Local flag: enable canonical (line-by-line) input mode.

ICANON - Static variable in class dev.tamboui.backend.panama.unix.PlatformConstants

Local flag: enable canonical (line-by-line) input mode.

ICRNL - Static variable in class dev.tamboui.backend.panama.unix.LibC
Input flag: translate carriage return to newline on input.

ICRNL - Static variable in class dev.tamboui.backend.panama.unix.PlatformConstants
Input flag: translate carriage return to newline on input.

id() - Method in class dev.tamboui.css.selector.IdSelector
Returns the identifier this selector matches.

id() - Method in interface dev.tamboui.export.Format
Returns a short identifier for this format (e.g.

id() - Method in class dev.tamboui.export.html.HtmlFormat

id() - Method in class dev.tamboui.export.svg.SvgFormat

id() - Method in class dev.tamboui.export.text.TextFormat

id() - Method in class dev.tamboui.layout.cassowary.Variable
Returns the unique identifier of this variable.

id() - Method in class dev.tamboui.style.Hyperlink
Returns the ID of this hyperlink, if set.

id() - Method in interface dev.tamboui.toolkit.element.Element
Returns the unique ID of this element, if set.

id() - Method in class dev.tamboui.toolkit.element.ElementRegistry.ElementInfo
Returns the element ID, or null if not set.

id() - Method in class dev.tamboui.toolkit.element.StyledElement

id() - Method in class dev.tamboui.toolkit.elements.LazyElement

id() - Method in interface dev.tamboui.toolkit.focus.Focusable
Returns the unique ID of this focusable element.

id(String) - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the element's ID for focus management and CSS targeting.

Ident(String, Token.Position) - Constructor for class dev.tamboui.css.parser.Token.Ident
Creates an identifier token.

IdentityPattern - Class in dev.tamboui.tfx.pattern
Identity pattern that returns the global alpha unchanged.

IdGenerator - Class in dev.tamboui.toolkit.id
Generates unique IDs for elements and components.

IdSelector - Class in dev.tamboui.css.selector
An ID selector that matches elements by their unique identifier.

IdSelector(String) - Constructor for class dev.tamboui.css.selector.IdSelector
Creates an ID selector for the given identifier.

IEXTEN - Static variable in class dev.tamboui.backend.panama.unix.LibC
Local flag: enable implementation-defined input processing.

IEXTEN - Static variable in class dev.tamboui.backend.panama.unix.PlatformConstants
Local flag: enable implementation-defined input processing.

IGNORE - Enum constant in enum class dev.tamboui.css.cascade.UnknownPropertyBehavior
Silently ignore unknown properties.

Image - Class in dev.tamboui.image
A widget for displaying images in the terminal.

Image.Builder - Class in dev.tamboui.image
Builder for `Image`.

ImageCapabilityProvider - Class in dev.tamboui.image.capability
Capability contributor for `tamboui-image`.

ImageCapabilityProvider() - Constructor for class dev.tamboui.image.capability.ImageCapabilityProvider
Creates a new image capability provider.

ImageData - Class in dev.tamboui.image
Immutable holder for image pixel data.

ImageProtocol - Interface in dev.tamboui.image.protocol
Protocol for rendering images to a terminal.

ImageProtocol.Resolution - Class in dev.tamboui.image.protocol
Resolution multiplier for a rendering protocol.

ImageScaling - Enum Class in dev.tamboui.image
Defines how an image should be scaled to fit the available terminal area.

implicitStyleName() - Method in enum class dev.tamboui.style.Modifier
Returns the implicit style name for this modifier.

implicitStyleNames() - Method in class dev.tamboui.style.Style
Returns the style names implied by this style's Named colors and modifiers.

important() - Method in class dev.tamboui.css.model.PropertyValue
Returns whether this value has the `!important` flag.

important(String) - Static method in class dev.tamboui.css.model.PropertyValue
Creates an important (!important) property value.

INDENT_WIDTH - Static variable in class dev.tamboui.toolkit.elements.TreeElement
CSS property for indent width (space per depth level).

indentWidth(int) - Method in class dev.tamboui.toolkit.elements.TreeElement
Sets the indent width per depth level.

indentWidth(int) - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Sets the indent width per depth level.

index() - Method in class dev.tamboui.style.Color.Indexed
Returns the palette index.

index() - Method in class dev.tamboui.toolkit.element.ChildPosition
Returns the zero-based index of this child.

indexed(int) - Static method in interface dev.tamboui.style.Color
Creates a 256-color indexed value.

Indexed(int) - Constructor for class dev.tamboui.style.Color.Indexed
Creates an indexed color.

indexedToRgb(int) - Static method in interface dev.tamboui.style.Color
Converts a 256-color indexed value to RGB.

INDICATOR_COLOR - Static variable in class dev.tamboui.widgets.select.Select
CSS property for the indicator foreground color.

indicatorColor(Color) - Method in class dev.tamboui.widgets.select.Select.Builder
Sets the foreground color for indicators.

INHERIT_KEYWORD - Static variable in class dev.tamboui.css.model.PropertyValue
The keyword used when a child wants to explicitly inherit a value from its parent.

inheritable() - Method in class dev.tamboui.style.PropertyDefinition.Builder
Marks this property as inheritable.

inheritable() - Static method in class dev.tamboui.style.StandardProperties
Returns all inheritable property definitions.

Inheritable properties: - Section in class dev.tamboui.style.StandardProperties

init(ProcessingEnvironment) - Method in class dev.tamboui.tui.bindings.processor.OnActionProcessor

initRecording() - Static method in class dev.tamboui.terminal.BackendFactory
Initializes recording if enabled via system properties.

InlineApp - Class in dev.tamboui.toolkit.app
Base class for inline DSL-based TUI applications.

InlineApp() - Constructor for class dev.tamboui.toolkit.app.InlineApp
Creates a new inline application.

inlineChoice(boolean) - Method in class dev.tamboui.widgets.toggle.Toggle.Builder
Enables inline choice mode, showing both options like "● Yes / ○ No".

InlineDisplay - Class in dev.tamboui.inline
Manages a fixed-height inline display area for Gradle/NPM-style progress UX.

InlineEventHandler - Interface in dev.tamboui.tui
Functional interface for handling inline TUI events.

InlineScopeElement - Class in dev.tamboui.toolkit.elements
A scope element that can show/hide its content dynamically.

InlineScopeElement() - Constructor for class dev.tamboui.toolkit.elements.InlineScopeElement
Creates an empty scope element.

InlineScopeElement(Element...) - Constructor for class dev.tamboui.toolkit.elements.InlineScopeElement
Creates a scope element with the given children.

inlineStyles(boolean) - Method in class dev.tamboui.export.html.HtmlOptions
Sets whether styles are inlined in spans (true) or in a stylesheet (false).

InlineToolkit - Class in dev.tamboui.toolkit
DSL factory for inline-specific elements.

InlineToolkitRunner - Class in dev.tamboui.toolkit.app
Element-based inline runner - no manual rendering.

InlineToolkitRunner.Builder - Class in dev.tamboui.toolkit.app
Builder for `InlineToolkitRunner` instances.

InlineTuiConfig - Class in dev.tamboui.tui
Configuration options for `InlineTuiRunner`.

InlineTuiConfig.Builder - Class in dev.tamboui.tui
Builder for `InlineTuiConfig`.

InlineTuiRunner - Class in dev.tamboui.tui
Event loop for inline displays.

inner(Margin) - Method in class dev.tamboui.layout.Rect
Returns the inner area after applying the given margin.

inner(Margin) - Static method in class dev.tamboui.tfx.CellFilter
Selects cells within the inner margin of the area.

inner(Rect) - Method in class dev.tamboui.layout.Margin
Returns the inner area after applying this margin.

inner(Rect) - Method in class dev.tamboui.widgets.block.Block
Returns the inner area after accounting for borders, titles, and padding.

INPCK - Static variable in class dev.tamboui.backend.panama.unix.LibC
Input flag: enable input parity check.

INPCK - Static variable in class dev.tamboui.backend.panama.unix.PlatformConstants
Input flag: enable input parity check.

INPUT_RECORD_LAYOUT - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
Layout for INPUT_RECORD structure.

InputTrigger - Interface in dev.tamboui.tui.bindings
Represents an input trigger that can match an `Event`.

insert(char) - Method in class dev.tamboui.widgets.input.TextAreaState

Inserts a character at the cursor position.

insert(char) - Method in class dev.tamboui.widgets.input.TextInputState
Inserts a character at the cursor position.

insert(String) - Method in class dev.tamboui.widgets.input.TextAreaState
Inserts a string at the cursor position.

insert(String) - Method in class dev.tamboui.widgets.input.TextInputState
Inserts a string at the cursor position.

INSERT - Enum constant in enum class dev.tamboui.tui.event.KeyCode
Insert key.

insertLines(int) - Method in class dev.tamboui.backend.aesh.AeshBackend

insertLines(int) - Method in class dev.tamboui.backend.jline3.JLineBackend

insertLines(int) - Method in class dev.tamboui.backend.panama.PanamaBackend

insertLines(int) - Method in interface dev.tamboui.terminal.Backend
Inserts N lines at the current cursor position, pushing existing lines down.

install(RecordingConfig) - Static method in class dev.tamboui.internal.record.AnsiTerminalCapture
Installs the capture by replacing System.out.

instance() - Static method in class dev.tamboui.export.html.HtmlFormat
Returns the singleton HTML format instance.

instance() - Static method in class dev.tamboui.export.svg.SvgFormat
Returns the singleton SVG format instance.

instance() - Static method in class dev.tamboui.export.text.TextFormat
Returns the singleton text format instance.

instance() - Static method in class dev.tamboui.layout.cassowary.LayoutCache
Returns the thread-local layout cache instance.

INSTANCE - Static variable in class dev.tamboui.css.property.AlignmentConverter
Singleton instance of the alignment converter.

INSTANCE - Static variable in class dev.tamboui.css.property.BorderSetConverter
Singleton instance.

INSTANCE - Static variable in class dev.tamboui.css.property.BorderTypeConverter
Singleton instance.

INSTANCE - Static variable in class dev.tamboui.css.property.ConstraintConverter
Singleton instance.

INSTANCE - Static variable in class dev.tamboui.css.property.DirectionConverter
Singleton instance.

INSTANCE - Static variable in class dev.tamboui.css.property.FlexConverter
Singleton instance.

INSTANCE - Static variable in class dev.tamboui.css.property.IntegerConverter
Singleton instance.

INSTANCE - Static variable in class dev.tamboui.css.property.MarginConverter
Singleton instance.

INSTANCE - Static variable in class dev.tamboui.css.property.ModifierConverter
Singleton instance.

INSTANCE - Static variable in class dev.tamboui.css.property.SpacingConverter
Singleton instance.

INSTANCE - Static variable in class dev.tamboui.css.property.WidthConverter
Singleton instance.

INSTANCE - Static variable in class dev.tamboui.css.selector.UniversalSelector

Singleton instance since the selector is stateless.

INSTANCE - Static variable in class dev.tamboui.layout.ConstraintConverter
Singleton instance of the constraint converter.

INSTANCE - Static variable in class dev.tamboui.layout.ContentAlignmentConverter
Singleton instance of the content alignment converter.

INSTANCE - Static variable in class dev.tamboui.layout.DirectionConverter
Singleton instance of the direction converter.

INSTANCE - Static variable in class dev.tamboui.layout.FlexConverter
Singleton instance of the flex converter.

INSTANCE - Static variable in class dev.tamboui.layout.MarginConverter
Singleton instance of the margin converter.

INSTANCE - Static variable in class dev.tamboui.layout.PaddingConverter
Singleton instance of the padding converter.

INSTANCE - Static variable in class dev.tamboui.style.AlignmentConverter
Singleton instance of the alignment converter.

INSTANCE - Static variable in class dev.tamboui.style.BorderCharConverter
Singleton instance.

INSTANCE - Static variable in class dev.tamboui.style.ColorConverter
Singleton instance of the color converter.

INSTANCE - Static variable in class dev.tamboui.style.DoubleConverter
Singleton instance of the double converter.

INSTANCE - Static variable in class dev.tamboui.style.IntegerConverter
Singleton instance of the integer converter.

INSTANCE - Static variable in class dev.tamboui.style.ModifierConverter
Singleton instance of the modifier converter.

INSTANCE - Static variable in class dev.tamboui.style.OverflowConverter
Singleton instance of the overflow converter.

INSTANCE - Static variable in class dev.tamboui.style.StringConverter
Singleton instance.

INSTANCE - Static variable in class dev.tamboui.tfx.pattern.IdentityPattern
Singleton instance of the identity pattern.

INSTANCE - Static variable in class dev.tamboui.toolkit.elements.ColumnOrderConverter
Singleton instance of the column order converter.

INSTANCE - Static variable in class dev.tamboui.toolkit.elements.ConstraintListConverter
Singleton instance.

INSTANCE - Static variable in class dev.tamboui.toolkit.elements.GridAreaConverter
Singleton instance.

INSTANCE - Static variable in class dev.tamboui.toolkit.elements.GridSizeConverter
Singleton instance.

INSTANCE - Static variable in class dev.tamboui.toolkit.elements.GutterConverter
Singleton instance.

INSTANCE - Static variable in class dev.tamboui.widgets.block.BorderTypeConverter
Singleton instance of the border type converter.

INSTANCE - Static variable in class dev.tamboui.widgets.Clear
Singleton instance of the Clear widget.

INSTANCE - Static variable in class dev.tamboui.widgets.spinner.SpinnerFrameSetConverter
Singleton instance of the spinner frame set converter.

INSTANCE - Static variable in class dev.tamboui.widgets.spinner.SpinnerStyleConverter
Singleton instance of the spinner style converter.

IntegerConverter - Class in dev.tamboui.css.property
Converts CSS integer values.

IntegerConverter - Class in dev.tamboui.style
Converts string values to Integer objects.

intellij() - Static method in class dev.tamboui.tui.bindings.BindingSets
IntelliJ IDEA-style binding set.

InternalSolverException - Exception Class in dev.tamboui.layout.cassowary
Thrown when an internal solver error occurs.

InternalSolverException(String) - Constructor for exception class dev.tamboui.layout.cassowary.InternalSolverException
Creates a new internal solver exception.

interpolation() - Method in class dev.tamboui.tfx.EffectTimer
Returns the interpolation method.

Interpolation - Enum Class in dev.tamboui.tfx
Easing functions (interpolation curves) for smooth animations.

intersection(Rect) - Method in class dev.tamboui.layout.Rect
Returns the intersection of this rectangle with another.

invalid(String) - Static method in class dev.tamboui.widgets.form.ValidationResult
Creates an invalid result with the given error message.

INVALID_HANDLE_VALUE - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
Sentinel value returned by handle functions on failure.

inverted() - Method in class dev.tamboui.toolkit.elements.WaveTextElement
Sets the effect to inverted mode (bright peak on dim text).

inverted(boolean) - Method in class dev.tamboui.toolkit.elements.WaveTextElement
Sets whether the effect is inverted.

inverted(boolean) - Method in class dev.tamboui.widgets.wavetext.WaveText.Builder
Sets whether the effect is inverted.

ioctl(int, long, MemorySegment) - Static method in class dev.tamboui.backend.panama.unix.LibC
Performs an I/O control operation.

IR_CHAR - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
VarHandle for the Unicode character in a KEY_EVENT_RECORD.

IR_EVENT_TYPE - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
VarHandle for the event type field of an INPUT_RECORD.

IR_KEY_DOWN - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
VarHandle for the key-down flag in a KEY_EVENT_RECORD.

isActive() - Method in class dev.tamboui.css.cascade.PseudoClassState
Returns whether the element is being activated.

isAlive() - Method in class dev.tamboui.tui.TerminalInputReader
Returns whether the input reader thread is alive.

isAtEnd() - Method in class dev.tamboui.widgets.scrollbar.ScrollbarState
Returns true if scrolled to the end.

isAtStart() - Method in class dev.tamboui.widgets.scrollbar.ScrollbarState
Returns true if scrolled to the beginning (position 0).

isatty(int) - Static method in class dev.tamboui.backend.panama.unix.LibC
Checks if a file descriptor refers to a terminal.

isBorderSymbol(String) - Static method in enum class dev.tamboui.symbols.merge.MergeStrategy
Checks if a symbol is a border symbol that can be merged.

isCancel() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is a "cancel" event (Escape) according to the bindings.

isCancelled() - Method in class dev.tamboui.toolkit.app.ToolkitRunner.ScheduledAction
Returns whether this action has been cancelled.

isChar(char) - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is a character event matching the given character (case-sensitive).

isCharIgnoreCase(char) - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is a character event matching the given character (case-insensitive).

isChecked() - Method in class dev.tamboui.widgets.checkbox.CheckboxState
Returns whether the checkbox is checked.

isClick() - Method in class dev.tamboui.tui.event.MouseEvent
Returns true if this is a "click" event (left mouse press) according to the bindings.

isConfirm() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is a "confirm" event (Enter) according to the bindings.

isConstant() - Method in class dev.tamboui.layout.cassowary.Expression
Returns true if this expression has no terms (only a constant).

isContinuation() - Method in class dev.tamboui.buffer.Cell
Returns whether this cell is a continuation placeholder for a wide character.

isCtrlC() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is a Ctrl+C event (common quit signal).

isDeleteBackward() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is a "delete backward" event (Backspace) according to the bindings.

isDeleteForward() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is a "delete forward" event (Delete) according to the bindings.

isDisabled() - Method in class dev.tamboui.css.cascade.PseudoClassState
Returns whether the element is disabled.

isDone() - Method in class dev.tamboui.toolkit.app.ToolkitRunner.ScheduledAction
Returns whether this action has completed.

isDown() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is a "down" navigation event according to the bindings.

isDraggable() - Method in interface dev.tamboui.toolkit.element.Element
Returns whether this element is draggable.

isDraggable() - Method in class dev.tamboui.toolkit.element.StyledElement

isDraggable() - Method in class dev.tamboui.toolkit.elements.LazyElement

isDragging() - Method in class dev.tamboui.toolkit.event.EventRouter
Returns whether a drag operation is in progress.

isEmpty() - Method in class dev.tamboui.buffer.Cell
Returns whether this cell is empty (single space with no style).

isEmpty() - Method in class dev.tamboui.buffer.DiffResult
Returns whether this diff result is empty.

isEmpty() - Method in class dev.tamboui.css.cascade.TypedPropertyMap
Returns true if this map is empty.

isEmpty() - Method in class dev.tamboui.layout.Rect
Returns true if width or height is zero.

isEmpty() - Method in class dev.tamboui.layout.Size
Returns true if either dimension is zero.

isEmpty() - Method in class dev.tamboui.style.Tags
Returns whether this Tags instance is empty.

isEmpty() - Method in class dev.tamboui.text.Line
Returns whether this line is empty (no spans or all spans empty).

isEmpty() - Method in class dev.tamboui.text.Span
Returns true if this span has no content.

isEmpty() - Method in class dev.tamboui.text.Text
Returns true if this text has no content.

isEmpty() - Method in class dev.tamboui.tui.event.KeyModifiers
Returns true if no modifiers are pressed.

isEmpty() - Method in class dev.tamboui.widgets.calendar.CalendarEventStore
Returns true if this store has no styled dates.

isEnabled() - Static method in class dev.tamboui.internal.record.RecordingConfig
Checks if recording is enabled via system properties.

isEnd() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is an "end" navigation event according to the bindings.

isEven() - Method in class dev.tamboui.toolkit.element.ChildPosition
Returns true if this child is at an even position (0, 2, 4, ...).

isExpanded() - Method in class dev.tamboui.widgets.tree.TreeNode
Returns whether this node is expanded.

isExpanded(TreeNode) - Method in class dev.tamboui.widgets.tree.TreeNode

isExpanded(T) - Method in interface dev.tamboui.widgets.tree.TreeModel
Returns whether the given node is currently expanded.

isFaultTolerant() - Method in class dev.tamboui.toolkit.app.ToolkitRunner
Returns whether fault-tolerant rendering is enabled.

isFaultTolerant() - Method in class dev.tamboui.toolkit.element.DefaultRenderContext
Returns whether fault-tolerant rendering is enabled.

isFill() - Method in class dev.tamboui.style.Width
Returns true if this width fills the container.

isFirst() - Method in class dev.tamboui.toolkit.element.ChildPosition
Returns true if this is the first child (index == 0).

isFirstChild() - Method in class dev.tamboui.css.cascade.PseudoClassState
Returns whether the element is the first child of its parent.

isFit() - Method in class dev.tamboui.style.Width
Returns true if this width fits the content.

isFixed() - Method in class dev.tamboui.style.Width
Returns true if this width is a fixed character count.

isFocusable() - Method in class dev.tamboui.toolkit.component.Component

isFocusable() - Method in interface dev.tamboui.toolkit.element.Element
Returns whether this element can receive focus.

isFocusable() - Method in class dev.tamboui.toolkit.element.StyledElement

isFocusable() - Method in class dev.tamboui.toolkit.elements.FormFieldElement

isFocusable() - Method in class dev.tamboui.toolkit.elements.LazyElement

isFocusable() - Method in class dev.tamboui.toolkit.elements.TextAreaElement

isFocusable() - Method in class dev.tamboui.toolkit.elements.TextInputElement
Returns whether this text input is focusable.

isFocusable() - Method in interface dev.tamboui.toolkit.focus.Focusable
Returns whether this element can receive focus.

isFocused() - Method in class dev.tamboui.css.cascade.PseudoClassState
Returns whether the element has keyboard focus.

isFocused() - Method in class dev.tamboui.toolkit.component.Component
Returns whether this component is currently focused.

isFocused(String) - Method in class dev.tamboui.toolkit.element.DefaultRenderContext

isFocused(String) - Method in interface dev.tamboui.toolkit.element.RenderContext
Returns whether the element with the given ID is currently focused.

isFocused(String) - Method in class dev.tamboui.toolkit.focus.FocusManager
Returns whether the element with the given ID is currently focused.

isFocusNext() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is a "focus next" event (Tab) according to the bindings.

isFocusPrevious() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is a "focus previous" event (Shift+Tab) according to the bindings.

isHandled() - Method in enum class dev.tamboui.toolkit.event.EventResult
Returns whether this result indicates the event was handled.

isHome() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is a "home" navigation event according to the bindings.

isHorizontal() - Method in enum class dev.tamboui.widgets.scrollbar.ScrollbarOrientation
Returns true if this orientation is horizontal.

isHovered() - Method in class dev.tamboui.css.cascade.PseudoClassState
Returns whether the mouse is over the element.

ISIG - Static variable in class dev.tamboui.backend.panama.unix.LibC
Local flag: enable signal generation for INTR, QUIT, SUSP characters.

ISIG - Static variable in class dev.tamboui.backend.panama.unix.PlatformConstants
Local flag: enable signal generation for INTR, QUIT, SUSP characters.

isInherit() - Method in class dev.tamboui.css.model.PropertyValue
Returns true if this value is the special "inherit" keyword, indicating the child wants to explicitly inherit from parent.

isInheritable() - Method in class dev.tamboui.style.PropertyDefinition
Returns whether this property is inherited from parent elements.

isInlineChoice() - Method in class dev.tamboui.widgets.toggle.Toggle
Returns whether inline choice mode is enabled.

isInstalled() - Static method in class dev.tamboui.internal.record.AnsiTerminalCapture
Returns true if capture is currently installed.

isKey(KeyCode) - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is a key event matching the given key code.

isLast() - Method in class dev.tamboui.toolkit.element.ChildPosition
Returns true if this is the last child (index == total - 1).

isLastChild() - Method in class dev.tamboui.css.cascade.PseudoClassState
Returns whether the element is the last child of its parent.

isLeaf() - Method in class dev.tamboui.widgets.tree.TreeNode
Returns whether this node is a leaf.

isLeaf(TreeNode) - Method in class dev.tamboui.widgets.tree.TreeNode

isLeaf(Predicate) - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Sets the predicate to check if a node is a leaf (functional shortcut).

isLeaf(T) - Method in interface dev.tamboui.widgets.tree.TreeModel
Returns whether the given node is a leaf (has no children).

isLeft() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is a "left" navigation event according to the bindings.

isLeftButton() - Method in class dev.tamboui.tui.event.MouseEvent

Returns true if this is a left button event.

isLinux() - Static method in class dev.tamboui.backend.panama.unix.PlatformConstants
Returns true if running on Linux.

isMacOS() - Static method in class dev.tamboui.backend.panama.unix.PlatformConstants
Returns true if running on macOS.

isMaskedField(String) - Method in class dev.tamboui.widgets.form.FormState
Returns whether the given field should be masked (e.g., password field).

isMouseCapture() - Method in class dev.tamboui.picocli.TuiMixin
Returns true if mouse capture is enabled.

isNegative() - Method in class dev.tamboui.layout.Fraction
Returns true if this fraction represents a negative value.

isNoAltScreen() - Method in class dev.tamboui.picocli.TuiMixin
Returns true if alternate screen mode is disabled.

isOdd() - Method in class dev.tamboui.toolkit.element.ChildPosition
Returns true if this child is at an odd position (1, 3, 5, ...).

isOn() - Method in class dev.tamboui.widgets.toggle.ToggleState
Returns whether the toggle is on.

isPageDown() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is a "page down" navigation event according to the bindings.

isPageUp() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is a "page up" navigation event according to the bindings.

isPercent() - Method in class dev.tamboui.style.Width
Returns true if this width is a percentage.

isPercentage() - Method in class dev.tamboui.css.parser.Token.Number
Returns whether this number is a percentage value.

isPositive() - Method in class dev.tamboui.layout.Fraction
Returns true if this fraction represents a positive value.

isPress() - Method in class dev.tamboui.tui.event.MouseEvent
Returns true if this is a press event.

isQuit() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is a "quit" event according to the bindings.

isRawModeEnabled() - Method in interface dev.tamboui.backend.panama.PlatformTerminal
Checks if raw mode is currently enabled.

isRawModeEnabled() - Method in class dev.tamboui.backend.panama.unix.UnixTerminal
Checks if raw mode is currently enabled.

isRawModeEnabled() - Method in class dev.tamboui.backend.panama.windows.WindowsTerminal

isRecording() - Method in class dev.tamboui.internal.record.RecordingBackend
Returns true if recording is still active.

isRegistered(String) - Static method in class dev.tamboui.style.PropertyRegistry
Checks if a property with the given name is registered.

isRelease() - Method in class dev.tamboui.tui.event.MouseEvent
Returns true if this is a release event.

isRenderThread() - Method in class dev.tamboui.toolkit.app.ToolkitRunner
Returns whether the current thread is the render thread.

isRenderThread() - Static method in class dev.tamboui.tui.RenderThread
Returns whether the current thread is the render thread.

isRenderThread() - Method in class dev.tamboui.tui.TuiRunner
Returns whether the current thread is the render thread.

isRequired() - Method in class dev.tamboui.layout.cassowary.CassowaryConstraint
Returns true if this is a required constraint.

isRequired() - Method in class dev.tamboui.layout.cassowary.Strength
Returns true if this is the REQUIRED strength.

isReversed() - Method in class dev.tamboui.tfx.EffectTimer
Returns true if the timer is reversed.

isRight() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is a "right" navigation event according to the bindings.

isRightButton() - Method in class dev.tamboui.tui.event.MouseEvent
Returns true if this is a right button event.

isRightClick() - Method in class dev.tamboui.tui.event.MouseEvent
Returns true if this is a "right click" event according to the bindings.

isRunning() - Method in class dev.tamboui.tfx.EffectManager
Returns whether there are any active effects currently being managed.

isRunning() - Method in class dev.tamboui.tfx.toolkit.ElementEffectRegistry
Returns whether any effects are currently running.

isRunning() - Method in class dev.tamboui.tfx.toolkit.ToolkitEffects
Returns whether any effects are currently running or pending.

isRunning() - Method in class dev.tamboui.tfx.tui.TfxIntegration
Returns whether any effects are currently running.

isRunning() - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner
Returns whether the runner is still running.

isRunning() - Method in class dev.tamboui.toolkit.app.ToolkitRunner
Returns whether the runner is still running.

isRunning() - Method in class dev.tamboui.tui.InlineTuiRunner
Returns whether the runner is still running.

isRunning() - Method in class dev.tamboui.tui.TuiRunner
Returns true if the runner is still running.

isScroll() - Method in class dev.tamboui.tui.event.MouseEvent
Returns true if this is a scroll event.

isScrollable() - Method in class dev.tamboui.style.RichTextState
Returns true if the content can be scrolled (content exceeds viewport).

isSelect() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is a "select" event (Enter or Space) according to the bindings.

isSelected() - Method in class dev.tamboui.css.cascade.PseudoClassState
Returns whether the element is selected.

isShowCursor() - Method in class dev.tamboui.picocli.TuiMixin
Returns true if the cursor should be shown.

isSubmitOnEnter() - Method in class dev.tamboui.toolkit.elements.FormElement
Returns whether submit on Enter is enabled.

isSupported() - Method in enum class dev.tamboui.terminal.Mode2027Status
Returns whether the terminal supports Mode 2027.

ISTRIP - Static variable in class dev.tamboui.backend.panama.unix.LibC
Input flag: strip eighth bit off input characters.

ISTRIP - Static variable in class dev.tamboui.backend.panama.unix.PlatformConstants
Input flag: strip eighth bit off input characters.

isUnhandled() - Method in enum class dev.tamboui.toolkit.event.EventResult
Returns whether this result indicates the event was not handled.

isUnix() - Static method in class dev.tamboui.backend.panama.unix.PlatformConstants

Returns true if running on a Unix-like system (Linux or macOS).

isUp() - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this is an "up" navigation event according to the bindings.

isUserScrolledAway() - Method in class dev.tamboui.widgets.list.ListState
Returns whether the user has scrolled away from the bottom (for sticky scroll).

isValid() - Method in class dev.tamboui.widgets.form.ValidationResult
Returns whether the validation passed.

isVertical() - Method in enum class dev.tamboui.widgets.scrollbar.ScrollbarOrientation
Returns true if this orientation is vertical.

isVisible() - Method in class dev.tamboui.toolkit.elements.InlineScopeElement
Returns whether this scope is currently visible.

isVisible() - Method in class dev.tamboui.tui.overlay.DebugOverlay
Returns whether the overlay is currently visible.

isVisible(int) - Static method in class dev.tamboui.image.ImageData
Returns true if the pixel is visible (alpha > 0).

isWindows() - Static method in class dev.tamboui.backend.panama.unix.PlatformConstants
Returns true if running on Windows.

isZero() - Method in class dev.tamboui.layout.Fraction
Returns true if this fraction represents zero.

isZero() - Method in class dev.tamboui.tfx.TFxDuration
Returns true if this duration is zero.

italic() - Method in class dev.tamboui.style.Style
Enables italic text.

italic() - Method in class dev.tamboui.text.Line
Returns a new line with italic applied to all spans.

italic() - Method in class dev.tamboui.text.Span
Returns a new span with italic style.

italic() - Method in class dev.tamboui.text.Text
Returns a new text with italic style.

italic() - Method in class dev.tamboui.toolkit.element.StyledElement
Applies the italic modifier.

ITALIC - Enum constant in enum class dev.tamboui.style.Modifier
Italic text.

item(Widget, int) - Method in class dev.tamboui.layout.flow.Flow.Builder
Adds an item with the given widget and width (height defaults to 1).

item(Widget, int, int) - Method in class dev.tamboui.layout.flow.Flow.Builder
Adds an item with the given widget, width, and height.

itemRenderer(Function) - Method in class dev.tamboui.toolkit.elements.ListElement
Sets the renderer function for converting data items to styled elements.

items(ListItem...) - Method in class dev.tamboui.widgets.list.ListWidget.Builder
Sets the list items from `ListItem` instances.

items(String...) - Method in class dev.tamboui.toolkit.elements.ListElement
Sets the list items from strings.

items(String...) - Method in class dev.tamboui.widgets.list.ListWidget.Builder
Sets the list items from strings.

items(List) - Method in class dev.tamboui.layout.flow.Flow.Builder
Sets the items from a list.

items(List) - Method in class dev.tamboui.widgets.list.ListWidget.Builder
Sets the list items.

items(List) - Method in class dev.tamboui.toolkit.elements.ListElement
Sets the list items from a collection of strings.

itemStyleResolver(BiFunction) - Method in class dev.tamboui.widgets.list.ListWidget.Builder
Sets a function to resolve styles for each item based on position.

iterator() - Method in class dev.tamboui.tfx.CellIterator

ITERM2 - Enum constant in enum class dev.tamboui.image.capability.TerminalImageProtocol
iTerm2 inline images protocol.

ITermProtocol - Class in dev.tamboui.image.protocol
Renders images using the iTerm2 inline images protocol.

ITermProtocol() - Constructor for class dev.tamboui.image.protocol.ITermProtocol
Creates an iTerm2 protocol instance using BEL terminator.

ITermProtocol(boolean) - Constructor for class dev.tamboui.image.protocol.ITermProtocol
Creates an iTerm2 protocol instance.

IXON - Static variable in class dev.tamboui.backend.panama.unix.LibC
Input flag: enable XON/XOFF flow control on output.

IXON - Static variable in class dev.tamboui.backend.panama.unix.PlatformConstants
Input flag: enable XON/XOFF flow control on output.

J

JLineBackend - Class in dev.tamboui.backend.jline3
JLine 3 based backend for terminal operations.

JLineBackend() - Constructor for class dev.tamboui.backend.jline3.JLineBackend
Creates a new JLine 3 backend using the system terminal.

JLineBackendProvider - Class in dev.tamboui.backend.jline3
`BackendProvider` implementation for JLine 3.

JLineBackendProvider() - Constructor for class dev.tamboui.backend.jline3.JLineBackendProvider
Creates a new JLine 3 backend provider.

jlineTerminal() - Method in class dev.tamboui.backend.jline3.JLineBackend
Returns the underlying JLine terminal for advanced operations.

K

Kernel32 - Class in dev.tamboui.backend.panama.windows
Panama FFI bindings to Windows Kernel32 functions for console operations.

key(KeyCode) - Static method in class dev.tamboui.tui.bindings.KeyTrigger
Creates a trigger for a special key code without modifiers.

key(KeyCode, boolean, boolean, boolean) - Static method in class dev.tamboui.tui.bindings.KeyTrigger
Creates a trigger for a special key code with modifiers.

KEY_EVENT - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
Input record event type: keyboard event.

Keyboard Navigation - Section in class dev.tamboui.toolkit.elements.TreeElement

KeyCode - Enum Class in dev.tamboui.tui.event
Represents keyboard key codes for special keys.

KeyEvent - Class in dev.tamboui.tui.event
Represents a keyboard input event.

KeyEvent(KeyCode, KeyModifiers, char) - Constructor for class dev.tamboui.tui.event.KeyEvent
Creates a key event with the default bindings.

KeyEvent(KeyCode, KeyModifiers, char, Bindings) - Constructor for class dev.tamboui.tui.event.KeyEvent

Creates a key event with specific bindings.

keyEventHandler() - Method in interface dev.tamboui.toolkit.element.Element
Returns the key event handler, if any.

keyEventHandler() - Method in class dev.tamboui.toolkit.element.StyledElement

keyEventHandler() - Method in class dev.tamboui.toolkit.elements.LazyElement

KeyEventHandler - Interface in dev.tamboui.toolkit.event
Handler for key events on an element.

Key Features - Section in class dev.tamboui.toolkit.elements.InlineScopeElement

keyHandler - Variable in class dev.tamboui.toolkit.element.StyledElement
The key event handler for this element.

KeyModifiers - Class in dev.tamboui.tui.event
Represents keyboard modifier keys (Ctrl, Alt, Shift).

KeyModifiers(boolean, boolean, boolean) - Constructor for class dev.tamboui.tui.event.KeyModifiers
Creates a new KeyModifiers instance with the specified modifier flags.

KeyTrigger - Class in dev.tamboui.tui.bindings
An `InputTrigger` that matches `KeyEvent`s.

kind() - Method in class dev.tamboui.tui.event.MouseEvent
Returns the event kind.

KITTY - Enum constant in enum class dev.tamboui.image.capability.TerminalImageProtocol
Kitty Graphics Protocol - modern, high-quality image display.

KittyProtocol - Class in dev.tamboui.image.protocol
Renders images using the Kitty Graphics Protocol.

KittyProtocol() - Constructor for class dev.tamboui.image.protocol.KittyProtocol
Creates a new Kitty protocol instance.

L

label() - Method in class dev.tamboui.widgets.barchart.Bar
Returns the bar's label, if set.

label() - Method in class dev.tamboui.widgets.barchart.BarGroup
Returns the group's label, if set.

label() - Method in class dev.tamboui.widgets.tree.TreeNode
Returns the display label.

label(Line) - Method in class dev.tamboui.widgets.barchart.Bar.Builder
Sets the bar's label.

label(Line) - Method in class dev.tamboui.widgets.barchart.BarGroup.Builder
Sets the group's label.

label(Line) - Method in class dev.tamboui.widgets.gauge.Gauge.Builder
Sets the label displayed centered in the gauge.

label(Line) - Method in class dev.tamboui.widgets.gauge.LineGauge.Builder
Sets the label displayed before the gauge line.

label(Span) - Method in class dev.tamboui.widgets.gauge.Gauge.Builder
Sets the label displayed centered in the gauge.

label(Span) - Method in class dev.tamboui.widgets.gauge.LineGauge.Builder
Sets the label displayed before the gauge line.

label(String) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Sets the field label.

label(String) - Method in class dev.tamboui.toolkit.elements.GaugeElement

Sets the label displayed in the gauge.

label(String) - Method in class dev.tamboui.toolkit.elements.LineGaugeElement
Sets the label displayed before the gauge line.

label(String) - Method in class dev.tamboui.toolkit.elements.SpinnerElement
Sets the label displayed next to the spinner.

label(String) - Method in class dev.tamboui.widgets.barchart.Bar.Builder
Sets the bar's label.

label(String) - Method in class dev.tamboui.widgets.barchart.BarGroup.Builder
Sets the group's label.

label(String) - Method in class dev.tamboui.widgets.gauge.Gauge.Builder
Sets the label displayed centered in the gauge.

label(String) - Method in class dev.tamboui.widgets.gauge.LineGauge.Builder
Sets the label displayed before the gauge line.

LABEL_COLOR - Static variable in class dev.tamboui.widgets.barchart.BarChart
Property key for the bar label color.

labelColor(Color) - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Sets the bar label color programmatically.

labels() - Method in class dev.tamboui.widgets.chart.Axis
Returns the axis labels.

labels(Span...) - Method in class dev.tamboui.widgets.chart.Axis.Builder
Sets the axis labels.

labels(String...) - Method in class dev.tamboui.widgets.chart.Axis.Builder
Sets the axis labels.

labels(List) - Method in class dev.tamboui.widgets.chart.Axis.Builder
Sets the axis labels.

labelsAlignment() - Method in class dev.tamboui.widgets.chart.Axis
Returns the labels alignment.

labelsAlignment(Alignment) - Method in class dev.tamboui.widgets.chart.Axis.Builder
Sets the labels alignment.

labelStyle(Style) - Method in class dev.tamboui.toolkit.elements.BarChartElement
Sets the label style.

labelStyle(Style) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Sets the label style.

labelStyle(Style) - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Sets the label style.

labelWidth(int) - Method in class dev.tamboui.toolkit.elements.FormElement
Sets the label width for all fields.

labelWidth(int) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Sets the label width in characters.

last() - Method in class dev.tamboui.widgets.scrollbar.ScrollbarState
Scrolls to the last position.

lastBranch() - Method in enum class dev.tamboui.widgets.tree.GuideStyle
Returns the last-branch connector string.

lastFlatEntries() - Method in class dev.tamboui.widgets.tree.TreeWidget
Returns the last rendered flat entries (for external state access).

lastRenderedArea - Variable in class dev.tamboui.toolkit.element.StyledElement
The last area this element was rendered in.

lastValidation() - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Returns the last validation result.

layer() - Method in class dev.tamboui.widgets.canvas.Context
Saves the current grid as a layer and resets for subsequent drawing.

Layout - Class in dev.tamboui.layout
A layout defines how to split a rectangular area into smaller areas based on constraints.

LayoutCache - Class in dev.tamboui.layout.cassowary
Thread-local cache for layout solver results.

layoutConstraint - Variable in class dev.tamboui.toolkit.element.StyledElement
The layout constraint for this element.

LayoutException - Exception Class in dev.tamboui.layout
Exception for layout related errors.

LayoutException(String) - Constructor for exception class dev.tamboui.layout.LayoutException
Creates a new layout exception with the given message.

LayoutException(String, Throwable) - Constructor for exception class dev.tamboui.layout.LayoutException
Creates a new layout exception with the given message and cause.

LayoutSolver - Class in dev.tamboui.layout.cassowary
Bridge between TamboUI layout constraints and the Cassowary solver.

LayoutSolver() - Constructor for class dev.tamboui.layout.cassowary.LayoutSolver
Creates a new layout solver.

lazy(Supplier) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a lazy element that evaluates the supplier on each render.

LazyElement - Class in dev.tamboui.toolkit.elements
An element that lazily evaluates its content on each render.

LazyElement(Supplier) - Constructor for class dev.tamboui.toolkit.elements.LazyElement
Creates a new lazy element with the given supplier.

LE - Enum constant in enum class dev.tamboui.layout.cassowary.Relation
Less than or equal constraint: the expression must be <= 0.

leaf() - Method in class dev.tamboui.widgets.tree.TreeNode
Marks this node as a leaf (cannot have children).

leafIndicator(String) - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Sets the indicator for leaf nodes.

leaveAlternateScreen() - Method in class dev.tamboui.backend.aesh.AeshBackend

leaveAlternateScreen() - Method in class dev.tamboui.backend.jline3.JLineBackend

leaveAlternateScreen() - Method in class dev.tamboui.backend.panama.PanamaBackend

leaveAlternateScreen() - Method in class dev.tamboui.internal.record.RecordingBackend

leaveAlternateScreen() - Method in interface dev.tamboui.terminal.Backend
Leaves the alternate screen buffer.

left() - Method in class dev.tamboui.layout.Margin
Returns the left margin.

left() - Method in class dev.tamboui.layout.Padding
Returns the left padding.

left() - Method in class dev.tamboui.layout.Rect
Returns the left edge (same as `Rect.x()`).

left() - Method in class dev.tamboui.text.Line
Returns a new line with left alignment.

left() - Method in class dev.tamboui.text.Text
Returns a new text with left alignment.

left() - Method in class dev.tamboui.widgets.block.Title

Returns a new left-aligned title.

left() - Method in class dev.tamboui.widgets.paragraph.Paragraph.Builder
Sets left alignment.

left(Element) - Method in class dev.tamboui.toolkit.elements.DockElement
Sets the left region element.

left(Element, Constraint) - Method in class dev.tamboui.toolkit.elements.DockElement
Sets the left region element with a width constraint.

left(Widget) - Method in class dev.tamboui.layout.dock.Dock.Builder
Sets the left region widget.

LEFT - Enum constant in enum class dev.tamboui.layout.Alignment
Left-aligned.

LEFT - Enum constant in enum class dev.tamboui.tui.event.KeyCode
Left arrow key.

LEFT - Enum constant in enum class dev.tamboui.tui.event.MouseButton
Left mouse button (button 1).

LEFT - Enum constant in enum class dev.tamboui.widgets.block.Borders
Left border.

LEFT - Enum constant in enum class dev.tamboui.widgets.chart.LegendPosition
Left side, vertically centered

LEFT_INDICATOR - Static variable in class dev.tamboui.widgets.select.Select
CSS property for the left navigation indicator.

LEFT_ONLY - Static variable in enum class dev.tamboui.widgets.block.Borders
Left border only.

LEFT_TO_RIGHT - Enum constant in enum class dev.tamboui.tfx.Motion
Movement from left to right

LEFT_TO_RIGHT - Enum constant in enum class dev.tamboui.widgets.sparkline.Sparkline.RenderDirection
Render data from left to right (default).

leftIndicator() - Method in class dev.tamboui.widgets.select.Select
Returns the left navigation indicator.

leftIndicator(String) - Method in class dev.tamboui.widgets.select.Select.Builder
Sets the left navigation indicator.

leftToRight(float) - Static method in class dev.tamboui.tfx.pattern.SweepPattern
Creates a left-to-right sweep pattern.

leftVertical() - Method in class dev.tamboui.widgets.block.BorderSet
Returns the left vertical border character.

leftVertical(String) - Method in class dev.tamboui.widgets.block.BorderSet.Builder
Sets the left vertical border character.

leftWidth(Constraint) - Method in class dev.tamboui.layout.dock.Dock.Builder
Sets the width constraint for the left region.

leftWidth(Constraint) - Method in class dev.tamboui.toolkit.elements.DockElement
Sets the width constraint for the left region.

legendPosition(LegendPosition) - Method in class dev.tamboui.toolkit.elements.ChartElement
Sets the legend position.

legendPosition(LegendPosition) - Method in class dev.tamboui.widgets.chart.Chart.Builder
Sets the legend position.

LegendPosition - Enum Class in dev.tamboui.widgets.chart
Position of the legend in a `Chart`.

length() - Method in class dev.tamboui.backend.panama.ByteArrayBuilder
Returns the current length of valid data in the buffer.

length() - Method in class dev.tamboui.widgets.input.TextInputState
Returns the text length.

length(int) - Static method in interface dev.tamboui.layout.Constraint
Creates a fixed length constraint.

length(int) - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the constraint to an exact length.

length(int) - Method in class dev.tamboui.toolkit.elements.DialogElement
Sets a fixed height for the dialog.

length(int) - Static method in class dev.tamboui.toolkit.elements.Spacer
Creates a spacer with a fixed length.

length(int) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a length constraint.

Length(int) - Constructor for class dev.tamboui.layout.Constraint.Length
Creates a fixed length constraint.

lerp(Color, Color, float) - Method in enum class dev.tamboui.tfx.TFxColorSpace
Interpolates between two colors using the specified color space.

lessThanOrEqual(long, Strength) - Method in class dev.tamboui.layout.cassowary.Expression
Creates a less-than-or-equal constraint: this <= value.

lessThanOrEqual(Expression, Strength) - Method in class dev.tamboui.layout.cassowary.Expression
Creates a less-than-or-equal constraint: this <= other.

lessThanOrEqual(Fraction, Strength) - Method in class dev.tamboui.layout.cassowary.Expression
Creates a less-than-or-equal constraint: this <= value.

LibC - Class in dev.tamboui.backend.panama.unix
Panama FFI bindings to libc functions for terminal operations.

LIGHT_BLUE - Static variable in interface dev.tamboui.style.Color
Light blue.

LIGHT_CYAN - Static variable in interface dev.tamboui.style.Color
Light cyan.

LIGHT_DOUBLE_DASHED - Enum constant in enum class dev.tamboui.widgets.block.BorderType
Light double-dashed border.

LIGHT_GREEN - Static variable in interface dev.tamboui.style.Color
Light green.

LIGHT_MAGENTA - Static variable in interface dev.tamboui.style.Color
Light magenta.

LIGHT_QUADRUPLE_DASHED - Enum constant in enum class dev.tamboui.widgets.block.BorderType
Light quadruple-dashed border.

LIGHT_RED - Static variable in interface dev.tamboui.style.Color
Light red.

LIGHT_TRIPLE_DASHED - Enum constant in enum class dev.tamboui.widgets.block.BorderType
Light triple-dashed border.

LIGHT_YELLOW - Static variable in interface dev.tamboui.style.Color
Light yellow.

Limitations - Section in class dev.tamboui.toolkit.elements.GenericWidgetElement

line() - Method in class dev.tamboui.css.parser.Token.Position
Returns the 1-based line number.

Line - Class in dev.tamboui.text
A single line of text composed of styled spans.

Line - Class in dev.tamboui.widgets.canvas.shapes

A line segment between two points.

Line(double, double, double, double, Color) - Constructor for class dev.tamboui.widgets.canvas.shapes.Line
Creates a line segment between two points.

Line(List, Alignment) - Constructor for class dev.tamboui.text.Line
Creates a new line with the given spans and alignment.

LINE - Enum constant in enum class dev.tamboui.widgets.chart.GraphType
Connects data points with lines.

LINE - Enum constant in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Classic line spinner: `-\|/`.

LINE_NUMBER_COLOR - Static variable in class dev.tamboui.widgets.input.TextArea
Property key for the line number gutter color.

Linear - Enum constant in enum class dev.tamboui.tfx.Interpolation
Linear interpolation (no easing)

lineCount() - Method in class dev.tamboui.widgets.error.ErrorDisplay
Returns the total number of content lines.

lineCount() - Method in class dev.tamboui.widgets.input.TextAreaState
Returns the number of lines.

lineGauge() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty line gauge.

lineGauge(double) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a line gauge with the given ratio (0.0-1.0).

lineGauge(int) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a line gauge with the given percentage (0-100).

LineGauge - Class in dev.tamboui.widgets.gauge
A progress indicator that renders as a horizontal line.

LineGauge.Builder - Class in dev.tamboui.widgets.gauge
Builder for `LineGauge`.

LineGauge.LineSet - Class in dev.tamboui.widgets.gauge
Defines the characters used for filled and unfilled portions of the line gauge.

LineGaugeElement - Class in dev.tamboui.toolkit.elements
A DSL wrapper for the LineGauge widget.

LineGaugeElement() - Constructor for class dev.tamboui.toolkit.elements.LineGaugeElement
Creates a line gauge with zero progress.

LineGaugeElement(double) - Constructor for class dev.tamboui.toolkit.elements.LineGaugeElement
Creates a line gauge with the given progress ratio.

LineGaugeElement(int) - Constructor for class dev.tamboui.toolkit.elements.LineGaugeElement
Creates a line gauge with the given progress percentage.

lineNumberColor(Color) - Method in class dev.tamboui.widgets.input.TextArea.Builder
Sets the line number gutter color programmatically.

lineNumberSeparator(String) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Sets the separator between line numbers and content.

lineNumberSeparator(String) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Sets the separator between line numbers and content.

lineNumberStyle(Style) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Sets the line number style.

lineNumberStyle(Style) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Sets the line number style.

lineNumberStyle(Style) - Method in class dev.tamboui.toolkit.elements.TextAreaElement
Sets the line number style.

lineNumberStyle(Style) - Method in class dev.tamboui.widgets.input.TextArea.Builder
Sets the line number style.

lines() - Method in class dev.tamboui.text.Text
Returns the lines of this text.

lineSet(LineGauge.LineSet) - Method in class dev.tamboui.toolkit.elements.LineGaugeElement
Sets the line character set.

lineSet(LineGauge.LineSet) - Method in class dev.tamboui.widgets.gauge.LineGauge.Builder
Sets the line character set to use.

LineSet(String, String) - Constructor for class dev.tamboui.widgets.gauge.LineGauge.LineSet
Creates a new line set with the given characters.

list() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty list.

list(StyledElement...) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a list with styled element items.

list(String...) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a list with the given items.

list(List) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a list with the given items.

listCopyOf() - Static method in class dev.tamboui.util.CollectionUtil
Returns an empty unmodifiable list.

listCopyOf(Collection) - Static method in class dev.tamboui.util.CollectionUtil
Returns an unmodifiable list copied from the given collection.

listCopyOf(T...) - Static method in class dev.tamboui.util.CollectionUtil
Returns an unmodifiable list containing the given elements.

ListElement<T> - Class in dev.tamboui.toolkit.elements
A scrollable container that displays a list of selectable items.

ListElement() - Constructor for class dev.tamboui.toolkit.elements.ListElement
Creates an empty list element.

ListElement(StyledElement...) - Constructor for class dev.tamboui.toolkit.elements.ListElement
Creates a list container with styled element items.

ListElement(String...) - Constructor for class dev.tamboui.toolkit.elements.ListElement
Creates a list element with the given string items.

ListElement(List) - Constructor for class dev.tamboui.toolkit.elements.ListElement
Creates a list element with the given string items.

ListItem - Class in dev.tamboui.widgets.list
An item in a list widget.

ListItem(Text, Style) - Constructor for class dev.tamboui.widgets.list.ListItem
Creates a new list item with the given content and style.

ListState - Class in dev.tamboui.widgets.list
State for a List widget, tracking selection and scroll offset.

ListState() - Constructor for class dev.tamboui.widgets.list.ListState
Creates a new list state with no selection.

ListWidget - Class in dev.tamboui.widgets.list
A list widget for displaying selectable items using `SizedWidget`.

ListWidget.Builder - Class in dev.tamboui.widgets.list
Builder for `ListWidget`.

load() - Static method in class dev.tamboui.internal.record.RecordingConfig
Loads recording configuration from system properties and installs capture.

load(InputStream) - Static method in class dev.tamboui.tui.bindings.BindingSets

Loads bindings from an input stream containing properties.

load(InputStream, Bindings) - Static method in class dev.tamboui.tui.bindings.BindingSets
Loads bindings from an input stream, starting with the given base bindings.

load(Class) - Static method in class dev.tamboui.util.SafeServiceLoader
Loads providers for the given service, skipping broken providers and continuing to try other providers.

load(Class, Consumer) - Static method in class dev.tamboui.util.SafeServiceLoader
Loads providers for the given service, skipping broken providers and continuing to try other providers.

load(Path) - Static method in class dev.tamboui.tui.bindings.BindingSets
Loads bindings from a properties file.

loadResource(String) - Static method in class dev.tamboui.tui.bindings.BindingSets
Loads bindings from a classpath resource.

loadResource(String, ClassLoader) - Static method in class dev.tamboui.tui.bindings.BindingSets
Loads bindings from a classpath resource using the specified class loader.

loadStylesheet(String) - Method in class dev.tamboui.css.engine.StyleEngine
Loads a stylesheet from the classpath.

loadStylesheet(String, String) - Method in class dev.tamboui.css.engine.StyleEngine
Loads a named stylesheet from the classpath.

loadStylesheet(String, Path) - Method in class dev.tamboui.css.engine.StyleEngine
Loads a named stylesheet from a file path.

loadStylesheet(Path) - Method in class dev.tamboui.css.engine.StyleEngine
Loads a stylesheet from a file path.

locale(Locale) - Method in class dev.tamboui.widgets.calendar.Monthly.Builder
Sets the locale.

logAndQuit(PrintStream) - Static method in class dev.tamboui.tui.error.RenderErrorHandlers
Returns a handler that logs the error to a stream and quits immediately.

Logo - Class in dev.tamboui.widgets.logo
A widget that renders the Tamboui logo.

Logo.Size - Enum Class in dev.tamboui.widgets.logo
The size of the logo.

loop() - Method in class dev.tamboui.tfx.Effect
Creates a new Effect that loops continuously from the beginning.

LOOP - Enum constant in enum class dev.tamboui.tfx.LoopMode
Restart from beginning when done.

LOOP - Enum constant in enum class dev.tamboui.widgets.wavetext.WaveText.Mode
Wave loops continuously in one direction.

loopMode() - Method in class dev.tamboui.tfx.EffectTimer
Returns the current loop mode.

loopMode(LoopMode) - Method in class dev.tamboui.tfx.EffectTimer
Sets the loop mode for this timer.

LoopMode - Enum Class in dev.tamboui.tfx
Defines how an effect should behave when it reaches its end.

M

magenta() - Method in class dev.tamboui.style.Style
Shorthand for `Style.fg(Color)` with `Color.MAGENTA`.

magenta() - Method in class dev.tamboui.text.Span
Returns a new span with magenta foreground color.

magenta() - Method in class dev.tamboui.toolkit.element.StyledElement

Sets the foreground color to magenta.

MAGENTA - Enum constant in enum class dev.tamboui.style.AnsiColor
Magenta (palette index 5).

MAGENTA - Static variable in interface dev.tamboui.style.Color
Magenta.

main(String[]) - Static method in class dev.tamboui.capability.Capabilities
Prints the capability report to standard output.

main(String[]) - Static method in class dev.tamboui.Main
Main entry point that prints diagnostic information.

Main - Class in dev.tamboui
Main entry point for the TamboUI core jar.

mapAlpha(float, int, int, Rect) - Method in class dev.tamboui.tfx.pattern.IdentityPattern

mapAlpha(float, int, int, Rect) - Method in interface dev.tamboui.tfx.pattern.Pattern
Maps a global alpha value to a position-specific alpha value using primitive coordinates.

mapAlpha(float, Position, Rect) - Method in class dev.tamboui.tfx.pattern.DiagonalPattern

mapAlpha(float, Position, Rect) - Method in class dev.tamboui.tfx.pattern.IdentityPattern

mapAlpha(float, Position, Rect) - Method in interface dev.tamboui.tfx.pattern.Pattern
Maps a global alpha value to a position-specific alpha value.

mapAlpha(float, Position, Rect) - Method in class dev.tamboui.tfx.pattern.RadialPattern

mapAlpha(float, Position, Rect) - Method in class dev.tamboui.tfx.pattern.SweepPattern

mapCopyOf() - Static method in class dev.tamboui.util.CollectionUtil
Returns an empty unmodifiable map.

mapCopyOf(Map) - Static method in class dev.tamboui.util.CollectionUtil
Returns an unmodifiable map copied from the given map.

mapCopyOf(K, V) - Static method in class dev.tamboui.util.CollectionUtil
Returns an unmodifiable singleton map.

mapRadial(float, float, float) - Method in class dev.tamboui.tfx.pattern.TransitionProgress
Maps radial patterns where smaller distances (closer to center) should be more active.

mapSpatial(float, float, float) - Method in class dev.tamboui.tfx.pattern.TransitionProgress
Maps spatial patterns where positions vary along a continuous dimension.

mapThreshold(float, float) - Method in class dev.tamboui.tfx.pattern.TransitionProgress
Maps discrete threshold patterns where cells have distinct activation thresholds.

margin() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the margin, if set.

margin() - Method in class dev.tamboui.layout.Layout
Returns the outer margin.

margin(int) - Method in class dev.tamboui.layout.Layout
Sets a uniform outer margin.

margin(int) - Method in class dev.tamboui.toolkit.elements.Column
Sets uniform margin around the column.

margin(int) - Method in class dev.tamboui.toolkit.elements.ColumnsElement
Sets uniform margin around the columns layout.

margin(int) - Method in class dev.tamboui.toolkit.elements.DockElement
Sets uniform margin around the dock layout.

margin(int) - Method in class dev.tamboui.toolkit.elements.FlowElement
Sets uniform margin around the flow layout.

margin(int) - Method in class dev.tamboui.toolkit.elements.GridElement
Sets uniform margin around the grid layout.

margin(int) - Method in class dev.tamboui.toolkit.elements.Panel
Sets uniform margin around the panel.

margin(int) - Method in class dev.tamboui.toolkit.elements.Row
Sets uniform margin around the row.

margin(int) - Method in class dev.tamboui.toolkit.elements.StackElement
Sets uniform margin around the stack layout.

margin(Margin) - Method in class dev.tamboui.css.cascade.CssStyleResolver.Builder
Sets the margin.

margin(Margin) - Method in class dev.tamboui.layout.Layout
Sets the outer margin.

margin(Margin) - Method in class dev.tamboui.toolkit.elements.Column
Sets the margin around the column.

margin(Margin) - Method in class dev.tamboui.toolkit.elements.ColumnsElement
Sets the margin around the columns layout.

margin(Margin) - Method in class dev.tamboui.toolkit.elements.DockElement
Sets the margin around the dock layout.

margin(Margin) - Method in class dev.tamboui.toolkit.elements.FlowElement
Sets the margin around the flow layout.

margin(Margin) - Method in class dev.tamboui.toolkit.elements.GridElement
Sets the margin around the grid layout.

margin(Margin) - Method in class dev.tamboui.toolkit.elements.Panel
Sets the margin around the panel.

margin(Margin) - Method in class dev.tamboui.toolkit.elements.Row
Sets the margin around the row.

margin(Margin) - Method in class dev.tamboui.toolkit.elements.StackElement
Sets the margin around the stack layout.

Margin - Class in dev.tamboui.layout
Margin values for top, right, bottom, and left sides.

Margin(int, int, int, int) - Constructor for class dev.tamboui.layout.Margin
Creates a margin.

MARGIN - Static variable in class dev.tamboui.style.StandardProperties
The `margin` property for outer spacing.

MarginConverter - Class in dev.tamboui.css.property
Converts CSS margin values to Margin objects.

MarginConverter - Class in dev.tamboui.layout
Converts string values to `Margin` objects.

markAsInherited(String) - Method in class dev.tamboui.css.cascade.CssStyleResolver.Builder
Marks a property as using the "inherit" keyword.

marker() - Method in class dev.tamboui.widgets.chart.Dataset
Returns the marker type.

marker(Marker) - Method in class dev.tamboui.toolkit.elements.CanvasElement
Sets the marker type for rendering points.

marker(Marker) - Method in class dev.tamboui.widgets.canvas.Canvas.Builder
Sets the marker type for rendering points.

marker(Dataset.Marker) - Method in class dev.tamboui.widgets.chart.Dataset.Builder
Sets the marker type for data points.

Marker - Enum Class in dev.tamboui.widgets.canvas

Marker types for rendering points on a `Canvas`.

markup() - Method in class dev.tamboui.toolkit.elements.MarkupTextElement
Returns the current markup content.

markup(String) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Sets the markup content.

markup(String) - Method in class dev.tamboui.toolkit.elements.MarkupTextElement
Sets the markup content.

MarkupParser - Class in dev.tamboui.text
Parses BBCode-style markup text and converts it to styled `Text` objects.

MarkupParser.EmojiResolver - Interface in dev.tamboui.text
Functional interface for resolving string expansion of emoji codes/names.

MarkupParser.StyleResolver - Interface in dev.tamboui.text
Functional interface for resolving custom tag styles.

markupText() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty inline markup text element.

markupText(String) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a simple inline markup text element that parses BBCode-style markup.

markupTextArea() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty scrollable markup text area.

markupTextArea(String) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a scrollable markup text area that parses BBCode-style markup.

MarkupTextAreaElement - Class in dev.tamboui.toolkit.elements
A toolkit element that parses BBCode-style markup and displays styled text.

MarkupTextAreaElement() - Constructor for class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Creates a MarkupTextAreaElement with empty content.

MarkupTextAreaElement(String) - Constructor for class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Creates a MarkupTextAreaElement with the given markup content.

MarkupTextElement - Class in dev.tamboui.toolkit.elements
A simple inline element that parses BBCode-style markup and displays styled text.

MarkupTextElement() - Constructor for class dev.tamboui.toolkit.elements.MarkupTextElement
Creates an empty markup text element.

MarkupTextElement(String) - Constructor for class dev.tamboui.toolkit.elements.MarkupTextElement
Creates a markup text element with the specified content.

markUserScrolledAway() - Method in class dev.tamboui.widgets.list.ListState
Marks that the user has scrolled away from the bottom.

maskChar() - Method in class dev.tamboui.text.Masked
Returns the character used for masking.

masked() - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Masks the input text with the default mask character ('*').

masked() - Method in class dev.tamboui.widgets.input.TextInput.Builder
Masks the input text with the default mask character ('*').

masked(char) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Masks the input text with the specified character.

masked(char) - Method in class dev.tamboui.widgets.input.TextInput.Builder
Masks the input text with the specified character.

Masked - Class in dev.tamboui.text
A wrapper around a string that is masked when displayed.

Masked(String, char) - Constructor for class dev.tamboui.text.Masked
Creates a new masked string.

maskedField(String) - Method in class dev.tamboui.widgets.form.FormState.Builder
Adds a masked text field (e.g., for passwords) with an empty initial value.

maskedField(String, String) - Method in class dev.tamboui.widgets.form.FormState.Builder
Adds a masked text field (e.g., for passwords) with the given initial value.

matches(int, int, Cell, Rect) - Method in class dev.tamboui.tfx.CellFilter
Checks if a cell matches this filter using primitive coordinates.

matches(Styleable, PseudoClassStateProvider, List) - Method in class dev.tamboui.css.selector.ChildSelector

matches(Styleable, PseudoClassStateProvider, List) - Method in class dev.tamboui.css.selector.DescendantSelector

matches(Styleable, PseudoClassStateProvider, List) - Method in interface dev.tamboui.css.selector.Selector
Tests whether this selector matches the given element, using a state provider for dynamic pseudo-class resolution.

matches(Styleable, PseudoClassState, List) - Method in class dev.tamboui.css.selector.AttributeSelector

matches(Styleable, PseudoClassState, List) - Method in class dev.tamboui.css.selector.ChildSelector

matches(Styleable, PseudoClassState, List) - Method in class dev.tamboui.css.selector.ClassSelector

matches(Styleable, PseudoClassState, List) - Method in class dev.tamboui.css.selector.CompoundSelector

matches(Styleable, PseudoClassState, List) - Method in class dev.tamboui.css.selector.DescendantSelector

matches(Styleable, PseudoClassState, List) - Method in class dev.tamboui.css.selector.IdSelector

matches(Styleable, PseudoClassState, List) - Method in class dev.tamboui.css.selector.PseudoClassSelector

matches(Styleable, PseudoClassState, List) - Method in interface dev.tamboui.css.selector.Selector
Tests whether this selector matches the given element.

matches(Styleable, PseudoClassState, List) - Method in class dev.tamboui.css.selector.TypeSelector

matches(Styleable, PseudoClassState, List) - Method in class dev.tamboui.css.selector.UniversalSelector

matches(Position, Cell, Rect) - Method in class dev.tamboui.tfx.CellFilter
Checks if a cell matches this filter.

matches(Event) - Method in interface dev.tamboui.tui.bindings.InputTrigger
Returns true if this trigger matches the given event.

matches(Event) - Method in class dev.tamboui.tui.bindings.KeyTrigger

matches(Event) - Method in class dev.tamboui.tui.bindings.MouseTrigger

matches(Event, String) - Method in interface dev.tamboui.tui.bindings.Bindings
Returns true if the event matches the given action.

matches(Event, String) - Method in class dev.tamboui.tui.bindings.DefaultBindings

matches(String) - Method in class dev.tamboui.tui.event.KeyEvent
Returns true if this event matches the given action in the configured bindings.

matches(String) - Method in class dev.tamboui.tui.event.MouseEvent
Returns true if this event matches the given action in the configured bindings.

matchesKey(KeyEvent) - Method in class dev.tamboui.tui.bindings.KeyTrigger
Returns true if this trigger matches the given key event.

matchesMouse(MouseEvent) - Method in class dev.tamboui.tui.bindings.MouseTrigger
Returns true if this trigger matches the given mouse event.

max() - Method in class dev.tamboui.widgets.chart.Axis

Returns the maximum bound.

max(int) - Static method in interface dev.tamboui.layout.Constraint
Creates a maximum size constraint.

max(int) - Method in class dev.tamboui.toolkit.element.StyledElement
Sets a maximum size constraint.

max(int) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a maximum constraint.

max(long) - Method in class dev.tamboui.toolkit.elements.BarChartElement
Sets the maximum value for scaling.

max(long) - Method in class dev.tamboui.toolkit.elements.SparklineElement
Sets the maximum value for scaling.

max(long) - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Sets the maximum value for scaling.

max(long) - Method in class dev.tamboui.widgets.sparkline.Sparkline.Builder
Sets the maximum value for scaling.

Max(int) - Constructor for class dev.tamboui.layout.Constraint.Max
Creates a maximum size constraint.

maxDurationMs() - Method in class dev.tamboui.internal.record.RecordingConfig
Returns the maximum recording duration in milliseconds.

maxFrameWidth() - Method in class dev.tamboui.widgets.spinner.Spinner
Returns the maximum display width across all frames.

maxLength(int) - Static method in class dev.tamboui.widgets.form.Validators
Creates a validator that requires a maximum length.

maxLength(int, String) - Static method in class dev.tamboui.widgets.form.Validators
Creates a validator that requires a maximum length with a custom message.

maxScrollCol() - Method in class dev.tamboui.style.RichTextState
Returns the maximum scroll column position.

maxScrollRow() - Method in class dev.tamboui.style.RichTextState
Returns the maximum scroll row position.

maxValue() - Method in class dev.tamboui.widgets.barchart.BarGroup
Returns the maximum value among all bars in this group.

medium() - Method in class dev.tamboui.layout.cassowary.Strength
Returns the medium weight component.

MEDIUM - Static variable in class dev.tamboui.layout.cassowary.Strength
Medium preference - moderate priority.

merge(Buffer, int, int) - Method in class dev.tamboui.buffer.Buffer
Merges another buffer into this one at the specified position.

merge(Stylesheet) - Method in class dev.tamboui.css.model.Stylesheet
Merges another stylesheet into this one.

merge(String, String) - Method in enum class dev.tamboui.symbols.merge.MergeStrategy
Merges two symbols using this merge strategy.

mergeBorders(MergeStrategy) - Method in class dev.tamboui.widgets.block.Block.Builder
Sets the merge strategy for borders.

MergeStrategy - Enum Class in dev.tamboui.symbols.merge
A strategy for merging two border symbols into one.

mergeSymbol(String, MergeStrategy) - Method in class dev.tamboui.buffer.Cell
Merges this cell's symbol with another symbol using the given merge strategy.

message() - Method in class dev.tamboui.tui.error.RenderError
Returns the error message from the cause, or the class name if no message.

MIDDLE - Enum constant in enum class dev.tamboui.text.CharWidth.TruncatePosition
Truncate in middle: "Hel...rld"

MIDDLE - Enum constant in enum class dev.tamboui.tui.event.MouseButton
Middle mouse button (button 2, scroll wheel click).

middleClick() - Static method in class dev.tamboui.tui.bindings.MouseTrigger
Creates a trigger for middle mouse button click (press).

min() - Method in class dev.tamboui.widgets.chart.Axis
Returns the minimum bound.

min(int) - Static method in interface dev.tamboui.layout.Constraint
Creates a minimum size constraint.

min(int) - Method in class dev.tamboui.toolkit.element.StyledElement
Sets a minimum size constraint.

min(int) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a minimum constraint.

Min(int) - Constructor for class dev.tamboui.layout.Constraint.Min
Creates a minimum size constraint.

minLength(int) - Static method in class dev.tamboui.widgets.form.Validators
Creates a validator that requires a minimum length.

minLength(int, String) - Static method in class dev.tamboui.widgets.form.Validators
Creates a validator that requires a minimum length with a custom message.

minus(long) - Method in class dev.tamboui.layout.cassowary.Expression
Subtracts a constant from this expression.

minus(Expression) - Method in class dev.tamboui.layout.cassowary.Expression
Subtracts another expression from this one.

minus(Variable) - Method in class dev.tamboui.layout.cassowary.Expression
Subtracts a variable from this expression.

minus(Fraction) - Method in class dev.tamboui.layout.cassowary.Expression
Subtracts a constant from this expression.

minWidth() - Method in class dev.tamboui.widgets.select.Select
Returns the minimum width (indicators only, no value).

minWidth(int) - Method in class dev.tamboui.toolkit.elements.DialogElement
Sets the minimum width for the dialog.

mirrored() - Method in class dev.tamboui.tfx.EffectTimer
Returns a mirrored timer that runs in reverse direction with flipped interpolation.

mode(WaveText.Mode) - Method in class dev.tamboui.toolkit.elements.WaveTextElement
Sets the animation mode.

mode(WaveText.Mode) - Method in class dev.tamboui.widgets.wavetext.WaveText.Builder
Sets the animation mode.

Mode2027Status - Enum Class in dev.tamboui.terminal
Represents the status of Mode 2027 (grapheme cluster mode) support in a terminal.

Mode2027Support - Class in dev.tamboui.terminal
Utility class for Mode 2027 (grapheme cluster mode) terminal support.

model(TreeModel) - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Sets the tree model for data access.

Modifier - Enum Class in dev.tamboui.style
Text style modifiers (SGR attributes).

ModifierConverter - Class in dev.tamboui.css.property
Converts CSS text-style values to TamboUI Modifier sets.

ModifierConverter - Class in dev.tamboui.style

Converts string values to sets of `Modifier` values.

modifiers() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the text modifiers.

modifiers() - Method in class dev.tamboui.tui.event.KeyEvent
Returns the modifier state.

modifiers() - Method in class dev.tamboui.tui.event.MouseEvent
Returns active keyboard modifiers.

monthHeaderStyle(Style) - Method in class dev.tamboui.widgets.calendar.Monthly.Builder
Shows the month header with the given style.

Monthly - Class in dev.tamboui.widgets.calendar
A calendar widget displaying a single month.

Monthly.Builder - Class in dev.tamboui.widgets.calendar
Builder for `Monthly`.

MOON - Enum constant in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Moon phases spinner.

Motion - Enum Class in dev.tamboui.tfx
Specifies the direction of movement for directional visual effects.

MouseButton - Enum Class in dev.tamboui.tui.event
Represents mouse buttons.

mouseCapture() - Method in class dev.tamboui.tui.TuiConfig
Returns whether mouse capture is enabled.

mouseCapture(boolean) - Method in class dev.tamboui.tui.TuiConfig.Builder
Sets whether to capture mouse events.

mouseCapture(boolean) - Method in class dev.tamboui.tui.TuiRunner.Builder
Sets whether to capture mouse events.

MouseEvent - Class in dev.tamboui.tui.event
Represents a mouse input event.

MouseEvent(MouseEventKind, MouseButton, int, int, KeyModifiers) - Constructor for class dev.tamboui.tui.event.MouseEvent
Creates a mouse event with the default bindings.

MouseEvent(MouseEventKind, MouseButton, int, int, KeyModifiers, Bindings) - Constructor for class dev.tamboui.tui.event.MouseEvent
Creates a mouse event with specific bindings.

mouseEventHandler() - Method in interface dev.tamboui.toolkit.element.Element
Returns the mouse event handler, if any.

mouseEventHandler() - Method in class dev.tamboui.toolkit.element.StyledElement

mouseEventHandler() - Method in class dev.tamboui.toolkit.elements.LazyElement

MouseEventHandler - Interface in dev.tamboui.toolkit.event
Handler for mouse events on an element.

MouseEventKind - Enum Class in dev.tamboui.tui.event
Represents the kind of mouse event.

mouseHandler - Variable in class dev.tamboui.toolkit.element.StyledElement
The mouse event handler for this element.

MouseTrigger - Class in dev.tamboui.tui.bindings
An `InputTrigger` that matches `MouseEvent`s.

move(int, int) - Static method in class dev.tamboui.tui.event.MouseEvent
Creates a mouse move event.

MOVE - Enum constant in enum class dev.tamboui.tui.event.MouseEventKind

Mouse was moved without any button pressed.

MOVE_DOWN - Static variable in class dev.tamboui.tui.bindings.Actions
Move down (arrow down, vim 'j', emacs Ctrl+n, etc.).

MOVE_LEFT - Static variable in class dev.tamboui.tui.bindings.Actions
Move left (arrow left, vim 'h', emacs Ctrl+b, etc.).

MOVE_RIGHT - Static variable in class dev.tamboui.tui.bindings.Actions
Move right (arrow right, vim 'l', emacs Ctrl+f, etc.).

MOVE_UP - Static variable in class dev.tamboui.tui.bindings.Actions
Move up (arrow up, vim 'k', emacs Ctrl+p, etc.).

moveCursorDown() - Method in class dev.tamboui.widgets.input.TextAreaState
Moves the cursor one row down.

moveCursorDown(int) - Method in class dev.tamboui.backend.aesh.AeshBackend

moveCursorDown(int) - Method in class dev.tamboui.backend.jline3.JLineBackend

moveCursorDown(int) - Method in class dev.tamboui.backend.panama.PanamaBackend

moveCursorDown(int) - Method in interface dev.tamboui.terminal.Backend
Moves the cursor down by N lines.

moveCursorLeft() - Method in class dev.tamboui.widgets.input.TextAreaState
Moves the cursor one position to the left.

moveCursorLeft() - Method in class dev.tamboui.widgets.input.TextInputState
Moves the cursor one position to the left.

moveCursorLeft(int) - Method in class dev.tamboui.backend.aesh.AeshBackend

moveCursorLeft(int) - Method in class dev.tamboui.backend.jline3.JLineBackend

moveCursorLeft(int) - Method in class dev.tamboui.backend.panama.PanamaBackend

moveCursorLeft(int) - Method in interface dev.tamboui.terminal.Backend
Moves the cursor left by N columns.

moveCursorRight() - Method in class dev.tamboui.widgets.input.TextAreaState
Moves the cursor one position to the right.

moveCursorRight() - Method in class dev.tamboui.widgets.input.TextInputState
Moves the cursor one position to the right.

moveCursorRight(int) - Method in class dev.tamboui.backend.aesh.AeshBackend

moveCursorRight(int) - Method in class dev.tamboui.backend.jline3.JLineBackend

moveCursorRight(int) - Method in class dev.tamboui.backend.panama.PanamaBackend

moveCursorRight(int) - Method in interface dev.tamboui.terminal.Backend
Moves the cursor right by N columns.

moveCursorToEnd() - Method in class dev.tamboui.widgets.input.TextAreaState
Moves the cursor to the very end of the text.

moveCursorToEnd() - Method in class dev.tamboui.widgets.input.TextInputState
Moves the cursor to the end.

moveCursorToLineEnd() - Method in class dev.tamboui.widgets.input.TextAreaState
Moves the cursor to the end of the current line.

moveCursorToLineStart() - Method in class dev.tamboui.widgets.input.TextAreaState
Moves the cursor to the start of the current line.

moveCursorToStart() - Method in class dev.tamboui.widgets.input.TextAreaState
Moves the cursor to the very beginning of the text.

moveCursorToStart() - Method in class dev.tamboui.widgets.input.TextInputState
Moves the cursor to the start.

moveCursorUp() - Method in class dev.tamboui.widgets.input.TextAreaState
Moves the cursor one row up.

moveCursorUp(int) - Method in class dev.tamboui.backend.aesh.AeshBackend

moveCursorUp(int) - Method in class dev.tamboui.backend.jline3.JLineBackend

moveCursorUp(int) - Method in class dev.tamboui.backend.panama.PanamaBackend

moveCursorUp(int) - Method in interface dev.tamboui.terminal.Backend
Moves the cursor up by N lines.

mul(float) - Method in class dev.tamboui.tfx.TFxDuration
Multiplies this duration by a float scalar.

mul(long) - Method in class dev.tamboui.tfx.TFxDuration
Multiplies this duration by a scalar.

multiply(Fraction) - Method in class dev.tamboui.layout.Fraction
Returns the product of this fraction and another.

mutableTimer() - Method in class dev.tamboui.tfx.effects.DissolveShader

mutableTimer() - Method in class dev.tamboui.tfx.effects.ExpandShader

mutableTimer() - Method in class dev.tamboui.tfx.effects.FadeShader

mutableTimer() - Method in class dev.tamboui.tfx.effects.PaintShader

mutableTimer() - Method in class dev.tamboui.tfx.effects.ParallelEffect

mutableTimer() - Method in class dev.tamboui.tfx.effects.SequentialEffect

mutableTimer() - Method in class dev.tamboui.tfx.effects.SlideShader

mutableTimer() - Method in class dev.tamboui.tfx.effects.StretchShader

mutableTimer() - Method in class dev.tamboui.tfx.effects.SweepShader

mutableTimer() - Method in interface dev.tamboui.tfx.Shader
Returns a mutable timer if available, or null if none.

mutate(int, int, CellIterator.MutableCell) - Method in interface dev.tamboui.tfx.CellIterator.CellMutator
Processes and optionally mutates a cell.

N

name() - Method in class dev.tamboui.backend.aesh.AeshBackendProvider

name() - Method in class dev.tamboui.backend.jline3.JLineBackendProvider

name() - Method in class dev.tamboui.css.parser.Token.Variable
Returns the variable name (without the leading $).

name() - Method in class dev.tamboui.image.protocol.BrailleProtocol

name() - Method in class dev.tamboui.image.protocol.HalfBlockProtocol

name() - Method in interface dev.tamboui.image.protocol.ImageProtocol
Returns a human-readable name for this protocol.

name() - Method in class dev.tamboui.image.protocol.ITermProtocol

name() - Method in class dev.tamboui.image.protocol.KittyProtocol

name() - Method in class dev.tamboui.image.protocol.SixelProtocol

name() - Method in class dev.tamboui.layout.cassowary.Variable
Returns the name of this variable.

name() - Method in class dev.tamboui.style.Color.Named
Returns the CSS class name for this color.

name() - Method in class dev.tamboui.style.PropertyDefinition
Returns the property name.

name() - Method in interface dev.tamboui.terminal.BackendProvider
Returns a simple identifier for this backend provider.

name() - Method in class dev.tamboui.tfx.Effect
Returns the name of the underlying shader.

name() - Method in class dev.tamboui.tfx.effects.DissolveShader

name() - Method in class dev.tamboui.tfx.effects.ExpandShader

name() - Method in class dev.tamboui.tfx.effects.FadeShader

name() - Method in class dev.tamboui.tfx.effects.PaintShader

name() - Method in class dev.tamboui.tfx.effects.ParallelEffect

name() - Method in class dev.tamboui.tfx.effects.SequentialEffect

name() - Method in class dev.tamboui.tfx.effects.SlideShader

name() - Method in class dev.tamboui.tfx.effects.StretchShader

name() - Method in class dev.tamboui.tfx.effects.SweepShader

name() - Method in class dev.tamboui.tfx.pattern.DiagonalPattern

name() - Method in class dev.tamboui.tfx.pattern.IdentityPattern

name() - Method in interface dev.tamboui.tfx.pattern.Pattern
Returns the name of this pattern.

name() - Method in class dev.tamboui.tfx.pattern.RadialPattern

name() - Method in class dev.tamboui.tfx.pattern.SweepPattern

name() - Method in interface dev.tamboui.tfx.Shader
Returns the name of this shader.

name() - Method in class dev.tamboui.widgets.chart.Dataset
Returns the dataset name.

name(Line) - Method in class dev.tamboui.widgets.chart.Dataset.Builder
Sets the dataset name.

name(String) - Method in class dev.tamboui.widgets.chart.Dataset.Builder
Sets the dataset name (for legend).

NAME_BACKGROUND - Static variable in class dev.tamboui.style.StandardProperties
Property name for background color.

NAME_BACKGROUND_COLOR - Static variable in class dev.tamboui.style.StandardProperties
Property name for background color (alias).

NAME_COLOR - Static variable in class dev.tamboui.style.StandardProperties
Property name for foreground/text color.

NAME_DIRECTION - Static variable in class dev.tamboui.style.StandardProperties

Property name for layout direction.

NAME_FLEX - Static variable in class dev.tamboui.style.StandardProperties
Property name for flex layout mode.

NAME_HEIGHT - Static variable in class dev.tamboui.style.StandardProperties
Property name for element height constraint.

NAME_MARGIN - Static variable in class dev.tamboui.style.StandardProperties
Property name for outer spacing.

NAME_PADDING - Static variable in class dev.tamboui.style.StandardProperties
Property name for inner spacing.

NAME_SPACING - Static variable in class dev.tamboui.style.StandardProperties
Property name for gap between elements.

NAME_TEXT_ALIGN - Static variable in class dev.tamboui.style.StandardProperties
Property name for text alignment.

NAME_TEXT_STYLE - Static variable in class dev.tamboui.style.StandardProperties
Property name for text modifiers (bold, italic, etc.).

NAME_WIDTH - Static variable in class dev.tamboui.style.StandardProperties
Property name for element width constraint.

Named(String, Color) - Constructor for class dev.tamboui.style.Color.Named
Creates a named color.

NEG_ONE - Static variable in class dev.tamboui.layout.Fraction
The fraction representing negative one (-1/1).

negate() - Method in class dev.tamboui.layout.cassowary.Expression
Negates this expression.

negate() - Method in class dev.tamboui.layout.cassowary.Term
Returns a new term with the coefficient negated.

negate() - Method in class dev.tamboui.layout.Fraction
Returns the negation of this fraction.

NEVER - Enum constant in enum class dev.tamboui.widgets.table.Table.HighlightSpacing
Never allocate space for the highlight symbol.

newId(Element) - Static method in class dev.tamboui.toolkit.id.IdGenerator
Generates a new unique ID for the given element using the default instance.

newPattern(float, float) - Static method in class dev.tamboui.tfx.pattern.RadialPattern
Creates a radial pattern with custom center point (0.0-1.0 normalized coordinates).

newPattern(DiagonalPattern.DiagonalDirection, float) - Static method in class dev.tamboui.tfx.pattern.DiagonalPattern
Creates a diagonal pattern with specified direction and transition width.

next() - Method in class dev.tamboui.tfx.DirectionalVariance
Generates the next variance value.

next() - Method in class dev.tamboui.widgets.scrollbar.ScrollbarState
Scrolls down by one position.

nextXY() - Method in class dev.tamboui.tfx.DirectionalVariance
Generates the next variance value as separate x and y components.

NINE_LEVELS - Static variable in class dev.tamboui.widgets.barchart.BarChart.BarSet
Nine-level vertical bar set.

NINE_LEVELS - Static variable in class dev.tamboui.widgets.sparkline.Sparkline.BarSet
Nine-level bar set with fine-grained fill levels.

node() - Method in class dev.tamboui.widgets.tree.TreeWidget.FlatEntry
Returns the node data.

nodeRenderer(Function) - Method in class dev.tamboui.toolkit.elements.TreeElement

Sets a custom renderer for tree nodes.

nodeRenderer(Function) - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Sets the full node renderer with explicit sizing.

none() - Static method in class dev.tamboui.tfx.CellFilter
Selects no cells.

NONE - Enum constant in enum class dev.tamboui.image.capability.TerminalImageProtocol
No image support available.

NONE - Enum constant in enum class dev.tamboui.image.ImageScaling
Do not scale the image.

NONE - Enum constant in enum class dev.tamboui.tui.event.MouseButton
No button (for move events).

NONE - Enum constant in enum class dev.tamboui.widgets.block.BorderType
No border - renders nothing but still reserves space if borders are enabled.

NONE - Enum constant in enum class dev.tamboui.widgets.common.ScrollBarPolicy
Never show the scrollbar.

NONE - Enum constant in enum class dev.tamboui.widgets.list.ScrollMode
No automatic scrolling.

NONE - Enum constant in enum class dev.tamboui.widgets.tree.GuideStyle
No guide characters.

NONE - Static variable in class dev.tamboui.css.cascade.PseudoClassState
Empty state with all flags set to false.

NONE - Static variable in class dev.tamboui.layout.Margin
A margin with zero on all sides.

NONE - Static variable in class dev.tamboui.layout.Padding
A padding with zero on all sides.

NONE - Static variable in class dev.tamboui.tui.event.KeyModifiers
No modifiers pressed.

NONE - Static variable in enum class dev.tamboui.widgets.block.Borders
No borders.

noneOf(List) - Static method in class dev.tamboui.tfx.CellFilter
Selects cells that match NONE of the given filters (logical NOR).

Non-inheritable properties: - Section in class dev.tamboui.style.StandardProperties

noop() - Static method in interface dev.tamboui.style.StyledAreaRegistry
Returns a no-op registry that ignores all registrations.

NORMAL - Enum constant in enum class dev.tamboui.style.Modifier
Normal (default) text style.

NORMAL - Enum constant in enum class dev.tamboui.widgets.logo.Logo.Size
A normal logo (4 lines).

NORMAL - Static variable in class dev.tamboui.widgets.gauge.LineGauge
Line character set using thin lines.

not(CellFilter) - Static method in class dev.tamboui.tfx.CellFilter
Inverts the result of the given filter (logical NOT).

NOT_SUPPORTED - Enum constant in enum class dev.tamboui.terminal.Mode2027Status
Terminal doesn't recognize Mode 2027.

notBold() - Method in class dev.tamboui.style.Style
Disables bold text.

notCrossedOut() - Method in class dev.tamboui.style.Style
Disables strikethrough.

notDim() - Method in class dev.tamboui.style.Style
Disables dim text.

Notes - Section in class dev.tamboui.export.html.HtmlExporter

Notes - Section in class dev.tamboui.export.svg.SvgExporter

Notes - Section in class dev.tamboui.export.text.TextExporter

notHidden() - Method in class dev.tamboui.style.Style
Unhides text.

noTick() - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner.Builder
Disables tick events.

noTick() - Method in class dev.tamboui.tui.InlineTuiConfig.Builder
Disables tick events.

noTick() - Method in class dev.tamboui.tui.TuiConfig.Builder
Disables automatic tick events.

noTick() - Method in class dev.tamboui.tui.TuiRunner.Builder
Disables automatic tick events.

notItalic() - Method in class dev.tamboui.style.Style
Disables italic text.

notReversed() - Method in class dev.tamboui.style.Style
Disables reverse video.

notUnderlined() - Method in class dev.tamboui.style.Style
Disables underline.

nthChild() - Method in class dev.tamboui.css.cascade.PseudoClassState
Returns the 1-based child position, or 0 if not set.

nthChild() - Method in class dev.tamboui.toolkit.element.ChildPosition
Returns the 1-based position (CSS nth-child uses 1-based counting).

Number(String, boolean, Token.Position) - Constructor for class dev.tamboui.css.parser.Token.Number
Creates a number token.

numerator() - Method in class dev.tamboui.layout.Constraint.Ratio
Returns the numerator.

numerator() - Method in class dev.tamboui.layout.Fraction
Returns the numerator of this fraction.

O

O_NOCTTY - Static variable in class dev.tamboui.backend.panama.unix.LibC
Open flag to not make the opened file the controlling terminal.

O_RDWR - Static variable in class dev.tamboui.backend.panama.unix.LibC
Open flag for read/write access.

of(boolean, boolean, boolean) - Static method in class dev.tamboui.tui.event.KeyModifiers
Creates modifiers with the specified flags.

of(double[][]) - Static method in class dev.tamboui.widgets.chart.Dataset
Creates a dataset with just data points.

of(double[][], Color) - Static method in class dev.tamboui.widgets.canvas.shapes.Points
Creates a points shape from coordinate pairs and a color.

of(double[], double[], Color) - Static method in class dev.tamboui.widgets.canvas.shapes.Points
Creates a points shape from x and y arrays.

of(double, double, double, double, Color) - Static method in class dev.tamboui.widgets.canvas.shapes.Line
Creates a line from (x1, y1) to (x2, y2) with the given color.

of(double, double, double, double, Color) - Static method in class dev.tamboui.widgets.canvas.shapes.Rectangle
Creates a rectangle at (x, y) with the given dimensions and color.

of(double, double, double, Color) - Static method in class dev.tamboui.widgets.canvas.shapes.Circle
Creates a circle centered at (x, y) with the given radius and color.

of(int) - Static method in class dev.tamboui.text.CharWidth
Returns the display width (0, 1, or 2) of a Unicode code point.

of(int, int) - Static method in class dev.tamboui.layout.Rect
Creates a rectangle at origin with the given size.

of(int, int) - Static method in class dev.tamboui.toolkit.element.ChildPosition
Creates a ChildPosition for the given index within a collection of the given size.

of(int, int) - Static method in class dev.tamboui.toolkit.element.Size
Creates a size with the given dimensions.

of(int, int) - Static method in class dev.tamboui.toolkit.elements.GridSize
Creates a grid size with explicit columns and rows.

of(int, int) - Static method in class dev.tamboui.toolkit.elements.Gutter
Creates a gutter with different horizontal and vertical spacing.

of(int, int) - Static method in class dev.tamboui.tui.event.ResizeEvent
Creates a resize event with the given dimensions.

of(long) - Static method in class dev.tamboui.layout.Fraction
Creates a fraction from an integer value.

of(long) - Static method in class dev.tamboui.widgets.barchart.Bar
Creates a bar with the given value.

of(long...) - Static method in class dev.tamboui.widgets.barchart.BarGroup
Creates a group from bar values.

of(long, long) - Static method in class dev.tamboui.layout.Fraction
Creates a fraction from a numerator and denominator.

of(long, String) - Static method in class dev.tamboui.widgets.barchart.Bar
Creates a bar with the given value and label.

of(long, Duration) - Static method in class dev.tamboui.tui.event.TickEvent
Creates a tick event with the given frame count and elapsed time.

of(ImageData) - Static method in class dev.tamboui.image.Image
Creates an image widget from the given image data.

of(Position, Size) - Static method in class dev.tamboui.layout.Rect
Creates a rectangle from a position and size.

of(Effect...) - Static method in class dev.tamboui.tfx.effects.ParallelEffect
Creates a parallel effect that runs the given effects simultaneously.

of(Effect...) - Static method in class dev.tamboui.tfx.effects.SequentialEffect
Creates a sequential effect that runs the given effects one after another.

of(Shader) - Static method in class dev.tamboui.tfx.Effect
Creates a new Effect with the specified shader.

of(TFxDuration) - Static method in class dev.tamboui.tfx.EffectTimer
Creates a new EffectTimer with the specified duration and Linear interpolation.

of(TFxDuration, Interpolation) - Static method in class dev.tamboui.tfx.EffectTimer
Creates a new EffectTimer with the specified duration and interpolation.

of(MouseEventKind, MouseButton, boolean, boolean, boolean) - Static method in class dev.tamboui.tui.bindings.MouseTrigger
Creates a mouse trigger with all parameters specified.

of(Widget) - Static method in class dev.tamboui.widgets.common.SizedWidget

Creates a SizedWidget with default width (fill) and height (1).

of(Widget, int) - Static method in class dev.tamboui.layout.flow.FlowItem
Creates a flow item with the given widget and width (height defaults to 1).

of(Widget, int, int) - Static method in class dev.tamboui.layout.flow.FlowItem
Creates a flow item with the given widget, width, and height.

of(Widget, int, int) - Static method in class dev.tamboui.widgets.common.SizedWidget
Creates a SizedWidget with explicit width and height.

of(Bar...) - Static method in class dev.tamboui.widgets.barchart.BarGroup
Creates a group from bars.

of(Dataset...) - Static method in class dev.tamboui.widgets.chart.Chart
Creates a chart with the given datasets.

of(Logo.Size) - Static method in class dev.tamboui.widgets.logo.Logo
Create a new Tamboui logo widget.

of(String) - Static method in class dev.tamboui.css.model.PropertyValue
Creates a regular (non-important) property value.

of(String) - Static method in class dev.tamboui.style.Hyperlink
Creates a hyperlink with just a URL.

of(String) - Static method in class dev.tamboui.style.Tags
Creates a Tags instance with a single tag.

of(String) - Static method in class dev.tamboui.text.CharWidth
Returns the total display width of a string.

of(String) - Static method in class dev.tamboui.tui.event.ActionEvent
Creates an action event for the given action name with no context.

of(String) - Static method in class dev.tamboui.widgets.tree.TreeNode
Creates a tree node with the given label.

of(String...) - Static method in class dev.tamboui.style.Tags
Creates a Tags instance with multiple tags.

of(String...) - Static method in class dev.tamboui.widgets.spinner.SpinnerFrameSet
Creates a frame set from the given frames.

of(String, double[][]) - Static method in class dev.tamboui.widgets.chart.Dataset
Creates a named dataset with data points.

of(String, Color) - Static method in class dev.tamboui.widgets.wavetext.WaveText
Creates a simple wave text with default settings.

of(String, PropertyConverter) - Static method in class dev.tamboui.style.PropertyDefinition
Creates a new property definition with the given name and converter.

of(String, Bar...) - Static method in class dev.tamboui.widgets.barchart.BarGroup
Creates a group from bars with a label.

of(String, TreeNode...) - Static method in class dev.tamboui.widgets.tree.TreeNode
Creates a tree node with the given label and children.

of(String, String) - Static method in class dev.tamboui.style.Hyperlink
Creates a hyperlink with a URL and an ID.

of(String, String) - Static method in class dev.tamboui.widgets.scrollbar.Scrollbar.SymbolSet
Creates a symbol set without begin/end markers.

of(String, String, String, String) - Static method in class dev.tamboui.widgets.scrollbar.Scrollbar.SymbolSet
Creates a symbol set with all components.

of(String, T) - Static method in class dev.tamboui.tui.event.ActionEvent
Creates an action event for the given action name and context.

of(String, T) - Static method in class dev.tamboui.widgets.tree.TreeNode
Creates a tree node with the given label and data.

of(Path, int, int, int, int) - Static method in class dev.tamboui.internal.record.RecordingConfig
Creates a config with explicit values (used by TuiRunner for config file support).

of(LocalDate, DateStyler) - Static method in class dev.tamboui.widgets.calendar.Monthly
Creates a calendar for the month containing the given date.

of(LocalDate, DateStyler, Locale) - Static method in class dev.tamboui.widgets.calendar.Monthly
Creates a calendar for the month containing the given date using custom locale.

of(List) - Static method in class dev.tamboui.tfx.effects.ParallelEffect
Creates a parallel effect that runs the given effects simultaneously.

of(List) - Static method in class dev.tamboui.tfx.effects.SequentialEffect
Creates a sequential effect that runs the given effects one after another.

of(List) - Static method in class dev.tamboui.widgets.spinner.SpinnerFrameSet
Creates a frame set from a list of frames.

of(Set) - Static method in class dev.tamboui.style.Tags
Creates a Tags instance from a set of tags.

of(T) - Static method in class dev.tamboui.toolkit.elements.GenericWidgetElement
Creates a new GenericWidgetElement wrapping the given widget.

ofChar(char) - Static method in class dev.tamboui.tui.event.KeyEvent
Creates a key event for a printable character with the default bindings.

ofChar(char, Bindings) - Static method in class dev.tamboui.tui.event.KeyEvent
Creates a key event for a printable character with specific bindings.

ofChar(char, KeyModifiers) - Static method in class dev.tamboui.tui.event.KeyEvent
Creates a key event for a printable character with modifiers and the default bindings.

ofChar(char, KeyModifiers, Bindings) - Static method in class dev.tamboui.tui.event.KeyEvent
Creates a key event for a printable character with modifiers and specific bindings.

ofCurrentMonth() - Static method in class dev.tamboui.widgets.calendar.Monthly
Creates a calendar for the current month with no special styling.

ofCurrentMonth(Locale) - Static method in class dev.tamboui.widgets.calendar.Monthly
Creates a calendar for the current month with custom locale and no special styling.

ofDefault() - Static method in class dev.tamboui.widgets.logo.Logo
Returns the default Tamboui logo (tiny size).

ofDisabled() - Static method in class dev.tamboui.css.cascade.PseudoClassState
Returns a state with only the disabled flag set.

off(String) - Method in class dev.tamboui.tui.bindings.ActionHandler
Removes all handlers for the specified action.

OFF_COLOR - Static variable in class dev.tamboui.widgets.toggle.Toggle
CSS property for the off state foreground color.

OFF_SYMBOL - Static variable in class dev.tamboui.widgets.toggle.Toggle
CSS property for the off symbol (single mode).

offColor(Color) - Method in class dev.tamboui.widgets.toggle.Toggle.Builder
Sets the foreground color when off.

offLabel(String) - Method in class dev.tamboui.widgets.toggle.Toggle.Builder
Sets the label for the "off" option (inline choice mode).

ofFocused() - Static method in class dev.tamboui.css.cascade.PseudoClassState
Returns a state with only the focused flag set.

offset() - Method in class dev.tamboui.widgets.list.ListState
Returns the scroll offset.

offset() - Method in class dev.tamboui.widgets.table.TableState
Returns the scroll offset.

offset() - Method in class dev.tamboui.widgets.tree.TreeState

Returns the scroll offset in rows.

offset(int) - Method in class dev.tamboui.widgets.tree.TreeState
Sets the scroll offset.

offset(int, int) - Method in class dev.tamboui.layout.Position
Returns a new position offset from this one.

offSymbol() - Method in class dev.tamboui.widgets.toggle.Toggle
Returns the symbol used for off state (single mode).

offSymbol(String) - Method in class dev.tamboui.widgets.toggle.Toggle.Builder
Sets the symbol to display when off (single mode).

ofHeight(Widget, int) - Static method in class dev.tamboui.widgets.common.SizedWidget
Creates a SizedWidget with explicit height, default width (fill).

ofHovered() - Static method in class dev.tamboui.css.cascade.PseudoClassState
Returns a state with only the hovered flag set.

ofKey(KeyCode) - Static method in class dev.tamboui.tui.event.KeyEvent
Creates a key event for a special key with the default bindings.

ofKey(KeyCode, Bindings) - Static method in class dev.tamboui.tui.event.KeyEvent
Creates a key event for a special key with specific bindings.

ofKey(KeyCode, KeyModifiers) - Static method in class dev.tamboui.tui.event.KeyEvent
Creates a key event for a special key with modifiers and the default bindings.

ofKey(KeyCode, KeyModifiers, Bindings) - Static method in class dev.tamboui.tui.event.KeyEvent
Creates a key event for a special key with modifiers and specific bindings.

ofSelected() - Static method in class dev.tamboui.css.cascade.PseudoClassState
Returns a state with only the selected flag set.

ofWidth(Widget, int) - Static method in class dev.tamboui.widgets.common.SizedWidget
Creates a SizedWidget with explicit width, default height (1).

on(InputTrigger, Consumer) - Method in class dev.tamboui.toolkit.element.StyledElement
Binds an input trigger directly to a handler on this element.

on(String, BiConsumer) - Method in class dev.tamboui.tui.bindings.ActionHandler
Registers a handler for the specified action that also receives the action name.

on(String, Consumer) - Method in class dev.tamboui.tui.bindings.ActionHandler
Registers a handler for the specified action.

ON_COLOR - Static variable in class dev.tamboui.widgets.toggle.Toggle
CSS property for the on state foreground color.

ON_SYMBOL - Static variable in class dev.tamboui.widgets.toggle.Toggle
CSS property for the on symbol (single mode).

onAction(ActionHandler) - Method in class dev.tamboui.toolkit.element.StyledElement
Sets an action handler for this element.

OnAction - Annotation Interface in dev.tamboui.annotations.bindings
Marks a method as an action handler for the specified action.

OnActionProcessor - Class in dev.tamboui.tui.bindings.processor
Annotation processor for `OnAction` annotations.

OnActionProcessor() - Constructor for class dev.tamboui.tui.bindings.processor.OnActionProcessor
Creates a new OnAction annotation processor.

onBlack() - Method in class dev.tamboui.style.Style
Shorthand for `Style.bg(Color)` with `Color.BLACK`.

onBlack() - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the background color to black.

onBlue() - Method in class dev.tamboui.style.Style
Shorthand for `Style.bg(Color)` with `Color.BLUE`.

onBlue() - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the background color to blue.

onCancel(Runnable) - Method in class dev.tamboui.toolkit.elements.DialogElement
Sets the callback to run when the dialog is cancelled (Escape key).

ONCE - Enum constant in enum class dev.tamboui.tfx.LoopMode
Run once and complete (default behavior).

onColor(Color) - Method in class dev.tamboui.widgets.toggle.Toggle.Builder
Sets the foreground color when on.

onConfirm(Runnable) - Method in class dev.tamboui.toolkit.elements.DialogElement
Sets the callback to run when the dialog is confirmed (Enter key).

onCyan() - Method in class dev.tamboui.style.Style
Shorthand for `Style.bg(Color)` with `Color.CYAN`.

onCyan() - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the background color to cyan.

onDrag(int, int, int, int) - Method in interface dev.tamboui.toolkit.event.DragHandler
Called during a drag operation with the current position.

onDrag(DragHandler) - Method in class dev.tamboui.toolkit.element.StyledElement
Makes this element draggable with the given handler.

onDragEnd(int, int) - Method in interface dev.tamboui.toolkit.event.DragHandler
Called when a drag operation ends.

onDragStart(int, int) - Method in interface dev.tamboui.toolkit.event.DragHandler
Called when a drag operation starts.

ONE - Static variable in class dev.tamboui.layout.Fraction
The fraction representing one (1/1).

oneEighth() - Method in class dev.tamboui.widgets.barchart.BarChart.BarSet
Returns the one-eighth fill symbol.

oneEighth() - Method in class dev.tamboui.widgets.sparkline.Sparkline.BarSet
Returns the one-eighth fill symbol.

oneQuarter() - Method in class dev.tamboui.widgets.barchart.BarChart.BarSet
Returns the one-quarter fill symbol.

oneQuarter() - Method in class dev.tamboui.widgets.sparkline.Sparkline.BarSet
Returns the one-quarter fill symbol.

onGreen() - Method in class dev.tamboui.style.Style
Shorthand for `Style.bg(Color)` with `Color.GREEN`.

onGreen() - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the background color to green.

onKeyEvent(KeyEventHandler) - Method in class dev.tamboui.toolkit.element.StyledElement
Sets a key event handler for this element.

onLabel(String) - Method in class dev.tamboui.widgets.toggle.Toggle.Builder
Sets the label for the "on" option (inline choice mode).

onMagenta() - Method in class dev.tamboui.style.Style
Shorthand for `Style.bg(Color)` with `Color.MAGENTA`.

onMagenta() - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the background color to magenta.

onMouseEvent(MouseEventHandler) - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the mouse event handler for this element.

onRed() - Method in class dev.tamboui.style.Style
Shorthand for `Style.bg(Color)` with `Color.RED`.

onRed() - Method in class dev.tamboui.toolkit.element.StyledElement

Sets the background color to red.

onResize(Runnable) - Method in class dev.tamboui.backend.aesh.AeshBackend

onResize(Runnable) - Method in class dev.tamboui.backend.jline3.JLineBackend

onResize(Runnable) - Method in class dev.tamboui.backend.panama.PanamaBackend

onResize(Runnable) - Method in interface dev.tamboui.backend.panama.PlatformTerminal
Registers a handler to be called when the terminal is resized.

onResize(Runnable) - Method in class dev.tamboui.backend.panama.unix.UnixTerminal
Registers a handler to be called when the terminal is resized.

onResize(Runnable) - Method in class dev.tamboui.backend.panama.windows.WindowsTerminal

onResize(Runnable) - Method in class dev.tamboui.internal.record.RecordingBackend

onResize(Runnable) - Method in interface dev.tamboui.terminal.Backend
Registers a handler to be called when the terminal is resized.

onStart() - Method in class dev.tamboui.toolkit.app.InlineApp
Called when the application starts, before the first render.

onStart() - Method in class dev.tamboui.toolkit.app.ToolkitApp
Called when the application starts, before the first render.

onStop() - Method in class dev.tamboui.toolkit.app.InlineApp
Called when the application is about to stop.

onStop() - Method in class dev.tamboui.toolkit.app.ToolkitApp
Called when the application is about to stop.

onStyleChange() - Method in interface dev.tamboui.css.engine.StyleEngine.StyleChangeListener
Called when the active stylesheet changes.

onSubmit(Runnable) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Sets a callback to be invoked when Enter is pressed.

onSubmit(Runnable) - Method in class dev.tamboui.toolkit.elements.TextInputElement
Sets a callback to be invoked when Enter is pressed.

onSubmit(Consumer) - Method in class dev.tamboui.toolkit.elements.FormElement
Sets the callback to invoke when the form is submitted.

onSymbol() - Method in class dev.tamboui.widgets.toggle.Toggle
Returns the symbol used for on state (single mode).

onSymbol(String) - Method in class dev.tamboui.widgets.toggle.Toggle.Builder
Sets the symbol to display when on (single mode).

onTextChange(TextAreaElement.TextChangeListener) - Method in class dev.tamboui.toolkit.elements.TextAreaElement
Sets a listener for text changes.

onTextChange(String) - Method in interface dev.tamboui.toolkit.elements.TextAreaElement.TextChangeListener
Called when the text content changes.

onWhite() - Method in class dev.tamboui.style.Style
Shorthand for `Style.bg(Color)` with `Color.WHITE`.

onWhite() - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the background color to white.

onYellow() - Method in class dev.tamboui.style.Style
Shorthand for `Style.bg(Color)` with `Color.YELLOW`.

onYellow() - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the background color to yellow.

open(String, int) - Static method in class dev.tamboui.backend.panama.unix.LibC

Opens a file.

OpenBrace(Token.Position) - Constructor for class dev.tamboui.css.parser.Token.OpenBrace
Creates an opening brace token.

OpenBracket(Token.Position) - Constructor for class dev.tamboui.css.parser.Token.OpenBracket
Creates an opening bracket token.

OpenParen(Token.Position) - Constructor for class dev.tamboui.css.parser.Token.OpenParen
Creates an opening parenthesis token.

operator() - Method in class dev.tamboui.css.selector.AttributeSelector
Returns the matching operator.

OPOST - Static variable in class dev.tamboui.backend.panama.unix.LibC
Output flag: enable implementation-defined output processing.

OPOST - Static variable in class dev.tamboui.backend.panama.unix.PlatformConstants
Output flag: enable implementation-defined output processing.

optionCount() - Method in class dev.tamboui.widgets.select.SelectState
Returns the number of options.

options() - Method in class dev.tamboui.widgets.form.SelectFieldState
Returns the list of available options.

options() - Method in class dev.tamboui.widgets.select.SelectState
Returns the list of available options.

options(Consumer) - Method in class dev.tamboui.export.ExportStep
Applies the given consumer to the format options (e.g.

or(EventResult) - Method in enum class dev.tamboui.toolkit.event.EventResult
Combines two results, returning HANDLED if either is HANDLED.

order(ColumnOrder) - Method in class dev.tamboui.layout.columns.Columns.Builder
Sets the ordering mode for children in the grid.

order(ColumnOrder) - Method in class dev.tamboui.toolkit.elements.ColumnsElement
Sets the ordering mode for children in the grid.

orientation() - Method in class dev.tamboui.widgets.scrollbar.Scrollbar
Returns the orientation of this scrollbar.

orientation(ScrollbarOrientation) - Method in class dev.tamboui.toolkit.elements.ScrollbarElement
Sets the orientation.

orientation(ScrollbarOrientation) - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.Builder
Sets the scrollbar orientation.

ORIGIN - Static variable in class dev.tamboui.layout.Position
The origin position at (0, 0).

original() - Method in class dev.tamboui.text.Masked
Returns the original (unmasked) text.

oscillate() - Method in class dev.tamboui.toolkit.elements.WaveTextElement
Sets the wave to oscillate back and forth.

oscillate() - Method in class dev.tamboui.widgets.wavetext.WaveText.Builder
Sets the wave to oscillate back and forth.

OSCILLATE - Enum constant in enum class dev.tamboui.widgets.wavetext.WaveText.Mode
Wave oscillates back and forth.

outer(Margin) - Static method in class dev.tamboui.tfx.CellFilter
Selects cells outside the inner margin of the area (border region).

outputPath() - Method in class dev.tamboui.internal.record.RecordingConfig
Returns the output file path.

overflow() - Method in class dev.tamboui.widgets.block.Title
Returns the overflow mode.

overflow(Overflow) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Sets the overflow mode.

overflow(Overflow) - Method in class dev.tamboui.toolkit.elements.MarkupTextElement
Sets the overflow mode.

overflow(Overflow) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Sets the overflow mode.

overflow(Overflow) - Method in class dev.tamboui.toolkit.elements.RichTextElement
Sets the overflow mode for text that doesn't fit.

overflow(Overflow) - Method in class dev.tamboui.toolkit.elements.TextElement
Sets the overflow mode for text that doesn't fit.

overflow(Overflow) - Method in class dev.tamboui.widgets.block.Title
Returns a new title with the given overflow mode.

overflow(Overflow) - Method in class dev.tamboui.widgets.paragraph.Paragraph.Builder
Sets the overflow mode.

Overflow - Enum Class in dev.tamboui.style
Text overflow handling mode.

OverflowConverter - Class in dev.tamboui.style
Converts string values to `Overflow` enum values.

overlap(int) - Static method in class dev.tamboui.layout.Spacing
Creates overlap with a fixed number of overlapping cells.

P

padding() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the padding, if set.

padding(int) - Method in class dev.tamboui.toolkit.elements.DialogElement
Sets the padding around content for width calculation.

padding(int) - Method in class dev.tamboui.toolkit.elements.Panel
Sets uniform padding inside the panel.

padding(int) - Method in class dev.tamboui.widgets.block.Block.Builder
Sets uniform padding on all sides.

padding(Padding) - Method in class dev.tamboui.css.cascade.CssStyleResolver.Builder
Sets the padding.

padding(Padding) - Method in class dev.tamboui.toolkit.elements.Panel
Sets the padding inside the panel.

padding(Padding) - Method in class dev.tamboui.widgets.block.Block.Builder
Sets the block padding.

padding(String, String) - Method in class dev.tamboui.toolkit.elements.TabsElement
Sets the padding around tab titles.

padding(String, String) - Method in class dev.tamboui.widgets.tabs.Tabs.Builder
Sets the padding on both sides of each tab title.

Padding - Class in dev.tamboui.layout
Padding inside a block.

Padding(int, int, int, int) - Constructor for class dev.tamboui.layout.Padding
Creates a padding with the given values.

PADDING - Static variable in class dev.tamboui.style.StandardProperties
The `padding` property for inner spacing.

PaddingConverter - Class in dev.tamboui.layout
Converts string values to `Padding` objects.

paddingLeft(String) - Method in class dev.tamboui.widgets.tabs.Tabs.Builder

Sets the left padding for each tab title.

paddingRight(String) - Method in class dev.tamboui.widgets.tabs.Tabs.Builder
Sets the right padding for each tab title.

PAGE_DOWN - Enum constant in enum class dev.tamboui.tui.event.KeyCode
Page Down key.

PAGE_DOWN - Static variable in class dev.tamboui.tui.bindings.Actions
Page down (PageDown, vim Ctrl+d, emacs Ctrl+v, etc.).

PAGE_UP - Enum constant in enum class dev.tamboui.tui.event.KeyCode
Page Up key.

PAGE_UP - Static variable in class dev.tamboui.tui.bindings.Actions
Page up (PageUp, vim Ctrl+u, emacs Alt+v, etc.).

pageDown() - Method in class dev.tamboui.style.RichTextState
Scrolls down by one page (viewport height - 1).

pageDown() - Method in class dev.tamboui.widgets.scrollbar.ScrollbarState
Scrolls down by a page (viewport length).

pageUp() - Method in class dev.tamboui.style.RichTextState
Scrolls up by one page (viewport height - 1).

pageUp() - Method in class dev.tamboui.widgets.scrollbar.ScrollbarState
Scrolls up by a page (viewport length).

paint(int, int, Color) - Method in class dev.tamboui.widgets.canvas.Painter
Paints a colored point at the specified grid coordinates.

paint(Color, Color, long, Interpolation) - Static method in class dev.tamboui.tfx.Fx
Creates a paint effect that applies foreground and/or background colors.

paint(Color, Color, EffectTimer) - Static method in class dev.tamboui.tfx.effects.PaintShader
Creates a paint shader that paints foreground and/or background colors.

paint(Color, Color, EffectTimer) - Static method in class dev.tamboui.tfx.Fx
Creates a paint effect that applies foreground and/or background colors.

paint(Consumer) - Method in class dev.tamboui.toolkit.elements.CanvasElement
Sets the paint callback for drawing shapes.

paint(Consumer) - Method in class dev.tamboui.widgets.canvas.Canvas.Builder
Sets the paint callback for drawing shapes.

paintBg(Color, long, Interpolation) - Static method in class dev.tamboui.tfx.Fx
Creates a paint effect that applies only the background color.

paintBg(Color, EffectTimer) - Static method in class dev.tamboui.tfx.effects.PaintShader
Creates a paint shader that paints only background color.

paintBg(Color, EffectTimer) - Static method in class dev.tamboui.tfx.Fx
Creates a paint effect that applies only the background color.

Painter - Class in dev.tamboui.widgets.canvas
Provides an interface for drawing on a `Canvas` grid.

Painter(Context) - Constructor for class dev.tamboui.widgets.canvas.Painter
Creates a painter that draws on the given context.

Painter.GridPoint - Class in dev.tamboui.widgets.canvas
A point in grid space (integer coordinates).

paintFg(Color, long, Interpolation) - Static method in class dev.tamboui.tfx.Fx
Creates a paint effect that applies only the foreground color.

paintFg(Color, EffectTimer) - Static method in class dev.tamboui.tfx.effects.PaintShader
Creates a paint shader that paints only foreground color.

paintFg(Color, EffectTimer) - Static method in class dev.tamboui.tfx.Fx
Creates a paint effect that applies only the foreground color.

PaintShader - Class in dev.tamboui.tfx.effects
A paint effect that immediately applies colors to cells.

PanamaBackend - Class in dev.tamboui.backend.panama
Terminal backend implementation using Panama FFI.

PanamaBackend() - Constructor for class dev.tamboui.backend.panama.PanamaBackend
Creates a new Panama backend.

PanamaBackendProvider - Class in dev.tamboui.backend.panama
`BackendProvider` implementation for Panama FFI backend.

PanamaBackendProvider() - Constructor for class dev.tamboui.backend.panama.PanamaBackendProvider
Creates a new Panama backend provider.

panel() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty panel.

panel(Element...) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a panel without a title.

panel(String, Element...) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a panel with a title and children.

panel(String, Supplier) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a panel with a title and lazy content.

panel(Supplier) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a panel with lazy content (no title).

Panel - Class in dev.tamboui.toolkit.elements
A container element with borders and title.

Panel() - Constructor for class dev.tamboui.toolkit.elements.Panel
Creates an empty panel.

Panel(Element...) - Constructor for class dev.tamboui.toolkit.elements.Panel
Creates a panel with children.

Panel(String, Element...) - Constructor for class dev.tamboui.toolkit.elements.Panel
Creates a panel with a title and children.

Paragraph - Class in dev.tamboui.widgets.paragraph
A paragraph widget for displaying styled text.

Paragraph.Builder - Class in dev.tamboui.widgets.paragraph
Builder for `Paragraph`.

parallel(Effect...) - Static method in class dev.tamboui.tfx.Fx
Runs the effects in parallel, all at the same time.

parallel(List) - Static method in class dev.tamboui.tfx.Fx
Runs the effects in parallel, all at the same time.

ParallelEffect - Class in dev.tamboui.tfx.effects
Shader implementation that runs multiple effects in parallel, simultaneously.

parent() - Method in class dev.tamboui.css.selector.ChildSelector
Returns the parent selector.

parent() - Method in class dev.tamboui.toolkit.element.ElementRegistry.ElementInfo
Returns the parent element info, or null if this is a root element.

parent() - Method in class dev.tamboui.widgets.tree.TreeWidget.FlatEntry
Returns the parent node, or null for roots.

parse(String) - Static method in class dev.tamboui.css.parser.CssParser
Parses CSS input into a stylesheet.

parse(String) - Static method in class dev.tamboui.css.selector.SelectorParser
Parses a CSS selector string into a Selector object.

parse(String) - Static method in class dev.tamboui.text.MarkupParser

Parses markup text using only built-in styles.

parse(String...) - Static method in class dev.tamboui.layout.grid.GridArea
Parses area template strings into a GridArea.

parse(String, MarkupParser.StyleResolver) - Static method in class dev.tamboui.text.MarkupParser
Parses markup text with custom style resolution.

parse(String, MarkupParser.StyleResolver, boolean) - Static method in class dev.tamboui.text.MarkupParser
Parses markup text with custom style resolution and emoji replacement control.

parse(String, MarkupParser.StyleResolver, MarkupParser.EmojiResolver) - Static method in class dev.tamboui.text.MarkupParser
Parses markup text with custom style and emoji resolution.

parseColor(String) - Method in class dev.tamboui.css.engine.StyleEngine
Parses a CSS color value string into a Color.

parseColor(String) - Method in class dev.tamboui.toolkit.element.DefaultRenderContext

parseColor(String) - Method in interface dev.tamboui.toolkit.element.RenderContext
Parses a CSS color value string into a Color.

parsedText() - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Returns the parsed text (useful for inspection or modification).

parsedText() - Method in class dev.tamboui.toolkit.elements.MarkupTextElement
Returns the parsed Text object.

parts() - Method in class dev.tamboui.css.selector.CompoundSelector
Returns the selector parts that make up this compound selector.

patch(Style) - Method in class dev.tamboui.style.Style
Combines this style with another.

patch(Tags) - Method in class dev.tamboui.style.Tags

patch(T) - Method in interface dev.tamboui.style.Patchable
Merges this value with another value of the same type.

Patchable<T> - Interface in dev.tamboui.style
Interface for style extensions that support custom merge behavior during `Style.patch(Style)`.

patchStyle(Style) - Method in class dev.tamboui.buffer.Cell
Returns a new cell with this cell's style patched by the given style.

patchStyle(Style) - Method in class dev.tamboui.text.Line
Applies a style patch to all spans.

patchStyle(Style) - Method in class dev.tamboui.text.Span
Returns a new span with the given style patch applied.

patchStyle(Style) - Method in class dev.tamboui.text.Text
Applies a style patch to all lines.

patchStyle(Style) - Method in class dev.tamboui.tfx.CellIterator.MutableCell
Patches the cell's style with the given style.

pattern() - Method in class dev.tamboui.tfx.effects.FadeShader

pattern() - Method in interface dev.tamboui.tfx.Shader
Returns the pattern for this shader, or null if not applicable.

pattern(String) - Static method in class dev.tamboui.widgets.form.Validators
Creates a validator that requires the value to match a regex pattern.

pattern(String, String) - Static method in class dev.tamboui.widgets.form.Validators
Creates a validator that requires the value to match a regex pattern.

Pattern - Interface in dev.tamboui.tfx.pattern
Interface for patterns that define spatial distribution of effects.

PEAK_COUNT - Static variable in class dev.tamboui.widgets.wavetext.WaveText
The `wave-peak-count` property for the number of peaks.

PEAK_WIDTH - Static variable in class dev.tamboui.widgets.wavetext.WaveText
The `wave-peak-width` property for the peak width in characters.

peakCount(int) - Method in class dev.tamboui.toolkit.elements.WaveTextElement
Sets the number of peaks in the wave.

peakCount(int) - Method in class dev.tamboui.widgets.wavetext.WaveText.Builder
Sets the number of peaks in the wave.

peakWidth(int) - Method in class dev.tamboui.toolkit.elements.WaveTextElement
Sets the width of the bright peak in characters.

peakWidth(int) - Method in class dev.tamboui.widgets.wavetext.WaveText.Builder
Sets the width of the wave peak in characters.

peek(int) - Method in class dev.tamboui.backend.aesh.AeshBackend

peek(int) - Method in class dev.tamboui.backend.jline3.JLineBackend

peek(int) - Method in class dev.tamboui.backend.panama.PanamaBackend

peek(int) - Method in interface dev.tamboui.backend.panama.PlatformTerminal
Peeks at the next character without consuming it.

peek(int) - Method in class dev.tamboui.backend.panama.unix.UnixTerminal
Peeks at the next character without consuming it.

peek(int) - Method in class dev.tamboui.backend.panama.windows.WindowsTerminal

peek(int) - Method in class dev.tamboui.internal.record.RecordingBackend

peek(int) - Method in interface dev.tamboui.terminal.Backend
Peeks at the next character without consuming it.

pendingCount() - Method in class dev.tamboui.tfx.toolkit.ElementEffectRegistry
Returns the total number of pending effects.

percent() - Method in class dev.tamboui.style.Width
Returns the percentage value (0.0 to 1.0).

percent(double) - Static method in class dev.tamboui.style.Width
Creates a percentage-based width.

percent(int) - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the constraint to a percentage of the parent's size.

percent(int) - Method in class dev.tamboui.toolkit.elements.GaugeElement
Sets the progress as a percentage (0-100).

percent(int) - Method in class dev.tamboui.toolkit.elements.LineGaugeElement
Sets the progress as a percentage (0-100).

percent(int) - Method in class dev.tamboui.toolkit.elements.Spacer
Sets the constraint to a percentage.

percent(int) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a percentage constraint.

percent(int) - Method in class dev.tamboui.widgets.gauge.Gauge.Builder
Sets the progress as a percentage (0-100).

percent(int) - Static method in class dev.tamboui.widgets.gauge.Gauge
Creates a gauge with the given percentage (0-100).

percent(int) - Method in class dev.tamboui.widgets.gauge.LineGauge.Builder
Sets the progress as a percentage (0-100).

percent(int) - Static method in class dev.tamboui.widgets.gauge.LineGauge

Creates a line gauge with the given percentage (0-100).

percentage(int) - Static method in interface dev.tamboui.layout.Constraint
Creates a percentage constraint.

Percentage(int) - Constructor for class dev.tamboui.layout.Constraint.Percentage
Creates a percentage constraint.

pi() - Static method in class dev.tamboui.tfx.TFxMath
Returns the value of pi.

PING_PONG - Enum constant in enum class dev.tamboui.tfx.LoopMode
Reverse direction when reaching end.

pingPong() - Method in class dev.tamboui.tfx.Effect
Creates a new Effect that ping-pongs back and forth.

pixelAt(int, int) - Method in class dev.tamboui.image.ImageData
Returns the pixel at the specified coordinates in ARGB format.

placeholder(String) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Sets the placeholder text for text inputs.

placeholder(String) - Method in class dev.tamboui.toolkit.elements.TextAreaElement
Sets the placeholder text.

placeholder(String) - Method in class dev.tamboui.toolkit.elements.TextInputElement
Sets the placeholder text.

placeholder(String) - Method in class dev.tamboui.widgets.input.TextArea.Builder
Sets the placeholder text shown when the text area is empty.

placeholder(String) - Method in class dev.tamboui.widgets.input.TextInput.Builder
Sets the placeholder text shown when the input is empty.

PLACEHOLDER_COLOR - Static variable in class dev.tamboui.widgets.input.TextArea
Property key for the placeholder text color.

PLACEHOLDER_COLOR - Static variable in class dev.tamboui.widgets.input.TextInput
Property key for the placeholder text color.

placeholderColor(Color) - Method in class dev.tamboui.toolkit.elements.TextAreaElement
Sets the placeholder color.

placeholderColor(Color) - Method in class dev.tamboui.toolkit.elements.TextInputElement
Sets the placeholder color.

placeholderColor(Color) - Method in class dev.tamboui.widgets.input.TextArea.Builder
Sets the placeholder text color programmatically.

placeholderColor(Color) - Method in class dev.tamboui.widgets.input.TextInput.Builder
Sets the placeholder text color programmatically.

placeholderStyle(Style) - Method in class dev.tamboui.toolkit.elements.TextAreaElement
Sets the placeholder style.

placeholderStyle(Style) - Method in class dev.tamboui.toolkit.elements.TextInputElement
Sets the placeholder style.

placeholderStyle(Style) - Method in class dev.tamboui.widgets.input.TextArea.Builder
Sets the placeholder text style.

placeholderStyle(Style) - Method in class dev.tamboui.widgets.input.TextInput.Builder
Sets the placeholder text style.

PLAIN - Enum constant in enum class dev.tamboui.widgets.block.BorderType
Plain border using single-line box-drawing characters.

PlatformConstants - Class in dev.tamboui.backend.panama.unix
Platform-specific constants for Unix terminal operations.

platformTerminal() - Method in class dev.tamboui.backend.panama.PanamaBackend
Returns the underlying platform terminal.

PlatformTerminal - Interface in dev.tamboui.backend.panama
Platform-independent terminal operations interface.

plus(long) - Method in class dev.tamboui.layout.cassowary.Expression
Adds a constant to this expression.

plus(Expression) - Method in class dev.tamboui.layout.cassowary.Expression
Adds another expression to this one.

plus(Term) - Method in class dev.tamboui.layout.cassowary.Expression
Adds a term to this expression.

plus(Variable) - Method in class dev.tamboui.layout.cassowary.Expression
Adds a variable to this expression.

plus(Fraction) - Method in class dev.tamboui.layout.cassowary.Expression
Adds a constant to this expression.

Points - Class in dev.tamboui.widgets.canvas.shapes
A collection of points (scatter plot).

Points(double[][], Color) - Constructor for class dev.tamboui.widgets.canvas.shapes.Points
Creates a points shape from coordinate pairs and a color.

poll(MemorySegment, int, int) - Static method in class dev.tamboui.backend.panama.unix.LibC
Waits for events on file descriptors.

POLLERR - Static variable in class dev.tamboui.backend.panama.unix.LibC
Poll event: error condition on the file descriptor.

pollEvent() - Method in class dev.tamboui.tui.TuiRunner
Polls for the next event without blocking.

pollEvent(Duration) - Method in class dev.tamboui.tui.InlineTuiRunner
Polls for the next event with the specified timeout.

pollEvent(Duration) - Method in class dev.tamboui.tui.TuiRunner
Polls for the next event with the specified timeout.

POLLFD_LAYOUT - Static variable in class dev.tamboui.backend.panama.unix.LibC
Layout for the pollfd structure.

POLLHUP - Static variable in class dev.tamboui.backend.panama.unix.LibC
Poll event: hang up on the file descriptor.

POLLIN - Static variable in class dev.tamboui.backend.panama.unix.LibC
Poll event: there is data to read.

POLLNVAL - Static variable in class dev.tamboui.backend.panama.unix.LibC
Poll event: invalid file descriptor.

POLLPRI - Static variable in class dev.tamboui.backend.panama.unix.LibC
Poll event: there is urgent data to read.

pollTimeout() - Method in class dev.tamboui.tui.InlineTuiConfig
Returns the poll timeout for reading events.

pollTimeout() - Method in class dev.tamboui.tui.TuiConfig
Returns the poll timeout for reading events.

pollTimeout(Duration) - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner.Builder
Sets the poll timeout.

pollTimeout(Duration) - Method in class dev.tamboui.tui.InlineTuiConfig.Builder
Sets the timeout for polling events.

pollTimeout(Duration) - Method in class dev.tamboui.tui.TuiConfig.Builder
Sets the timeout for polling events.

pollTimeout(Duration) - Method in class dev.tamboui.tui.TuiRunner.Builder
Sets the timeout for polling events.

popContextKey() - Method in class dev.tamboui.terminal.Frame

Pops the most recent context key from the stack.

position() - Method in class dev.tamboui.css.parser.Token
Returns the position of this token in the source.

position() - Method in class dev.tamboui.layout.Rect
Returns the top-left position.

position() - Method in class dev.tamboui.tfx.CellIterator.CellEntry
Returns the position of this cell entry.

position() - Method in class dev.tamboui.tfx.CellIterator.MutableCell
Returns a Position object for this cell.

position() - Method in class dev.tamboui.widgets.scrollbar.ScrollbarState
Returns the current scroll position.

position(int) - Method in class dev.tamboui.widgets.scrollbar.ScrollbarState
Sets the current scroll position.

Position - Class in dev.tamboui.layout
A position in 2D space, representing x and y coordinates.

Position(int, int) - Constructor for class dev.tamboui.css.parser.Token.Position
Creates a position with the given line and column.

Position(int, int) - Constructor for class dev.tamboui.layout.Position
Creates a position.

positionFn(Predicate) - Static method in class dev.tamboui.tfx.CellFilter
Selects cells using a custom position-based predicate function.

positions() - Method in class dev.tamboui.layout.Rect
Returns a stream of all positions (cells) within this rectangle, row by row.

postRenderProcessor(ToolkitPostRenderProcessor) - Method in class dev.tamboui.toolkit.app.ToolkitRunner.Builder
Adds a post-render processor.

postRenderProcessor(PostRenderProcessor) - Method in class dev.tamboui.tui.TuiConfig.Builder
Adds a post-render processor.

PostRenderProcessor - Interface in dev.tamboui.tui
Processor called after each frame is rendered.

postRenderProcessors() - Method in class dev.tamboui.tui.TuiConfig
Returns the list of post-render processors.

powf(float, float) - Static method in class dev.tamboui.tfx.TFxMath
Raises a float base to a float exponent.

powi(float, int) - Static method in class dev.tamboui.tfx.TFxMath
Raises a float base to an integer exponent.

precededByWhitespace() - Method in class dev.tamboui.css.parser.Token
Returns whether this token was preceded by whitespace in the source.

preferredSize() - Method in interface dev.tamboui.toolkit.element.Element
Convenience method for unconstrained preferred size.

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.component.Component

preferredSize(int, int, RenderContext) - Method in interface dev.tamboui.toolkit.element.Element
Returns the preferred size of this element.

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.BarChartElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.CalendarElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.CanvasElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.ChartElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.Column

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.ColumnsElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.DialogElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.DockElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.ErrorPlaceholder

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.FlowElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.FormElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.FormFieldElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.GaugeElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.GenericWidgetElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.GridElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.InlineScopeElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.LazyElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.LineGaugeElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.ListElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.MarkupTextElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.Panel

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.RichTextElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.Row

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.ScrollbarElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.Spacer

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.SparklineElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.SpinnerElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.StackElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.TableElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.TabsElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.TextAreaElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.TextElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.TextInputElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.TreeElement

preferredSize(int, int, RenderContext) - Method in class dev.tamboui.toolkit.elements.WaveTextElement

press(MouseButton) - Static method in class dev.tamboui.tui.bindings.MouseTrigger
Creates a trigger for a mouse button press.

press(MouseButton, boolean, boolean, boolean) - Static method in class dev.tamboui.tui.bindings.MouseTrigger
Creates a trigger for a mouse button press with modifiers.

press(MouseButton, int, int) - Static method in class dev.tamboui.tui.event.MouseEvent
Creates a mouse press event.

press(MouseButton, int, int, Bindings) - Static method in class dev.tamboui.tui.event.MouseEvent
Creates a mouse press event with specific bindings.

PRESS - Enum constant in enum class dev.tamboui.tui.event.MouseEventKind
Mouse button was pressed down.

prev() - Method in class dev.tamboui.widgets.scrollbar.ScrollbarState
Scrolls up by one position.

print(double, double, Line) - Method in class dev.tamboui.widgets.canvas.Context
Prints styled text at the specified canvas coordinates.

print(double, double, Span) - Method in class dev.tamboui.widgets.canvas.Context
Prints a styled span at the specified canvas coordinates.

print(double, double, String) - Method in class dev.tamboui.widgets.canvas.Context
Prints text at the specified canvas coordinates.

print(PrintStream) - Static method in class dev.tamboui.capability.Capabilities
Detects capabilities and prints the report to the given stream.

print(PrintStream) - Method in class dev.tamboui.capability.CapabilityReport
Prints this capability report to the given stream.

println(Text) - Method in class dev.tamboui.inline.InlineDisplay
Prints styled text above the display area.

println(Text) - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner
Prints styled text above the viewport.

println(Text) - Method in class dev.tamboui.tui.InlineTuiRunner
Prints styled text above the viewport.

println(Element) - Method in class dev.tamboui.toolkit.app.InlineApp
Prints an element above the viewport as a single line.

println(Element) - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner
Prints an element above the viewport.

println(String) - Method in class dev.tamboui.inline.InlineDisplay
Prints a line of text above the display area.

println(String) - Method in class dev.tamboui.toolkit.app.InlineApp
Prints a plain text message above the viewport.

println(String) - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner
Prints a plain text message above the viewport.

println(String) - Method in class dev.tamboui.tui.InlineTuiRunner
Prints a plain text message above the viewport.

process(Frame) - Method in interface dev.tamboui.tui.PostRenderProcessor
Processes the frame after rendering.

process(Frame, ElementRegistry, StyledAreaRegistry, FocusManager, Duration) - Method in interface dev.tamboui.toolkit.app.ToolkitPostRenderProcessor
Processes the frame after rendering.

process(TFxDuration) - Method in class dev.tamboui.tfx.EffectTimer

Processes the timer by reducing the remaining duration by the specified amount.

process(TFxDuration, Buffer, Rect) - Method in class dev.tamboui.tfx.Effect
Processes the effect for the given duration.

process(TFxDuration, Buffer, Rect) - Method in class dev.tamboui.tfx.effects.DissolveShader

process(TFxDuration, Buffer, Rect) - Method in class dev.tamboui.tfx.effects.ExpandShader

process(TFxDuration, Buffer, Rect) - Method in class dev.tamboui.tfx.effects.FadeShader

process(TFxDuration, Buffer, Rect) - Method in class dev.tamboui.tfx.effects.PaintShader

process(TFxDuration, Buffer, Rect) - Method in class dev.tamboui.tfx.effects.ParallelEffect

process(TFxDuration, Buffer, Rect) - Method in class dev.tamboui.tfx.effects.SequentialEffect

process(TFxDuration, Buffer, Rect) - Method in class dev.tamboui.tfx.effects.SlideShader

process(TFxDuration, Buffer, Rect) - Method in class dev.tamboui.tfx.effects.StretchShader

process(TFxDuration, Buffer, Rect) - Method in class dev.tamboui.tfx.effects.SweepShader

process(TFxDuration, Buffer, Rect) - Method in interface dev.tamboui.tfx.Shader
Processes the shader for the given duration.

process(Set, RoundEnvironment) - Method in class dev.tamboui.tui.bindings.processor.OnActionProcessor

processEffects(TFxDuration, Buffer, Rect) - Method in class dev.tamboui.tfx.EffectManager
Processes all active effects for the given duration.

processEffects(TFxDuration, Buffer, Rect, ElementRegistry, StyledAreaRegistry, FocusManager) - Method in class dev.tamboui.tfx.toolkit.ElementEffectRegistry
Processes all active effects with dynamic area lookup from both registries.

properties() - Method in class dev.tamboui.css.cascade.TypedPropertyMap
Returns all property definitions in this map.

propertiesBySource() - Method in class dev.tamboui.capability.CapabilityReport
Java/system properties (and similar) grouped by provider source.

property(String, String) - Method in class dev.tamboui.capability.CapabilityReportBuilder
Adds a property key that should be printed (value resolved at print-time).

PropertyConverter<T> - Interface in dev.tamboui.css.property
Converts CSS property values to typed objects.

PropertyConverter<T> - Interface in dev.tamboui.style
A functional interface for converting string values to typed property values.

PropertyDefinition<T> - Class in dev.tamboui.style
A typed definition for a style property, bundling the property name with its converter, inheritance behavior, and optional default value.

PropertyDefinition.Builder<T> - Class in dev.tamboui.style
Builder for PropertyDefinition.

PropertyRegistry - Class in dev.tamboui.style
Thread-safe registry for style property definitions.

PropertyValue - Class in dev.tamboui.css.model
Represents a CSS property value as parsed from the stylesheet.

PropertyValue(String, boolean) - Constructor for class dev.tamboui.css.model.PropertyValue
Creates a property value.

protocol() - Method in class dev.tamboui.image.Image
Returns the protocol used for rendering.

protocol(ImageProtocol) - Method in class dev.tamboui.image.Image.Builder

Sets a specific protocol for rendering.

protocolFor(TerminalImageProtocol) - Method in class dev.tamboui.image.capability.TerminalImageCapabilities
Returns a protocol implementation for the specified support level.

Protocol Format - Section in class dev.tamboui.image.protocol.ITermProtocol

Protocol Format - Section in class dev.tamboui.image.protocol.KittyProtocol

Protocol Format - Section in class dev.tamboui.image.protocol.SixelProtocol

protocolType() - Method in class dev.tamboui.image.protocol.BrailleProtocol

protocolType() - Method in class dev.tamboui.image.protocol.HalfBlockProtocol

protocolType() - Method in interface dev.tamboui.image.protocol.ImageProtocol
Returns the terminal image protocol type for capability checking.

protocolType() - Method in class dev.tamboui.image.protocol.ITermProtocol

protocolType() - Method in class dev.tamboui.image.protocol.KittyProtocol

protocolType() - Method in class dev.tamboui.image.protocol.SixelProtocol

pseudoClass() - Method in class dev.tamboui.css.selector.PseudoClassSelector
Returns the pseudo-class name (without the leading colon).

PseudoClassSelector - Class in dev.tamboui.css.selector
A pseudo-class selector that matches elements in a particular state.

PseudoClassSelector(String) - Constructor for class dev.tamboui.css.selector.PseudoClassSelector
Creates a pseudo-class selector for the given pseudo-class name.

PseudoClassState - Class in dev.tamboui.css.cascade
Represents the current pseudo-class state of an element.

PseudoClassState(boolean, boolean, boolean, boolean, boolean, boolean, boolean, int) - Constructor for class dev.tamboui.css.cascade.PseudoClassState
Creates a pseudo-class state with the given flags.

PseudoClassStateProvider - Interface in dev.tamboui.css.cascade
Provides the pseudo-class state for any element during selector matching.

push(Span) - Method in class dev.tamboui.text.Text
Extends the last line with the given span, or adds a new line if empty.

pushContextKey(String) - Method in class dev.tamboui.terminal.Frame
Pushes a context key onto the stack.

put(PropertyDefinition, T) - Method in class dev.tamboui.css.cascade.TypedPropertyMap.Builder
Puts a property value into the map.

Q

QuadIn - Enum constant in enum class dev.tamboui.tfx.Interpolation
Quadratic easing - in

QuadInOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Quadratic easing - in-out

QuadOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Quadratic easing - out

QUADRANT_INSIDE - Enum constant in enum class dev.tamboui.widgets.block.BorderType
Quadrant border rendered inside the content area.

QUADRANT_OUTSIDE - Enum constant in enum class dev.tamboui.widgets.block.BorderType
Quadrant border rendered outside the content area.

QuartIn - Enum constant in enum class dev.tamboui.tfx.Interpolation
Quartic easing - in

QuartInOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Quartic easing - in-out

QuartOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Quartic easing - out

query(Backend, int) - Static method in class dev.tamboui.terminal.Mode2027Support
Queries the terminal for Mode 2027 support status.

query(String) - Method in class dev.tamboui.toolkit.element.ElementRegistry
Queries for a single element matching the selector.

query(String, PseudoClassState) - Method in class dev.tamboui.toolkit.element.ElementRegistry
Queries for a single element matching the selector with pseudo-class state.

queryAll(String) - Method in class dev.tamboui.toolkit.element.ElementRegistry
Queries for all elements matching the selector.

queryAll(String, PseudoClassState) - Method in class dev.tamboui.toolkit.element.ElementRegistry
Queries for all elements matching the selector with pseudo-class state.

querySequence() - Static method in class dev.tamboui.terminal.Mode2027Support
Constructs the DECRQM query sequence for Mode 2027.

QuintIn - Enum constant in enum class dev.tamboui.tfx.Interpolation
Quintic easing - in

QuintInOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Quintic easing - in-out

QuintOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Quintic easing - out

quit() - Method in class dev.tamboui.toolkit.app.InlineApp
Signals the application to quit.

quit() - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner
Signals the runner to stop.

quit() - Method in class dev.tamboui.toolkit.app.ToolkitApp
Signals the application to quit.

quit() - Method in class dev.tamboui.toolkit.app.ToolkitRunner
Signals the runner to stop.

quit() - Method in interface dev.tamboui.tui.error.ErrorContext
Signals the runner to stop.

quit() - Method in class dev.tamboui.tui.InlineTuiRunner
Signals the runner to stop.

quit() - Method in class dev.tamboui.tui.TuiRunner.ConfiguredRunner
Signals the runner to stop.

quit() - Method in class dev.tamboui.tui.TuiRunner
Signals the runner to stop.

QUIT - Static variable in class dev.tamboui.tui.bindings.Actions
Quit the application (q, Ctrl+c, etc.).

QUIT_IMMEDIATELY - Enum constant in enum class dev.tamboui.tui.error.ErrorAction
Clean up the terminal and quit immediately without displaying the error.

R

r() - Method in class dev.tamboui.style.Color.Rgb
Returns the red component.

RadialPattern - Class in dev.tamboui.tfx.pattern

Pattern implementation for radial (circular) expansion effects.

radius() - Method in class dev.tamboui.widgets.canvas.shapes.Circle
Returns the radius of the circle.

range() - Method in class dev.tamboui.widgets.chart.Axis
Returns the range (max - min).

range(int, int) - Static method in class dev.tamboui.widgets.form.Validators
Creates a validator that requires a numeric value within a range.

range(int, int, String) - Static method in class dev.tamboui.widgets.form.Validators
Creates a validator that requires a numeric value within a range with a custom message.

RAPID_BLINK - Enum constant in enum class dev.tamboui.style.Modifier
Rapid blink text.

rapidBlink() - Method in class dev.tamboui.style.Style
Enables rapid blink.

ratio(double) - Method in class dev.tamboui.toolkit.elements.GaugeElement
Sets the progress as a ratio (0.0-1.0).

ratio(double) - Method in class dev.tamboui.toolkit.elements.LineGaugeElement
Sets the progress as a ratio (0.0-1.0).

ratio(double) - Method in class dev.tamboui.widgets.gauge.Gauge.Builder
Sets the progress as a ratio (0.0-1.0).

ratio(double) - Static method in class dev.tamboui.widgets.gauge.Gauge
Creates a gauge with the given ratio (0.0-1.0).

ratio(double) - Method in class dev.tamboui.widgets.gauge.LineGauge.Builder
Sets the progress as a ratio (0.0-1.0).

ratio(double) - Static method in class dev.tamboui.widgets.gauge.LineGauge
Creates a line gauge with the given ratio (0.0-1.0).

ratio(int, int) - Static method in interface dev.tamboui.layout.Constraint
Creates a ratio constraint.

ratio(int, int) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a ratio constraint.

Ratio(int, int) - Constructor for class dev.tamboui.layout.Constraint.Ratio
Creates a ratio constraint.

raw() - Method in class dev.tamboui.css.model.PropertyValue
Returns the raw value string.

raw(String) - Static method in class dev.tamboui.text.Span
Creates an unstyled span from the given content.

raw(String) - Static method in class dev.tamboui.text.Text
Creates a text from a raw string, splitting on newlines.

rawContent() - Method in class dev.tamboui.text.Line
Returns the raw text content without styling.

rawContent() - Method in class dev.tamboui.text.Text
Returns the raw text content without styling.

rawMode() - Method in class dev.tamboui.tui.TuiConfig
Returns whether raw mode is enabled.

rawMode(boolean) - Method in class dev.tamboui.tui.TuiConfig.Builder
Sets whether to enable raw mode.

rawMode(boolean) - Method in class dev.tamboui.tui.TuiRunner.Builder
Sets whether to enable raw mode.

rawOutput(Frame) - Static method in class dev.tamboui.terminal.FrameInternal
Returns the raw output stream for the given frame.

RawOutputCapable - Interface in dev.tamboui.widget
Interface for widgets that can render using raw terminal output.

read(int) - Method in class dev.tamboui.backend.aesh.AeshBackend

read(int) - Method in class dev.tamboui.backend.jline3.JLineBackend

read(int) - Method in class dev.tamboui.backend.panama.PanamaBackend

read(int) - Method in interface dev.tamboui.backend.panama.PlatformTerminal
Reads a single character from the terminal with timeout.

read(int) - Method in class dev.tamboui.backend.panama.unix.UnixTerminal
Reads a single character from the terminal with timeout.

read(int) - Method in class dev.tamboui.backend.panama.windows.WindowsTerminal

read(int) - Method in class dev.tamboui.internal.record.RecordingBackend

read(int) - Method in interface dev.tamboui.terminal.Backend
Reads a single character from the terminal input with timeout.

read(int, MemorySegment, long) - Static method in class dev.tamboui.backend.panama.unix.LibC
Reads from a file descriptor.

readConsoleInput(MemorySegment, MemorySegment, int, MemorySegment) - Static method in class dev.tamboui.backend.panama.windows.Kernel32
Reads data from a console input buffer.

readEvent(Backend, int) - Static method in class dev.tamboui.tui.event.EventParser
Reads and parses the next event from the backend using the default bindings.

readEvent(Backend, int, Bindings) - Static method in class dev.tamboui.tui.event.EventParser
Reads and parses the next event from the backend.

rebind(InputTrigger, String) - Method in interface dev.tamboui.tui.bindings.Bindings.Builder
Replaces all triggers for an action with the given trigger.

reciprocal() - Method in class dev.tamboui.layout.Fraction
Returns the reciprocal of this fraction.

recordFrame() - Method in class dev.tamboui.tui.overlay.DebugOverlay
Records a frame render for FPS calculation.

RecordingBackend - Class in dev.tamboui.internal.record
A backend wrapper that records frames to an Asciinema cast file.

RecordingBackend(Backend, RecordingConfig) - Constructor for class dev.tamboui.internal.record.RecordingBackend
Creates a new recording backend wrapping the given delegate.

RecordingConfig - Class in dev.tamboui.internal.record
Configuration for Asciinema (.cast) recording, loaded from system properties.

Rect - Class in dev.tamboui.layout
A rectangular area defined by its position and size.

Rect(int, int, int, int) - Constructor for class dev.tamboui.layout.Rect
Creates a rectangle at the given position and size.

Rectangle - Class in dev.tamboui.widgets.canvas.shapes
A rectangle defined by position and size.

Rectangle(double, double, double, double, Color) - Constructor for class dev.tamboui.widgets.canvas.shapes.Rectangle
Creates a rectangle at the given position with the given dimensions and color.

red() - Method in class dev.tamboui.style.Style
Shorthand for `Style.fg(Color)` with `Color.RED`.

red() - Method in class dev.tamboui.text.Span

Returns a new span with red foreground color.

red() - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the foreground color to red.

red(int) - Static method in class dev.tamboui.image.ImageData
Returns the red component of a pixel (0-255).

RED - Enum constant in enum class dev.tamboui.style.AnsiColor
Red (palette index 1).

RED - Static variable in interface dev.tamboui.style.Color
Red.

refresh() - Static method in class dev.tamboui.image.capability.TerminalImageCapabilities
Forces re-detection of terminal capabilities.

register(PropertyDefinition) - Static method in class dev.tamboui.style.PropertyRegistry
Registers a property definition.

register(Style, Rect, String) - Method in interface dev.tamboui.style.StyledAreaRegistry
Registers a styled area.

register(String, Rect) - Method in class dev.tamboui.toolkit.element.ElementRegistry
Registers an element's rendered area by ID only.

register(String, String, Set, Rect) - Method in class dev.tamboui.toolkit.element.ElementRegistry
Registers an element with full information.

register(String, String, Set, Map, Rect, ElementRegistry.ElementInfo) - Method in class dev.tamboui.toolkit.element.ElementRegistry
Registers an element with full information including parent.

register(T, ActionHandler) - Method in interface dev.tamboui.tui.bindings.ActionHandlerRegistrar
Registers the action handlers from the target object with the handler.

registerAll(PropertyDefinition...) - Static method in class dev.tamboui.style.PropertyRegistry
Registers multiple property definitions.

registerAnnotated(T) - Method in class dev.tamboui.tui.bindings.ActionHandler
Discovers and registers action handlers from the target object.

registerElement(Element, Rect) - Method in class dev.tamboui.toolkit.element.DefaultRenderContext
Registers an element for event routing and focus management.

registerElement(Element, Rect) - Method in class dev.tamboui.toolkit.event.EventRouter
Registers an element for event routing.

registerFocusable(String, Rect) - Method in class dev.tamboui.toolkit.focus.FocusManager
Registers a focusable element with its rendered area.

registry() - Method in class dev.tamboui.tfx.toolkit.ToolkitEffects
Returns the underlying effect registry.

relation() - Method in class dev.tamboui.layout.cassowary.CassowaryConstraint
Returns the relation type of this constraint.

Relation - Enum Class in dev.tamboui.layout.cassowary
The type of relationship in a constraint.

release() - Method in class dev.tamboui.inline.InlineDisplay
Explicitly releases the display before close().

release(MouseButton) - Static method in class dev.tamboui.tui.bindings.MouseTrigger
Creates a trigger for a mouse button release.

release(MouseButton, int, int) - Static method in class dev.tamboui.tui.event.MouseEvent
Creates a mouse release event.

RELEASE - Enum constant in enum class dev.tamboui.tui.event.MouseEventKind
Mouse button was released.

reloadStylesheet(String) - Method in class dev.tamboui.css.engine.StyleEngine

Reloads a named stylesheet from its original source.

remaining() - Method in class dev.tamboui.tfx.EffectTimer
Returns the remaining duration.

removeChangeListener(StyleEngine.StyleChangeListener) - Method in class dev.tamboui.css.engine.StyleEngine
Removes a change listener.

removeClass(String) - Method in class dev.tamboui.toolkit.element.StyledElement
Removes a CSS class from this element.

removeConstraint(CassowaryConstraint) - Method in class dev.tamboui.layout.cassowary.Solver
Removes a constraint from the solver.

removeEditVariable(Variable) - Method in class dev.tamboui.layout.cassowary.Solver
Removes an edit variable.

removeGlobalHandler(GlobalEventHandler) - Method in class dev.tamboui.toolkit.event.EventRouter
Removes a global event handler.

removeModifier(Modifier) - Method in class dev.tamboui.style.Style
Returns a new style with the given modifier removed (subtracted).

render() - Method in class dev.tamboui.toolkit.app.InlineApp
Renders the application UI.

render() - Method in class dev.tamboui.toolkit.app.ToolkitApp
Renders the application UI.

render() - Method in class dev.tamboui.toolkit.component.Component
Renders the component's content.

render(ImageData, Rect, Buffer, OutputStream) - Method in class dev.tamboui.image.protocol.BrailleProtocol

render(ImageData, Rect, Buffer, OutputStream) - Method in class dev.tamboui.image.protocol.HalfBlockProtocol

render(ImageData, Rect, Buffer, OutputStream) - Method in interface dev.tamboui.image.protocol.ImageProtocol
Renders the image to the given terminal area.

render(ImageData, Rect, Buffer, OutputStream) - Method in class dev.tamboui.image.protocol.ITermProtocol

render(ImageData, Rect, Buffer, OutputStream) - Method in class dev.tamboui.image.protocol.KittyProtocol

render(ImageData, Rect, Buffer, OutputStream) - Method in class dev.tamboui.image.protocol.SixelProtocol

render(Rect, Buffer) - Method in class dev.tamboui.image.Image

render(Rect, Buffer) - Method in class dev.tamboui.layout.columns.Columns

render(Rect, Buffer) - Method in class dev.tamboui.layout.dock.Dock

render(Rect, Buffer) - Method in class dev.tamboui.layout.flow.Flow

render(Rect, Buffer) - Method in class dev.tamboui.layout.grid.Grid

render(Rect, Buffer) - Method in class dev.tamboui.layout.stack.Stack

render(Rect, Buffer) - Method in interface dev.tamboui.widget.Widget
Renders this widget to the given buffer area.

render(Rect, Buffer) - Method in class dev.tamboui.widgets.barchart.BarChart

render(Rect, Buffer) - Method in class dev.tamboui.widgets.block.Block

render(Rect, Buffer) - Method in class dev.tamboui.widgets.calendar.Monthly

render(Rect, Buffer) - Method in class dev.tamboui.widgets.canvas.Canvas

render(Rect, Buffer) - Method in class dev.tamboui.widgets.chart.Chart

render(Rect, Buffer) - Method in class dev.tamboui.widgets.Clear

render(Rect, Buffer) - Method in class dev.tamboui.widgets.error.ErrorDisplay

render(Rect, Buffer) - Method in class dev.tamboui.widgets.gauge.Gauge

render(Rect, Buffer) - Method in class dev.tamboui.widgets.gauge.LineGauge

render(Rect, Buffer) - Method in class dev.tamboui.widgets.logo.Logo

render(Rect, Buffer) - Method in class dev.tamboui.widgets.paragraph.Paragraph

render(Rect, Buffer) - Method in class dev.tamboui.widgets.sparkline.Sparkline

render(Rect, Buffer, CheckboxState) - Method in class dev.tamboui.widgets.checkbox.Checkbox

render(Rect, Buffer, TextAreaState) - Method in class dev.tamboui.widgets.input.TextArea

render(Rect, Buffer, TextInputState) - Method in class dev.tamboui.widgets.input.TextInput

render(Rect, Buffer, ListState) - Method in class dev.tamboui.widgets.list.ListWidget

render(Rect, Buffer, ScrollbarState) - Method in class dev.tamboui.widgets.scrollbar.Scrollbar

render(Rect, Buffer, SelectState) - Method in class dev.tamboui.widgets.select.Select

render(Rect, Buffer, SpinnerState) - Method in class dev.tamboui.widgets.spinner.Spinner

render(Rect, Buffer, TableState) - Method in class dev.tamboui.widgets.table.Table

render(Rect, Buffer, TabsState) - Method in class dev.tamboui.widgets.tabs.Tabs

render(Rect, Buffer, ToggleState) - Method in class dev.tamboui.widgets.toggle.Toggle

render(Rect, Buffer, TreeState) - Method in class dev.tamboui.widgets.tree.TreeWidget

render(Rect, Buffer, WaveTextState) - Method in class dev.tamboui.widgets.wavetext.WaveText

render(Rect, Buffer, OutputStream) - Method in class dev.tamboui.image.Image
Renders the image to the given area with optional raw output support.

render(Rect, Buffer, OutputStream) - Method in interface dev.tamboui.widget.RawOutputCapable
Renders this widget to the given area with raw output support.

render(Rect, Buffer, S) - Method in interface dev.tamboui.widget.StatefulWidget
Renders this widget to the given buffer area with the provided state.

render(Frame) - Method in interface dev.tamboui.tui.Renderer
Renders the user interface to the given frame.

render(Frame, Rect) - Method in class dev.tamboui.tui.overlay.DebugOverlay
Renders the debug overlay in the top-right corner.

render(Frame, Rect, RenderContext) - Method in interface dev.tamboui.toolkit.element.Element
Renders this element to the given frame within the specified area.

render(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.element.StyledElement
Renders this element.

render(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.ErrorPlaceholder

render(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.LazyElement

render(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.Spacer

render(BiConsumer) - Method in class dev.tamboui.inline.InlineDisplay
Renders widgets to the display area.

render(BiConsumer, int, int, int) - Method in class dev.tamboui.inline.InlineDisplay
Renders widgets to the display area with explicit cursor positioning.

renderChild(Element, Frame, Rect) - Method in class dev.tamboui.toolkit.element.DefaultRenderContext

renderChild(Element, Frame, Rect) - Method in interface dev.tamboui.toolkit.element.RenderContext
Renders a child element within the given area.

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.component.Component

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.element.StyledElement
Renders the content of this element.

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.BarChartElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.CalendarElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.CanvasElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.ChartElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.Column

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.ColumnsElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.DialogElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.DockElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.FlowElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.FormElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.FormFieldElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.GaugeElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.GenericWidgetElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.GridElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.InlineScopeElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.LineGaugeElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.ListElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.MarkupTextElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.Panel

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.RichTextElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.Row

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.ScrollbarElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.SparklineElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.SpinnerElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.StackElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.TableElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.TabsElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.TextAreaElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.TextElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.TextInputElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.TreeElement

renderContent(Frame, Rect, RenderContext) - Method in class dev.tamboui.toolkit.elements.WaveTextElement

RenderContext - Interface in dev.tamboui.toolkit.element
Context provided during rendering, giving access to focus state and CSS styling.

renderedArea() - Method in interface dev.tamboui.toolkit.element.Element
Returns the last rendered area of this element.

renderedArea() - Method in class dev.tamboui.toolkit.element.StyledElement

renderedArea() - Method in class dev.tamboui.toolkit.elements.LazyElement

renderer(Renderer) - Method in class dev.tamboui.tui.TuiRunner.Builder
Sets the renderer for the application.

Renderer - Interface in dev.tamboui.tui
Functional interface for rendering the TUI.

RenderError - Class in dev.tamboui.tui.error
Immutable container for render error information.

RenderErrorHandler - Interface in dev.tamboui.tui.error
Handler for render errors.

RenderErrorHandlers - Class in dev.tamboui.tui.error
Factory methods for common error handler implementations.

renderStatefulWidget(StatefulWidget, Rect, S) - Method in class dev.tamboui.terminal.Frame
Renders a stateful widget to the given area.

RenderThread - Class in dev.tamboui.tui
Utility class for render thread management.

renderWidget(Widget, Rect) - Method in class dev.tamboui.terminal.Frame
Renders a widget to the given area.

renderWithCursor(Rect, Buffer, TextAreaState, Frame) - Method in class dev.tamboui.widgets.input.TextArea
Renders the widget and sets the cursor position on the frame.

renderWithCursor(Rect, Buffer, TextInputState, Frame) - Method in class dev.tamboui.widgets.input.TextInput
Renders the widget and sets the cursor position on the frame.

REPLACE - Enum constant in enum class dev.tamboui.symbols.merge.MergeStrategy
Replaces the previous symbol with the next one.

replaceEmoji(String) - Static method in class dev.tamboui.text.MarkupParser
Replaces emoji codes in text with Unicode emoji characters using the default resolver.

replaceEmoji(String, MarkupParser.EmojiResolver) - Static method in class dev.tamboui.text.MarkupParser
Replaces emoji codes in text with Unicode emoji characters.

required() - Static method in class dev.tamboui.widgets.form.Validators
Creates a validator that requires a non-empty value.

required(String) - Static method in class dev.tamboui.widgets.form.Validators
Creates a validator that requires a non-empty value with a custom message.

REQUIRED - Static variable in class dev.tamboui.layout.cassowary.Strength
Required constraints must be satisfied.

requiresRawOutput() - Method in class dev.tamboui.image.protocol.BrailleProtocol

requiresRawOutput() - Method in class dev.tamboui.image.protocol.HalfBlockProtocol

requiresRawOutput() - Method in interface dev.tamboui.image.protocol.ImageProtocol
Returns true if this protocol requires raw byte output.

requiresRawOutput() - Method in class dev.tamboui.image.protocol.ITermProtocol

requiresRawOutput() - Method in class dev.tamboui.image.protocol.KittyProtocol

requiresRawOutput() - Method in class dev.tamboui.image.protocol.SixelProtocol

reset() - Method in class dev.tamboui.backend.panama.ByteArrayBuilder
Resets the builder for reuse.

reset() - Method in class dev.tamboui.buffer.Cell
Returns the empty cell singleton.

reset() - Method in class dev.tamboui.layout.cassowary.Solver
Resets the solver to an empty state.

reset() - Method in class dev.tamboui.tfx.EffectTimer
Resets the timer to its initial duration.

reset() - Method in class dev.tamboui.widgets.spinner.SpinnerState
Resets the tick to 0.

reset() - Method in class dev.tamboui.widgets.wavetext.WaveTextState
Resets the tick to 0.

Reset() - Constructor for class dev.tamboui.style.Color.Reset
Creates a reset color instance.

RESET - Static variable in interface dev.tamboui.style.Color
Reset to default terminal color.

RESET - Static variable in class dev.tamboui.terminal.AnsiStringBuilder
ANSI reset sequence that clears all formatting.

resize(int, int) - Method in class dev.tamboui.image.ImageData
Creates a resized copy of this image.

ResizeEvent - Class in dev.tamboui.tui.event
Represents a terminal window resize event.

ResizeEvent(int, int) - Constructor for class dev.tamboui.tui.event.ResizeEvent

Creates a resize event with the given dimensions.

resizeGracePeriod() - Method in class dev.tamboui.tui.TuiConfig
Returns the resize grace period.

resizeGracePeriod(Duration) - Method in class dev.tamboui.tui.TuiConfig.Builder
Sets the resize grace period.

resizeGracePeriod(Duration) - Method in class dev.tamboui.tui.TuiRunner.Builder
Sets the resize grace period.

resolution() - Method in class dev.tamboui.image.protocol.BrailleProtocol

resolution() - Method in class dev.tamboui.image.protocol.HalfBlockProtocol

resolution() - Method in interface dev.tamboui.image.protocol.ImageProtocol
Returns the resolution multiplier for this protocol.

resolution() - Method in class dev.tamboui.image.protocol.ITermProtocol

resolution() - Method in class dev.tamboui.image.protocol.KittyProtocol

resolution() - Method in class dev.tamboui.image.protocol.SixelProtocol

Resolution(int, int) - Constructor for class dev.tamboui.image.protocol.ImageProtocol.Resolution
Creates a resolution multiplier.

resolve(Styleable) - Method in class dev.tamboui.css.engine.StyleEngine
Resolves the style for an element with default state and no ancestors.

resolve(Styleable, PseudoClassState, List) - Method in class dev.tamboui.css.engine.StyleEngine
Resolves the style for an element.

resolve(Styleable, PseudoClassState, List, List, Map) - Method in class dev.tamboui.css.cascade.CascadeResolver
Resolves the final computed style for an element.

resolve(PropertyDefinition, T) - Method in interface dev.tamboui.style.StylePropertyResolver
Resolves the effective value for a property.

resolve(String) - Method in interface dev.tamboui.text.MarkupParser.EmojiResolver
Resolves a string expansion for the given tag name.

resolve(String) - Method in interface dev.tamboui.text.MarkupParser.StyleResolver
Resolves a style for the given tag name.

resolveEffectiveStyle(RenderContext, String, PseudoClassState, Style, Style) - Method in class dev.tamboui.toolkit.element.StyledElement
Resolves a style for a sub-component with pseudo-class state, following the priority: explicit > CSS > default.

resolveEffectiveStyle(RenderContext, String, Style, Style) - Method in class dev.tamboui.toolkit.element.StyledElement
Resolves a style for a sub-component following the priority: explicit > CSS > default.

resolveIndex(int, int, int, int) - Method in enum class dev.tamboui.layout.columns.ColumnOrder
Resolves the child index for a given grid position based on this ordering mode.

resolveStyle(Styleable) - Method in class dev.tamboui.toolkit.element.DefaultRenderContext

resolveStyle(Styleable) - Method in interface dev.tamboui.toolkit.element.RenderContext
Resolves the CSS style for an element.

resolveStyle(String, String...) - Method in class dev.tamboui.toolkit.element.DefaultRenderContext

resolveStyle(String, String...) - Method in interface dev.tamboui.toolkit.element.RenderContext
Resolves the CSS style for a virtual element with the given type and classes.

resolveVariable(String) - Method in class dev.tamboui.css.model.Stylesheet
Resolves a variable reference.

resolveVariables(String, Map) - Static method in interface dev.tamboui.css.property.PropertyConverter
Resolves variable references in a value.

resumeAutoScroll() - Method in class dev.tamboui.widgets.list.ListState
Resumes auto-scrolling to the bottom (for sticky scroll).

reverse() - Method in class dev.tamboui.tfx.effects.ExpandShader

reverse() - Method in class dev.tamboui.tfx.effects.StretchShader

reverse() - Method in interface dev.tamboui.tfx.Shader
Reverses the shader's playback direction.

Reverse - Enum constant in enum class dev.tamboui.tfx.Interpolation
Reverse (1 - t)

reversed() - Method in class dev.tamboui.style.Style
Enables reverse video.

reversed() - Method in class dev.tamboui.text.Span
Returns a new span with reversed style.

reversed() - Method in class dev.tamboui.tfx.Effect
Creates a new Effect with the shader's reverse flag toggled.

reversed() - Method in class dev.tamboui.tfx.EffectTimer
Returns a new timer with reversed direction.

reversed() - Method in class dev.tamboui.toolkit.element.StyledElement
Applies the reversed modifier.

REVERSED - Enum constant in enum class dev.tamboui.style.Modifier
Reversed (inverse) video text.

rgb(int, int, int) - Static method in interface dev.tamboui.style.Color
Creates an RGB true-color value.

Rgb(int, int, int) - Constructor for class dev.tamboui.style.Color.Rgb
Creates an RGB color.

RGB - Enum constant in enum class dev.tamboui.tfx.TFxColorSpace
Linear RGB interpolation (fastest but not perceptually uniform)

richText() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty inline rich text element.

richText(Text) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a simple inline rich text element with styled text.

richText(String) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a simple inline rich text element from a plain string.

richTextArea() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty scrollable rich text area.

richTextArea(Text) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a scrollable rich text area with styled text.

richTextArea(String) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a scrollable rich text area from a plain string.

RichTextAreaElement - Class in dev.tamboui.toolkit.elements
A toolkit element for displaying styled text with scrolling support.

RichTextAreaElement() - Constructor for class dev.tamboui.toolkit.elements.RichTextAreaElement
Creates a RichTextAreaElement with empty text.

RichTextAreaElement(Text) - Constructor for class dev.tamboui.toolkit.elements.RichTextAreaElement
Creates a RichTextAreaElement from styled text.

RichTextAreaElement(String) - Constructor for class dev.tamboui.toolkit.elements.RichTextAreaElement
Creates a RichTextAreaElement from a string.

RichTextElement - Class in dev.tamboui.toolkit.elements
A simple inline element for displaying styled `Text`.

RichTextElement() - Constructor for class dev.tamboui.toolkit.elements.RichTextElement
Creates an empty rich text element.

RichTextElement(Text) - Constructor for class dev.tamboui.toolkit.elements.RichTextElement
Creates a rich text element with the specified text.

RichTextElement(String) - Constructor for class dev.tamboui.toolkit.elements.RichTextElement
Creates a rich text element from a plain string.

RichTextState - Class in dev.tamboui.style
State for managing scroll position and viewport information in scrollable text elements.

RichTextState() - Constructor for class dev.tamboui.style.RichTextState
Creates a new RichTextState with default values.

right() - Method in class dev.tamboui.layout.Margin
Returns the right margin.

right() - Method in class dev.tamboui.layout.Padding
Returns the right padding.

right() - Method in class dev.tamboui.layout.Rect
Returns the right edge (exclusive).

right() - Method in class dev.tamboui.text.Line
Returns a new line with right alignment.

right() - Method in class dev.tamboui.text.Text
Returns a new text with right alignment.

right() - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Aligns text to the right.

right() - Method in class dev.tamboui.toolkit.elements.MarkupTextElement
Aligns text to the right.

right() - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Aligns text to the right.

right() - Method in class dev.tamboui.toolkit.elements.RichTextElement
Aligns text to the right.

right() - Method in class dev.tamboui.toolkit.elements.TextElement
Aligns text to the right.

right() - Method in class dev.tamboui.widgets.block.Title
Returns a new right-aligned title.

right() - Method in class dev.tamboui.widgets.paragraph.Paragraph.Builder
Sets right alignment.

right(Element) - Method in class dev.tamboui.toolkit.elements.DockElement
Sets the right region element.

right(Element, Constraint) - Method in class dev.tamboui.toolkit.elements.DockElement
Sets the right region element with a width constraint.

right(Widget) - Method in class dev.tamboui.layout.dock.Dock.Builder
Sets the right region widget.

RIGHT - Enum constant in enum class dev.tamboui.layout.Alignment
Right-aligned.

RIGHT - Enum constant in enum class dev.tamboui.tui.event.KeyCode
Right arrow key.

RIGHT - Enum constant in enum class dev.tamboui.tui.event.MouseButton
Right mouse button (button 3).

RIGHT - Enum constant in enum class dev.tamboui.widgets.block.Borders

Right border.

RIGHT - Enum constant in enum class dev.tamboui.widgets.chart.LegendPosition
Right side, vertically centered

RIGHT_CLICK - Static variable in class dev.tamboui.tui.bindings.Actions
Secondary click (right mouse button press).

RIGHT_INDICATOR - Static variable in class dev.tamboui.widgets.select.Select
CSS property for the right navigation indicator.

RIGHT_ONLY - Static variable in enum class dev.tamboui.widgets.block.Borders
Right border only.

RIGHT_TO_LEFT - Enum constant in enum class dev.tamboui.tfx.Motion
Movement from right to left

RIGHT_TO_LEFT - Enum constant in enum class dev.tamboui.widgets.sparkline.Sparkline.RenderDirection
Render data from right to left.

rightClick() - Static method in class dev.tamboui.tui.bindings.MouseTrigger
Creates a trigger for right mouse button click (press).

rightIndicator() - Method in class dev.tamboui.widgets.select.Select
Returns the right navigation indicator.

rightIndicator(String) - Method in class dev.tamboui.widgets.select.Select.Builder
Sets the right navigation indicator.

rightToLeft() - Method in class dev.tamboui.toolkit.elements.SparklineElement
Renders data from right to left.

rightToLeft(float) - Static method in class dev.tamboui.tfx.pattern.SweepPattern
Creates a right-to-left sweep pattern.

rightVertical() - Method in class dev.tamboui.widgets.block.BorderSet
Returns the right vertical border character.

rightVertical(String) - Method in class dev.tamboui.widgets.block.BorderSet.Builder
Sets the right vertical border character.

rightWidth(Constraint) - Method in class dev.tamboui.layout.dock.Dock.Builder
Sets the width constraint for the right region.

rightWidth(Constraint) - Method in class dev.tamboui.toolkit.elements.DockElement
Sets the width constraint for the right region.

root() - Method in interface dev.tamboui.widgets.tree.TreeModel
Returns the root node of the tree.

root() - Method in class dev.tamboui.widgets.tree.TreeNode

roots(TreeNode...) - Method in class dev.tamboui.toolkit.elements.TreeElement
Sets the root nodes.

roots(List) - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Sets the root nodes from a list.

roots(T...) - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Sets the root nodes (for functional approach or multiple roots).

round(float) - Static method in class dev.tamboui.tfx.TFxMath
Rounds a float value to the nearest integer.

rounded() - Method in class dev.tamboui.toolkit.elements.BarChartElement
Uses rounded borders.

rounded() - Method in class dev.tamboui.toolkit.elements.CalendarElement
Uses rounded borders.

rounded() - Method in class dev.tamboui.toolkit.elements.CanvasElement
Uses rounded borders.

rounded() - Method in class dev.tamboui.toolkit.elements.ChartElement
Uses rounded borders.

rounded() - Method in class dev.tamboui.toolkit.elements.DialogElement
Sets the border type to rounded.

rounded() - Method in class dev.tamboui.toolkit.elements.FormElement
Uses rounded borders for all field inputs.

rounded() - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Uses rounded borders for the input.

rounded() - Method in class dev.tamboui.toolkit.elements.GaugeElement
Sets rounded borders.

rounded() - Method in class dev.tamboui.toolkit.elements.ListElement
Uses rounded borders.

rounded() - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Uses rounded borders.

rounded() - Method in class dev.tamboui.toolkit.elements.Panel
Sets the border type to rounded.

rounded() - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Uses rounded borders.

rounded() - Method in class dev.tamboui.toolkit.elements.SparklineElement
Uses rounded borders.

rounded() - Method in class dev.tamboui.toolkit.elements.TableElement
Uses rounded borders.

rounded() - Method in class dev.tamboui.toolkit.elements.TabsElement
Uses rounded borders.

rounded() - Method in class dev.tamboui.toolkit.elements.TextAreaElement
Uses rounded borders.

rounded() - Method in class dev.tamboui.toolkit.elements.TextInputElement
Uses rounded borders.

rounded() - Method in class dev.tamboui.toolkit.elements.TreeElement
Uses rounded borders.

ROUNDED - Enum constant in enum class dev.tamboui.widgets.block.BorderType
Rounded border using single-line box-drawing characters with rounded corners.

route(Event) - Method in class dev.tamboui.toolkit.event.EventRouter
Routes an event to the appropriate element(s).

RoutingEvent - Class in dev.tamboui.toolkit.jfr
JFR duration event for a single toolkit routing operation.

row() - Method in class dev.tamboui.layout.grid.GridArea.AreaBounds
Returns the start row (0-based).

row() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty row.

row(Element...) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a horizontal row layout.

row(Row) - Method in class dev.tamboui.toolkit.elements.TableElement
Adds a row.

row(String...) - Method in class dev.tamboui.toolkit.elements.TableElement
Adds a row from strings.

row(Supplier) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a row with lazy content.

Row - Class in dev.tamboui.toolkit.elements

A horizontal layout container that arranges children in a row.

Row - Class in dev.tamboui.widgets.table
A row in a `Table`.

Row() - Constructor for class dev.tamboui.toolkit.elements.Row
Creates an empty row.

Row(Element...) - Constructor for class dev.tamboui.toolkit.elements.Row
Creates a row with the given children.

ROW_FIRST - Enum constant in enum class dev.tamboui.layout.columns.ColumnOrder
Items fill left-to-right, then top-to-bottom.

rowConstraints(Constraint...) - Method in class dev.tamboui.layout.grid.Grid.AreaBuilder
Sets the height constraints for rows.

rowConstraints(Constraint...) - Method in class dev.tamboui.layout.grid.Grid.ChildrenBuilder
Sets the height constraints for rows.

rowConstraints(List) - Method in class dev.tamboui.layout.grid.Grid.AreaBuilder
Sets the height constraints for rows from a list.

rowConstraints(List) - Method in class dev.tamboui.layout.grid.Grid.ChildrenBuilder
Sets the height constraints for rows from a list.

rowCount(int) - Method in class dev.tamboui.layout.grid.Grid.ChildrenBuilder
Sets the number of rows.

rowHeights(int...) - Method in class dev.tamboui.layout.columns.Columns.Builder
Sets explicit row heights.

rowHeights(int...) - Method in class dev.tamboui.layout.grid.Grid.ChildrenBuilder
Sets explicit row heights.

rows() - Method in class dev.tamboui.layout.grid.GridArea
Returns the number of rows in the grid template.

rows() - Method in class dev.tamboui.layout.Rect
Returns an iterator over rows in this rectangle.

rows() - Method in class dev.tamboui.toolkit.elements.GridSize
Returns the number of rows (0 means auto-derive from children count).

rows() - Method in class dev.tamboui.widgets.table.Table
Returns the rows in this table.

rows(Row...) - Method in class dev.tamboui.toolkit.elements.TableElement
Sets all rows.

rows(Row...) - Method in class dev.tamboui.widgets.table.Table.Builder
Sets the data rows.

rows(List) - Method in class dev.tamboui.toolkit.elements.TableElement
Sets all rows from a list.

rows(List) - Method in class dev.tamboui.widgets.table.Table.Builder
Sets the data rows.

rowSpacing(int) - Method in class dev.tamboui.toolkit.elements.FlowElement
Sets the vertical spacing between wrapped rows.

rowSpan() - Method in class dev.tamboui.layout.grid.GridArea.AreaBounds
Returns the number of rows spanned.

rowStyleResolver(BiFunction) - Method in class dev.tamboui.widgets.table.Table.Builder
Sets a function to resolve styles for each row based on position.

Rule - Class in dev.tamboui.css.model
Represents a CSS rule consisting of a selector and declarations.

Rule(Selector, Map, int) - Constructor for class dev.tamboui.css.model.Rule
Creates a new rule.

rules() - Method in class dev.tamboui.css.model.Stylesheet
Returns the CSS rules defined in this stylesheet.

run() - Method in class dev.tamboui.toolkit.app.InlineApp
Runs the application.

run() - Method in class dev.tamboui.toolkit.app.ToolkitApp
Runs the application.

run() - Method in class dev.tamboui.tui.event.UiRunnable
Executes the enclosed action.

run() - Method in class dev.tamboui.tui.TerminalInputReader

run() - Method in class dev.tamboui.tui.TuiRunner.ConfiguredRunner
Runs the TUI application.

run(EventHandler, Renderer) - Method in class dev.tamboui.tui.TuiRunner
Runs the main event loop with the given handler and renderer.

run(InlineEventHandler, Renderer) - Method in class dev.tamboui.tui.InlineTuiRunner
Runs the main event loop with the given handler and renderer.

run(Supplier) - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner
Runs the application with the given element supplier.

run(Supplier) - Method in class dev.tamboui.toolkit.app.ToolkitRunner
Runs the application with the given element supplier.

runLater(Runnable) - Method in class dev.tamboui.tui.InlineTuiRunner
Queues an action to be executed on the render thread.

runLater(Runnable) - Method in class dev.tamboui.tui.TuiRunner
Queues an action to be executed on the render thread.

runner() - Method in class dev.tamboui.toolkit.app.InlineApp
Returns the current runner, or null if not running.

runner() - Method in class dev.tamboui.toolkit.app.ToolkitApp
Returns the current runner, or null if not running.

runner() - Method in class dev.tamboui.tui.TuiRunner.ConfiguredRunner
Returns the underlying TuiRunner.

running() - Method in class dev.tamboui.tfx.Effect
Returns true if the effect is still running.

running() - Method in interface dev.tamboui.tfx.Shader
Returns true if the shader is still running.

runningCount() - Method in class dev.tamboui.tfx.toolkit.ElementEffectRegistry
Returns the number of running effects (global + element-targeted + styled-area-targeted).

runOnRenderThread(Runnable) - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner
Executes an action on the render thread.

runOnRenderThread(Runnable) - Method in class dev.tamboui.toolkit.app.ToolkitRunner
Executes an action on the render thread.

runOnRenderThread(Runnable) - Method in class dev.tamboui.tui.InlineTuiRunner
Executes an action on the render thread.

runOnRenderThread(Runnable) - Method in class dev.tamboui.tui.TuiRunner
Executes an action on the render thread.

RuntimeIOException - Exception Class in dev.tamboui.error
Exception thrown when a terminal I/O operation fails.

RuntimeIOException(String) - Constructor for exception class dev.tamboui.error.RuntimeIOException
Creates a new runtime/unchecked IO exception with the given message.

RuntimeIOException(String, Throwable) - Constructor for exception class dev.tamboui.error.RuntimeIOException

Creates a new runtime/unchecked I/O exception with the given message and cause.

runTui(TuiRunner) - Method in class dev.tamboui.picocli.TuiCommand
Runs the TUI application.

runWith(TuiRunner, EventHandler, Renderer) - Method in class dev.tamboui.tfx.tui.TfxIntegration
Utility method to run a TUI application with TFX integration.

S

SA_RESETHAND - Static variable in class dev.tamboui.backend.panama.unix.LibC
Sigaction flag: reset signal handler to default after first signal.

SA_RESTART - Static variable in class dev.tamboui.backend.panama.unix.LibC
Sigaction flag: restart interrupted system calls.

SafeServiceLoader - Class in dev.tamboui.util
ServiceLoader that is more resilient to errors by skipping broken providers and continuing to try other providers.

scaledDimensionsToFill(int, int) - Method in class dev.tamboui.image.ImageData
Calculates the scaled dimensions to fill the given bounds while preserving aspect ratio.

scaledDimensionsToFit(int, int) - Method in class dev.tamboui.image.ImageData
Calculates the scaled dimensions to fit within the given bounds while preserving aspect ratio.

scaling() - Method in class dev.tamboui.image.Image
Returns the scaling mode.

scaling(ImageScaling) - Method in class dev.tamboui.image.Image.Builder
Sets the scaling mode.

SCATTER - Enum constant in enum class dev.tamboui.widgets.chart.GraphType
Renders individual points without connecting lines.

schedule(Runnable, Duration) - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner
Schedules an action to run after a delay.

schedule(Runnable, Duration) - Method in class dev.tamboui.toolkit.app.ToolkitRunner
Schedules an action to run after a delay.

scheduler() - Method in class dev.tamboui.tui.InlineTuiConfig
Returns the externally-managed scheduler, or null if the runner should create its own.

scheduler() - Method in class dev.tamboui.tui.InlineTuiRunner
Returns the shared scheduler for scheduling tasks.

scheduler() - Method in class dev.tamboui.tui.TuiConfig
Returns the externally-managed scheduler, or null if the runner should create its own.

scheduler() - Method in class dev.tamboui.tui.TuiRunner
Returns the shared scheduler for scheduling tasks.

scheduler(ScheduledExecutorService) - Method in class dev.tamboui.tui.InlineTuiConfig.Builder
Sets an externally-managed scheduler.

scheduler(ScheduledExecutorService) - Method in class dev.tamboui.tui.TuiConfig.Builder
Sets an externally-managed scheduler.

scheduleRepeating(Runnable, Duration) - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner
Schedules an action to run repeatedly at a fixed interval.

scheduleRepeating(Runnable, Duration) - Method in class dev.tamboui.toolkit.app.ToolkitRunner
Schedules an action to run repeatedly at a fixed interval.

scheduleWithFixedDelay(Runnable, Duration) - Method in class dev.tamboui.toolkit.app.ToolkitRunner
Schedules an action to run repeatedly with a fixed delay between runs.

scope(boolean, Element...) - Static method in class dev.tamboui.toolkit.InlineToolkit
Creates an inline scope element with the given visibility and children.

scope(Element...) - Static method in class dev.tamboui.toolkit.InlineToolkit
Creates an inline scope element with the given children.

scroll(int) - Method in class dev.tamboui.widgets.error.ErrorDisplay.Builder
Sets the scroll offset.

scroll(int) - Method in class dev.tamboui.widgets.paragraph.Paragraph.Builder
Sets the scroll offset.

SCROLL - Static variable in class dev.tamboui.tui.bindings.Actions
Scroll (mouse scroll wheel).

SCROLL_DOWN - Enum constant in enum class dev.tamboui.tui.event.MouseEventKind
Scroll wheel was scrolled down.

SCROLL_DOWN - Static variable in class dev.tamboui.tui.bindings.Actions
Scroll down (mouse scroll wheel down).

SCROLL_TO_END - Enum constant in enum class dev.tamboui.widgets.list.ScrollMode
Always scroll to show the last items.

SCROLL_UP - Enum constant in enum class dev.tamboui.tui.event.MouseEventKind
Scroll wheel was scrolled up.

SCROLL_UP - Static variable in class dev.tamboui.tui.bindings.Actions
Scroll up (mouse scroll wheel up).

scrollbar() - Method in class dev.tamboui.toolkit.elements.ListElement
Enables showing a scrollbar on the right side of the list (always visible).

scrollbar() - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Enables a scrollbar (always visible).

scrollbar() - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Enables a scrollbar (always visible).

scrollbar() - Method in class dev.tamboui.toolkit.elements.TreeElement
Enables showing a scrollbar (always visible).

scrollbar() - Static method in class dev.tamboui.toolkit.Toolkit
Creates a scrollbar.

scrollbar() - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Enables the scrollbar.

scrollbar(int, int, int) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a scrollbar with the given parameters.

scrollbar(ScrollBarPolicy) - Method in class dev.tamboui.toolkit.elements.ListElement
Sets the scrollbar policy.

scrollbar(ScrollBarPolicy) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Sets the scrollbar policy.

scrollbar(ScrollBarPolicy) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Sets the scrollbar policy.

scrollbar(ScrollBarPolicy) - Method in class dev.tamboui.toolkit.elements.TreeElement
Sets the scrollbar policy.

scrollbar(ScrollbarState) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a scrollbar with the given state.

Scrollbar - Class in dev.tamboui.widgets.scrollbar
A scrollbar widget for displaying scroll position.

SCROLLBAR_POLICY - Static variable in class dev.tamboui.toolkit.elements.ListElement
CSS property for scrollbar policy.

SCROLLBAR_POLICY - Static variable in class dev.tamboui.toolkit.elements.TreeElement
CSS property for scrollbar policy.

Scrollbar.Builder - Class in dev.tamboui.widgets.scrollbar

Builder for `Scrollbar`.

Scrollbar.SymbolSet - Class in dev.tamboui.widgets.scrollbar
Scrollbar symbol set for rendering.

ScrollbarElement - Class in dev.tamboui.toolkit.elements
A DSL wrapper for the Scrollbar widget.

ScrollbarElement() - Constructor for class dev.tamboui.toolkit.elements.ScrollbarElement
Creates a scrollbar element with default vertical right orientation.

ScrollbarOrientation - Enum Class in dev.tamboui.widgets.scrollbar
Orientation and position of a `Scrollbar`.

scrollBarPolicy(ScrollBarPolicy) - Method in class dev.tamboui.widgets.list.ListWidget.Builder
Sets the scrollbar policy.

ScrollBarPolicy - Enum Class in dev.tamboui.widgets.common
Policy for displaying a scrollbar.

ScrollbarState - Class in dev.tamboui.widgets.scrollbar
State for a `Scrollbar` widget.

ScrollbarState() - Constructor for class dev.tamboui.widgets.scrollbar.ScrollbarState
Creates a new scrollbar state with default values.

ScrollbarState(int) - Constructor for class dev.tamboui.widgets.scrollbar.ScrollbarState
Creates a new scrollbar state with the given content length.

scrollbarThumbColor(Color) - Method in class dev.tamboui.toolkit.elements.ListElement
Sets the scrollbar thumb color.

scrollbarThumbColor(Color) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Sets the scrollbar thumb color.

scrollbarThumbColor(Color) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Sets the scrollbar thumb color.

scrollbarThumbColor(Color) - Method in class dev.tamboui.toolkit.elements.TreeElement
Sets the scrollbar thumb color.

scrollbarThumbStyle(Style) - Method in class dev.tamboui.widgets.list.ListWidget.Builder
Sets the scrollbar thumb style.

scrollbarThumbStyle(Style) - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Sets the scrollbar thumb style.

scrollbarTrackColor(Color) - Method in class dev.tamboui.toolkit.elements.ListElement
Sets the scrollbar track color.

scrollbarTrackColor(Color) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Sets the scrollbar track color.

scrollbarTrackColor(Color) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Sets the scrollbar track color.

scrollbarTrackColor(Color) - Method in class dev.tamboui.toolkit.elements.TreeElement
Sets the scrollbar track color.

scrollbarTrackStyle(Style) - Method in class dev.tamboui.widgets.list.ListWidget.Builder
Sets the scrollbar track style.

scrollbarTrackStyle(Style) - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Sets the scrollbar track style.

scrollBy(int) - Method in class dev.tamboui.widgets.list.ListState
Adjusts the scroll offset by a delta.

scrollBy(int) - Method in class dev.tamboui.widgets.scrollbar.ScrollbarState
Scrolls by the given amount.

scrollCol() - Method in class dev.tamboui.style.RichTextState
Returns the current horizontal scroll offset (number of columns scrolled from left).

scrollCol() - Method in class dev.tamboui.widgets.input.TextAreaState
Returns the horizontal scroll offset.

scrollDown() - Method in class dev.tamboui.style.RichTextState
Scrolls down by one line.

scrollDown() - Static method in class dev.tamboui.tui.bindings.MouseTrigger
Creates a trigger for scroll wheel down.

scrollDown(int) - Method in class dev.tamboui.backend.aesh.AeshBackend

scrollDown(int) - Method in class dev.tamboui.backend.jline3.JLineBackend

scrollDown(int) - Method in class dev.tamboui.backend.panama.PanamaBackend

scrollDown(int) - Method in class dev.tamboui.internal.record.RecordingBackend

scrollDown(int) - Method in class dev.tamboui.style.RichTextState
Scrolls down by the specified number of lines.

scrollDown(int) - Method in interface dev.tamboui.terminal.Backend
Scrolls the screen down by the given number of lines.

scrollDown(int, int) - Static method in class dev.tamboui.tui.event.MouseEvent
Creates a scroll down event.

scrollDown(int, int) - Method in class dev.tamboui.widgets.input.TextAreaState
Scrolls down by the given amount of rows.

scrollLeft() - Method in class dev.tamboui.style.RichTextState
Scrolls left by one column.

scrollLeft(int) - Method in class dev.tamboui.style.RichTextState
Scrolls left by the specified number of columns.

scrollMode(ScrollMode) - Method in class dev.tamboui.widgets.list.ListWidget.Builder
Sets the scroll mode.

ScrollMode - Enum Class in dev.tamboui.widgets.list
Scroll mode for list widgets.

scrollPercentage() - Method in class dev.tamboui.widgets.scrollbar.ScrollbarState
Calculates the scroll percentage (0.0 to 1.0).

scrollRight() - Method in class dev.tamboui.style.RichTextState
Scrolls right by one column.

scrollRight(int) - Method in class dev.tamboui.style.RichTextState
Scrolls right by the specified number of columns.

scrollRow() - Method in class dev.tamboui.style.RichTextState
Returns the current vertical scroll offset (number of lines scrolled from top).

scrollRow() - Method in class dev.tamboui.widgets.input.TextAreaState
Returns the vertical scroll offset.

scrollToBottom() - Method in class dev.tamboui.style.RichTextState
Scrolls to the bottom of the content.

scrollToEnd() - Method in class dev.tamboui.toolkit.elements.ListElement
Scrolls the list to show the last items.

scrollToEnd(int, List) - Method in class dev.tamboui.widgets.list.ListState
Scrolls the list to show the last items without changing selection.

scrollToLine(int) - Method in class dev.tamboui.style.RichTextState
Scrolls to show the specified line.

scrollToLine(int) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Scrolls to show the specified line.

scrollToLine(int) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement

Scrolls to show the specified line.

scrollToSelected(int, int[]) - Method in class dev.tamboui.widgets.list.ListState
Scrolls the list to ensure the selected item is visible, using pre-computed item heights.

scrollToSelected(int, int, int, int) - Method in class dev.tamboui.widgets.tree.TreeState
Adjusts scroll offset to keep the selected item visible within the viewport.

scrollToSelected(int, List) - Method in class dev.tamboui.widgets.list.ListState
Scrolls the list to ensure the selected item is visible.

scrollToSelected(int, List) - Method in class dev.tamboui.widgets.table.TableState
Scrolls to make the selected row visible.

scrollToTop() - Method in class dev.tamboui.style.RichTextState
Scrolls to the top of the content.

scrollUp() - Method in class dev.tamboui.style.RichTextState
Scrolls up by one line.

scrollUp() - Static method in class dev.tamboui.tui.bindings.MouseTrigger
Creates a trigger for scroll wheel up.

scrollUp(int) - Method in class dev.tamboui.backend.aesh.AeshBackend

scrollUp(int) - Method in class dev.tamboui.backend.jline3.JLineBackend

scrollUp(int) - Method in class dev.tamboui.backend.panama.PanamaBackend

scrollUp(int) - Method in class dev.tamboui.internal.record.RecordingBackend

scrollUp(int) - Method in class dev.tamboui.style.RichTextState
Scrolls up by the specified number of lines.

scrollUp(int) - Method in interface dev.tamboui.terminal.Backend
Scrolls the screen up by the given number of lines.

scrollUp(int) - Method in class dev.tamboui.widgets.input.TextAreaState
Scrolls up by the given amount of rows.

scrollUp(int, int) - Static method in class dev.tamboui.tui.event.MouseEvent
Creates a scroll up event.

select(int) - Method in class dev.tamboui.widgets.table.TableState
Selects the row at the given index.

select(int) - Method in class dev.tamboui.widgets.tabs.TabsState
Selects the tab at the given index.

select(int) - Method in class dev.tamboui.widgets.tree.TreeState
Sets the selected index.

select(Integer) - Method in class dev.tamboui.widgets.list.ListState
Selects the item at the given index.

Select - Class in dev.tamboui.widgets.select
An inline select widget that displays the current selection with navigation indicators.

SELECT - Enum constant in enum class dev.tamboui.widgets.form.FieldType
Dropdown selection from a list of options.

SELECT - Static variable in class dev.tamboui.tui.bindings.Actions
Select or confirm (Enter or Space).

Select.Builder - Class in dev.tamboui.widgets.select
Builder for `Select`.

selected() - Method in class dev.tamboui.toolkit.elements.ListElement
Returns the currently selected index.

selected() - Method in class dev.tamboui.toolkit.elements.TreeElement
Returns the currently selected index in the flattened visible list.

selected() - Method in class dev.tamboui.widgets.list.ListState
Returns the index of the currently selected item, or null if nothing is selected.

selected() - Method in class dev.tamboui.widgets.table.TableState
Returns the index of the currently selected row, or null if nothing is selected.

selected() - Method in class dev.tamboui.widgets.tabs.TabsState
Returns the index of the currently selected tab, or null if nothing is selected.

selected() - Method in class dev.tamboui.widgets.tree.TreeState
Returns the selected index in the flattened visible list.

selected(int) - Method in class dev.tamboui.toolkit.elements.ListElement
Sets the selected index.

selected(int) - Method in class dev.tamboui.toolkit.elements.TabsElement
Sets the selected tab index.

selected(int) - Method in class dev.tamboui.toolkit.elements.TreeElement
Sets the selected index in the flattened visible list.

SELECTED_COLOR - Static variable in class dev.tamboui.widgets.select.Select
CSS property for the selected value foreground color.

SELECTED_COLOR - Static variable in class dev.tamboui.widgets.toggle.Toggle
CSS property for the selected color (inline choice mode).

SELECTED_INDICATOR - Static variable in class dev.tamboui.widgets.toggle.Toggle
CSS property for the selected indicator (inline choice mode).

selectedColor(Color) - Method in class dev.tamboui.widgets.select.Select.Builder
Sets the foreground color for the selected value.

selectedColor(Color) - Method in class dev.tamboui.widgets.toggle.Toggle.Builder
Sets the color for the selected option indicator (inline choice mode).

selectedIndex() - Method in class dev.tamboui.widgets.form.SelectFieldState
Returns the currently selected index.

selectedIndex() - Method in class dev.tamboui.widgets.select.SelectState
Returns the currently selected index.

selectedIndicator(String) - Method in class dev.tamboui.widgets.toggle.Toggle.Builder
Sets the indicator for the selected option (inline choice mode).

selectedNode() - Method in class dev.tamboui.toolkit.elements.TreeElement
Returns the currently selected tree node, or `null` if the tree is empty.

selectedValue() - Method in class dev.tamboui.widgets.form.SelectFieldState
Returns the currently selected value.

selectedValue() - Method in class dev.tamboui.widgets.select.SelectState
Returns the currently selected value.

selectField(String) - Method in class dev.tamboui.widgets.form.FormState
Returns the SelectFieldState for the given field name.

selectField(String, List) - Method in class dev.tamboui.widgets.form.FormState.Builder
Adds a select field with the given options, selecting the first option.

selectField(String, List, int) - Method in class dev.tamboui.widgets.form.FormState.Builder
Adds a select field with the given options and initial selection.

SelectFieldState - Class in dev.tamboui.widgets.form
State for a select form field (dropdown selection).

SelectFieldState(String...) - Constructor for class dev.tamboui.widgets.form.SelectFieldState
Creates a new select field state with the given options, selecting the first option.

SelectFieldState(List) - Constructor for class dev.tamboui.widgets.form.SelectFieldState
Creates a new select field state with the given options, selecting the first option.

SelectFieldState(List, int) - Constructor for class dev.tamboui.widgets.form.SelectFieldState

Creates a new select field state with the given options and initial selection.

selectFirst() - Method in class dev.tamboui.toolkit.elements.ListElement
Selects the first item.

selectFirst() - Method in class dev.tamboui.toolkit.elements.TreeElement
Selects the first visible node.

selectFirst() - Method in class dev.tamboui.widgets.list.ListState
Selects the first item.

selectFirst() - Method in class dev.tamboui.widgets.select.SelectState
Selects the first option.

selectFirst() - Method in class dev.tamboui.widgets.table.TableState
Selects the first row.

selectFirst() - Method in class dev.tamboui.widgets.tabs.TabsState
Selects the first tab.

selectFirst() - Method in class dev.tamboui.widgets.tree.TreeState
Selects the first item.

selectIndex(int) - Method in class dev.tamboui.widgets.form.SelectFieldState
Selects the option at the given index.

selectIndex(int) - Method in class dev.tamboui.widgets.select.SelectState
Sets the selected index.

selectIndex(String) - Method in class dev.tamboui.widgets.form.FormState
Returns the currently selected index for the given field name.

selectIndex(String, int) - Method in class dev.tamboui.widgets.form.FormState
Selects the option at the given index for the given field name.

selectLast() - Method in class dev.tamboui.toolkit.elements.TreeElement
Selects the last visible node.

selectLast() - Method in class dev.tamboui.widgets.select.SelectState
Selects the last option.

selectLast(int) - Method in class dev.tamboui.toolkit.elements.ListElement
Selects the last item.

selectLast(int) - Method in class dev.tamboui.widgets.list.ListState
Selects the last item.

selectLast(int) - Method in class dev.tamboui.widgets.table.TableState
Selects the last row.

selectLast(int) - Method in class dev.tamboui.widgets.tabs.TabsState
Selects the last tab.

selectLast(int) - Method in class dev.tamboui.widgets.tree.TreeState
Selects the last item.

selectNext() - Method in class dev.tamboui.toolkit.elements.TreeElement
Selects the next visible node.

selectNext() - Method in class dev.tamboui.widgets.form.SelectFieldState
Selects the next option, wrapping to the first if at the end.

selectNext() - Method in class dev.tamboui.widgets.select.SelectState
Selects the next option, wrapping to the first if at the end.

selectNext(int) - Method in class dev.tamboui.toolkit.elements.ListElement
Selects the next item.

selectNext(int) - Method in class dev.tamboui.widgets.list.ListState
Selects the next item.

selectNext(int) - Method in class dev.tamboui.widgets.table.TableState
Selects the next row.

selectNext(int) - Method in class dev.tamboui.widgets.tabs.TabsState
Selects the next tab, wrapping to the first if at the end.

selectNext(int) - Method in class dev.tamboui.widgets.tree.TreeState
Selects the next item if possible.

selector() - Method in class dev.tamboui.css.model.Rule
Returns the selector that determines which elements this rule applies to.

Selector - Interface in dev.tamboui.css.selector
Represents a CSS selector that matches elements.

SelectorParser - Class in dev.tamboui.css.selector
Parses CSS selector strings into `Selector` objects.

selectPrevious() - Method in class dev.tamboui.toolkit.elements.ListElement
Selects the previous item.

selectPrevious() - Method in class dev.tamboui.toolkit.elements.TreeElement
Selects the previous visible node.

selectPrevious() - Method in class dev.tamboui.widgets.form.SelectFieldState
Selects the previous option, wrapping to the last if at the beginning.

selectPrevious() - Method in class dev.tamboui.widgets.list.ListState
Selects the previous item.

selectPrevious() - Method in class dev.tamboui.widgets.select.SelectState
Selects the previous option, wrapping to the last if at the beginning.

selectPrevious() - Method in class dev.tamboui.widgets.table.TableState
Selects the previous row.

selectPrevious() - Method in class dev.tamboui.widgets.tree.TreeState
Selects the previous item if possible.

selectPrevious(int) - Method in class dev.tamboui.widgets.tabs.TabsState
Selects the previous tab, wrapping to the last if at the beginning.

SelectState - Class in dev.tamboui.widgets.select
State for the `Select` widget, tracking options and selected index.

SelectState(String...) - Constructor for class dev.tamboui.widgets.select.SelectState
Creates a new state with the given options.

SelectState(List, int) - Constructor for class dev.tamboui.widgets.select.SelectState
Creates a new state with the given options and initial selection.

selectValue(String) - Method in class dev.tamboui.widgets.form.FormState
Returns the currently selected value for the given field name.

selectValues() - Method in class dev.tamboui.widgets.form.FormState
Returns all select field values as a map.

self() - Method in class dev.tamboui.toolkit.element.StyledElement
Returns this element cast to the concrete type for method chaining.

Semicolon(Token.Position) - Constructor for class dev.tamboui.css.parser.Token.Semicolon
Creates a semicolon token.

separator(String) - Method in class dev.tamboui.widgets.toggle.Toggle.Builder
Sets the separator between choices (inline choice mode).

sequence(Effect...) - Static method in class dev.tamboui.tfx.Fx
Runs the effects in sequence, one after the other.

sequence(List) - Static method in class dev.tamboui.tfx.Fx
Runs the effects in sequence, one after the other.

SequentialEffect - Class in dev.tamboui.tfx.effects
Shader implementation that runs multiple effects sequentially, one after another.

set() - Method in enum class dev.tamboui.widgets.block.BorderType

Returns the border characters for this type.

set(int, int, Cell) - Method in class dev.tamboui.buffer.Buffer
Sets the cell at the given position.

set(Position, Cell) - Method in class dev.tamboui.buffer.Buffer
Sets the cell at the given position.

set(PropertyDefinition, T) - Method in class dev.tamboui.css.cascade.CssStyleResolver.Builder
Sets a typed property value.

setActiveStylesheet(String) - Method in class dev.tamboui.css.engine.StyleEngine
Sets the active named stylesheet.

setArea(Rect) - Method in class dev.tamboui.tfx.Effect
Updates the area where this effect is applied.

setArea(Rect) - Method in class dev.tamboui.tfx.effects.DissolveShader

setArea(Rect) - Method in class dev.tamboui.tfx.effects.ExpandShader

setArea(Rect) - Method in class dev.tamboui.tfx.effects.FadeShader

setArea(Rect) - Method in class dev.tamboui.tfx.effects.PaintShader

setArea(Rect) - Method in class dev.tamboui.tfx.effects.ParallelEffect

setArea(Rect) - Method in class dev.tamboui.tfx.effects.SequentialEffect

setArea(Rect) - Method in class dev.tamboui.tfx.effects.SlideShader

setArea(Rect) - Method in class dev.tamboui.tfx.effects.StretchShader

setArea(Rect) - Method in class dev.tamboui.tfx.effects.SweepShader

setArea(Rect) - Method in interface dev.tamboui.tfx.Shader
Sets the area where the shader effect will be applied.

setBg(Color) - Method in class dev.tamboui.tfx.CellIterator.MutableCell
Sets the cell's background color directly.

setBindings(Bindings) - Method in class dev.tamboui.toolkit.element.DefaultRenderContext
Sets the bindings used for action matching.

setBindings(Bindings) - Method in class dev.tamboui.tui.bindings.ActionHandler
Sets the bindings used for matching events to actions.

setBooleanValue(String, boolean) - Method in class dev.tamboui.widgets.form.FormState
Sets the boolean value for the given field name.

setCell(Cell) - Method in class dev.tamboui.tfx.CellIterator.MutableCell
Sets the entire cell.

setCellFilter(CellFilter) - Method in class dev.tamboui.tfx.effects.DissolveShader

setCellFilter(CellFilter) - Method in class dev.tamboui.tfx.effects.ExpandShader

setCellFilter(CellFilter) - Method in class dev.tamboui.tfx.effects.FadeShader

setCellFilter(CellFilter) - Method in class dev.tamboui.tfx.effects.PaintShader

setCellFilter(CellFilter) - Method in class dev.tamboui.tfx.effects.ParallelEffect

setCellFilter(CellFilter) - Method in class dev.tamboui.tfx.effects.SequentialEffect

setCellFilter(CellFilter) - Method in class dev.tamboui.tfx.effects.SlideShader

setCellFilter(CellFilter) - Method in class dev.tamboui.tfx.effects.StretchShader

setCellFilter(CellFilter) - Method in class dev.tamboui.tfx.effects.SweepShader

setCellFilter(CellFilter) - Method in interface dev.tamboui.tfx.Shader
Sets the cell filter for this shader.

setChecked(boolean) - Method in class dev.tamboui.widgets.checkbox.CheckboxState
Sets the checked state.

setColorSpace(TFxColorSpace) - Method in class dev.tamboui.tfx.effects.FadeShader

setColorSpace(TFxColorSpace) - Method in class dev.tamboui.tfx.effects.ParallelEffect

setColorSpace(TFxColorSpace) - Method in class dev.tamboui.tfx.effects.SequentialEffect

setColorSpace(TFxColorSpace) - Method in class dev.tamboui.tfx.effects.SweepShader

setColorSpace(TFxColorSpace) - Method in interface dev.tamboui.tfx.Shader
Sets the color space for this shader.

setConsoleMode(MemorySegment, int) - Static method in class dev.tamboui.backend.panama.windows.Kernel32
Sets the input mode of a console's input buffer or output mode of a screen buffer.

setContentHeight(int) - Method in class dev.tamboui.style.RichTextState
Sets the content height.

setContentHeight(int) - Method in class dev.tamboui.tui.InlineTuiRunner
Sets the content height for the next draw.

setContentWidth(int) - Method in class dev.tamboui.style.RichTextState
Sets the content width.

setCursorPosition(int, int) - Method in class dev.tamboui.terminal.Frame
Sets the cursor position using x and y coordinates.

setCursorPosition(Position) - Method in class dev.tamboui.internal.record.RecordingBackend

setCursorPosition(Position) - Method in class dev.tamboui.terminal.AbstractBackend
Sets the cursor to the given position and flushes.

setCursorPosition(Position) - Method in interface dev.tamboui.terminal.Backend
Sets the cursor position.

setCursorPosition(Position) - Method in class dev.tamboui.terminal.Frame
Sets the cursor position.

setExpanded(TreeNode, boolean) - Method in class dev.tamboui.widgets.tree.TreeNode

setExpanded(T, boolean) - Method in interface dev.tamboui.widgets.tree.TreeModel
Sets the expanded state of a node.

setFaultTolerant(boolean) - Method in class dev.tamboui.toolkit.element.DefaultRenderContext
Enables or disables fault-tolerant rendering.

setFg(Color) - Method in class dev.tamboui.tfx.CellIterator.MutableCell
Sets the cell's foreground color directly.

setFocus(String) - Method in class dev.tamboui.toolkit.focus.FocusManager
Sets focus to the element with the given ID.

setLine(int, int, Line) - Method in class dev.tamboui.buffer.Buffer
Sets a line at the given position.

setLine(int, Text) - Method in class dev.tamboui.inline.InlineDisplay
Sets a single line of styled text in the display area.

setLine(int, String) - Method in class dev.tamboui.inline.InlineDisplay
Sets a single line of text in the display area.

setLoopMode(LoopMode) - Method in interface dev.tamboui.tfx.Shader
Sets the loop mode for this shader's timer.

setOffset(int) - Method in class dev.tamboui.widgets.list.ListState
Sets the scroll offset directly.

setOffset(int) - Method in class dev.tamboui.widgets.table.TableState
Sets the scroll offset directly.

setOn(boolean) - Method in class dev.tamboui.widgets.toggle.ToggleState
Sets the on/off state.

setOptions(String...) - Method in class dev.tamboui.widgets.select.SelectState
Replaces the available options.

setOptions(List) - Method in class dev.tamboui.widgets.select.SelectState
Replaces the available options.

setPattern(Pattern) - Method in class dev.tamboui.tfx.effects.FadeShader

setPattern(Pattern) - Method in interface dev.tamboui.tfx.Shader
Sets the pattern for this shader.

setRaw(String, String) - Method in class dev.tamboui.css.cascade.CssStyleResolver.Builder
Sets a raw property value for lazy conversion.

setResult(EventResult) - Method in class dev.tamboui.toolkit.jfr.RoutingEvent
Sets the routing result label.

setSigactionFlags(MemorySegment, int) - Static method in class dev.tamboui.backend.panama.unix.LibC
Sets the flags in a sigaction structure.

setSigactionHandler(MemorySegment, MemorySegment) - Static method in class dev.tamboui.backend.panama.unix.LibC
Sets the handler pointer in a sigaction structure.

setSigactionMask(MemorySegment, int) - Static method in class dev.tamboui.backend.panama.unix.LibC
Sets the signal mask in a sigaction structure.

setSigactionTramp(MemorySegment, MemorySegment) - Static method in class dev.tamboui.backend.panama.unix.LibC
Sets the trampoline pointer in a sigaction structure.

setSpan(int, int, Span) - Method in class dev.tamboui.buffer.Buffer
Sets a span at the given position.

setString(int, int, String, Style) - Method in class dev.tamboui.buffer.Buffer
Sets a string at the given position with the given style.

setStyle(Rect, Style) - Method in class dev.tamboui.buffer.Buffer
Sets the style for all cells in the given area.

setStyle(Style) - Method in class dev.tamboui.tfx.CellIterator.MutableCell
Sets the cell's style.

setStyledAreaRegistry(StyledAreaRegistry) - Method in class dev.tamboui.terminal.Frame
Sets the styled area registry for tracking styled content.

setStyledContentListener(BiConsumer) - Method in class dev.tamboui.buffer.Buffer
Sets a listener to be notified when styled content is written to this buffer.

setStyleEngine(StyleEngine) - Method in class dev.tamboui.toolkit.element.DefaultRenderContext
Sets the style engine for CSS resolution.

setSymbol(String) - Method in class dev.tamboui.tfx.CellIterator.MutableCell
Sets the cell's symbol.

setText(String) - Method in class dev.tamboui.widgets.input.TextAreaState
Replaces the text content and moves the cursor to the end.

setText(String) - Method in class dev.tamboui.widgets.input.TextInputState
Replaces the text content.

setTextValue(String, String) - Method in class dev.tamboui.widgets.form.FormState
Sets the text value for the given field name.

setTick(long) - Method in class dev.tamboui.widgets.spinner.SpinnerState
Sets the tick to a specific value.

setTick(long) - Method in class dev.tamboui.widgets.wavetext.WaveTextState
Sets the tick to a specific value.

setValidationResult(String, ValidationResult) - Method in class dev.tamboui.widgets.form.FormState
Sets the validation result for the given field name.

setValue(boolean) - Method in class dev.tamboui.widgets.checkbox.CheckboxState
Alias for `CheckboxState.setChecked(boolean)` for compatibility with form state patterns.

setValue(boolean) - Method in class dev.tamboui.widgets.form.BooleanFieldState
Sets the value.

setValue(boolean) - Method in class dev.tamboui.widgets.toggle.ToggleState
Alias for `ToggleState.setOn(boolean)` for compatibility with form state patterns.

setViewportHeight(int) - Method in class dev.tamboui.style.RichTextState
Sets the viewport height.

setViewportWidth(int) - Method in class dev.tamboui.style.RichTextState
Sets the viewport width.

sevenEighths() - Method in class dev.tamboui.widgets.barchart.BarChart.BarSet
Returns the seven-eighths fill symbol.

sevenEighths() - Method in class dev.tamboui.widgets.sparkline.Sparkline.BarSet
Returns the seven-eighths fill symbol.

Shader - Interface in dev.tamboui.tfx
Interface representing a shader that applies visual effects to terminal cells.

Shape - Interface in dev.tamboui.widgets.canvas
A shape that can be drawn on a `Canvas`.

shift() - Method in class dev.tamboui.tui.event.KeyModifiers
Returns whether the Shift modifier is active.

SHIFT - Static variable in class dev.tamboui.tui.event.KeyModifiers
Only Shift pressed.

shiftClick() - Static method in class dev.tamboui.tui.bindings.MouseTrigger
Creates a trigger for Shift+left click.

show() - Method in class dev.tamboui.toolkit.elements.InlineScopeElement
Shows this scope (sets visibility to true).

showCursor() - Method in class dev.tamboui.backend.aesh.AeshBackend

showCursor() - Method in class dev.tamboui.backend.jline3.JLineBackend

showCursor() - Method in class dev.tamboui.backend.panama.PanamaBackend

showCursor() - Method in class dev.tamboui.internal.record.RecordingBackend

showCursor() - Method in interface dev.tamboui.terminal.Backend
Shows the cursor.

showCursor() - Method in class dev.tamboui.terminal.Terminal
Shows the cursor.

showCursor(boolean) - Method in class dev.tamboui.toolkit.elements.TextAreaElement
Sets whether to show the cursor.

showCursor(boolean) - Method in class dev.tamboui.toolkit.elements.TextInputElement
Sets whether to show the cursor.

showInlineErrors(boolean) - Method in class dev.tamboui.toolkit.elements.FormElement
Sets whether to show inline error messages.

showInlineErrors(boolean) - Method in class dev.tamboui.toolkit.elements.FormFieldElement

Sets whether to show inline error messages.

showLineNumbers() - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Enables line numbers.

showLineNumbers() - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Enables line numbers.

showLineNumbers() - Method in class dev.tamboui.toolkit.elements.TextAreaElement
Enables line number display.

showLineNumbers(boolean) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Sets whether to show line numbers.

showLineNumbers(boolean) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Sets whether to show line numbers.

showLineNumbers(boolean) - Method in class dev.tamboui.widgets.input.TextArea.Builder
Sets whether to show line numbers.

showMonthHeader() - Method in class dev.tamboui.toolkit.elements.CalendarElement
Shows the month header with bold style.

showMonthHeader(Style) - Method in class dev.tamboui.toolkit.elements.CalendarElement
Shows the month header with the given style.

showMonthHeader(Style) - Method in class dev.tamboui.widgets.calendar.Monthly
Returns a new calendar with the month header shown.

showSurrounding() - Method in class dev.tamboui.toolkit.elements.CalendarElement
Shows surrounding days with dim style.

showSurrounding(Style) - Method in class dev.tamboui.toolkit.elements.CalendarElement
Shows surrounding days (from previous/next month) with the given style.

showSurrounding(Style) - Method in class dev.tamboui.widgets.calendar.Monthly
Returns a new calendar with surrounding days shown.

showWeekdaysHeader() - Method in class dev.tamboui.toolkit.elements.CalendarElement
Shows the weekdays header with cyan color.

showWeekdaysHeader(Style) - Method in class dev.tamboui.toolkit.elements.CalendarElement
Shows the weekdays header with the given style.

showWeekdaysHeader(Style) - Method in class dev.tamboui.widgets.calendar.Monthly
Returns a new calendar with the weekdays header shown.

shutdownHook() - Method in class dev.tamboui.tui.TuiConfig
Returns whether a shutdown hook is registered to restore the terminal.

shutdownHook(boolean) - Method in class dev.tamboui.tui.TuiConfig.Builder
Sets whether to register a JVM shutdown hook for cleanup.

shutdownHook(boolean) - Method in class dev.tamboui.tui.TuiRunner.Builder
Sets whether to register a JVM shutdown hook for cleanup.

sigaction(int, MemorySegment, MemorySegment) - Static method in class dev.tamboui.backend.panama.unix.LibC
Installs a signal handler using sigaction().

SIGACTION_LAYOUT - Static variable in class dev.tamboui.backend.panama.unix.LibC
Layout for the sigaction structure.

signal(int, MemorySegment) - Static method in class dev.tamboui.backend.panama.unix.LibC
Installs a signal handler using signal().

signum() - Method in class dev.tamboui.layout.Fraction
Returns the sign of this fraction.

SIGWINCH - Static variable in class dev.tamboui.backend.panama.unix.LibC
Signal number for terminal window size change.

SIGWINCH - Static variable in class dev.tamboui.backend.panama.unix.PlatformConstants

Signal number for terminal window size change.

simpleNodeRenderer(Function) - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Sets a simple node renderer that returns a widget with default size.

SimpleRng - Class in dev.tamboui.tfx
A simple pseudo-random number generator using the Linear Congruential Generator algorithm.

SimpleRng(int) - Constructor for class dev.tamboui.tfx.SimpleRng
Creates a new SimpleRng with the specified seed.

sin(float) - Static method in class dev.tamboui.tfx.TFxMath
Computes the sine of a float value in radians.

SineIn - Enum constant in enum class dev.tamboui.tfx.Interpolation
Sine easing - in

SineInOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Sine easing - in-out

SineOut - Enum constant in enum class dev.tamboui.tfx.Interpolation
Sine easing - out

SIXEL - Enum constant in enum class dev.tamboui.image.capability.TerminalImageProtocol
Sixel graphics protocol (DEC standard).

SixelProtocol - Class in dev.tamboui.image.protocol
Renders images using the Sixel graphics protocol.

SixelProtocol() - Constructor for class dev.tamboui.image.protocol.SixelProtocol
Creates a Sixel protocol with default settings (256 colors).

SixelProtocol(int) - Constructor for class dev.tamboui.image.protocol.SixelProtocol
Creates a Sixel protocol with a custom color limit.

size() - Method in class dev.tamboui.backend.aesh.AeshBackend

size() - Method in class dev.tamboui.backend.jline3.JLineBackend

size() - Method in class dev.tamboui.backend.panama.PanamaBackend

size() - Method in class dev.tamboui.buffer.DiffResult
Returns the number of cell updates in this result.

size() - Method in class dev.tamboui.css.cascade.TypedPropertyMap
Returns the number of properties in this map.

size() - Method in class dev.tamboui.internal.record.RecordingBackend

size() - Method in class dev.tamboui.layout.Rect
Returns the size.

size() - Method in interface dev.tamboui.style.StyledAreaRegistry
Returns the number of registered areas.

size() - Method in interface dev.tamboui.terminal.Backend
Returns the current terminal size.

size() - Method in class dev.tamboui.terminal.Terminal
Returns the current terminal size.

size() - Method in class dev.tamboui.tfx.EffectManager
Returns the number of active effects.

size() - Method in class dev.tamboui.toolkit.element.ElementRegistry
Returns the number of registered elements.

size() - Method in class dev.tamboui.widgets.barchart.BarGroup
Returns the number of bars in this group.

size() - Method in class dev.tamboui.widgets.calendar.CalendarEventStore
Returns the number of styled dates.

size() - Method in class dev.tamboui.widgets.chart.Dataset
Returns the number of data points.

size() - Method in class dev.tamboui.widgets.form.SelectFieldState
Returns the number of available options.

size() - Method in class dev.tamboui.widgets.tabs.Tabs
Returns the number of tabs.

size(Logo.Size) - Method in class dev.tamboui.widgets.logo.Logo
Set the size of the logo.

Size - Class in dev.tamboui.layout
A size representing width and height dimensions.

Size - Class in dev.tamboui.toolkit.element
Represents the preferred dimensions of an element.

Size(int, int) - Constructor for class dev.tamboui.layout.Size
Creates a size.

Size(int, int) - Constructor for class dev.tamboui.toolkit.element.Size
Creates a new preferred size with the given dimensions.

SizedWidget - Class in dev.tamboui.widgets.common
Pairs a `Widget` with optional explicit width and height dimensions.

slideIn(Motion, int, int, Color, long, Interpolation) - Static method in class dev.tamboui.tfx.Fx
Creates a slide effect that slides in using block characters (shutter animation).

slideIn(Motion, int, int, Color, EffectTimer) - Static method in class dev.tamboui.tfx.Fx
Creates a slide effect that slides in using block characters (shutter animation).

slideOut(Motion, int, int, Color, long, Interpolation) - Static method in class dev.tamboui.tfx.Fx
Creates a slide effect that slides out using block characters (shutter animation).

slideOut(Motion, int, int, Color, EffectTimer) - Static method in class dev.tamboui.tfx.effects.SlideShader
Creates a slide shader that slides out in the specified direction.

slideOut(Motion, int, int, Color, EffectTimer) - Static method in class dev.tamboui.tfx.Fx
Creates a slide effect that slides out using block characters (shutter animation).

SlideShader - Class in dev.tamboui.tfx.effects
A slide effect that uses block characters to create a "shutter" animation.

SlidingWindowAlpha - Class in dev.tamboui.tfx
Calculates alpha values for positions based on a sliding window gradient.

SLOW_BLINK - Enum constant in enum class dev.tamboui.style.Modifier
Slow blink text.

slowBlink() - Method in class dev.tamboui.style.Style
Enables slow blink.

solve(List, int, int, Flex) - Method in class dev.tamboui.layout.cassowary.LayoutSolver
Solves layout constraints and returns the computed sizes.

Solver - Class in dev.tamboui.layout.cassowary
Cassowary constraint solver using the dual simplex method.

Solver() - Constructor for class dev.tamboui.layout.cassowary.Solver
Creates a new empty solver in lenient mode (default).

SolverException - Exception Class in dev.tamboui.layout.cassowary
Base exception for Cassowary solver errors.

SolverException(String) - Constructor for exception class dev.tamboui.layout.cassowary.SolverException
Creates a new solver exception with the given message.

SolverException(String, Throwable) - Constructor for exception class dev.tamboui.layout.cassowary.SolverException
Creates a new solver exception with the given message and cause.

source() - Method in interface dev.tamboui.capability.CapabilityProvider
A stable, user-friendly source id for this provider.

source() - Method in class dev.tamboui.capability.core.CoreCapabilityProvider

source() - Method in class dev.tamboui.image.capability.ImageCapabilityProvider

sourceOrder() - Method in class dev.tamboui.css.model.Rule
Returns the order in which this rule appeared in the stylesheet.

space() - Method in enum class dev.tamboui.widgets.tree.GuideStyle
Returns the space string (for children of last items).

space(int) - Static method in class dev.tamboui.layout.Spacing
Creates spacing with a fixed number of cells between segments.

SPACE_AROUND - Enum constant in enum class dev.tamboui.layout.Flex
Distribute space around elements.

SPACE_BETWEEN - Enum constant in enum class dev.tamboui.layout.Flex
Distribute space between elements.

SPACE_EVENLY - Enum constant in enum class dev.tamboui.layout.Flex
Distribute space evenly between and around elements.

spacer() - Static method in class dev.tamboui.toolkit.Toolkit
Creates a spacer that fills available space.

spacer(int) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a spacer with a fixed length.

Spacer - Class in dev.tamboui.toolkit.elements
An empty element that takes up space in layouts.

Spacer() - Constructor for class dev.tamboui.toolkit.elements.Spacer
Creates a spacer that fills available space.

Spacer(int) - Constructor for class dev.tamboui.toolkit.elements.Spacer
Creates a spacer with a fixed length.

spacing() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the spacing (gap between elements), if set.

spacing() - Method in class dev.tamboui.layout.Layout
Returns the spacing between areas.

spacing(int) - Method in class dev.tamboui.layout.columns.Columns.Builder
Sets the spacing between columns in cells.

spacing(int) - Method in class dev.tamboui.layout.Layout
Sets the spacing (in cells) between split areas.

spacing(int) - Method in class dev.tamboui.toolkit.elements.Column
Sets the spacing between children.

spacing(int) - Method in class dev.tamboui.toolkit.elements.ColumnsElement
Sets the spacing between columns.

spacing(int) - Method in class dev.tamboui.toolkit.elements.DialogElement
Sets the spacing (gap) between children.

spacing(int) - Method in class dev.tamboui.toolkit.elements.FlowElement
Sets the horizontal spacing between items on the same row.

spacing(int) - Method in class dev.tamboui.toolkit.elements.FormElement
Sets the spacing between label and input for all fields.

spacing(int) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Sets the spacing between label and input.

spacing(int) - Method in class dev.tamboui.toolkit.elements.Panel
Sets the spacing (gap) between children.

spacing(int) - Method in class dev.tamboui.toolkit.elements.Row
Sets the spacing between children.

spacing(Spacing) - Method in class dev.tamboui.layout.Layout
Sets the spacing between split areas using a Spacing object.

spacing(Integer) - Method in class dev.tamboui.css.cascade.CssStyleResolver.Builder
Sets the spacing (gap between elements).

Spacing - Class in dev.tamboui.layout
Represents the spacing between segments in a layout.

SPACING - Static variable in class dev.tamboui.style.StandardProperties
The `spacing` property for gap between elements.

Spacing.Overlap - Class in dev.tamboui.layout
Represents negative spacing, causing overlap between segments.

Spacing.Space - Class in dev.tamboui.layout
Represents positive spacing between segments.

SpacingConverter - Class in dev.tamboui.css.property
Converts CSS padding/margin values to Padding objects.

Span - Class in dev.tamboui.text
A string with a single style applied.

Span(String, Style) - Constructor for class dev.tamboui.text.Span
Creates a new span with the given content and style.

spans() - Method in class dev.tamboui.text.Line
Returns the spans composing this line.

sparkline() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty sparkline.

sparkline(int...) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a sparkline with the given data values.

sparkline(long...) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a sparkline with the given data values.

sparkline(Collection) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a sparkline with the given data values.

Sparkline - Class in dev.tamboui.widgets.sparkline
A sparkline widget for displaying data trends in a compact form.

Sparkline.BarSet - Class in dev.tamboui.widgets.sparkline
Symbol set for rendering bar heights.

Sparkline.Builder - Class in dev.tamboui.widgets.sparkline
Builder for `Sparkline`.

Sparkline.RenderDirection - Enum Class in dev.tamboui.widgets.sparkline
Direction for rendering sparkline data.

SparklineElement - Class in dev.tamboui.toolkit.elements
A DSL wrapper for the Sparkline widget.

SparklineElement() - Constructor for class dev.tamboui.toolkit.elements.SparklineElement
Creates a sparkline element with no data.

SparklineElement(int...) - Constructor for class dev.tamboui.toolkit.elements.SparklineElement
Creates a sparkline element with the given integer data values.

SparklineElement(long...) - Constructor for class dev.tamboui.toolkit.elements.SparklineElement
Creates a sparkline element with the given data values.

SparklineElement(Collection) - Constructor for class dev.tamboui.toolkit.elements.SparklineElement
Creates a sparkline element with data values from a collection.

specificity() - Method in class dev.tamboui.css.model.Rule

Returns the specificity of this rule's selector.

specificity() - Method in class dev.tamboui.css.selector.AttributeSelector

specificity() - Method in class dev.tamboui.css.selector.ChildSelector

specificity() - Method in class dev.tamboui.css.selector.ClassSelector

specificity() - Method in class dev.tamboui.css.selector.CompoundSelector

specificity() - Method in class dev.tamboui.css.selector.DescendantSelector

specificity() - Method in class dev.tamboui.css.selector.IdSelector

specificity() - Method in class dev.tamboui.css.selector.PseudoClassSelector

specificity() - Method in interface dev.tamboui.css.selector.Selector
Returns the specificity of this selector.

specificity() - Method in class dev.tamboui.css.selector.TypeSelector

specificity() - Method in class dev.tamboui.css.selector.UniversalSelector

speed(double) - Method in class dev.tamboui.toolkit.elements.WaveTextElement
Sets the animation speed multiplier.

speed(double) - Method in class dev.tamboui.widgets.wavetext.WaveText.Builder
Sets the animation speed multiplier.

SPEED - Static variable in class dev.tamboui.widgets.wavetext.WaveText
The `wave-speed` property for animation speed multiplier.

spinner() - Static method in class dev.tamboui.toolkit.Toolkit
Creates a spinner with the default DOTS style.

spinner(SpinnerStyle) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a spinner with the given style.

spinner(SpinnerStyle, String) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a spinner with the given style and label.

spinner(String) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a spinner with a label (DOTS style).

Spinner - Class in dev.tamboui.widgets.spinner
A widget that renders an animated spinner by cycling through frame characters.

SPINNER_FRAMES - Static variable in class dev.tamboui.widgets.spinner.Spinner
The `spinner-frames` property for custom spinner frame characters.

SPINNER_STYLE - Static variable in class dev.tamboui.widgets.spinner.Spinner
The `spinner-style` property for selecting a predefined spinner style.

Spinner.Builder - Class in dev.tamboui.widgets.spinner
Builder for `Spinner`.

SpinnerElement - Class in dev.tamboui.toolkit.elements
An element that displays an animated spinner with an optional label.

SpinnerElement() - Constructor for class dev.tamboui.toolkit.elements.SpinnerElement
Creates a spinner element with the default DOTS style.

SpinnerElement(SpinnerStyle) - Constructor for class dev.tamboui.toolkit.elements.SpinnerElement
Creates a spinner element with the given style.

SpinnerElement(SpinnerStyle, String) - Constructor for class dev.tamboui.toolkit.elements.SpinnerElement
Creates a spinner element with a style and label.

SpinnerElement(String) - Constructor for class dev.tamboui.toolkit.elements.SpinnerElement
Creates a spinner element with a label.

SpinnerFrameSet - Class in dev.tamboui.widgets.spinner
A set of frames that define a spinner animation.

SpinnerFrameSet.Builder - Class in dev.tamboui.widgets.spinner
Builder for SpinnerFrameSet.

SpinnerFrameSetConverter - Class in dev.tamboui.widgets.spinner
Converts string values to `SpinnerFrameSet`.

SpinnerState - Class in dev.tamboui.widgets.spinner
State for the `Spinner` widget, tracking animation progress.

SpinnerState() - Constructor for class dev.tamboui.widgets.spinner.SpinnerState
Creates a new state with tick starting at 0.

SpinnerState(long) - Constructor for class dev.tamboui.widgets.spinner.SpinnerState
Creates a new state with the given initial tick.

spinnerStyle(SpinnerStyle) - Method in class dev.tamboui.toolkit.elements.SpinnerElement
Sets the spinner style.

spinnerStyle(SpinnerStyle) - Method in class dev.tamboui.widgets.spinner.Spinner.Builder
Sets the spinner style (predefined frame set).

SpinnerStyle - Enum Class in dev.tamboui.widgets.spinner
Built-in spinner frame sets for the `Spinner` widget.

SpinnerStyleConverter - Class in dev.tamboui.widgets.spinner
Converts string values to `SpinnerStyle` enum values.

split(Rect) - Method in class dev.tamboui.layout.Layout
Split the given area according to this layout's constraints.

sqrt(float) - Static method in class dev.tamboui.tfx.TFxMath
Computes the square root of a float value.

SQUARE_CORNERS - Enum constant in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Square corners spinner.

stack() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty stack layout.

stack(Element...) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a stack layout with the given children.

stack(Collection) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a stack layout from a collection.

Stack - Class in dev.tamboui.layout.stack
An overlapping layers widget where children render on top of each other using a painter's algorithm (last child on top).

Stack.Builder - Class in dev.tamboui.layout.stack
Builder for `Stack`.

StackElement - Class in dev.tamboui.toolkit.elements
An overlapping layers layout element where children render on top of each other using a painter's algorithm (last child on top).

StackElement() - Constructor for class dev.tamboui.toolkit.elements.StackElement
Creates an empty stack layout.

StackElement(Element...) - Constructor for class dev.tamboui.toolkit.elements.StackElement
Creates a stack layout with the given children.

StackElement(Collection) - Constructor for class dev.tamboui.toolkit.elements.StackElement
Creates a stack layout with the given children.

standard() - Static method in class dev.tamboui.tui.bindings.BindingSets
Standard binding set using only arrow keys and standard keys.

StandardProperties - Class in dev.tamboui.style

Central registry of all standard property definitions.

start() - Method in class dev.tamboui.tui.TerminalInputReader
Starts the input reader thread.

START - Enum constant in enum class dev.tamboui.layout.Flex
Pack elements to the start.

START - Enum constant in enum class dev.tamboui.text.CharWidth.TruncatePosition
Truncate at start: "...World"

started() - Method in class dev.tamboui.tfx.EffectTimer
Returns true if the timer has started (i.e., remaining != total).

STARTS_WITH - Enum constant in enum class dev.tamboui.css.selector.AttributeSelector.Operator
Starts with

state() - Method in class dev.tamboui.tfx.SimpleRng
Returns the current state (for copying/debugging).

state() - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Returns the internal scroll state for programmatic control.

state() - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Returns the internal scroll state for programmatic control.

state(int, int, int) - Method in class dev.tamboui.toolkit.elements.ScrollbarElement
Creates a new state with the given parameters.

state(BooleanFieldState) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Sets the boolean field state.

state(SelectFieldState) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Sets the select field state.

state(TextAreaState) - Method in class dev.tamboui.toolkit.elements.TextAreaElement
Sets the text area state.

state(TextInputState) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Sets the text input state.

state(TextInputState) - Method in class dev.tamboui.toolkit.elements.TextInputElement
Sets the text input state.

state(ScrollbarState) - Method in class dev.tamboui.toolkit.elements.ScrollbarElement
Sets the scrollbar state.

state(SpinnerState) - Method in class dev.tamboui.toolkit.elements.SpinnerElement
Sets the animation state.

state(TableState) - Method in class dev.tamboui.toolkit.elements.TableElement
Sets the table state for selection tracking.

state(TabsState) - Method in class dev.tamboui.toolkit.elements.TabsElement
Sets the tabs state for selection tracking.

state(WaveTextState) - Method in class dev.tamboui.toolkit.elements.WaveTextElement
Sets the state for animation.

stateFor(Styleable) - Method in interface dev.tamboui.css.cascade.PseudoClassStateProvider
Returns the pseudo-class state for the given element.

StatefulWidget<S> - Interface in dev.tamboui.widget
A widget that maintains state between renders.

STD_INPUT_HANDLE - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
Handle identifier for standard input.

STD_OUTPUT_HANDLE - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
Handle identifier for standard output.

STDERR_FILENO - Static variable in class dev.tamboui.backend.panama.unix.LibC
Standard error file descriptor.

STDIN_FILENO - Static variable in class dev.tamboui.backend.panama.unix.LibC
Standard input file descriptor.

STDOUT_FILENO - Static variable in class dev.tamboui.backend.panama.unix.LibC
Standard output file descriptor.

STICKY_SCROLL - Enum constant in enum class dev.tamboui.widgets.list.ScrollMode
Auto-scroll to end, but pause when the user scrolls away.

stickyScroll() - Method in class dev.tamboui.toolkit.elements.ListElement
Enables sticky scroll behavior for the list.

stop(long) - Method in class dev.tamboui.tui.TerminalInputReader
Stops the input reader thread and waits for it to terminate.

strength() - Method in class dev.tamboui.layout.cassowary.CassowaryConstraint
Returns the strength of this constraint.

Strength - Class in dev.tamboui.layout.cassowary
Constraint strength representing priority in the constraint hierarchy.

STRETCH - Enum constant in enum class dev.tamboui.image.ImageScaling
Stretch the image to exactly fill the bounds.

STRETCH - Enum constant in enum class dev.tamboui.layout.ContentAlignment
Stretch to fill the entire container.

StretchShader - Class in dev.tamboui.tfx.effects
A shader that applies a stretching effect to terminal cells, expanding or shrinking rectangular areas using block characters.

StretchShader(Style, Motion, EffectTimer) - Constructor for class dev.tamboui.tfx.effects.StretchShader
Creates a new stretch shader.

StringConverter - Class in dev.tamboui.style
Identity converter for String properties.

StringToken(String, Token.Position) - Constructor for class dev.tamboui.css.parser.Token.StringToken
Creates a string token.

strong() - Method in class dev.tamboui.layout.cassowary.Strength
Returns the strong weight component.

STRONG - Static variable in class dev.tamboui.layout.cassowary.Strength
Strong preference - high priority but can be violated if necessary.

style - Variable in class dev.tamboui.toolkit.element.StyledElement
The inline style applied to this element.

style() - Method in class dev.tamboui.buffer.Cell
Returns the visual style of this cell.

style() - Method in class dev.tamboui.text.Span
Returns the style of this span.

style() - Method in class dev.tamboui.widgets.barchart.Bar
Returns the bar's style, if set.

style() - Method in class dev.tamboui.widgets.chart.Axis
Returns the axis style.

style() - Method in class dev.tamboui.widgets.chart.Dataset
Returns the style.

style() - Method in class dev.tamboui.widgets.list.ListItem
Returns the item style.

style() - Method in class dev.tamboui.widgets.table.Cell
Returns the style of this cell.

style() - Method in class dev.tamboui.widgets.table.Row
Returns the style of this row.

style(Style) - Method in class dev.tamboui.buffer.Cell
Returns a new cell with the given style and this cell's symbol.

style(Style) - Method in class dev.tamboui.text.Span
Returns a new span with the given style replacing the current one.

style(Style) - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the style for this element.

style(Style) - Method in class dev.tamboui.widgets.barchart.Bar.Builder
Sets the bar's style.

style(Style) - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Sets the overall chart style.

style(Style) - Method in class dev.tamboui.widgets.block.Block.Builder
Sets the block style.

style(Style) - Method in class dev.tamboui.widgets.chart.Axis.Builder
Sets the axis style.

style(Style) - Method in class dev.tamboui.widgets.chart.Chart.Builder
Sets the chart style.

style(Style) - Method in class dev.tamboui.widgets.chart.Dataset.Builder
Sets the dataset style.

style(Style) - Method in class dev.tamboui.widgets.checkbox.Checkbox.Builder
Sets the base style for rendering.

style(Style) - Method in class dev.tamboui.widgets.gauge.Gauge.Builder
Sets the style for the widget background (not the filled bar).

style(Style) - Method in class dev.tamboui.widgets.gauge.LineGauge.Builder
Sets the overall style for the widget.

style(Style) - Method in class dev.tamboui.widgets.input.TextArea.Builder
Sets the base style.

style(Style) - Method in class dev.tamboui.widgets.input.TextInput.Builder
Sets the base style.

style(Style) - Method in class dev.tamboui.widgets.list.ListItem
Returns a new list item with the given style applied.

style(Style) - Method in class dev.tamboui.widgets.list.ListWidget.Builder
Sets the base style.

style(Style) - Method in class dev.tamboui.widgets.paragraph.Paragraph.Builder
Sets the base style.

style(Style) - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.Builder
Sets the base style applied to all scrollbar components.

style(Style) - Method in class dev.tamboui.widgets.select.Select.Builder
Sets the base style for rendering.

style(Style) - Method in class dev.tamboui.widgets.sparkline.Sparkline.Builder
Sets the style for the sparkline bars.

style(Style) - Method in class dev.tamboui.widgets.spinner.Spinner.Builder
Sets the style for the spinner text.

style(Style) - Method in class dev.tamboui.widgets.table.Cell
Returns a new cell with the given style.

style(Style) - Method in class dev.tamboui.widgets.table.Row
Returns a new row with the given style.

style(Style) - Method in class dev.tamboui.widgets.table.Table.Builder
Sets the base style.

style(Style) - Method in class dev.tamboui.widgets.tabs.Tabs.Builder

Sets the base style for unselected tabs.

style(Style) - Method in class dev.tamboui.widgets.toggle.Toggle.Builder
Sets the base style for rendering.

style(Style) - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Sets the base style.

style(Style) - Method in class dev.tamboui.widgets.wavetext.WaveText.Builder
Sets the base style (modifiers like bold, italic).

Style - Class in dev.tamboui.style
A complete style definition including foreground, background, and modifiers.

Style(Color, Color, Color, EnumSet, EnumSet) - Constructor for class dev.tamboui.style.Style
Creates a style with the given colors and modifiers.

Style(Color, Color, Color, EnumSet, EnumSet, Map) - Constructor for class dev.tamboui.style.Style
Creates a style with the given colors, modifiers, and extensions.

Styleable - Interface in dev.tamboui.css
Interface for elements that can be styled via CSS.

styleAttributes() - Method in interface dev.tamboui.css.Styleable
Returns the style attributes for attribute selector matching.

styleAttributes() - Method in class dev.tamboui.toolkit.element.ElementRegistry.ElementInfo

styleAttributes() - Method in class dev.tamboui.toolkit.element.StyledElement

styleAttributes() - Method in class dev.tamboui.toolkit.elements.BarChartElement

styleAttributes() - Method in class dev.tamboui.toolkit.elements.CalendarElement

styleAttributes() - Method in class dev.tamboui.toolkit.elements.CanvasElement

styleAttributes() - Method in class dev.tamboui.toolkit.elements.ChartElement

styleAttributes() - Method in class dev.tamboui.toolkit.elements.DialogElement

styleAttributes() - Method in class dev.tamboui.toolkit.elements.GaugeElement

styleAttributes() - Method in class dev.tamboui.toolkit.elements.LineGaugeElement

styleAttributes() - Method in class dev.tamboui.toolkit.elements.ListElement

styleAttributes() - Method in class dev.tamboui.toolkit.elements.Panel

styleAttributes() - Method in class dev.tamboui.toolkit.elements.SparklineElement

styleAttributes() - Method in class dev.tamboui.toolkit.elements.TableElement

styleAttributes() - Method in class dev.tamboui.toolkit.elements.TabsElement

styleAttributes() - Method in class dev.tamboui.toolkit.elements.TextAreaElement

styleAttributes() - Method in class dev.tamboui.toolkit.elements.TextInputElement

styleAttributes() - Method in class dev.tamboui.toolkit.elements.TreeElement

styleAttrs - Variable in class dev.tamboui.toolkit.element.StyledElement
The style attributes for CSS attribute selector matching.

styled(Masked, Style) - Static method in class dev.tamboui.text.Span
Creates a styled span from a masked string.

styled(String, Style) - Static method in class dev.tamboui.text.Line
Creates a line from styled text.

styled(String, Style) - Static method in class dev.tamboui.text.Span
Creates a styled span from the given content.

styled(String, Style) - Static method in class dev.tamboui.text.Text
Creates a styled text from a string, splitting on newlines.

StyledAreaInfo - Class in dev.tamboui.style
Information about a styled area that has been rendered.

StyledAreaInfo(Tags, Rect, String) - Constructor for class dev.tamboui.style.StyledAreaInfo
Creates a new styled area info.

styledAreaRegistry() - Method in class dev.tamboui.toolkit.app.ToolkitRunner
Returns the styled area registry for styled span lookups.

StyledAreaRegistry - Interface in dev.tamboui.style
Registry that stores information about styled areas rendered to a buffer.

StyledElement<T> - Class in dev.tamboui.toolkit.element
Abstract base for elements that support styling and event handling.

StyledElement() - Constructor for class dev.tamboui.toolkit.element.StyledElement
Creates a new styled element with default values.

StyledSpan - Class in dev.tamboui.toolkit.element
A styled span that can be targeted by CSS selectors.

StyledSpan(StyledAreaInfo, ElementRegistry) - Constructor for class dev.tamboui.toolkit.element.StyledSpan
Creates a new styled span wrapping the given StyledAreaInfo.

styleEngine() - Method in class dev.tamboui.toolkit.element.DefaultRenderContext
Returns the style engine, if configured.

styleEngine(StyleEngine) - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner.Builder
Sets the style engine for CSS styling.

styleEngine(StyleEngine) - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner
Sets the style engine for CSS styling.

styleEngine(StyleEngine) - Method in class dev.tamboui.toolkit.app.ToolkitRunner.Builder
Sets the style engine for CSS styling.

styleEngine(StyleEngine) - Method in class dev.tamboui.toolkit.app.ToolkitRunner
Sets the style engine for CSS styling.

StyleEngine - Class in dev.tamboui.css.engine
Main entry point for CSS styling.

StyleEngine.StyleChangeListener - Interface in dev.tamboui.css.engine
Listener for stylesheet changes.

StylePropertyResolver - Interface in dev.tamboui.style
A resolver for retrieving typed property values by definition.

styleResolver(StylePropertyResolver) - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Sets the property resolver for style-aware properties.

styleResolver(StylePropertyResolver) - Method in class dev.tamboui.widgets.block.Block.Builder
Sets the property resolver for style-aware properties.

styleResolver(StylePropertyResolver) - Method in class dev.tamboui.widgets.checkbox.Checkbox.Builder
Sets the style resolver for CSS property resolution.

styleResolver(StylePropertyResolver) - Method in class dev.tamboui.widgets.gauge.Gauge.Builder
Sets the property resolver for style-aware properties.

styleResolver(StylePropertyResolver) - Method in class dev.tamboui.widgets.gauge.LineGauge.Builder
Sets the property resolver for style-aware properties.

styleResolver(StylePropertyResolver) - Method in class dev.tamboui.widgets.input.TextArea.Builder
Sets the property resolver for style-aware properties.

styleResolver(StylePropertyResolver) - Method in class dev.tamboui.widgets.input.TextInput.Builder

Sets the property resolver for style-aware properties.

styleResolver(StylePropertyResolver) - Method in class dev.tamboui.widgets.paragraph.Paragraph.Builder
Sets the property resolver for style-aware properties.

styleResolver(StylePropertyResolver) - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.Builder
Sets the property resolver for style-aware properties.

styleResolver(StylePropertyResolver) - Method in class dev.tamboui.widgets.select.Select.Builder
Sets the style resolver for CSS property resolution.

styleResolver(StylePropertyResolver) - Method in class dev.tamboui.widgets.sparkline.Sparkline.Builder
Sets the property resolver for style-aware properties.

styleResolver(StylePropertyResolver) - Method in class dev.tamboui.widgets.table.Table.Builder
Sets the property resolver for style-aware properties.

styleResolver(StylePropertyResolver) - Method in class dev.tamboui.widgets.tabs.Tabs.Builder
Sets the property resolver for style-aware properties.

styleResolver(StylePropertyResolver) - Method in class dev.tamboui.widgets.toggle.Toggle.Builder
Sets the style resolver for CSS property resolution.

styleResolver(StylePropertyResolver) - Method in class dev.tamboui.widgets.tree.TreeWidget.Builder
Sets the style property resolver.

styleResolver(StylePropertyResolver) - Method in class dev.tamboui.widgets.wavetext.WaveText.Builder
Sets the property resolver for style-aware properties.

styleResolver(RenderContext) - Method in class dev.tamboui.toolkit.element.StyledElement
Gets the StylePropertyResolver for CSS property resolution.

styles(boolean) - Method in class dev.tamboui.export.text.TextOptions
Sets whether to include ANSI escape codes (true) or plain text only (false).

styles(StylePropertyResolver) - Method in class dev.tamboui.export.html.HtmlOptions
Sets the style property resolver for default export foreground/background.

styles(StylePropertyResolver) - Method in class dev.tamboui.export.svg.SvgOptions
Sets the style property resolver for default export foreground/background.

Stylesheet - Class in dev.tamboui.css.model
Represents a parsed CSS stylesheet.

Stylesheet(Map, List) - Constructor for class dev.tamboui.css.model.Stylesheet
Creates a new stylesheet.

Stylesheet Types - Section in class dev.tamboui.css.engine.StyleEngine

styleToAnsi(Style) - Static method in class dev.tamboui.terminal.AnsiStringBuilder
Converts a `Style` to an ANSI SGR (Select Graphic Rendition) escape sequence.

styleType() - Method in interface dev.tamboui.css.Styleable
Returns the style type name used for type selectors.

styleType() - Method in class dev.tamboui.toolkit.element.ElementRegistry.ElementInfo

styleType() - Method in class dev.tamboui.toolkit.element.StyledSpan

styleTypesOf(Styleable) - Static method in interface dev.tamboui.css.Styleable
Builds the list of style types for an element, ordered by precedence.

sub(TFxDuration) - Method in class dev.tamboui.tfx.TFxDuration
Subtracts another duration.

submit() - Method in class dev.tamboui.toolkit.elements.FormElement
Submits the form.

submitOnEnter(boolean) - Method in class dev.tamboui.toolkit.elements.FormElement
Sets whether pressing Enter in any field should trigger form submission.

subModifiers() - Method in class dev.tamboui.style.Style

Returns the modifiers explicitly removed from this style.

substringByWidth(String, int) - Static method in class dev.tamboui.text.CharWidth
Returns a substring that fits within the given display width, respecting code point and grapheme cluster boundaries.

substringByWidthFromEnd(String, int) - Static method in class dev.tamboui.text.CharWidth
Returns a substring starting from the end that fits within the given display width.

subtract(Fraction) - Method in class dev.tamboui.layout.Fraction
Returns the difference of this fraction and another.

suggestValue(Variable, Fraction) - Method in class dev.tamboui.layout.cassowary.Solver
Suggests a new value for an edit variable.

sundayFirst() - Method in class dev.tamboui.toolkit.elements.CalendarElement
Sets the first day of week to Sunday.

SUPPORTED_DISABLED - Enum constant in enum class dev.tamboui.terminal.Mode2027Status
Terminal recognizes Mode 2027 but has it disabled (Ps=2 or Ps=4 in DECRPM response).

supportedProtocols() - Method in class dev.tamboui.image.capability.TerminalImageCapabilities
Returns all supported protocols.

Supported Selectors - Section in class dev.tamboui.toolkit.element.ElementRegistry

supports(TerminalImageProtocol) - Method in class dev.tamboui.image.capability.TerminalImageCapabilities
Returns true if the specified protocol is supported.

supportsNativeImages() - Method in class dev.tamboui.image.capability.TerminalImageCapabilities
Returns true if any native image protocol is supported.

suppress() - Static method in class dev.tamboui.tui.error.RenderErrorHandlers
Returns a handler that suppresses errors and continues.

SUPPRESS - Enum constant in enum class dev.tamboui.tui.error.ErrorAction
Suppress the error and attempt to continue rendering.

surroundingStyle(Style) - Method in class dev.tamboui.widgets.calendar.Monthly.Builder
Shows surrounding days with the given style.

svg() - Method in class dev.tamboui.export.ExportRequest
Shorthand for `as(Formats.SVG)`.

SVG - Static variable in class dev.tamboui.export.Formats
SVG format.

SvgExporter - Class in dev.tamboui.export.svg
Exports a `Buffer` to an SVG in the same spirit as Rich's `Console.export_svg`.

SvgFormat - Class in dev.tamboui.export.svg
SVG export format.

SvgOptions - Class in dev.tamboui.export.svg
Options for SVG export.

SvgOptions() - Constructor for class dev.tamboui.export.svg.SvgOptions
Creates default SVG export options.

sweepIn(Motion, int, int, Color, long, Interpolation) - Static method in class dev.tamboui.tfx.Fx
Creates a sweep effect that sweeps in from a specified color.

sweepIn(Motion, int, int, Color, EffectTimer) - Static method in class dev.tamboui.tfx.effects.SweepShader
Creates a sweep shader that sweeps in from a specified color.

sweepIn(Motion, int, int, Color, EffectTimer) - Static method in class dev.tamboui.tfx.Fx
Creates a sweep effect that sweeps in from a specified color.

sweepOut(Motion, int, int, Color, long, Interpolation) - Static method in class dev.tamboui.tfx.Fx
Creates a sweep effect that sweeps out to a specified color.

sweepOut(Motion, int, int, Color, EffectTimer) - Static method in class dev.tamboui.tfx.Fx

Creates a sweep effect that sweeps out to a specified color.

SweepPattern - Class in dev.tamboui.tfx.pattern
Pattern implementation for linear sweep effects in cardinal directions.

SweepShader - Class in dev.tamboui.tfx.effects
A sweep effect that transitions from a faded color to the original content.

symbol() - Method in class dev.tamboui.buffer.Cell
Returns the symbol displayed in this cell.

symbol() - Method in enum class dev.tamboui.layout.cassowary.Relation
Returns the symbol representation of this relation.

symbol() - Method in enum class dev.tamboui.widgets.chart.Dataset.Marker
Returns the marker symbol.

symbol(String) - Method in class dev.tamboui.buffer.Cell
Returns a new cell with the given symbol and this cell's style.

symbolForLevel(double) - Method in class dev.tamboui.widgets.sparkline.Sparkline.BarSet
Returns the symbol for the given fill level (0.0 to 1.0).

symbols() - Method in class dev.tamboui.widgets.barchart.BarChart.BarSet
Returns the symbols as an array for indexed access.

symbols(Scrollbar.SymbolSet) - Method in class dev.tamboui.toolkit.elements.ScrollbarElement
Sets the symbol set.

symbols(Scrollbar.SymbolSet) - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.Builder
Sets the symbol set for this scrollbar.

SymbolSet(String, String, String, String) - Constructor for class dev.tamboui.widgets.scrollbar.Scrollbar.SymbolSet
Creates a new symbol set.

symmetric(int, int) - Static method in class dev.tamboui.layout.Margin
Returns a margin with vertical and horizontal values.

symmetric(int, int) - Static method in class dev.tamboui.layout.Padding
Returns a padding with symmetric vertical and horizontal values.

T

TAB - Enum constant in enum class dev.tamboui.tui.event.KeyCode
Tab key.

table() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty table.

Table - Class in dev.tamboui.widgets.table
A table widget for displaying data in rows and columns.

Table.Builder - Class in dev.tamboui.widgets.table
Builder for `Table`.

Table.HighlightSpacing - Enum Class in dev.tamboui.widgets.table
Controls when space is allocated for the highlight symbol.

TableElement - Class in dev.tamboui.toolkit.elements
A DSL wrapper for the Table widget.

TableElement() - Constructor for class dev.tamboui.toolkit.elements.TableElement
Creates a new empty table element.

TableState - Class in dev.tamboui.widgets.table
State for a `Table` widget.

TableState() - Constructor for class dev.tamboui.widgets.table.TableState
Creates a new table state with no selection.

tabs() - Static method in class dev.tamboui.toolkit.Toolkit

Creates empty tabs.

tabs(String...) - Static method in class dev.tamboui.toolkit.Toolkit
Creates tabs with the given titles.

tabs(List) - Static method in class dev.tamboui.toolkit.Toolkit
Creates tabs with the given titles.

Tabs - Class in dev.tamboui.widgets.tabs
A horizontal set of tabs with a single tab selected.

Tabs.Builder - Class in dev.tamboui.widgets.tabs
Builder for `Tabs`.

TabsElement - Class in dev.tamboui.toolkit.elements
A DSL wrapper for the Tabs widget.

TabsElement() - Constructor for class dev.tamboui.toolkit.elements.TabsElement
Creates a new empty tabs element.

TabsElement(String...) - Constructor for class dev.tamboui.toolkit.elements.TabsElement
Creates a new tabs element with the given titles.

TabsElement(List) - Constructor for class dev.tamboui.toolkit.elements.TabsElement
Creates a new tabs element with the given titles.

TabsState - Class in dev.tamboui.widgets.tabs
State for a `Tabs` widget.

TabsState() - Constructor for class dev.tamboui.widgets.tabs.TabsState
Creates a new tabs state with no selection.

TabsState(int) - Constructor for class dev.tamboui.widgets.tabs.TabsState
Creates a new tabs state with the given selection.

tags() - Method in class dev.tamboui.style.StyledAreaInfo
Returns the tags associated with this styled area.

Tags - Class in dev.tamboui.style
A collection of tag names associated with a Style.

TamboUIException - Exception Class in dev.tamboui.error
Abstract base exception for all TamboUI framework errors.

TamboUIException(String) - Constructor for exception class dev.tamboui.error.TamboUIException
Creates a new TamboUI exception with the given message.

TamboUIException(String, Throwable) - Constructor for exception class dev.tamboui.error.TamboUIException
Creates a new TamboUI exception with the given message and cause.

targetType() - Method in interface dev.tamboui.tui.bindings.ActionHandlerRegistrar
Returns the target class this registrar handles.

tau() - Static method in class dev.tamboui.tfx.TFxMath
Returns the value of tau (2 * pi).

tcgetattr(int, MemorySegment) - Static method in class dev.tamboui.backend.panama.unix.LibC
Gets terminal attributes.

TCSADRAIN - Static variable in class dev.tamboui.backend.panama.unix.LibC
Apply termios changes after all output has been transmitted.

TCSAFLUSH - Static variable in class dev.tamboui.backend.panama.unix.LibC
Apply termios changes after all output has been transmitted, discarding pending input.

TCSANOW - Static variable in class dev.tamboui.backend.panama.unix.LibC
Apply termios changes immediately.

tcsetattr(int, int, MemorySegment) - Static method in class dev.tamboui.backend.panama.unix.LibC
Sets terminal attributes.

term(Term) - Static method in class dev.tamboui.layout.cassowary.Expression
Creates an expression containing a single term.

Term - Class in dev.tamboui.layout.cassowary
A term in a linear expression, representing a coefficient multiplied by a variable.

Term(Variable) - Constructor for class dev.tamboui.layout.cassowary.Term
Creates a new term with coefficient 1.

Term(Variable, Fraction) - Constructor for class dev.tamboui.layout.cassowary.Term
Creates a new term with the given variable and coefficient.

terminal() - Method in class dev.tamboui.tui.TuiRunner
Returns the underlying terminal.

Terminal<B> - Class in dev.tamboui.terminal
The main terminal abstraction.

Terminal(B) - Constructor for class dev.tamboui.terminal.Terminal
Creates a new terminal instance with the given backend.

terminalConnection() - Method in class dev.tamboui.backend.aesh.AeshBackend
Returns the underlying TerminalConnection for advanced operations.

Terminal Detection - Section in class dev.tamboui.image.capability.TerminalImageCapabilities

TerminalDrawEvent - Class in dev.tamboui.jfr
JFR event measuring time spent in `Terminal.draw()`.

TerminalDrawEvent() - Constructor for class dev.tamboui.jfr.TerminalDrawEvent
Creates a new draw event instance.

TerminalImageCapabilities - Class in dev.tamboui.image.capability
Detects and caches terminal image capabilities.

TerminalImageProtocol - Enum Class in dev.tamboui.image.capability
Types of image display support available in terminals.

TerminalInputReader - Class in dev.tamboui.tui
A dedicated thread for reading terminal input.

TerminalInputReader(Backend, BlockingQueue, Bindings, AtomicBoolean, Duration) - Constructor for class dev.tamboui.tui.TerminalInputReader
Creates a new terminal input reader.

TerminalIOException - Exception Class in dev.tamboui.error
Exception thrown when a terminal I/O operation fails.

TerminalIOException(String) - Constructor for exception class dev.tamboui.error.TerminalIOException
Creates a new terminal I/O exception with the given message.

TerminalIOException(String, Throwable) - Constructor for exception class dev.tamboui.error.TerminalIOException
Creates a new terminal I/O exception with the given message and cause.

TERMIOS_CC_OFFSET - Static variable in class dev.tamboui.backend.panama.unix.PlatformConstants
Offset to the c_cc array in the termios structure.

TERMIOS_FLAG_LAYOUT - Static variable in class dev.tamboui.backend.panama.unix.PlatformConstants
Value layout for termios flags (int on Linux, long on macOS).

TERMIOS_LAYOUT - Static variable in class dev.tamboui.backend.panama.unix.LibC
Layout for the termios structure.

TERMIOS_LAYOUT - Static variable in class dev.tamboui.backend.panama.unix.PlatformConstants
Termios structure layout.

terms() - Method in class dev.tamboui.layout.cassowary.Expression
Returns the terms of this expression.

text() - Method in class dev.tamboui.export.ExportRequest
Shorthand for `as(Formats.TEXT)`.

text() - Static method in class dev.tamboui.tfx.CellFilter
Selects cells containing textual content.

text() - Method in class dev.tamboui.toolkit.elements.RichTextElement
Returns the current text content.

text() - Method in class dev.tamboui.widgets.input.TextAreaState
Returns the full text content.

text() - Method in class dev.tamboui.widgets.input.TextInputState
Returns the current text.

text() - Method in class dev.tamboui.widgets.wavetext.WaveText
Returns the text being displayed.

text(Text) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Sets the text to display.

text(Text) - Method in class dev.tamboui.toolkit.elements.RichTextElement
Sets the text content.

text(Text) - Method in class dev.tamboui.widgets.paragraph.Paragraph.Builder
Sets the text content.

text(Object) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a text element from any value (uses toString).

text(Object...) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a text element with multiple values concatenated.

text(String) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Sets the text from a string.

text(String) - Method in class dev.tamboui.toolkit.elements.TextAreaElement
Sets the initial text.

text(String) - Method in class dev.tamboui.toolkit.elements.TextInputElement
Sets the initial text.

text(String) - Method in class dev.tamboui.toolkit.elements.WaveTextElement
Sets the text to display.

text(String) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a text element with the given content.

text(String) - Method in class dev.tamboui.widgets.paragraph.Paragraph.Builder
Sets the text content from a string.

text(String) - Method in class dev.tamboui.widgets.wavetext.WaveText.Builder
Sets the text to display.

Text - Class in dev.tamboui.text
Multi-line styled text, composed of Lines.

Text(List, Alignment) - Constructor for class dev.tamboui.text.Text
Creates a new text with the given lines and alignment.

TEXT - Enum constant in enum class dev.tamboui.widgets.form.FieldType
Single-line text input (default).

TEXT - Static variable in class dev.tamboui.export.Formats
Text format (plain or ANSI).

TEXT_ALIGN - Static variable in class dev.tamboui.style.StandardProperties
The `text-align` property for text alignment.

TEXT_AREA - Enum constant in enum class dev.tamboui.widgets.form.FieldType
Multi-line text input for longer content.

TEXT_OVERFLOW - Static variable in class dev.tamboui.style.StandardProperties
The `text-overflow` property for text wrapping/truncation behavior.

TEXT_STYLE - Static variable in class dev.tamboui.style.StandardProperties
The `text-style` property for text modifiers.

textArea() - Static method in class dev.tamboui.toolkit.Toolkit

Creates a text area with a new state.

textArea(TextAreaState) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a text area with the given state.

TextArea - Class in dev.tamboui.widgets.input
A text area widget for multi-line text entry.

TextArea.Builder - Class in dev.tamboui.widgets.input
Builder for `TextArea`.

TextAreaElement - Class in dev.tamboui.toolkit.elements
A DSL wrapper for the TextArea widget.

TextAreaElement() - Constructor for class dev.tamboui.toolkit.elements.TextAreaElement
Creates a new text area element with a default state.

TextAreaElement(TextAreaState) - Constructor for class dev.tamboui.toolkit.elements.TextAreaElement
Creates a new text area element with the given state.

TextAreaElement.TextChangeListener - Interface in dev.tamboui.toolkit.elements
Listener for text changes in the text area.

TextAreaState - Class in dev.tamboui.widgets.input
State for a TextArea widget, tracking multi-line text, cursor position, and scroll offset.

TextAreaState() - Constructor for class dev.tamboui.widgets.input.TextAreaState
Creates a new empty text area state.

TextAreaState(String) - Constructor for class dev.tamboui.widgets.input.TextAreaState
Creates a new text area state with the given initial text.

TextElement - Class in dev.tamboui.toolkit.elements
A simple text element that displays styled text.

TextElement(Object) - Constructor for class dev.tamboui.toolkit.elements.TextElement
Creates a new text element from any value using its string representation.

TextElement(String) - Constructor for class dev.tamboui.toolkit.elements.TextElement
Creates a new text element with the given string content.

TextExporter - Class in dev.tamboui.export.text
Exports a `Buffer` to text in the same spirit as Rich's `Console.export_text`.

textField(String) - Method in class dev.tamboui.widgets.form.FormState.Builder
Adds a text field with an empty initial value.

textField(String) - Method in class dev.tamboui.widgets.form.FormState
Returns the TextInputState for the given field name.

textField(String, String) - Method in class dev.tamboui.widgets.form.FormState.Builder
Adds a text field with the given initial value.

TextFormat - Class in dev.tamboui.export.text
Plain text or ANSI-styled text export format.

textInput() - Static method in class dev.tamboui.toolkit.Toolkit
Creates a text input with a new state.

textInput(TextInputState) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a text input with the given state.

TextInput - Class in dev.tamboui.widgets.input
A text input widget for single-line text entry.

TextInput.Builder - Class in dev.tamboui.widgets.input
Builder for `TextInput`.

TextInputElement - Class in dev.tamboui.toolkit.elements
A DSL wrapper for the TextInput widget.

TextInputElement() - Constructor for class dev.tamboui.toolkit.elements.TextInputElement
Creates a new text input element with a default state.

TextInputElement(TextInputState) - Constructor for class dev.tamboui.toolkit.elements.TextInputElement
Creates a new text input element with the given state.

TextInputState - Class in dev.tamboui.widgets.input
State for a TextInput widget, tracking the input text and cursor position.

TextInputState() - Constructor for class dev.tamboui.widgets.input.TextInputState
Creates a new empty text input state.

TextInputState(String) - Constructor for class dev.tamboui.widgets.input.TextInputState
Creates a new text input state with the given initial text.

TextOptions - Class in dev.tamboui.export.text
Options for text export (plain or ANSI-styled).

TextOptions() - Constructor for class dev.tamboui.export.text.TextOptions
Creates default text export options (plain text, no ANSI).

textOverflow() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the text-overflow behavior, if set.

textValue() - Method in class dev.tamboui.widgets.barchart.Bar
Returns the custom text value, if set.

textValue(String) - Method in class dev.tamboui.widgets.barchart.Bar.Builder
Sets a custom text value to display instead of the numeric value.

textValue(String) - Method in class dev.tamboui.widgets.form.FormState
Returns the current text value for the given field name.

textValues() - Method in class dev.tamboui.widgets.form.FormState
Returns all text field values as a map.

TFxColorSpace - Enum Class in dev.tamboui.tfx
Defines the color space used for color interpolation in effects.

TFxDuration - Class in dev.tamboui.tfx
Duration abstraction for effects with millisecond precision.

TfxIntegration - Class in dev.tamboui.tfx.tui
Integrates TFX effects with the TuiRunner event loop.

TfxIntegration() - Constructor for class dev.tamboui.tfx.tui.TfxIntegration
Creates a new TfxIntegration instance.

TFxMath - Class in dev.tamboui.tfx
Math utilities for effects.

thick() - Method in class dev.tamboui.toolkit.elements.LineGaugeElement
Uses thick line characters.

thick() - Method in class dev.tamboui.toolkit.elements.Panel
Sets the border type to thick.

THICK - Enum constant in enum class dev.tamboui.widgets.block.BorderType
Thick border using heavy box-drawing characters.

THICK - Static variable in class dev.tamboui.widgets.gauge.LineGauge
Line character set using thick lines.

THREE_LEVELS - Static variable in class dev.tamboui.widgets.barchart.BarChart.BarSet
Three-level vertical bar set.

THREE_LEVELS - Static variable in class dev.tamboui.widgets.sparkline.Sparkline.BarSet
Three-level bar set with coarse fill levels.

threeEighths() - Method in class dev.tamboui.widgets.barchart.BarChart.BarSet
Returns the three-eighths fill symbol.

threeEighths() - Method in class dev.tamboui.widgets.sparkline.Sparkline.BarSet
Returns the three-eighths fill symbol.

threeLevels() - Method in class dev.tamboui.toolkit.elements.BarChartElement

Uses three-level bar set.

threeLevels() - Method in class dev.tamboui.toolkit.elements.SparklineElement
Uses three-level bar set (coarser display).

threeQuarters() - Method in class dev.tamboui.widgets.barchart.BarChart.BarSet
Returns the three-quarters fill symbol.

threeQuarters() - Method in class dev.tamboui.widgets.sparkline.Sparkline.BarSet
Returns the three-quarters fill symbol.

thumb() - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.SymbolSet
Returns the thumb character.

THUMB_COLOR - Static variable in class dev.tamboui.widgets.scrollbar.Scrollbar
Property key for the thumb (position indicator) color.

thumbColor(Color) - Method in class dev.tamboui.toolkit.elements.ScrollbarElement
Sets the thumb color.

thumbColor(Color) - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.Builder
Sets the thumb (position indicator) color programmatically.

thumbStyle(Style) - Method in class dev.tamboui.toolkit.elements.ScrollbarElement
Sets the thumb style.

thumbStyle(Style) - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.Builder
Sets the style for the thumb (position indicator).

thumbSymbol(String) - Method in class dev.tamboui.toolkit.elements.ScrollbarElement
Sets the thumb symbol.

thumbSymbol(String) - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.Builder
Sets the thumb (position indicator) symbol.

tick() - Method in class dev.tamboui.widgets.spinner.SpinnerState
Returns the current tick value.

tick() - Method in class dev.tamboui.widgets.wavetext.WaveTextState
Returns the current tick value.

TickEvent - Class in dev.tamboui.tui.event
Represents an animation timer tick event.

TickEvent(long, Duration) - Constructor for class dev.tamboui.tui.event.TickEvent
Creates a tick event with the given frame count and elapsed time.

tickRate() - Method in class dev.tamboui.tui.InlineTuiConfig
Returns the tick interval for animations.

tickRate() - Method in class dev.tamboui.tui.TuiConfig
Returns the tick interval, or null if ticks are disabled.

tickRate(Duration) - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner.Builder
Sets the tick interval for animations.

tickRate(Duration) - Method in class dev.tamboui.tui.InlineTuiConfig.Builder
Sets the tick interval for animations.

tickRate(Duration) - Method in class dev.tamboui.tui.TuiConfig.Builder
Sets the interval between tick events.

tickRate(Duration) - Method in class dev.tamboui.tui.TuiRunner.Builder
Sets the interval between tick events.

ticksEnabled() - Method in class dev.tamboui.tui.InlineTuiConfig
Returns whether tick events are enabled.

ticksEnabled() - Method in class dev.tamboui.tui.TuiConfig
Returns true if tick events are enabled.

timer() - Method in class dev.tamboui.tfx.effects.DissolveShader

timer() - Method in class dev.tamboui.tfx.effects.ExpandShader

timer() - Method in class dev.tamboui.tfx.effects.FadeShader

timer() - Method in class dev.tamboui.tfx.effects.PaintShader

timer() - Method in class dev.tamboui.tfx.effects.ParallelEffect

timer() - Method in class dev.tamboui.tfx.effects.SequentialEffect

timer() - Method in class dev.tamboui.tfx.effects.SlideShader

timer() - Method in class dev.tamboui.tfx.effects.StretchShader

timer() - Method in class dev.tamboui.tfx.effects.SweepShader

timer() - Method in interface dev.tamboui.tfx.Shader
Returns the timer associated with this shader effect, or null if none.

times(long) - Method in class dev.tamboui.layout.cassowary.Expression
Multiplies this expression by a scalar.

times(long) - Method in class dev.tamboui.layout.cassowary.Variable
Creates a term with this variable and the given coefficient.

times(Fraction) - Method in class dev.tamboui.layout.cassowary.Expression
Multiplies this expression by a scalar.

times(Fraction) - Method in class dev.tamboui.layout.cassowary.Term
Returns a new term with the coefficient multiplied by the given factor.

times(Fraction) - Method in class dev.tamboui.layout.cassowary.Variable
Creates a term with this variable and the given coefficient.

timestamp() - Method in class dev.tamboui.tui.error.RenderError
Returns the timestamp when the error was captured.

tiny() - Static method in class dev.tamboui.widgets.logo.Logo
Create a new Tamboui logo widget with a tiny size.

TINY - Enum constant in enum class dev.tamboui.widgets.logo.Logo.Size
A tiny logo (2 lines).

Tiny (default, 2 lines) - Section in class dev.tamboui.widgets.logo.Logo

TIOCGWINSZ - Static variable in class dev.tamboui.backend.panama.unix.LibC
ioctl request code to get terminal window size.

TIOCGWINSZ - Static variable in class dev.tamboui.backend.panama.unix.PlatformConstants
ioctl request code to get terminal window size.

title() - Method in class dev.tamboui.widgets.chart.Axis
Returns the axis title.

title(Line) - Method in class dev.tamboui.toolkit.elements.Panel
Sets the panel title with styled text.

title(Line) - Method in class dev.tamboui.widgets.chart.Axis.Builder
Sets the axis title.

title(Span...) - Method in class dev.tamboui.widgets.chart.Axis.Builder
Sets the axis title with styling.

title(Title) - Method in class dev.tamboui.widgets.block.Block.Builder
Sets the top title.

title(String) - Method in class dev.tamboui.export.svg.SvgOptions
Sets the window title.

title(String) - Method in class dev.tamboui.toolkit.elements.BarChartElement

Sets the title.

title(String) - Method in class dev.tamboui.toolkit.elements.CalendarElement
Sets the title.

title(String) - Method in class dev.tamboui.toolkit.elements.CanvasElement
Sets the title.

title(String) - Method in class dev.tamboui.toolkit.elements.ChartElement
Sets the title.

title(String) - Method in class dev.tamboui.toolkit.elements.DialogElement
Sets the dialog title.

title(String) - Method in class dev.tamboui.toolkit.elements.GaugeElement
Sets the title for the gauge's border.

title(String) - Method in class dev.tamboui.toolkit.elements.ListElement
Sets the title.

title(String) - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Sets the title.

title(String) - Method in class dev.tamboui.toolkit.elements.Panel
Sets the panel title.

title(String) - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Sets the title.

title(String) - Method in class dev.tamboui.toolkit.elements.SparklineElement
Sets the title.

title(String) - Method in class dev.tamboui.toolkit.elements.TableElement
Sets the title.

title(String) - Method in class dev.tamboui.toolkit.elements.TabsElement
Sets the title for the border.

title(String) - Method in class dev.tamboui.toolkit.elements.TextAreaElement
Sets the title for the border.

title(String) - Method in class dev.tamboui.toolkit.elements.TextInputElement
Sets the title for the border.

title(String) - Method in class dev.tamboui.toolkit.elements.TreeElement
Sets the title.

title(String) - Method in class dev.tamboui.widgets.block.Block.Builder
Sets the top title from a string.

title(String) - Method in class dev.tamboui.widgets.chart.Axis.Builder
Sets the axis title.

title(String) - Method in class dev.tamboui.widgets.error.ErrorDisplay.Builder
Sets the title shown at the top of the border.

Title - Class in dev.tamboui.widgets.block
A title for a block, with optional alignment and overflow handling.

Title(Line, Alignment, Overflow) - Constructor for class dev.tamboui.widgets.block.Title
Creates a new title.

titleBottom(Title) - Method in class dev.tamboui.widgets.block.Block.Builder
Sets the bottom title.

titleBottom(String) - Method in class dev.tamboui.widgets.block.Block.Builder
Sets the bottom title from a string.

titleEllipsis() - Method in class dev.tamboui.toolkit.elements.Panel
Truncate title with ellipsis at end if it doesn't fit: "Long title..."

titleEllipsisStart() - Method in class dev.tamboui.toolkit.elements.Panel
Truncate title with ellipsis at start if it doesn't fit: "...ong title"

titleOverflow(Overflow) - Method in class dev.tamboui.toolkit.elements.Panel
Sets the title overflow mode.

titles() - Method in class dev.tamboui.widgets.tabs.Tabs
Returns the tab titles.

titles(Line...) - Method in class dev.tamboui.widgets.tabs.Tabs.Builder
Sets the tab titles from lines.

titles(String...) - Method in class dev.tamboui.toolkit.elements.TabsElement
Sets the tab titles.

titles(String...) - Method in class dev.tamboui.widgets.tabs.Tabs.Builder
Sets the tab titles from strings.

titles(List) - Method in class dev.tamboui.widgets.tabs.Tabs.Builder
Sets the tab titles from a list.

titles(List) - Method in class dev.tamboui.toolkit.elements.TabsElement
Sets the tab titles from a list.

to(OutputStream) - Method in class dev.tamboui.export.ExportStep
Writes the exported output to the given stream (UTF-8).

to(Writer) - Method in class dev.tamboui.export.ExportStep
Writes the exported output to the given writer.

toAnsiBackground() - Method in class dev.tamboui.style.Color.Ansi

toAnsiBackground() - Method in class dev.tamboui.style.Color.Indexed

toAnsiBackground() - Method in class dev.tamboui.style.Color.Named

toAnsiBackground() - Method in class dev.tamboui.style.Color.Reset

toAnsiBackground() - Method in class dev.tamboui.style.Color.Rgb

toAnsiBackground() - Method in interface dev.tamboui.style.Color
Converts this color to an ANSI background color code.

toAnsiForeground() - Method in class dev.tamboui.style.Color.Ansi

toAnsiForeground() - Method in class dev.tamboui.style.Color.Indexed

toAnsiForeground() - Method in class dev.tamboui.style.Color.Named

toAnsiForeground() - Method in class dev.tamboui.style.Color.Reset

toAnsiForeground() - Method in class dev.tamboui.style.Color.Rgb

toAnsiForeground() - Method in interface dev.tamboui.style.Color
Converts this color to an ANSI foreground color code.

toAnsiString() - Method in class dev.tamboui.buffer.Buffer
Renders the buffer content as an ANSI-escaped string.

toAnsiStringTrimmed() - Method in class dev.tamboui.buffer.Buffer
Renders the buffer content as an ANSI-escaped string, trimming trailing whitespace from each line.

toAnsiStringWithCursorPositioning() - Method in class dev.tamboui.buffer.Buffer
Renders the buffer content as an ANSI-escaped string using explicit cursor positioning.

toAnsiUnderline() - Method in class dev.tamboui.style.Color.Indexed

toAnsiUnderline() - Method in class dev.tamboui.style.Color.Named

toAnsiUnderline() - Method in class dev.tamboui.style.Color.Rgb

toAnsiUnderline() - Method in interface dev.tamboui.style.Color

Converts this color to an ANSI underline color code.

toBufferedImage() - Method in class dev.tamboui.image.ImageData
Converts this image data to a BufferedImage.

toBuilder() - Method in interface dev.tamboui.tui.bindings.Bindings
Returns a builder pre-populated with this bindings' triggers.

toBuilder() - Method in class dev.tamboui.tui.bindings.DefaultBindings

toByteArray() - Method in class dev.tamboui.backend.panama.ByteArrayBuilder
Creates a new byte array containing only the valid data.

toBytes() - Method in class dev.tamboui.export.ExportStep
Returns the exported output as UTF-8 bytes.

toConfig() - Method in class dev.tamboui.picocli.TuiMixin
Creates a TuiConfig based on the parsed CLI options.

toCss() - Method in class dev.tamboui.css.selector.AttributeSelector

toCss() - Method in class dev.tamboui.css.selector.ChildSelector

toCss() - Method in class dev.tamboui.css.selector.ClassSelector

toCss() - Method in class dev.tamboui.css.selector.CompoundSelector

toCss() - Method in class dev.tamboui.css.selector.DescendantSelector

toCss() - Method in class dev.tamboui.css.selector.IdSelector

toCss() - Method in class dev.tamboui.css.selector.PseudoClassSelector

toCss() - Method in interface dev.tamboui.css.selector.Selector
Returns a CSS string representation of this selector.

toCss() - Method in class dev.tamboui.css.selector.TypeSelector

toCss() - Method in class dev.tamboui.css.selector.UniversalSelector

today(Style) - Static method in class dev.tamboui.widgets.calendar.CalendarEventStore
Creates an event store with today's date styled.

toDouble() - Method in class dev.tamboui.layout.Fraction
Converts this fraction to a double.

toExpression() - Method in class dev.tamboui.layout.cassowary.Term
Converts this term to an expression.

toExpression() - Method in class dev.tamboui.layout.cassowary.Variable
Creates an expression containing only this variable with coefficient 1.

toFile(Path) - Method in class dev.tamboui.export.ExportRequest
Exports the buffer to the given path.

toFile(Path) - Method in class dev.tamboui.export.ExportStep
Writes the exported output to the given path.

toFraction() - Method in class dev.tamboui.layout.Constraint.Ratio
Converts this ratio to a Fraction for exact arithmetic.

toggle() - Method in class dev.tamboui.tui.overlay.DebugOverlay
Toggles the visibility of the debug overlay.

toggle() - Method in class dev.tamboui.widgets.checkbox.CheckboxState
Toggles the checked state and returns the new value.

toggle() - Method in class dev.tamboui.widgets.form.BooleanFieldState
Toggles the value (true becomes false, false becomes true).

toggle() - Method in class dev.tamboui.widgets.toggle.ToggleState

Toggles the on/off state and returns the new value.

Toggle - Class in dev.tamboui.widgets.toggle
A toggle switch widget that displays an on/off state.

TOGGLE - Enum constant in enum class dev.tamboui.widgets.form.FieldType
On/off toggle switch for boolean values.

TOGGLE - Enum constant in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Toggle spinner with two states.

TOGGLE_DEBUG_OVERLAY - Static variable in class dev.tamboui.tui.bindings.Actions
Toggle the debug overlay.

Toggle.Builder - Class in dev.tamboui.widgets.toggle
Builder for `Toggle`.

toggleClass(String, boolean) - Method in class dev.tamboui.toolkit.element.StyledElement
Toggles a CSS class based on a condition.

toggleExpanded() - Method in class dev.tamboui.widgets.tree.TreeNode
Toggles the expanded state.

toggleSelected() - Method in class dev.tamboui.toolkit.elements.TreeElement
Toggles the expanded state of the selected node.

ToggleState - Class in dev.tamboui.widgets.toggle
State for the `Toggle` widget, tracking on/off status.

ToggleState() - Constructor for class dev.tamboui.widgets.toggle.ToggleState
Creates a new state in the off position.

ToggleState(boolean) - Constructor for class dev.tamboui.widgets.toggle.ToggleState
Creates a new state with the given initial value.

toHsl(Color) - Static method in enum class dev.tamboui.tfx.TFxColorSpace
Converts a color to HSL components.

toHsv(Color) - Static method in enum class dev.tamboui.tfx.TFxColorSpace
Converts a color to HSV components.

toInt() - Method in class dev.tamboui.layout.Fraction
Converts this fraction to an int by truncating toward zero.

toJavaDuration() - Method in class dev.tamboui.tfx.TFxDuration
Converts to java.time.Duration.

Token - Class in dev.tamboui.css.parser
Represents a token in the CSS lexer output.

Token(Token.Position) - Constructor for class dev.tamboui.css.parser.Token
Creates a token at the given source position.

Token.CloseBrace - Class in dev.tamboui.css.parser
A closing brace "}".

Token.CloseBracket - Class in dev.tamboui.css.parser
A closing bracket "]".

Token.CloseParen - Class in dev.tamboui.css.parser
A closing parenthesis ")".

Token.Colon - Class in dev.tamboui.css.parser
A colon token ":".

Token.Comma - Class in dev.tamboui.css.parser
A comma ",".

Token.Delim - Class in dev.tamboui.css.parser
A delimiter character (e.g., ".", ">", "*", "&").

Token.EOF - Class in dev.tamboui.css.parser
End of file marker.

Token.Hash - Class in dev.tamboui.css.parser
A hash token for colors or IDs (e.g., "#ff0000", "#sidebar").

Token.Ident - Class in dev.tamboui.css.parser
An identifier token (e.g., "color", "Panel", "bold").

Token.Number - Class in dev.tamboui.css.parser
A number token (e.g., "42", "3.14", "50%").

Token.OpenBrace - Class in dev.tamboui.css.parser
An opening brace "{".

Token.OpenBracket - Class in dev.tamboui.css.parser
An opening bracket "[".

Token.OpenParen - Class in dev.tamboui.css.parser
An opening parenthesis "(".

Token.Position - Class in dev.tamboui.css.parser
Position in source code (line and column, 1-based).

Token.Semicolon - Class in dev.tamboui.css.parser
A semicolon token ";".

Token.StringToken - Class in dev.tamboui.css.parser
A string token (e.g., "hello world" or 'hello world').

Token.Variable - Class in dev.tamboui.css.parser
A variable reference (e.g., "$primary").

Token.Whitespace - Class in dev.tamboui.css.parser
Whitespace (spaces, tabs, newlines).

tokenize() - Method in class dev.tamboui.css.parser.CssLexer
Tokenizes the entire input and returns a list of tokens.

tokenizeFiltered() - Method in class dev.tamboui.css.parser.CssLexer
Tokenizes the input, filtering out whitespace tokens.

toList(Stream) - Static method in class dev.tamboui.util.CollectionUtil
Collects a stream into a list.

toLong() - Method in class dev.tamboui.layout.Fraction
Converts this fraction to a long by truncating toward zero.

Toolkit - Class in dev.tamboui.toolkit
Static factory methods for building UI elements with the DSL.

ToolkitApp - Class in dev.tamboui.toolkit.app
Base class for DSL-based TUI applications.

ToolkitApp() - Constructor for class dev.tamboui.toolkit.app.ToolkitApp
Creates a new ToolkitApp.

ToolkitEffects - Class in dev.tamboui.tfx.toolkit
High-level API for integrating TFX effects with the Toolkit DSL.

ToolkitEffects() - Constructor for class dev.tamboui.tfx.toolkit.ToolkitEffects
Creates a new ToolkitEffects instance.

ToolkitPostRenderProcessor - Interface in dev.tamboui.toolkit.app
Processor called after each frame is rendered.

ToolkitRunner - Class in dev.tamboui.toolkit.app
Runner for DSL applications with automatic event routing.

ToolkitRunner.Builder - Class in dev.tamboui.toolkit.app
Builder for `ToolkitRunner` instances.

ToolkitRunner.ScheduledAction - Class in dev.tamboui.toolkit.app
A handle to a scheduled action that can be cancelled.

top() - Method in class dev.tamboui.layout.Margin

Returns the top margin.

top() - Method in class dev.tamboui.layout.Padding
Returns the top padding.

top() - Method in class dev.tamboui.layout.Rect
Returns the top edge (same as `Rect.y()`).

top(Element) - Method in class dev.tamboui.toolkit.elements.DockElement
Sets the top region element.

top(Element, Constraint) - Method in class dev.tamboui.toolkit.elements.DockElement
Sets the top region element with a height constraint.

top(Widget) - Method in class dev.tamboui.layout.dock.Dock.Builder
Sets the top region widget.

TOP - Enum constant in enum class dev.tamboui.widgets.block.Borders
Top border.

TOP - Enum constant in enum class dev.tamboui.widgets.chart.LegendPosition
Top center

TOP_CENTER - Enum constant in enum class dev.tamboui.layout.ContentAlignment
Top center.

TOP_LEFT - Enum constant in enum class dev.tamboui.layout.ContentAlignment
Top-left corner.

TOP_LEFT - Enum constant in enum class dev.tamboui.widgets.chart.LegendPosition
Top left corner

TOP_LEFT_TO_BOTTOM_RIGHT - Enum constant in enum class dev.tamboui.tfx.pattern.DiagonalPattern.DiagonalDirection
Sweeps diagonally from top-left corner to bottom-right corner

TOP_ONLY - Static variable in enum class dev.tamboui.widgets.block.Borders
Top border only.

TOP_RIGHT - Enum constant in enum class dev.tamboui.layout.ContentAlignment
Top-right corner.

TOP_RIGHT - Enum constant in enum class dev.tamboui.widgets.chart.LegendPosition
Top right corner (default)

TOP_RIGHT_TO_BOTTOM_LEFT - Enum constant in enum class dev.tamboui.tfx.pattern.DiagonalPattern.DiagonalDirection
Sweeps diagonally from top-right corner to bottom-left corner

topHeight(Constraint) - Method in class dev.tamboui.layout.dock.Dock.Builder
Sets the height constraint for the top region.

topHeight(Constraint) - Method in class dev.tamboui.toolkit.elements.DockElement
Sets the height constraint for the top region.

topHorizontal() - Method in class dev.tamboui.widgets.block.BorderSet
Returns the top horizontal border character.

topHorizontal(String) - Method in class dev.tamboui.widgets.block.BorderSet.Builder
Sets the top horizontal border character.

topLeft() - Method in class dev.tamboui.widgets.block.BorderSet
Returns the top-left corner character.

topLeft(String) - Method in class dev.tamboui.widgets.block.BorderSet.Builder
Sets the top-left corner character.

topLeftToBottomRight() - Static method in class dev.tamboui.tfx.pattern.DiagonalPattern
Creates a diagonal pattern from top-left to bottom-right.

toPng() - Method in class dev.tamboui.image.ImageData
Encodes this image as PNG bytes.

topRight() - Method in class dev.tamboui.widgets.block.BorderSet
Returns the top-right corner character.

topRight(String) - Method in class dev.tamboui.widgets.block.BorderSet.Builder
Sets the top-right corner character.

topRightToBottomLeft() - Static method in class dev.tamboui.tfx.pattern.DiagonalPattern
Creates a diagonal pattern from top-right to bottom-left.

toRgb() - Method in class dev.tamboui.style.Color.Ansi

toRgb() - Method in class dev.tamboui.style.Color.Indexed

toRgb() - Method in class dev.tamboui.style.Color.Named

toRgb() - Method in class dev.tamboui.style.Color.Reset

toRgb() - Method in class dev.tamboui.style.Color.Rgb

toRgb() - Method in interface dev.tamboui.style.Color
Converts this color to RGB.

toSizedWidget() - Method in class dev.tamboui.widgets.list.ListItem
Converts this list item to a `SizedWidget` for use with the new `ListWidget` builder.

toString() - Method in class dev.tamboui.buffer.Buffer

toString() - Method in class dev.tamboui.buffer.Cell

toString() - Method in class dev.tamboui.buffer.DiffResult

toString() - Method in class dev.tamboui.css.cascade.CssStyleResolver

toString() - Method in class dev.tamboui.css.cascade.PseudoClassState

toString() - Method in class dev.tamboui.css.cascade.TypedPropertyMap

toString() - Method in class dev.tamboui.css.model.PropertyValue

toString() - Method in class dev.tamboui.css.model.Rule

toString() - Method in class dev.tamboui.css.model.Stylesheet

toString() - Method in class dev.tamboui.css.parser.Token.CloseBrace

toString() - Method in class dev.tamboui.css.parser.Token.CloseBracket

toString() - Method in class dev.tamboui.css.parser.Token.CloseParen

toString() - Method in class dev.tamboui.css.parser.Token.Colon

toString() - Method in class dev.tamboui.css.parser.Token.Comma

toString() - Method in class dev.tamboui.css.parser.Token.Delim

toString() - Method in class dev.tamboui.css.parser.Token.EOF

toString() - Method in class dev.tamboui.css.parser.Token.Hash

toString() - Method in class dev.tamboui.css.parser.Token.Ident

toString() - Method in class dev.tamboui.css.parser.Token.Number

toString() - Method in class dev.tamboui.css.parser.Token.OpenBrace

toString() - Method in class dev.tamboui.css.parser.Token.OpenBracket

toString() - Method in class dev.tamboui.css.parser.Token.OpenParen

toString() - Method in class dev.tamboui.css.parser.Token.Position

toString() - Method in class dev.tamboui.css.parser.Token.Semicolon

toString() - Method in class dev.tamboui.css.parser.Token.StringToken

toString() - Method in class dev.tamboui.css.parser.Token.Variable

toString() - Method in class dev.tamboui.css.parser.Token.Whitespace

toString() - Method in class dev.tamboui.css.selector.AttributeSelector

toString() - Method in class dev.tamboui.css.selector.ChildSelector

toString() - Method in class dev.tamboui.css.selector.ClassSelector

toString() - Method in class dev.tamboui.css.selector.CompoundSelector

toString() - Method in class dev.tamboui.css.selector.DescendantSelector

toString() - Method in class dev.tamboui.css.selector.IdSelector

toString() - Method in class dev.tamboui.css.selector.PseudoClassSelector

toString() - Method in class dev.tamboui.css.selector.TypeSelector

toString() - Method in class dev.tamboui.css.selector.UniversalSelector

toString() - Method in class dev.tamboui.export.ExportStep
Returns the exported output as a string.

toString() - Method in class dev.tamboui.image.capability.TerminalImageCapabilities

toString() - Method in class dev.tamboui.layout.cassowary.CassowaryConstraint

toString() - Method in class dev.tamboui.layout.cassowary.Expression

toString() - Method in enum class dev.tamboui.layout.cassowary.Relation

toString() - Method in class dev.tamboui.layout.cassowary.Strength

toString() - Method in class dev.tamboui.layout.cassowary.Term

toString() - Method in class dev.tamboui.layout.cassowary.Variable

toString() - Method in class dev.tamboui.layout.Constraint.Fill

toString() - Method in class dev.tamboui.layout.Constraint.Fit

toString() - Method in class dev.tamboui.layout.Constraint.Length

toString() - Method in class dev.tamboui.layout.Constraint.Max

toString() - Method in class dev.tamboui.layout.Constraint.Min

toString() - Method in class dev.tamboui.layout.Constraint.Percentage

toString() - Method in class dev.tamboui.layout.Constraint.Ratio

toString() - Method in class dev.tamboui.layout.Fraction

toString() - Method in class dev.tamboui.layout.grid.GridArea.AreaBounds

toString() - Method in class dev.tamboui.layout.Margin

toString() - Method in class dev.tamboui.layout.Padding

toString() - Method in class dev.tamboui.layout.Position

toString() - Method in class dev.tamboui.layout.Rect

toString() - Method in class dev.tamboui.layout.Size

toString() - Method in class dev.tamboui.layout.Spacing.Overlap

toString() - Method in class dev.tamboui.layout.Spacing.Space

toString() - Method in class dev.tamboui.style.Color.Ansi

toString() - Method in class dev.tamboui.style.Color.Indexed

toString() - Method in class dev.tamboui.style.Color.Named

toString() - Method in class dev.tamboui.style.Color.Reset

toString() - Method in class dev.tamboui.style.Color.Rgb

toString() - Method in class dev.tamboui.style.Hyperlink

toString() - Method in class dev.tamboui.style.PropertyDefinition

toString() - Method in class dev.tamboui.style.Style

toString() - Method in class dev.tamboui.style.StyledAreaInfo

toString() - Method in class dev.tamboui.style.Tags

toString() - Method in class dev.tamboui.style.Width

toString() - Method in class dev.tamboui.terminal.CompletedFrame

toString() - Method in class dev.tamboui.text.Line

toString() - Method in class dev.tamboui.text.Masked

toString() - Method in class dev.tamboui.text.Span

toString() - Method in class dev.tamboui.text.Text

toString() - Method in class dev.tamboui.tfx.EffectTimer

toString() - Method in class dev.tamboui.tfx.SimpleRng

toString() - Method in class dev.tamboui.tfx.TFxDuration

toString() - Method in class dev.tamboui.toolkit.element.ChildPosition

toString() - Method in class dev.tamboui.toolkit.element.Size

toString() - Method in class dev.tamboui.toolkit.element.StyledSpan

toString() - Method in class dev.tamboui.toolkit.elements.GridSize

toString() - Method in class dev.tamboui.toolkit.elements.Gutter

toString() - Method in class dev.tamboui.tui.bindings.KeyTrigger

toString() - Method in class dev.tamboui.tui.bindings.MouseTrigger

toString() - Method in class dev.tamboui.tui.error.RenderError

toString() - Method in class dev.tamboui.tui.event.ActionEvent

toString() - Method in class dev.tamboui.tui.event.KeyEvent

toString() - Method in class dev.tamboui.tui.event.KeyModifiers

toString() - Method in class dev.tamboui.tui.event.MouseEvent

toString() - Method in class dev.tamboui.tui.event.ResizeEvent

toString() - Method in class dev.tamboui.tui.event.TickEvent

toString() - Method in class dev.tamboui.tui.InlineTuiConfig

toString() - Method in class dev.tamboui.tui.TuiConfig

toString() - Method in class dev.tamboui.widgets.barchart.BarChart.BarSet

toString() - Method in class dev.tamboui.widgets.block.BorderSet

toString() - Method in class dev.tamboui.widgets.block.Title

toString() - Method in class dev.tamboui.widgets.canvas.Painter.GridPoint

toString() - Method in class dev.tamboui.widgets.canvas.shapes.Circle

toString() - Method in class dev.tamboui.widgets.canvas.shapes.Line

toString() - Method in class dev.tamboui.widgets.canvas.shapes.Points

toString() - Method in class dev.tamboui.widgets.canvas.shapes.Rectangle

toString() - Method in class dev.tamboui.widgets.form.ValidationResult

toString() - Method in class dev.tamboui.widgets.gauge.LineGauge.LineSet

toString() - Method in class dev.tamboui.widgets.list.ListItem

toString() - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.SymbolSet

toString() - Method in class dev.tamboui.widgets.sparkline.Sparkline.BarSet

toString() - Method in class dev.tamboui.widgets.spinner.SpinnerFrameSet

toString() - Method in class dev.tamboui.widgets.tree.TreeNode
Returns a string representation of this node.

toStyle() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Converts this resolved style to a TamboUI Style object.

total() - Method in class dev.tamboui.toolkit.element.ChildPosition
Returns the total number of children.

totalHeight() - Method in class dev.tamboui.widgets.table.Row
Returns the total height including bottom margin.

toTemplates() - Method in class dev.tamboui.layout.grid.GridArea
Returns the row templates that were used to create this GridArea.

track() - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.SymbolSet
Returns the track character.

TRACK_COLOR - Static variable in class dev.tamboui.widgets.scrollbar.Scrollbar
Property key for the track (background) color.

trackColor(Color) - Method in class dev.tamboui.toolkit.elements.ScrollbarElement
Sets the track color.

trackColor(Color) - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.Builder
Sets the track (background) color programmatically.

trackStyle(Style) - Method in class dev.tamboui.toolkit.elements.ScrollbarElement
Sets the track style.

trackStyle(Style) - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.Builder
Sets the style for the track (background).

trackSymbol(String) - Method in class dev.tamboui.toolkit.elements.ScrollbarElement
Sets the track symbol.

trackSymbol(String) - Method in class dev.tamboui.widgets.scrollbar.Scrollbar.Builder
Sets the track (background) symbol.

TransitionProgress - Class in dev.tamboui.tfx.pattern
Encapsulates alpha progression with smooth transitions.

TransitionProgress(float) - Constructor for class dev.tamboui.tfx.pattern.TransitionProgress
Creates a new transition progress handler with the specified transition width.

transitionWidth() - Method in class dev.tamboui.tfx.pattern.TransitionProgress
Returns the transition width.

tree() - Static method in class dev.tamboui.toolkit.Toolkit
Creates an empty tree.

tree(TreeNode...) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a tree with the given root nodes.

TreeElement<T> - Class in dev.tamboui.toolkit.elements
A scrollable, keyboard-navigable hierarchical tree view.

TreeElement() - Constructor for class dev.tamboui.toolkit.elements.TreeElement
Creates an empty tree element.

TreeElement(TreeNode...) - Constructor for class dev.tamboui.toolkit.elements.TreeElement
Creates a tree element with the given root nodes.

TreeModel<T> - Interface in dev.tamboui.widgets.tree
Interface for accessing tree data in a decoupled manner.

TreeNode<T> - Class in dev.tamboui.widgets.tree
A node in a tree data structure that also implements `TreeModel`.

TreeState - Class in dev.tamboui.widgets.tree
State for a tree widget, tracking selection and scroll position.

TreeState() - Constructor for class dev.tamboui.widgets.tree.TreeState
Creates a new tree state with default values.

TreeWidget<T> - Class in dev.tamboui.widgets.tree
A widget for displaying hierarchical tree data.

TreeWidget.Builder<T> - Class in dev.tamboui.widgets.tree
Builder for `TreeWidget`.

TreeWidget.FlatEntry<T> - Class in dev.tamboui.widgets.tree
A flattened entry representing a visible tree node.

triggersFor(String) - Method in interface dev.tamboui.tui.bindings.Bindings
Returns all triggers for the given action.

triggersFor(String) - Method in class dev.tamboui.tui.bindings.DefaultBindings

truncateWithEllipsis(String, int, CharWidth.TruncatePosition) - Static method in class dev.tamboui.text.CharWidth
Truncates a string to fit within the given display width, adding an ellipsis.

truncateWithEllipsis(String, int, String, CharWidth.TruncatePosition) - Static method in class dev.tamboui.text.CharWidth
Truncates a string to fit within the given display width, adding a custom ellipsis.

TuiCommand - Class in dev.tamboui.picocli
Base class for PicoCLI commands that run TUI applications.

TuiCommand() - Constructor for class dev.tamboui.picocli.TuiCommand
Creates a new TuiCommand.

TuiConfig - Class in dev.tamboui.tui
Configuration options for `TuiRunner`.

TuiConfig(boolean, boolean, boolean, boolean, Duration, Duration, Duration, boolean, Bindings, RenderErrorHandler, PrintStream, boolean, List, Backend, ScheduledExecutorService) - Constructor for class dev.tamboui.tui.TuiConfig
Creates a new TUI configuration with the specified options.

TuiConfig.Builder - Class in dev.tamboui.tui
Builder for `TuiConfig`.

TuiException - Exception Class in dev.tamboui.tui.error
Exception for TUI framework related errors.

TuiException(String) - Constructor for exception class dev.tamboui.tui.error.TuiException
Creates a new TUI exception with the given message.

TuiException(String, Throwable) - Constructor for exception class dev.tamboui.tui.error.TuiException
Creates a new TUI exception with the given message and cause.

TuiMixin - Class in dev.tamboui.picocli
PicoCLI mixin that provides common TUI-related command line options.

TuiMixin() - Constructor for class dev.tamboui.picocli.TuiMixin
Creates a new TuiMixin with default option values.

tuiOptions() - Method in class dev.tamboui.picocli.TuiCommand
Returns the TUI options mixin.

tuiRunner() - Method in class dev.tamboui.toolkit.app.InlineToolkitRunner
Returns the underlying InlineTuiRunner.

tuiRunner() - Method in class dev.tamboui.toolkit.app.ToolkitRunner
Returns the underlying TuiRunner.

TuiRunner - Class in dev.tamboui.tui
Main entry point for running TUI applications.

TuiRunner.Builder - Class in dev.tamboui.tui
Builder for `TuiRunner` instances.

TuiRunner.ConfiguredRunner - Class in dev.tamboui.tui
A fully configured TuiRunner ready to execute.

type() - Method in class dev.tamboui.toolkit.element.ElementRegistry.ElementInfo
Returns the element type name.

type(FieldType) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Sets the field type.

TypedPropertyMap - Class in dev.tamboui.css.cascade
A type-safe heterogeneous map for CSS property values.

TypedPropertyMap.Builder - Class in dev.tamboui.css.cascade
Builder for TypedPropertyMap.

typeName() - Method in class dev.tamboui.css.selector.TypeSelector
Returns the type name this selector matches.

TypeSelector - Class in dev.tamboui.css.selector
A type selector that matches elements by their type name.

TypeSelector(String) - Constructor for class dev.tamboui.css.selector.TypeSelector

Creates a type selector for the given type name.

U

UiRunnable - Class in dev.tamboui.tui.event
An event that encapsulates a `Runnable` to be executed on the render thread.

UiRunnable(Runnable) - Constructor for class dev.tamboui.tui.event.UiRunnable
Creates a new UiRunnable with the given action.

unbind(String) - Method in interface dev.tamboui.tui.bindings.Bindings.Builder
Removes all triggers for an action.

UNCHECKED_COLOR - Static variable in class dev.tamboui.widgets.checkbox.Checkbox
CSS property for the unchecked state foreground color.

UNCHECKED_SYMBOL - Static variable in class dev.tamboui.widgets.checkbox.Checkbox
CSS property for the unchecked symbol.

uncheckedColor(Color) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Sets the color when checkbox is unchecked.

uncheckedColor(Color) - Method in class dev.tamboui.widgets.checkbox.Checkbox.Builder
Sets the foreground color when unchecked.

uncheckedSymbol() - Method in class dev.tamboui.widgets.checkbox.Checkbox
Returns the symbol used for unchecked state.

uncheckedSymbol(String) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Sets the symbol to display when checkbox is unchecked.

uncheckedSymbol(String) - Method in class dev.tamboui.widgets.checkbox.Checkbox.Builder
Sets the symbol to display when unchecked.

underlineColor() - Method in class dev.tamboui.style.Style
Returns the underline color if set.

underlineColor(Color) - Method in class dev.tamboui.style.Style
Returns a new style with the given underline color.

underlined() - Method in class dev.tamboui.style.Style
Enables underline.

underlined() - Method in class dev.tamboui.text.Line
Returns a new line with underline applied to all spans.

underlined() - Method in class dev.tamboui.text.Span
Returns a new span with underlined style.

underlined() - Method in class dev.tamboui.text.Text
Returns a new text with underlined style.

underlined() - Method in class dev.tamboui.toolkit.element.StyledElement
Applies the underlined modifier.

UNDERLINED - Enum constant in enum class dev.tamboui.style.Modifier
Underlined text.

unfilled() - Method in class dev.tamboui.widgets.gauge.LineGauge.LineSet
Returns the character used for the unfilled portion.

UNFILLED_COLOR - Static variable in class dev.tamboui.widgets.gauge.LineGauge
Property key for the unfilled portion color.

unfilledColor(Color) - Method in class dev.tamboui.toolkit.elements.LineGaugeElement
Sets the color for the unfilled portion.

unfilledColor(Color) - Method in class dev.tamboui.widgets.gauge.LineGauge.Builder
Sets the unfilled portion color programmatically.

unfilledStyle(Style) - Method in class dev.tamboui.toolkit.elements.LineGaugeElement

Sets the style for the unfilled portion.

unfilledStyle(Style) - Method in class dev.tamboui.widgets.gauge.LineGauge.Builder
Sets the style for the unfilled portion of the gauge.

UNHANDLED - Enum constant in enum class dev.tamboui.toolkit.event.EventResult
The event was not handled and should continue propagating.

UNICODE - Enum constant in enum class dev.tamboui.widgets.tree.GuideStyle
Unicode box-drawing characters: ├──, │, └──.

uniform(int) - Static method in class dev.tamboui.layout.Margin
Returns a uniform margin on all sides.

uniform(int) - Static method in class dev.tamboui.layout.Padding
Returns a uniform padding on all sides.

uniform(int) - Static method in class dev.tamboui.toolkit.elements.Gutter
Creates a gutter with uniform spacing in both directions.

uninstall() - Static method in class dev.tamboui.internal.record.AnsiTerminalCapture
Uninstalls the capture and restores original System.out.

union(Rect) - Method in class dev.tamboui.layout.Rect
Returns the union of this rectangle with another.

uniqueId(String) - Method in class dev.tamboui.export.svg.SvgOptions
Sets a custom unique ID prefix for CSS classes and clip paths.

UniversalSelector - Class in dev.tamboui.css.selector
A universal selector that matches all elements.

unixTerminal() - Method in class dev.tamboui.backend.panama.PanamaBackend
Returns the underlying Unix terminal for advanced operations.

UnixTerminal - Class in dev.tamboui.backend.panama.unix
Unix terminal operations using Panama FFI.

UnixTerminal() - Constructor for class dev.tamboui.backend.panama.unix.UnixTerminal
Creates a new Unix terminal instance.

UNKNOWN - Enum constant in enum class dev.tamboui.tui.event.KeyCode
Unknown or unrecognized key

UNKNOWN - Static variable in class dev.tamboui.css.parser.Token.Position
Position representing an unknown source location.

UNKNOWN - Static variable in class dev.tamboui.toolkit.element.Size
Unknown size - element should fill available space in both dimensions.

UnknownConstraintException - Exception Class in dev.tamboui.layout.cassowary
Thrown when attempting to remove a constraint that does not exist in the solver.

UnknownConstraintException(CassowaryConstraint) - Constructor for exception class dev.tamboui.layout.cassowary.UnknownConstraintException
Creates a new exception for the unknown constraint.

UnknownCssPropertyException - Exception Class in dev.tamboui.css.cascade
Exception thrown when an unknown CSS property is encountered
and `UnknownPropertyBehavior.FAIL` is configured.

UnknownCssPropertyException(String, String) - Constructor for exception class dev.tamboui.css.cascade.UnknownCssPropertyException
Creates a new exception for an unknown CSS property.

UnknownPropertyBehavior - Enum Class in dev.tamboui.css.cascade
Defines behavior when encountering unknown CSS properties.

UnsatisfiableConstraintException - Exception Class in dev.tamboui.layout.cassowary
Thrown when a required constraint cannot be satisfied.

UnsatisfiableConstraintException(CassowaryConstraint) - Constructor for exception class dev.tamboui.layout.cassowary.UnsatisfiableConstraintException
Creates a new exception for the unsatisfiable constraint.

UNSELECTED_COLOR - Static variable in class dev.tamboui.widgets.toggle.Toggle
CSS property for the unselected color (inline choice mode).

UNSELECTED_INDICATOR - Static variable in class dev.tamboui.widgets.toggle.Toggle
CSS property for the unselected indicator (inline choice mode).

unselectedColor(Color) - Method in class dev.tamboui.widgets.toggle.Toggle.Builder
Sets the color for the unselected option indicator (inline choice mode).

unselectedIndicator(String) - Method in class dev.tamboui.widgets.toggle.Toggle.Builder
Sets the indicator for the unselected option (inline choice mode).

UP - Enum constant in enum class dev.tamboui.tui.event.KeyCode
Up arrow key.

UP_TO_DOWN - Enum constant in enum class dev.tamboui.tfx.Motion
Movement from top to bottom

updateVariables() - Method in class dev.tamboui.layout.cassowary.Solver
Updates all variable values after constraint changes.

upToDown(float) - Static method in class dev.tamboui.tfx.pattern.SweepPattern
Creates an up-to-down sweep pattern.

url() - Method in class dev.tamboui.style.Hyperlink
Returns the URL of this hyperlink.

Usage Example - Section in class dev.tamboui.css.engine.StyleEngine

Usage Examples - Section in class dev.tamboui.widgets.tree.TreeWidget

Usage in widgets: - Section in interface dev.tamboui.style.StylePropertyResolver

useUnicode(boolean) - Method in class dev.tamboui.toolkit.elements.GaugeElement
Enables or disables unicode block characters.

useUnicode(boolean) - Method in class dev.tamboui.widgets.gauge.Gauge.Builder
Enables or disables unicode block characters for smoother rendering.

V

valid() - Static method in class dev.tamboui.widgets.form.ValidationResult
Creates a valid result indicating the validation passed.

validate(Validator...) - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Adds validators to this field.

validate(String) - Method in interface dev.tamboui.widgets.form.Validator
Validates the given value.

validateAll() - Method in class dev.tamboui.toolkit.elements.FormElement
Validates all fields in the form.

validateField() - Method in class dev.tamboui.toolkit.elements.FormFieldElement
Validates the current field value.

validateOnSubmit(boolean) - Method in class dev.tamboui.toolkit.elements.FormElement
Sets whether to validate all fields before submitting.

validationErrors() - Method in class dev.tamboui.toolkit.elements.FormElement
Returns validation errors for all fields.

validationResult(String) - Method in class dev.tamboui.widgets.form.FormState
Returns the validation result for the given field name.

ValidationResult - Class in dev.tamboui.widgets.form

Represents the result of a validation check.

Validator - Interface in dev.tamboui.widgets.form
A validator that checks if a string value meets certain criteria.

Validators - Class in dev.tamboui.widgets.form
Built-in validators for common validation scenarios.

value() - Element in annotation interface dev.tamboui.annotations.bindings.OnAction
The action name to handle.

value() - Method in class dev.tamboui.css.parser.Token.Delim
Returns the delimiter character.

value() - Method in class dev.tamboui.css.parser.Token.Hash
Returns the hash value (without the leading #).

value() - Method in class dev.tamboui.css.parser.Token.Ident
Returns the identifier value.

value() - Method in class dev.tamboui.css.parser.Token.Number
Returns the numeric value as a string.

value() - Method in class dev.tamboui.css.parser.Token.StringToken
Returns the string value (without quotes).

value() - Method in class dev.tamboui.css.parser.Token.Whitespace
Returns the whitespace characters.

value() - Method in class dev.tamboui.css.selector.AttributeSelector
Returns the value to match against (null for EXISTS operator).

value() - Method in class dev.tamboui.layout.Constraint.Length
Returns the fixed size in cells.

value() - Method in class dev.tamboui.layout.Constraint.Max
Returns the maximum size.

value() - Method in class dev.tamboui.layout.Constraint.Min
Returns the minimum size.

value() - Method in class dev.tamboui.layout.Constraint.Percentage
Returns the percentage value.

value() - Method in class dev.tamboui.layout.Spacing.Overlap

value() - Method in class dev.tamboui.layout.Spacing.Space

value() - Method in class dev.tamboui.layout.Spacing
Returns the spacing value as an integer.

value() - Method in class dev.tamboui.text.Masked
Returns the underlying string, with all characters masked.

value() - Method in class dev.tamboui.widgets.barchart.Bar
Returns the bar's value.

value() - Method in class dev.tamboui.widgets.checkbox.CheckboxState
Alias for `CheckboxState.isChecked()` for compatibility with form state patterns.

value() - Method in class dev.tamboui.widgets.form.BooleanFieldState
Returns the current value.

value() - Method in class dev.tamboui.widgets.select.SelectState
Alias for `SelectState.selectedValue()` for compatibility with form state patterns.

value() - Method in class dev.tamboui.widgets.toggle.ToggleState
Alias for `ToggleState.isOn()` for compatibility with form state patterns.

value(long) - Method in class dev.tamboui.widgets.barchart.Bar.Builder
Sets the bar's value.

value(String) - Method in class dev.tamboui.toolkit.elements.FormFieldElement

Sets the initial text value for a text field.

VALUE_COLOR - Static variable in class dev.tamboui.widgets.barchart.BarChart
Property key for the value label color.

valueColor(Color) - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Sets the value label color programmatically.

valueOf(Variable) - Method in class dev.tamboui.layout.cassowary.Solver
Returns the current value of a variable.

valueOf(String) - Static method in enum class dev.tamboui.css.cascade.UnknownPropertyBehavior
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.css.selector.AttributeSelector.Operator
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.image.capability.TerminalImageProtocol
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.image.ImageScaling
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.layout.Alignment
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.layout.cassowary.Relation
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.layout.columns.ColumnOrder
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.layout.ContentAlignment
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.layout.Direction
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.layout.Flex
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.style.AnsiColor
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.style.Modifier
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.style.Overflow
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.symbols.merge.MergeStrategy
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.terminal.Mode2027Status
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.text.CharWidth.TruncatePosition
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.tfx.ExpandDirection
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.tfx.Interpolation
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.tfx.LoopMode
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.tfx.Motion
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.tfx.pattern.DiagonalPattern.DiagonalDirection
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.tfx.TFxColorSpace
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.toolkit.event.EventResult
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.tui.error.ErrorAction
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.tui.event.KeyCode
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.tui.event.MouseButton
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.tui.event.MouseEventKind
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.widgets.block.Borders
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.widgets.block.BorderType
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.widgets.canvas.Marker
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.widgets.chart.Dataset.Marker
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.widgets.chart.GraphType
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.widgets.chart.LegendPosition
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.widgets.common.ScrollBarPolicy
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.widgets.form.FieldType
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.widgets.list.ScrollMode
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.widgets.logo.Logo.Size
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.widgets.scrollbar.ScrollbarOrientation
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.widgets.sparkline.Sparkline.RenderDirection
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.widgets.table.Table.HighlightSpacing
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.widgets.tree.GuideStyle
Returns the enum constant of this class with the specified name.

valueOf(String) - Static method in enum class dev.tamboui.widgets.wavetext.WaveText.Mode
Returns the enum constant of this class with the specified name.

values() - Static method in enum class dev.tamboui.css.cascade.UnknownPropertyBehavior
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.css.selector.AttributeSelector.Operator
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.image.capability.TerminalImageProtocol

Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.image.ImageScaling
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.layout.Alignment
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.layout.cassowary.Relation
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.layout.columns.ColumnOrder
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.layout.ContentAlignment
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.layout.Direction
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.layout.Flex
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.style.AnsiColor
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.style.Modifier
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.style.Overflow
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Method in class dev.tamboui.style.Tags
Returns the set of tag values.

values() - Static method in enum class dev.tamboui.symbols.merge.MergeStrategy
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.terminal.Mode2027Status
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.text.CharWidth.TruncatePosition
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.tfx.ExpandDirection
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.tfx.Interpolation
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.tfx.LoopMode
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.tfx.Motion
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.tfx.pattern.DiagonalPattern.DiagonalDirection
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.tfx.TFxColorSpace
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.toolkit.event.EventResult
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.tui.error.ErrorAction
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.tui.event.KeyCode
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.tui.event.MouseButton
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.tui.event.MouseEventKind
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.widgets.block.Borders
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.widgets.block.BorderType
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.widgets.canvas.Marker
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.widgets.chart.Dataset.Marker
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.widgets.chart.GraphType
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.widgets.chart.LegendPosition
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.widgets.common.ScrollBarPolicy
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.widgets.form.FieldType
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.widgets.list.ScrollMode
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.widgets.logo.Logo.Size
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.widgets.scrollbar.ScrollbarOrientation
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.widgets.sparkline.Sparkline.RenderDirection
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.widgets.table.Table.HighlightSpacing
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.widgets.tree.GuideStyle
Returns an array containing the constants of this enum class, in the order they are declared.

values() - Static method in enum class dev.tamboui.widgets.wavetext.WaveText.Mode
Returns an array containing the constants of this enum class, in the order they are declared.

valueStyle() - Method in class dev.tamboui.widgets.barchart.Bar
Returns the value's style, if set.

valueStyle(Style) - Method in class dev.tamboui.toolkit.elements.BarChartElement
Sets the value display style.

valueStyle(Style) - Method in class dev.tamboui.widgets.barchart.Bar.Builder
Sets the value's style.

valueStyle(Style) - Method in class dev.tamboui.widgets.barchart.BarChart.Builder
Sets the value display style.

VAR_PATTERN - Static variable in interface dev.tamboui.css.property.PropertyConverter
Pattern matching CSS variable references like $variable-name.

variable() - Method in class dev.tamboui.layout.cassowary.Term
Returns the variable of this term.

variable(Variable) - Static method in class dev.tamboui.layout.cassowary.Expression
Creates an expression containing a single variable with coefficient 1.

Variable - Class in dev.tamboui.layout.cassowary

A variable in the Cassowary constraint system.

Variable() - Constructor for class dev.tamboui.layout.cassowary.Variable
Creates a new variable with no name.

Variable(String) - Constructor for class dev.tamboui.layout.cassowary.Variable
Creates a new variable with the given name.

Variable(String, Token.Position) - Constructor for class dev.tamboui.css.parser.Token.Variable
Creates a variable reference token.

variables() - Method in class dev.tamboui.css.model.Stylesheet
Returns the CSS variables defined in this stylesheet.

vertical() - Static method in class dev.tamboui.layout.Layout
Creates a vertical layout (top-to-bottom).

vertical() - Method in class dev.tamboui.toolkit.elements.BarChartElement
Sets vertical direction.

vertical() - Method in class dev.tamboui.toolkit.elements.DialogElement
Sets the layout direction to vertical.

vertical() - Method in class dev.tamboui.toolkit.elements.Gutter
Returns the vertical gutter (between rows).

vertical() - Method in class dev.tamboui.toolkit.elements.Panel
Sets the layout direction to vertical.

vertical() - Method in class dev.tamboui.toolkit.elements.ScrollbarElement
Sets vertical right-aligned orientation.

vertical() - Static method in class dev.tamboui.widgets.scrollbar.Scrollbar
Creates a vertical right-aligned scrollbar with default settings.

vertical() - Method in enum class dev.tamboui.widgets.tree.GuideStyle
Returns the vertical continuation string.

vertical(int) - Static method in class dev.tamboui.layout.Margin
Returns a margin applied vertically only.

vertical(int) - Static method in class dev.tamboui.layout.Padding
Returns a padding applied vertically only.

vertical(String) - Method in class dev.tamboui.widgets.block.BorderSet.Builder
Sets both vertical border characters (left and right).

VERTICAL - Enum constant in enum class dev.tamboui.layout.Direction
Vertical direction (top-to-bottom).

VERTICAL - Enum constant in enum class dev.tamboui.tfx.ExpandDirection
Expands vertically from center (up and down simultaneously).

VERTICAL - Static variable in class dev.tamboui.widgets.scrollbar.Scrollbar.SymbolSet
Vertical scrollbar with single-line track and arrows.

VERTICAL_GAUGE - Enum constant in enum class dev.tamboui.widgets.spinner.SpinnerStyle
Growing vertical bar spinner (bottom to top).

VERTICAL_LEFT - Enum constant in enum class dev.tamboui.widgets.scrollbar.ScrollbarOrientation
Vertical scrollbar on the left side of the content area.

VERTICAL_RIGHT - Enum constant in enum class dev.tamboui.widgets.scrollbar.ScrollbarOrientation
Vertical scrollbar on the right side of the content area.

verticalGutter(int) - Method in class dev.tamboui.layout.grid.Grid.AreaBuilder
Sets the vertical gutter between rows.

verticalGutter(int) - Method in class dev.tamboui.layout.grid.Grid.ChildrenBuilder
Sets the vertical gutter between rows.

verticalLeft() - Method in class dev.tamboui.toolkit.elements.ScrollbarElement
Sets vertical left-aligned orientation.

verticalSpacing(int) - Method in class dev.tamboui.layout.flow.Flow.Builder
Sets the vertical gap between rows.

verticalTotal() - Method in class dev.tamboui.layout.Margin
Returns the sum of top and bottom margins.

verticalTotal() - Method in class dev.tamboui.layout.Padding
Returns the sum of top and bottom padding.

viewportContentLength() - Method in class dev.tamboui.widgets.scrollbar.ScrollbarState
Returns the viewport content length.

viewportContentLength(int) - Method in class dev.tamboui.widgets.scrollbar.ScrollbarState
Sets the viewport content length.

viewportHeight() - Method in class dev.tamboui.style.RichTextState
Returns the viewport height (visible lines).

viewportWidth() - Method in class dev.tamboui.style.RichTextState
Returns the viewport width (visible columns).

vim() - Static method in class dev.tamboui.tui.bindings.BindingSets
Vim-style binding set with hjkl navigation.

visible(boolean) - Method in class dev.tamboui.toolkit.elements.InlineScopeElement
Sets the visibility of this scope.

VMIN - Static variable in class dev.tamboui.backend.panama.unix.LibC
Control character index for minimum number of bytes for non-canonical read.

VMIN - Static variable in class dev.tamboui.backend.panama.unix.PlatformConstants
Control character index for minimum number of bytes for non-canonical read.

vscode() - Static method in class dev.tamboui.tui.bindings.BindingSets
Visual Studio Code-style binding set.

VTIME - Static variable in class dev.tamboui.backend.panama.unix.LibC
Control character index for timeout in deciseconds for non-canonical read.

VTIME - Static variable in class dev.tamboui.backend.panama.unix.PlatformConstants
Control character index for timeout in deciseconds for non-canonical read.

W

WAIT_FAILED - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
WaitForSingleObject return value: the function has failed.

WAIT_OBJECT_0 - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
WaitForSingleObject return value: the object is signaled.

WAIT_TIMEOUT - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
WaitForSingleObject return value: the timeout interval elapsed.

waitForSingleObject(MemorySegment, int) - Static method in class dev.tamboui.backend.panama.windows.Kernel32
Waits until the specified object is in the signaled state or the timeout interval elapses.

WARN - Enum constant in enum class dev.tamboui.css.cascade.UnknownPropertyBehavior
Log a warning for unknown properties.

waveText(String) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a wave text element with the given text.

waveText(String, Color) - Static method in class dev.tamboui.toolkit.Toolkit
Creates a wave text element with the given text and color.

WaveText - Class in dev.tamboui.widgets.wavetext
A widget that renders text with an animated wave brightness effect.

WaveText.Builder - Class in dev.tamboui.widgets.wavetext
Builder for `WaveText`.

WaveText.Mode - Enum Class in dev.tamboui.widgets.wavetext
Animation mode for the wave.

WaveTextElement - Class in dev.tamboui.toolkit.elements
An element that displays text with an animated wave brightness effect.

WaveTextElement(String) - Constructor for class dev.tamboui.toolkit.elements.WaveTextElement
Creates a wave text element with the given text.

WaveTextElement(String, Color) - Constructor for class dev.tamboui.toolkit.elements.WaveTextElement
Creates a wave text element with the given text and color.

WaveTextState - Class in dev.tamboui.widgets.wavetext
State for the `WaveText` widget, tracking animation progress.

WaveTextState() - Constructor for class dev.tamboui.widgets.wavetext.WaveTextState
Creates a new state with tick starting at 0.

WaveTextState(long) - Constructor for class dev.tamboui.widgets.wavetext.WaveTextState
Creates a new state with the given initial tick.

weak() - Method in class dev.tamboui.layout.cassowary.Strength
Returns the weak weight component.

WEAK - Static variable in class dev.tamboui.layout.cassowary.Strength
Weak preference - low priority, easily overridden.

weekdaysHeaderStyle(Style) - Method in class dev.tamboui.widgets.calendar.Monthly.Builder
Shows the weekdays header with the given style.

weight() - Method in class dev.tamboui.layout.Constraint.Fill
Returns the fill weight.

WHEN_SELECTED - Enum constant in enum class dev.tamboui.widgets.table.Table.HighlightSpacing
Only allocate space when a row is selected.

When to Use - Section in class dev.tamboui.toolkit.elements.GenericWidgetElement

white() - Method in class dev.tamboui.style.Style
Shorthand for `Style.fg(Color)` with `Color.WHITE`.

white() - Method in class dev.tamboui.text.Span
Returns a new span with white foreground color.

white() - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the foreground color to white.

WHITE - Enum constant in enum class dev.tamboui.style.AnsiColor
White (palette index 7).

WHITE - Static variable in interface dev.tamboui.style.Color
White.

Whitespace(String, Token.Position) - Constructor for class dev.tamboui.css.parser.Token.Whitespace
Creates a whitespace token.

widget() - Method in class dev.tamboui.layout.flow.FlowItem
Returns the widget.

widget() - Method in class dev.tamboui.toolkit.elements.GenericWidgetElement
Returns the wrapped widget.

widget() - Method in class dev.tamboui.widgets.common.SizedWidget
Returns the wrapped widget.

widget(T) - Static method in class dev.tamboui.toolkit.elements.GenericWidgetElement
Creates a new GenericWidgetElement wrapping the given widget.

widget(T) - Static method in class dev.tamboui.toolkit.Toolkit
Wraps any low-level `Widget` as a `GenericWidgetElement`.

Widget - Interface in dev.tamboui.widget

A widget that can render itself to a buffer.

width() - Method in class dev.tamboui.buffer.Buffer
Returns the width of this buffer.

width() - Method in class dev.tamboui.image.ImageData
Returns the image width in pixels.

width() - Method in class dev.tamboui.inline.InlineDisplay
Returns the width of this display in characters.

width() - Method in class dev.tamboui.internal.record.RecordingConfig
Returns the recording width in columns.

width() - Method in class dev.tamboui.layout.flow.FlowItem
Returns the item width in cells.

width() - Method in class dev.tamboui.layout.Rect
Returns the width.

width() - Method in class dev.tamboui.layout.Size
Returns the width.

width() - Method in class dev.tamboui.terminal.Frame
Returns the terminal width.

width() - Method in class dev.tamboui.text.Line
Returns the display width of this line (sum of span widths).

width() - Method in class dev.tamboui.text.Span
Returns the display width of this span in terminal columns.

width() - Method in class dev.tamboui.text.Text
Returns the maximum width of any line.

width() - Method in class dev.tamboui.toolkit.element.Size
Returns the preferred width.

width() - Method in class dev.tamboui.tui.event.ResizeEvent
Returns the new terminal width in columns.

width() - Method in class dev.tamboui.tui.InlineTuiRunner
Returns the viewport width.

width() - Method in class dev.tamboui.widgets.canvas.shapes.Rectangle
Returns the width.

width() - Method in class dev.tamboui.widgets.checkbox.Checkbox
Returns the display width of this checkbox.

width() - Method in class dev.tamboui.widgets.common.SizedWidget
Returns the explicit width, or `SizedWidget.DEFAULT` for default behavior.

width() - Method in class dev.tamboui.widgets.table.Cell
Returns the width of this cell (maximum line width).

width() - Method in class dev.tamboui.widgets.toggle.Toggle
Returns the display width of this toggle.

width(int) - Method in class dev.tamboui.toolkit.elements.DialogElement
Sets a fixed width for the dialog.

width(Constraint) - Method in class dev.tamboui.css.cascade.CssStyleResolver.Builder
Sets the width constraint.

width(SelectState) - Method in class dev.tamboui.widgets.select.Select
Returns the display width for the given state.

Width - Class in dev.tamboui.style
Represents the width of an element.

WIDTH - Static variable in class dev.tamboui.style.StandardProperties
The `width` property for element width constraint.

widthConstraint() - Method in class dev.tamboui.css.cascade.CssStyleResolver
Returns the width constraint, if set.

WidthConverter - Class in dev.tamboui.css.property
Converts CSS width values to Width.

widthMultiplier() - Method in class dev.tamboui.image.protocol.ImageProtocol.Resolution
Returns the width multiplier.

widthOnly(int) - Static method in class dev.tamboui.toolkit.element.Size
Creates a size with known width and unknown height (fill vertically).

widthOr(int) - Method in class dev.tamboui.toolkit.element.Size
Returns the width if known, otherwise returns the default value.

widthOr(int) - Method in class dev.tamboui.widgets.common.SizedWidget
Returns the width if explicitly set, or the given default value.

widths(Constraint...) - Method in class dev.tamboui.toolkit.elements.TableElement
Sets the column width constraints.

widths(Constraint...) - Method in class dev.tamboui.widgets.table.Table.Builder
Sets the column width constraints.

widths(List) - Method in class dev.tamboui.toolkit.elements.TableElement
Sets the column width constraints from a list.

widths(List) - Method in class dev.tamboui.widgets.table.Table.Builder
Sets the column width constraints.

WINDOW_BUFFER_SIZE_EVENT - Static variable in class dev.tamboui.backend.panama.windows.Kernel32
Input record event type: console window buffer size change.

windowsTerminal() - Method in class dev.tamboui.backend.panama.PanamaBackend
Returns the underlying Windows terminal for advanced operations.

WindowsTerminal - Class in dev.tamboui.backend.panama.windows
Windows terminal operations using Panama FFI.

WindowsTerminal() - Constructor for class dev.tamboui.backend.panama.windows.WindowsTerminal
Creates a new Windows terminal instance.

WINSIZE_LAYOUT - Static variable in class dev.tamboui.backend.panama.unix.LibC
Layout for the winsize structure.

withActive(boolean) - Method in class dev.tamboui.css.cascade.PseudoClassState
Returns a new state with the active flag set.

withAnimation(Duration) - Static method in class dev.tamboui.tui.TuiConfig
Returns a configuration suitable for animated applications.

withArea(Rect) - Method in class dev.tamboui.tfx.Effect
Creates a new Effect with the specified area.

withAutoBindingRegistration() - Method in class dev.tamboui.toolkit.app.ToolkitRunner.Builder
Enables automatic registration of action handlers.

withAutoBindingRegistration() - Method in class dev.tamboui.tui.TuiRunner.Builder
Enables automatic registration of action handlers.

withBackend(int, int, Backend) - Static method in class dev.tamboui.inline.InlineDisplay
Creates an InlineDisplay using an existing backend.

withBackend(int, Backend) - Static method in class dev.tamboui.inline.InlineDisplay
Creates an InlineDisplay with the specified height using an existing backend.

withCenter(float, float) - Method in class dev.tamboui.tfx.pattern.RadialPattern
Creates a new pattern with a different center point.

withColorSpace(TFxColorSpace) - Method in class dev.tamboui.tfx.Effect
Creates a new Effect with the specified color space.

withDisabled(boolean) - Method in class dev.tamboui.css.cascade.PseudoClassState

Returns a new state with the disabled flag set.

withElement(Styleable, Style, CssStyleResolver, Runnable) - Method in class dev.tamboui.toolkit.element.DefaultRenderContext
Executes an action with an element, style, and CSS resolver pushed onto their stacks.

withElement(Styleable, Style, Runnable) - Method in class dev.tamboui.toolkit.element.DefaultRenderContext
Executes an action with an element and style pushed onto their stacks.

withExtension(Class, T) - Method in class dev.tamboui.style.Style
Returns a new style with the given extension property set.

withFallback(CssStyleResolver) - Method in class dev.tamboui.css.cascade.CssStyleResolver
Creates a new resolver that uses this resolver's properties but falls back to the given resolver for CSS-inheritable properties not set in this resolver.

withFallback(TypedPropertyMap) - Method in class dev.tamboui.css.cascade.TypedPropertyMap
Creates a new property map that uses this map's values, falling back to the given fallback map for inherited properties that are not set in this map.

withFilter(CellFilter) - Method in class dev.tamboui.tfx.Effect
Creates a new Effect with the specified cell filter.

withFirstChild(boolean) - Method in class dev.tamboui.css.cascade.PseudoClassState
Returns a new state with the firstChild flag set.

withFocused(boolean) - Method in class dev.tamboui.css.cascade.PseudoClassState
Returns a new state with the focused flag set.

withHovered(boolean) - Method in class dev.tamboui.css.cascade.PseudoClassState
Returns a new state with the hovered flag set.

withLastChild(boolean) - Method in class dev.tamboui.css.cascade.PseudoClassState
Returns a new state with the lastChild flag set.

withLines(String...) - Static method in class dev.tamboui.buffer.Buffer
Creates a buffer from an array of strings.

withNthChild(int) - Method in class dev.tamboui.css.cascade.PseudoClassState
Returns a new state with the nthChild position set.

withPattern(Pattern) - Method in class dev.tamboui.tfx.Effect
Creates a new Effect with the specified pattern.

withRng(SimpleRng, Motion, int) - Static method in class dev.tamboui.tfx.DirectionalVariance
Creates a new DirectionalVariance instance with a provided RNG.

withRules(List) - Method in class dev.tamboui.css.model.Stylesheet
Returns a new stylesheet with the given rules appended.

withSelected(boolean) - Method in class dev.tamboui.css.cascade.PseudoClassState
Returns a new state with the selected flag set.

withSupport(Set) - Static method in class dev.tamboui.image.capability.TerminalImageCapabilities
Creates capabilities with explicitly specified support.

withTransition(float, float, float) - Static method in class dev.tamboui.tfx.pattern.RadialPattern
Creates a radial pattern with custom center and transition width.

withTransitionWidth(float) - Method in class dev.tamboui.tfx.pattern.DiagonalPattern
Creates a new pattern with a different transition width.

withTransitionWidth(float) - Method in class dev.tamboui.tfx.pattern.RadialPattern
Creates a new pattern with a different transition width.

withVariables(Map) - Method in class dev.tamboui.css.model.Stylesheet
Returns a new stylesheet with the given variables merged.

withWeight(int) - Method in class dev.tamboui.toolkit.elements.Spacer
Sets the constraint to fill available space with given weight.

WRAP_CHARACTER - Enum constant in enum class dev.tamboui.style.Overflow

Wrap at character boundaries.

WRAP_WORD - Enum constant in enum class dev.tamboui.style.Overflow
Wrap at word boundaries.

wrapCharacter() - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Convenience method to wrap at character boundaries.

wrapCharacter() - Method in class dev.tamboui.toolkit.elements.MarkupTextElement
Sets character wrapping mode.

wrapCharacter() - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Convenience method to wrap at character boundaries.

wrapCharacter() - Method in class dev.tamboui.toolkit.elements.RichTextElement
Sets character wrapping mode.

wrapHandler(EventHandler) - Method in class dev.tamboui.tfx.toolkit.ToolkitEffects
Wraps an event handler to capture tick timing and force redraws.

wrapHandler(EventHandler) - Method in class dev.tamboui.tfx.tui.TfxIntegration
Wraps an event handler to capture tick timing and force redraws when effects are running.

wrapRenderer(Renderer) - Method in class dev.tamboui.tfx.tui.TfxIntegration
Wraps a renderer to process effects after rendering.

wrapRenderer(Renderer, ElementRegistry, StyledAreaRegistry, FocusManager) - Method in class dev.tamboui.tfx.toolkit.ToolkitEffects
Wraps a renderer to resolve and process effects after rendering.

wrapWord() - Method in class dev.tamboui.toolkit.elements.MarkupTextAreaElement
Convenience method to wrap at word boundaries.

wrapWord() - Method in class dev.tamboui.toolkit.elements.MarkupTextElement
Sets word wrapping mode.

wrapWord() - Method in class dev.tamboui.toolkit.elements.RichTextAreaElement
Convenience method to wrap at word boundaries.

wrapWord() - Method in class dev.tamboui.toolkit.elements.RichTextElement
Sets word wrapping mode.

write(byte[]) - Method in interface dev.tamboui.backend.panama.PlatformTerminal
Writes data to the terminal.

write(byte[]) - Method in class dev.tamboui.backend.panama.unix.UnixTerminal
Writes data to the terminal.

write(byte[]) - Method in class dev.tamboui.backend.panama.windows.WindowsTerminal

write(byte[], int, int) - Method in interface dev.tamboui.backend.panama.PlatformTerminal
Writes a portion of a byte array to the terminal.

write(byte[], int, int) - Method in class dev.tamboui.backend.panama.unix.UnixTerminal
Writes a portion of a byte array to the terminal.

write(byte[], int, int) - Method in class dev.tamboui.backend.panama.windows.WindowsTerminal

write(byte[], int, int) - Method in class dev.tamboui.internal.record.AnsiTerminalCapture

write(int) - Method in class dev.tamboui.internal.record.AnsiTerminalCapture

write(int, MemorySegment, long) - Static method in class dev.tamboui.backend.panama.unix.LibC
Writes to a file descriptor.

write(String) - Method in interface dev.tamboui.backend.panama.PlatformTerminal
Writes a string to the terminal.

write(String) - Method in class dev.tamboui.backend.panama.unix.UnixTerminal
Writes a string to the terminal.

write(String) - Method in class dev.tamboui.backend.panama.windows.WindowsTerminal

writeCell(Cell) - Method in class dev.tamboui.terminal.AnsiCellWriter
Writes a single cell to the output sink.

writeConsole(MemorySegment, MemorySegment, int, MemorySegment, MemorySegment) - Static method in class dev.tamboui.backend.panama.windows.Kernel32
Writes a character string to a console screen buffer.

writeRaw(byte[]) - Method in class dev.tamboui.backend.aesh.AeshBackend

writeRaw(byte[]) - Method in class dev.tamboui.backend.jline3.JLineBackend

writeRaw(byte[]) - Method in class dev.tamboui.backend.panama.PanamaBackend

writeRaw(byte[]) - Method in class dev.tamboui.internal.record.RecordingBackend

writeRaw(byte[]) - Method in interface dev.tamboui.terminal.Backend
Writes raw bytes directly to the terminal output.

writeRaw(CharSequence) - Method in interface dev.tamboui.terminal.Backend
Writes a CharSequence directly to the terminal output.

writeRaw(String) - Method in class dev.tamboui.backend.aesh.AeshBackend

writeRaw(String) - Method in class dev.tamboui.backend.jline3.JLineBackend

writeRaw(String) - Method in class dev.tamboui.backend.panama.PanamaBackend

writeRaw(String) - Method in class dev.tamboui.internal.record.RecordingBackend

writeRaw(String) - Method in interface dev.tamboui.terminal.Backend
Writes a raw string directly to the terminal output.

writeToFile(Path) - Static method in class dev.tamboui.tui.error.RenderErrorHandlers
Returns a handler that writes the error to a file, then displays in the UI.

X

x() - Method in class dev.tamboui.layout.Position
Returns the x coordinate.

x() - Method in class dev.tamboui.layout.Rect
Returns the x coordinate.

x() - Method in class dev.tamboui.tfx.CellIterator.MutableCell
Returns the cell's x coordinate.

x() - Method in class dev.tamboui.tui.event.MouseEvent
Returns the x coordinate (0-based).

x() - Method in class dev.tamboui.widgets.canvas.Painter.GridPoint
Returns the x coordinate.

x() - Method in class dev.tamboui.widgets.canvas.shapes.Circle
Returns the x coordinate of the center.

x() - Method in class dev.tamboui.widgets.canvas.shapes.Rectangle
Returns the x coordinate.

x1() - Method in class dev.tamboui.widgets.canvas.shapes.Line
Returns the x coordinate of the start point.

x2() - Method in class dev.tamboui.widgets.canvas.shapes.Line
Returns the x coordinate of the end point.

xAxis(Axis) - Method in class dev.tamboui.toolkit.elements.ChartElement
Sets the X-axis configuration.

xAxis(Axis) - Method in class dev.tamboui.widgets.chart.Chart.Builder

Sets the X-axis configuration.

xBounds(double, double) - Method in class dev.tamboui.toolkit.elements.CanvasElement
Sets the X-axis bounds.

xBounds(double, double) - Method in class dev.tamboui.widgets.canvas.Canvas.Builder
Sets the x-axis bounds.

Y

y() - Method in class dev.tamboui.layout.Position
Returns the y coordinate.

y() - Method in class dev.tamboui.layout.Rect
Returns the y coordinate.

y() - Method in class dev.tamboui.tfx.CellIterator.MutableCell
Returns the cell's y coordinate.

y() - Method in class dev.tamboui.tui.event.MouseEvent
Returns the y coordinate (0-based).

y() - Method in class dev.tamboui.widgets.canvas.Painter.GridPoint
Returns the y coordinate.

y() - Method in class dev.tamboui.widgets.canvas.shapes.Circle
Returns the y coordinate of the center.

y() - Method in class dev.tamboui.widgets.canvas.shapes.Rectangle
Returns the y coordinate.

y1() - Method in class dev.tamboui.widgets.canvas.shapes.Line
Returns the y coordinate of the start point.

y2() - Method in class dev.tamboui.widgets.canvas.shapes.Line
Returns the y coordinate of the end point.

yAxis(Axis) - Method in class dev.tamboui.toolkit.elements.ChartElement
Sets the Y-axis configuration.

yAxis(Axis) - Method in class dev.tamboui.widgets.chart.Chart.Builder
Sets the Y-axis configuration.

yBounds(double, double) - Method in class dev.tamboui.toolkit.elements.CanvasElement
Sets the Y-axis bounds.

yBounds(double, double) - Method in class dev.tamboui.widgets.canvas.Canvas.Builder
Sets the y-axis bounds.

yellow() - Method in class dev.tamboui.style.Style
Shorthand for `Style.fg(Color)` with `Color.YELLOW`.

yellow() - Method in class dev.tamboui.text.Span
Returns a new span with yellow foreground color.

yellow() - Method in class dev.tamboui.toolkit.element.StyledElement
Sets the foreground color to yellow.

YELLOW - Enum constant in enum class dev.tamboui.style.AnsiColor
Yellow (palette index 3).

YELLOW - Static variable in interface dev.tamboui.style.Color
Yellow.

Z

zero() - Static method in class dev.tamboui.layout.cassowary.Expression
Returns an expression representing zero.

ZERO - Static variable in class dev.tamboui.layout.Fraction

The fraction representing zero (0/1).

ZERO - Static variable in class dev.tamboui.layout.Rect
A zero-sized rectangle at the origin.

ZERO - Static variable in class dev.tamboui.layout.Size
A size with zero width and height.

ZERO - Static variable in class dev.tamboui.tfx.TFxDuration
A duration of zero milliseconds.

ZERO - Static variable in class dev.tamboui.toolkit.element.Size
Explicitly zero-sized - element should collapse in both dimensions.