

CS2106: Introduction to Operating Systems

Lab Assignment 1 (A1)

Advanced C Programming and Shell Scripting

IMPORTANT

The deadline of submission through LumiNUS: **10th Sept, 2022, 11.59 PM Saturday**

The total weightage is 8%:

- Exercise 1: 0.5%
- Exercise 2: 2% [**Lab demo exercise**]
- Exercise 3: 1%
- Exercise 4: 0%
- Exercise 5: 1%
- Exercise 6: 1%
- Exercise 7: 2%
- Exercise 8: 0.5%

You must ensure the exercises work properly on the VM provided or on the SoC Cluster.

1 General Information

Here are some simple guidelines that will come in handy for all future labs.

1.1 Lab Assignment Duration & Lab Demonstration

Each lab assignment spans about **two to three weeks** and consists of multiple exercises. **One of the exercises is chosen to be the “lab demo exercise” which you will have to demonstrate to your lab TA. Ex2 is graded for a total of 2% where 1% is allocated through demo and 1% through submission.**

This demonstration serves as a good way to “kick start” your lab assignment efforts. You are **strongly encouraged to** finish the demo exercise before coming to the lab.

The remaining lab exercises are usually quite intensive. Do not expect to finish the exercise during the allocated lab session. **The main purpose of the lab session is to demo your exercise and clarify doubts with the lab TAs.**

1.2 Lab Setup

For this semester:

- We provide a virtual machine image with Ubuntu (i.e. Ubuntu 20.04 with LXQt instead of GNOME) installation that can be used with VirtualBox on your personal computer ([link](#)).

- Additionally, you can also use the SoC Compute Cluster to test your assignments. You can also develop your assignments on these machines (more will be shared in exercise 1).
- Alternatively, you might install Ubuntu 20.04 natively on your personal computer.

You may use any of the three methods above to develop your assignments. Take note that: **Your submissions will be tested on virtual machine provided or on the SoC cluster.**

To read details about the nodes on the SoC Compute Cluster check: <https://docthub.comp.nus.edu.sg/cf/guides/compute-cluster/hardware>. Nodes **xcne4**, **xcne5**, **xcne6** and **xcne7** have been reserved for CS2106 for the entire semester.

The software configuration for these nodes follows:

```
Ubuntu 20.04
gcc version 9.3.0
GNU bash, version 5.0.17(1)-release
```

You must use your SoC account to use these nodes. If you do not have an SoC account, you can retrieve or create an account using the link provided here: <https://mysoc.nus.edu.sg/~newacct/>

To use these nodes, you **must enable SoC Compute Cluster** from your MySoC Account page (<https://mysoc.nus.edu.sg/~myacct/services.cgi>).

Exercise 1 will run through the basics of connecting to these nodes remotely, along with steps to set up a development environment that will be useful for all future lab assignments.

1.3 Setting up the exercise

For every lab, we will release two files under the LumiNUS “**Labs**” folder:

- **labX.pdf**: A document to describe the lab question, including the specification and the expected output for all the exercises.
- **labX.tar.gz**: An archive for setting up the directories and skeleton files given for the lab.

For unpacking the archive:

1. Copy or download the archive `labX.tar.gz` into your account.
2. Enter the following command in the terminal (console):

```
tar -xf labX.tar.gz
```

Remember to replace **X** with actual lab number.

3. The above command should setup the files in the following structure:

```
ex2/          subdirectory for exercise 2
  ex2.c       skeleton files for exercise 2
  sample.in   sample test inputs
  sample.out  sample test outputs
ex3/
...
ex4/
```

2 Exercises in Lab 1

There are **eight exercises** in this lab. The main motivation for this lab is to familiarize you with:

- using the VM or the SoC Compute Cluster,
- some advanced aspects of C programming,
- compiling and running C programs in Linux, and
- using the shell in Linux.

As such, you will need to write a combination of C programs and shell scripts (shell commands) to achieve some simple tasks. The **techniques and shell commands** used in these exercises are quite commonly used in OS related topics, and they will help you in completing the next lab assignments.

2.1 Exercise 1: Setting up your development environment – 0.5%

There are many ways to go about doing the development of your lab assignment. This exercise will run through some basic shell commands, as well as some advanced options that may aid you with your development. You should find what set-up works best for you.

Before we begin, make sure you have gone through [Section 1.2](#), especially the part on the SoC Compute Cluster if not using the VM. We will be using our terminal (for Linux or Mac) or command prompt (for Windows) to connect to the remote nodes. You can think of the terminal or command prompt as an interactive program that allows you to type commands to complete some tasks without a graphical interface.

2.1.1 Using the Virtual Machine

The simplest option to set up your development environment is by using the virtual machine (VM) image provided. Please download the image from the LumiNUS Files folder. Then, install the virtual box ([link](#)) on your computer. After installing the virtual box, load the given image by **Machine → Add → CS2106-2010-VM**. Finally, start the VM. Refer to ([link](#)) on how to share files between host and VM.

For Mac OS as host: Sometime you may come across “Kernel not found error”. In this case you will need to give permission to Oracle virtual box in your computer. Go to System Preference → Security & Privacy. Then, **Allow** “System Software from developers Oracle America, Inc was blocked from loading” ([link](#)) option.

We have collected possible errors you may encountered while using VM in the following document ([link](#)). Please check the document for your error before asking the TA.

Note: VM may not work for the latest MacBook M1 Pro or M2. Please use the SoC cluster or Ubuntu installed system in that case.

2.1.2 SoC Computer Cluster

We will now discuss two possible ways to connect to the remote nodes:

A Secure Shell (SSH) to xcne4-xcne7 through stu.comp.nus.edu.sg

Secure Shell (SSH) is a network protocol that allows us to work with remote nodes securely. We will first utilize this protocol to access our SoC Compute Cluster nodes.

To reach the SoC Compute Cluster nodes, we would normally need to perform the `ssh` command twice – once to get access to the `stu.comp.nus.edu.sg` node ([link](#)), then once more from the `stu` node to the `xcne` node. The steps are as follows:

1. In your computer's terminal or command prompt, enter

```
ssh <your_soc_account_id>@stu.comp.nus.edu.sg
```

You will be prompted for your SoC account password. Once entered, you should be looking at the shell of the remote `stu` node, and you will be placed at the home directory of your `stu` account.

2. To access `xcne[4-7]`, you can type e.g., `ssh xcne6` for `xcne6`. You will once again be prompted for your password. Once entered, you should now see that you are now in the `xcne` node.

Alternatively, instead of using these two steps, we can use a single `ssh` command using the `-J` flag. For example, in your computer's terminal or command prompt, enter:

```
ssh -J <your_soc_account_id>@stu.comp.nus.edu.sg <your_soc_account_id>@xcne6
```

You will be prompted twice for your SoC account password, once for `stu`, and another for `xcne6`. Once entered, you should be looking at the shell of the remote `xcne6` node, and you will be placed at the home directory of your account.

B Secure Shell (SSH) directly to xcne4-xcne7 from the SoC Network

Finding it tedious to have to enter your password twice? You can `ssh` directly into the `xcne` remote node **if you are connected to the SoC VPN!**¹

After connecting to SoC VPN, simply enter the command (using `xcne6` as an example):

```
ssh <your_soc_account_id>@xcne6.comp.nus.edu.sg
```

For those interested in further optimizing the developer experience for yourself, you can read up on hostnames and **SSH keys**, to eliminate the need to retype the long host addresses and your SoC account password respectively.

2.1.3 Basic Commands in the Terminal

Once you have setup your VM or connected to cluster, you can navigate around. To do so in the shell, you need to be familiar with basic commands such as:

- `pwd`: print current working directory
- `cd`: change directory
- `ls`: list files in current directory

You can also type `man <command>` on the terminal to view the user manual of the command and read more about it.

¹<https://dochub.comp.nus.edu.sg/cf/guides/network/vpn>

2.1.4 Development Set-Up

When programming your assignments, you have a few options. You may choose to:

1. Work locally using the virtual machine image provided, or
2. Code directly on the remote node (xcne[4-7]), or
3. Use your own Ubuntu set-up.

For coding directly on the remote node, you can choose to either:

1. Use terminal-based text editors like Vim, which might seem less user-friendly, or
2. Setup remote development using SSH with your favourite code editor for a smoother development experience. For example, Visual Studio Code provides a SSH extension that lets you modify files on the xcne[4-7] remote nodes as if you were editing a local file².

Please **do not** develop on the `stu.comp.nus.edu.sg` remote node.

2.1.5 File Transfer

Once you set up your development environment, you can download the `lab1` files from LumiNUS. Once the files are downloaded, follow the instructions in [Section 1.3](#) to unpack the files for Lab 1.

To transfer your code to and from the remote nodes, you can either use the `sftp` command, which uses the secure file transfer protocol to transfer your files onto the node. Use `man` to find out how to use `sftp`.

For those coding directly on the remote node, we also **strongly recommend** keeping a copy of the code locally, just in case anything unexpected happens to your data on the remote nodes. Once again, you can either use the `sftp` command to transfer files from the remote node to local or use a **private git repository**.

2.1.6 Grading

Simply by submitting this lab assignment, you will obtain the 0.5% for this first exercise! That being said, do take the time to run through this first exercise fully, as your development set-up and your familiarity with the various commands directly affects your efficiency for this lab and all future labs.

²<https://code.visualstudio.com/docs/remote/ssh>

2.2 Exercise 2: Singly Linked List in C [Lab Demo Exercise] (1% demo + 1% submission)

Exercise 2 requires you to implement in C some functionalities for a singly linked list. Singly linked lists are commonly used in the Linux Kernel, such as for process and memory management. This exercise allows you to become more familiar with C syntax and appreciate the challenge behind implementing different parts of the operating system.

For this exercise, we represent a node in our linked list as follows (in `node.h`):

```
typedef struct NODE {
    int data;
    struct NODE *next;
} node;
```


The list representation looks like this:

```
typedef struct {
    node *head;
} list;
```


Initially, the list will be empty:

head NULL

Upon inserting the first node with data equals 1, we will have a singly linked list:



Thereafter, every insertion will expand this singly linked list:



You need to implement five functions shown below to work with the singly linked list:

```
void insert_node_at(list *lst, int index, int data)
```

This function inserts a new node that contains data at `index` of `lst` counting from the head (index starts from 0). You should use `malloc` to allocate memory to create the new node. Assume that `index` is between 0 and length of the list, both inclusive.

```
void delete_node_at(list *lst, int index)
```

This function deletes the node at `index` of `lst` counting from the head (index starts from 0). You should use `free` to delete memory allocated. Assume that `index` is between 0 inclusive and the length of the list exclusive. If the head node is deleted, the next node at index 1 (before deletion) should be the next head, if such a node exists. If no next node exists, the head of `lst` should be set to NULL.

```
int search_list(list *lst, int element)
```

This function searches for the `element` in the entire list and **returns** the index of the `element` in the list if present, else it returns -1. If the list is empty, it return -2. (**Note:** `print_index()`, which is already provided in `ex2.c` is automatically called to print the index returned).

```
void reverse_list(list *lst)
```

This function reverses the order of the nodes in `lst`. The head pointer of `lst` should now point to the original “tail” node. You should not be reallocating memory for the nodes or modifying the data of the nodes, but instead **modify the pointers** for this reversal. You may use additional memory to store temporary data during the operation, though it is not necessary.

```
void reset_list(list *lst)
```

This function deletes all nodes in `lst` and resets its head to NULL.

The folder structure of `ex2` is as follows:

```
/ex2
```

<code>ex2.c</code>	(not to be modified)
<code>node.h</code>	(not to be modified)
<code>node.c</code>	(modify)
<code>*.in</code>	(files used for testing)
<code>*.out</code>	(files used for testing)
<code>Makefile</code>	(not to be modified)

You should **only** modify `node.c` for this exercise. Please take note that changes to any other file will be overwritten when we run the grading script.

We defined specific macros for each of the functions:

```
#define PRINT_LIST      0
#define INSERT_AT       1
#define DELETE_AT       2
#define SEARCH_LIST     3
#define REVERSE_LIST    4
#define RESET_LIST      5
```

The function `print_list` has already been written for you within the runner `ex2.c`. Feel free to look at the `ex2.c` to understand how the runner works. Understanding how the runner works will help greatly when doing the next exercise.

After you have finished implementation, use the following command to compile your code:

```
$ gcc -std=c99 -Wall -Wextra node.c ex2.c -o ex2
```

This will produce the executable `ex2` by running `gcc` compiler with `c99` standard, enabling warnings, and creating an output `ex2`. You may use `-Werror` option in `gcc` to make all warnings into errors. You can also use `make` to compile the code. We will not penalize marks for having warnings, but we may use them to aid us in finding bugs in your programs.

You can use the sample test case we have provided to test your code.

```
$ ./ex2 < sample.in | diff -Z sample.out -
```

(Note the `-` at the end!)

The above bash command passes the `sample.in` input file into the test runner and compares the output against the expected. Details about how this command runs follow:

- The bash spawns two processes. The first process runs `ex2` and the second process runs `diff`.
- We used **input redirection** (`<`) to replace the standard input (`stdin`) with the file `sample.in` for the first process (running `ex2`)
- We have made use of a **pipe** (`|`) to pass the output from the first process (running the command `./ex2 < sample.in`) into the input of the second process running (running the command `diff sample.out -`). The `-` sign stands for the second input file being replaced with standard input (here, with the output produced by `ex2`).

Apart from `sample.in`, we have two more test cases to help verify your program. To get the demo exercise grade for this lab, you have to show your lab TA that you are familiar with basic bash syntax and have a working singly linked list that works for all test cases.

Also, take note that the runner will call `reset_list` to delete all nodes in the list before it terminates the program. The only file that needs changes is `node.c`.

Refer below for an explanation of the sample input. The input file uses a specific numbering scheme to refer to the five functions defined above:

sample.in

```
1 0 1    // insert_node_at(lst, 0, 1)
0        // print_list
1 0 3    // insert_node_at(lst, 0, 3)
0
1 1 2
0
1 0 100
0
1 4 200
0
2 1      // delete_node_at(lst, 1)
0
3 100    // search_list(lst, 100)
4        // reverse_list(lst)
0
3 2
5        // reset_list(lst)
0
1 0 1000
0
```

sample.out

```
[ 1 ]
[ 3 1 ]
[ 3 2 1 ]
[ 100 3 2 1 ]
[ 100 3 2 1 200 ]
[ 100 2 1 200 ]
{0}
[ 200 1 2 100 ]
{2}
[ ]
[ 1000 ]
```

2.3 Exercise 3: Function Pointer – 1%

This exercise extends the functionalities of the singly linked list implementation by applying several operations on its nodes. These operations are added by making use of function pointers in C.

Function Pointer Overview

You can refer to [this link](#) for more information on function pointers. Unlike normal pointer, which points to memory location for **data storage**, a function pointer **points to a piece of code (function)**. By dereferencing a function pointer, we **invoke the function** that is referred by that pointer. This technique is commonly used in **system call / interrupt handlers**.

In C, it is possible to define a **function pointer** to refer to a function. For example:

```
void (*fptr) (int);
```

To understand this declaration (check out this rather [handy website](#)), imagine if you replace (`*fptr`) as `F`, then you have:

```
void F (int);
```

So, `F` is “a function that takes an integer as input and returns nothing (`void`)”. Now, since (`*fptr`) is `F`, `fptr` is “a **pointer to a function** that takes an integer as input and returns nothing (`void`)”.

Let’s use the function pointers to define and use a group of functions that can **map** different operations to the singly linked list from exercise 2.

Exercise 3 is an extension of exercise 2. For this exercise, you must write the test runner `ex3.c` and `node.c`. The runner

- **reads the input file provided as a command line argument** (reading from a file can be done using any library. We recommend using `stdio` (`fopen`, `fclose`, `fread`). Make sure that you gracefully handle an invalid file name), and
- **applies the operations listed in the input file** on the singly linked list.

The macros corresponding to the functions that can be applied on the list are:

```
#define SUM_LIST      0
#define INSERT_AT     1
#define DELETE_AT     2
#define SEARCH_LIST   3
#define REVERSE_LIST   4
#define RESET_LIST     5
#define LIST_LEN      6
#define MAP            7
```

`INSERT`, `DELETE`, `SEARCH`, `REVERSE`, and `RESET` operations are similar with exercise 2 (no changes are needed). We have added `MAP` and `LIST_LEN` and replaced `PRINT_LIST` with `SUM_LIST`. You need to implement three functions:

```
long sum_list(list *lst)
```

This function sums the data of all nodes in the `lst` and returns the sum. If `lst` is empty, return 0.

```
int list_len(list *lst)
```

This function finds the number of nodes in the `lst` and returns the length.

```
void map(list *lst, int (*func) (int))
```

This function updates `lst` by applying `func` to the data element of every node.

The `sum_list` and `list_len` are straightforward. The `map` function (MAP) uses function pointers. You need to implement this function by applying the function `func` on each element of the singly linked list.

MAP can be used to apply five operations on the list. Indices for these operations are given below:

0	add_one
1	add_two
2	multiply_five
3	square
4	cube

The implementation for these functions is provided in file `functions.c`. The runner `ex3.c` simply calls the right function based on the index given in the input file.

To apply the five MAP operations, you will need to initialize an array of function pointers with indices 0 to 4. This array has already been declared in `function_pointers.h`, but not initialized. Use the index from the input file to call the corresponding map function. This array of function pointers is:

- named `func_list`,
- has been declared in `function_pointers.h` file, and
- **will need to be initialized in `function_pointers.c`**. You may choose to use `update_functions` (defined in `function_pointers.h` and implemented in `function_pointers.c`) to help you with the initialization. `update_functions` is called in the main function of `ex3.c` (please do not modify this call).

For this exercise the file structure is as follows:

/ex3

ex3.c	(modify)
node.c	(modify)
node.h	(not to be modified)
function_pointers.c	(modify)
function_pointers.h	(not to be modified)
functions.c	(not to be modified)
functions.h	(not to be modified)
*.in	(files used for testing)
*.out	(files used for testing)
Makefile	(not to be modified)

As explained earlier, we provide the functions used by MAP in `functions.c` and `functions.h`. These files should not be modified.

Use the Makefile provided to compile your code:

```
$ make
```

Command `make` uses the instructions found in the Makefile to compile your code. Note that you must either call `gcc` or `make` to compile your code (there is no need to call both of them, in sequence).

Test your `ex3` as follows:

```
$ ./ex3 sample.in > res.out
$ diff -Z res.out sample.out # (to compare your output with the given
↪ output)
```

Apart from the sample, we have provided two more test cases for testing. Do take note that getting the right answer for these files will not guarantee full marks for this exercise (see **Exercise 4**). Please test your code rigorously on your own. Other test cases will be used during grading.

Your runner should also free any memory it allocates and reset the list before the program terminates.

A sample input and output are shown below:

sample.in

```
1 0 1    // first three same as ex2
1 0 3
1 1 2
0        // sum list and prints it
7 0      // runs maps on list with add_one function
0
7 2      // runs maps on list with multiply_five function
0
1 2 4
1 3 5
0
6        // find length of list and prints it
7 4
0
```

sample.out

```
6
9
45
54
5
12564
```

2.4 Exercise 4: Checking for Memory Errors – 0%

In this exercise, we introduce `valgrind`, a tool commonly used to identify and fix any kind of memory errors (memory leak detection / out of bound array access etc.). You might use `valgrind` for future lab assignments.

We want you to try using `valgrind` on the executable from `ex2` and `ex3`. You used `malloc` or `free` a couple of times in the code and there is a possibility of memory leaks occurring if any resource obtained dynamically is not freed.

To use `valgrind`, `cd` into `ex2` directory and run the below command:

```
$ valgrind ./ex2 < sample.in > res.out
```

You should see output like this:

Sample Output

```
==12539== Memcheck, a memory error detector
==12539== Copyright (C) 2002-2017, and GNU GPL'd, by Julian Seward et al.
==12539== Using Valgrind-3.15.0 and LibVEX; rerun with -h for copyright
=> info
==12539== Command: ./ex2
==12539==
==12539== HEAP SUMMARY:
==12539==    in use at exit: 0 bytes in 0 blocks
==12539==   total heap usage: 9 allocs, 9 frees, 16,488 bytes allocated
==12539==
==12539== All heap blocks were freed -- no leaks are possible
==12539==
==12539== For lists of detected and suppressed errors, rerun with: -s
==12539== ERROR SUMMARY: 0 errors from 0 contexts (suppressed: 0 from 0)
```

As you can see, `valgrind` has done the hard work of checking for any potential memory leaks for us! Suppose our `ex3` had some memory leaks. `valgrind` detects memory problems and shows how to rerun to see additional details. When running on the sample input, you might see output as follows:

Sample Output

```
==3388== Memcheck, a memory error detector
==3388== Copyright (C) 2002-2017, and GNU GPL'd, by Julian Seward et al.
==3388== Using Valgrind-3.15.0 and LibVEX; rerun with -h for copyright
↳ info
==3388== Command: ./ex3
==3388==
==3388==
==3388== HEAP SUMMARY:
==3388==       in use at exit: 8 bytes in 1 blocks
==3388==       total heap usage: 7 allocs, 6 frees, 8,824 bytes allocated
==3388==
==3388== LEAK SUMMARY:
==3388==       definitely lost: 8 bytes in 1 blocks
==3388==       indirectly lost: 0 bytes in 0 blocks
==3388==       possibly lost: 0 bytes in 0 blocks
==3388==       still reachable: 0 bytes in 0 blocks
==3388==       suppressed: 0 bytes in 0 blocks
==3388== Rerun with --leak-check=full to see details of leaked memory
==3388==
==3388== For counts of detected and suppressed errors, rerun with: -v
==3388== ERROR SUMMARY: 0 errors from 0 contexts (suppressed: 0 from 0)
```

This exercise is not graded but take note that we will deduct marks if there are memory errors in either ex2 or ex3 (even if the expected output is correct).

2.5 Exercise 5: Shell scripting to find out about our system – 1%

In the next three exercises, we will write some shell scripts! A shell script is a list of commands designed to be run by the Linux shell. Earlier when we talked about `cd` and `pwd`, commands you can use in the terminal (shell). You can think of a shell script as running a sequence of these commands. For this lab, we will be focusing on the bash shell.

Exercise 5 requires you to write a simple shell script to learn more about your operating system and system. Use the man pages and online search to find out about bash.

A simple bash shell script that prints the current working directory is as follows:

```
check_dir.sh

#!/bin/bash
dir=$(pwd)
echo Current directory: $dir
```

The first line of the script is known as an interpreter directive, and it starts with the magic sequence `#!` known as a shebang. The directive is parsed by the kernel and instructs the kernel to run the script using the given program, in this case `/bin/bash`. This directive can also be used for other shells (e.g., `zsh`, `fish`) and for other scripting languages (e.g., Python).

Following this, we just have a variable that takes in the return value of the `pwd` command, and we print it out using `echo`.

To run the above script, use the following commands:

```
$ chmod +x ./check_dir.sh
$ ./check_dir.sh
```

The first command helps to change the file permissions to make the script executable. The second command runs the script. You should be able to see your current directory being printed onto the screen.

The output of the script you are supposed to write for this exercise should look as follows:

Sample Expected Output

```
Hostname: cs2106-2010-vm
Machine Hardware: Linux x86_64
Max User Processes: 4194304
User Processes: 32
User With Most Processes: root
Memory Free (%): 80.9471
```

The actual values differ based on the system you are using. We have provided in `ex5` folder a skeleton bash script `check_system.sh` that you can use to start work on this. You do not have to install anything else on your system to get the above information.

To get you started, here are some helpful commands that may be of use to you:

- `sort`
- `awk`
- pipe in shell (`|`)

As always, do check the man pages to find out more about these commands. You will need to discover the other commands on your own to complete this exercise.

Once you have figured out the commands that you might need, you can run them in the terminal to test them and copy them into the bash script once they give the output you desire.

2.6 Exercise 6: Know your syscalls – 1%

For this exercise, we will be writing another shell script to help us list the system calls done by a C program. A system call allows a user program to request services that are provided by the operating system. To find out what system calls are made by a program, we use a tool known as `strace`.

Within the `ex6` folder, you may find a sample C program `pid_checker.c` that prints its own process ID and its parent's process ID. We have also given a bash script skeleton `check_syscalls.sh` for you to update.

You need to complete the bash script to obtain a report on the system calls made by the program and the time spent in each call.

The expected output has the following format (values might differ, depending on the program that you are running):

Sample Expected Output					
Printing system call report					
Process ID: 12785					
Parent Process ID: 12782					
% time	seconds	usecs/call	calls	errors	syscall
21.97	0.000266	38	7		mmap
15.11	0.000183	30	6		pread64
9.66	0.000117	39	3		fstat
9.17	0.000111	37	3		mprotect
7.60	0.000092	30	3		brk
6.94	0.000084	42	2		openat
5.62	0.000068	34	2		close
4.95	0.000060	30	2	1	arch_prctl
3.88	0.000047	47	1		munmap
2.97	0.000036	36	1		getpid
2.89	0.000035	35	1	1	access
2.73	0.000033	33	1		read
2.64	0.000032	32	1		execve
2.39	0.000029	29	1		getppid
1.49	0.000018	9	2		write
100.00	0.001211		36	2	total

Again, reading the Linux manual for `strace` should allow you to do this exercise rather quickly.

2.7 Exercise 7: More Fun with Shell Scripting – 2%

For this exercise, we will be writing a shell script to familiarize with basic shell scripting commands and syntax. The exercise involves writing a bash script that allows a user to input a prefix and a range of numbers and then create dummy files with the inputted prefix and numbers. Then, you will need to rename the newly created files with a new prefix inputted by the user again.

For this exercise, here are some helpful commands that may be of use to you:

- `bash if` statement
- `bash for` loop
- `touch`, `cat`
- `mv`

Within the `ex7` folder, you may find a bash script skeleton `file_renaming.sh` for you to update. You need to complete the bash script to do the following:

- Read prefix (`prefix`) from the user. If the prefix contains any characters other than `[a-z or A-Z]` print `INVALID` and request for a valid prefix.
e.g., `ABC`
- Read the number of files (`N`) to create from the user.
e.g., `N = 2`
- Read the `N` numbers (`num1`, `num2`, ..., `numN`) from the user.
e.g., `123, 3456`
- Create `N` files with the filenames as follows: `prefix_numN.txt`. Print `INVALID` and request for a valid number if `num1` contains any other character other than numbers between `[0-9]`.
e.g., `ABC_123.txt`, `ABC_3456.txt`
- Read a new prefix (`new_prefix`) from the user (same constraints apply).
e.g., `XYZ`
- Rename all the files with the new prefix: `new_prefix_numN.txt`
e.g., renamed files: `XYZ_123.txt`, `XYZ_3456.txt`

The expected input/output are as follows:

Sample Expected Output

```
Enter prefix (only alphabets):
ABC
Number of files to create:
2
Enter 2 numbers:
123
3456

Files Created
ABC_123.txt ABC_3456.txt

Enter NEW prefix (only alphabets):
XYZ

Files Renamed
XYZ_123.txt XYZ_3456.txt
```

Sample Expected Output

```
Enter prefix (only alphabets):
A123
INVALID
Please enter a valid prefix [a-z A-Z]:
AbC
Number of files to create:
2
Enter 2 numbers:
12df
INVALID
Please enter a valid number [0-9]:
123
34b
INVALID
Please enter a valid number [0-9]:
3456

Files Created
AbC_123.txt AbC_3456.txt

Enter NEW prefix (only alphabets):
XYZ

Files Renamed
XYZ_123.txt XYZ_3456.txt
```

2.8 Exercise 8: Check your archive before submission – 0.5%

Before you submit your lab assignment, run our check archive script named `check_zip.sh`.

The script checks the following:

1. The name of the archive you provide matches the naming convention mentioned in Section 3
2. Your zip file can be unarchived, and the folder structure follows the structure presented in Section 3
3. All files for each exercise with the required names are present
4. Each exercise can be compiled and/or executed.
5. The output your exercise produces using our sample input matches the expected output.

Once you have the zip file, you will be able to check it by doing:

```
$ chmod +x ./check_zip.sh
$ ./check_zip.sh E0123456.zip           % replace with your zip file name
```

During execution, the script prints if the checks have been successfully conducted, and which checks failed. Successfully passing checks ensures that we can grade your assignment. You will receive 0.5% simply for having a valid submission file!

Expected Successful Output

```
Checking zip file....
Unzipping file: E0123456.zip Transferring necessary skeleton files
ex2: Success
ex3: Success
ex5: Success
ex6: Success
ex7: Success
```

3 Submission through LumiNUS

Zip the folder E0123456 as E0123456.zip (use your NUSNET id, NOT your student no A012...B, and use capital 'E' as prefix). The folder E0123456 should have five sub folders. Do **not** add any additional folder structure during zipping. The file structure should be: E0123456.zip contains the following content:

```
E0123456/  
  ex2/  
    node.c  
  ex3/  
    function_pointers.c  
    node.c  
    ex3.c  
  ex5/  
    check_system.sh  
  ex6/  
    check_system.sh  
  ex7/  
    file_renaming.sh
```

Upload the zip file to the Student Submissions “Lab 1” folder on LumiNUS. Note the deadline for the submission is **10th Sept, 2022, 11.59 PM Saturday**. Please ensure that you follow the instructions carefully (output format, how to zip the files etc.). Deviations will be penalized.